

III. SUB-BOTTOM DEPTHS OF INTERVALS CORED DURING LEGS 44 AND 44A

DSDP Staff

APPENDIX III

Sub-Bottom Depths of Intervals Cored During Legs 44 and 44A

APPENDIX III – Continued

Hole	Core	Top (m)	Bottom (m)	Recovery (m)	Last Section (No.)	Length of "0" Section	Hole	Core	Top (m)	Bottom (m)	Recovery (m)	Last Section (No.)	Length of "0" Section
Leg 44							Leg 44 – Continued						
388							391A	21	649.0	658.5	9.1	6	
388A	1	0.0	8.5	4.2	4		391B	1	0.0	9.5	9.3	6	20
388A	2	37.0	46.5	3.8	3		391C	1	335.5	345.0	3.1	2	
388A	3	46.5	53.5	0.15			391C	2	611.0	620.5	9.5	6	40
388A	4	208.0	217.5	0.8	1		391C	3	658.5	668.0	0.3		
388A	5	246.0	255.5	9.5	6	50	391C	4	668.0	677.5	0.7	1	
388A	6	284.0	293.5	1.7	2		391C	5	677.5	687.0	1.0	1	
388A	7	293.5	300.5	5.0	4		391C	6	687.0	696.5	9.5	6	50
388A	8	303.0	312.5	1.3	1		391C	7	725.0	734.5	2.0	2	
388A	9	312.5	322.0	7.0	6		391C	8	782.0	791.5	2.2	2	
388A	10	322.0	331.5	1.2	1		391C	9	839.0	848.5	4.2	3	
388A	11	331.5	341.0	7.8	6	50	391C	10	896.0	905.5	3.9	3	
389	1	30.0	39.5	3.5	3		391C	11	924.5	934.0	4.7	3	
390	1	0.0	9.5	8.2	6		391C	12	953.0	962.5	8.6	6	40
390	2	123.5	133.0	0.40	1		391C	13	981.5	991.0	0.2		
390	3	133.0	142.5	4.1	3		391C	14	1000.5	1010.0	3.8	3	
390	4	142.5	152.0	2.2	2		391C	15	1010.0	1019.5	4.2	3	
390	5	152.0	161.5	2.4	2		391C	16	1019.5	1029.0	5.6	4	
390	6	161.5	171.0	0.6	1		391C	17	1029.0	1038.5	2.4	2	
390	7	171.0	180.5	0.0			391C	18	1038.5	1048.0	1.1	1	
390	8	180.5	190.0	7.7	6		391C	19	1048.0	1057.5	0.0		
390	9	190.0	199.5	1.6	1		391C	20	1057.5	1067.0	0.40	1	
390	10	199.5	206.0	0.05			391C	21	1086.0	1095.5	5.5	4	
390A	1	9.5	19.0	1.2	1		391C	22	1095.5	1104.0	0.05		
390A	2	19.0	28.5	2.3	2		391C	23	1114.5	1124.0	0.0		
390A	3	28.5	38.0	4.8	4		391C	24	1124.0	1133.5	8.5	6	
390A	4	38.0	47.5	9.5	6	40	391C	25	1133.5	1143.0	5.7	4	
390A	5	47.5	57.0	4.1	4		391C	26	1143.0	1152.5	5.0	4	
390A	6	57.0	66.5	9.5	6	40	391C	27	1152.5	1162.0	5.7	4	
390A	7	66.5	76.0	5.3	4		391C	28	1162.0	1171.5	4.7	3	
390A	8	76.0	85.5	4.9	4		391C	29	1171.5	1181.0	7.1	5	
390A	9	85.5	95.0	1.3	1		391C	30	1181.0	1190.5	5.1	4	
390A	10	95.0	104.5	9.5	6	40	391C	31	1190.5	1200.0	8.5	6	
390A	11	104.5	114.0	7.8	6		391C	32	1200.0	1209.5	5.1	4	
390A	12	114.0	123.5	9.5	6	45	391C	33	1209.5	1219.0	3.8	3	
390A	13	123.5	133.0	9.5	6	40	391C	34	1219.0	1228.5	5.1	4	
390A	14	133.0	142.5	7.6	5		391C	35	1228.5	1238.0	6.1	4	
391	1	0.0	4.5	2.3	2		391C	36	1238.0	1247.5	7.1	5	
391A	1	86.0	95.5	8.1	7		391C	37	1247.5	1257.0	2.0	2	
391A	2	31.5	41.0	5.0	4		391C	38	1257.0	1266.5	6.0	4	
391A	3	145.5	155.0	8.2	6		391C	39	1266.5	1276.0	6.3	5	
391A	4	202.5	212.0	6.2	4		391C	40	1276.0	1285.5	6.3	5	
391A	5	259.5	269.0	9.5	6	40	391C	41	1285.5	1295.0	6.1	4	
391A	6	316.5	326.0	7.7	5		391C	42	1295.0	1304.5	7.1	5	
391A	7	326.0	335.5	7.2	5		391C	43	1304.5	1314.0	5.9	4	
391A	8	335.5	345.0	1.4	1		391C	44	1314.0	1323.5	8.0	6	
391A	9	354.5	364.0	9.5	6	50	391C	45	1323.5	1333.0	4.2	3	
391A	10	373.5	383.0	9.5	6	40	391C	46	1333.0	1342.5	1.3	1	
391A	11	411.5	421.0	8.7	6	50	391C	47	1342.5	1352.0	1.0	1	
391A	12	468.5	478.0	9.6	6	50	391C	48	1352.0	1361.5	1.9	2	
391A	13	525.5	535.0	9.5	6	50	391C	49	1361.5	1371.0	1.70	2	
391A	14	535.0	544.5	0.01			391C	50	1371.0	1380.5	1.3	1	
391A	15	544.5	554.0	0.05			391C	51	1380.5	1385.5	1.7	2	
391A	16	554.0	563.5	2.2	2		391C	52	1390.0	1399.5	5.0	4	
391A	17	568.5	573.0	5.0	4		391C	53	1399.5	1409.0	0.03		
391A	18	573.0	582.5	0.1			391C	54	1409.0	1412.0	0.0		
391A	19	582.5	592.0	5.2	4		392	1	47.5	57.0	0.2		
391A	20	639.5	649.0	8.3	6		392	2	57.0	59.0	3.1	2	

APPENDIX III – *Continued*

Hole	Core	Top (m)	Bottom (m)	Recovery (m)	Last Section (No.)	Length of "0" Section
Leg 44 – <i>Continued</i>						
392A	1	50.5	60.0	2.7	2	
392A	2	66.0	69.5	3.5	3	
392A	3	79.0	88.5	3.7	3	
392A	4	88.5	98.0	0.6	1	
392A	5	98.0	107.5	1.7	2	
392A	6	107.5	117.0	0.9	1	
392A	7	117.0	126.5	0.2	1	
392A	8	126.5	136.0	0.2	1	
392A	9	136.0	139.0	1.5	1	
392A	10	139.0	145.5	1.6	2	
392A	11	145.5	155.0	0.95	1	
392A	12	155.0	164.5	0.1		
392A	13	164.5	174.0	0.1		
392A	14	174.0	176.0	0.1		
392A	15	176.0	183.5	0.3	1	
392A	16	183.5	193.0	0.9	1	
392A	17	193.0	202.5	1.0	1	
392A	18	202.5	212.0	0.1		
392A	19	212.0	221.5	0.8	1	
392A	20	221.5	231.0	0.9	1	
392A	21	231.0	240.5	0.7	1	
392A	22	240.5	250.0	0.7	1	

APPENDIX III – *Continued*

Hole	Core	Top (m)	Bottom (m)	Recovery (m)	Last Section (No.)	Length of "0" Section
392A	23	250.0	259.3	0.7	1	
392A	24	259.5	269.0	0.2		
392A	25	269.0	278.5	0.2		
392A	26	278.5	288.0	0.6	1	
392A	27	288.0	297.5	0.1		
392A	28	297.5	307.0	0.4		
392A	29	307.0	316.5	0.1		
392A	30	316.5	326.0	0.1		
392A	31	326.0	335.5	0.2		
392A	32	335.5	345.0	0.0		
392A	33	345.0	349.0	0.0		
393	1	0.0	8.0	4.4	6	
393A	1	0.0	58.5	9.63	6	50
Leg 44A						
394						
394A	1	89.0	98.5	3.2	2	
394A	2	98.5	108.0	0.5	1	
394A	3	174.5	184.0	0.3	1	
394A	4	184.0	193.5	0.1		
394A	5	279.0	288.5	4.10	3	
394A	6	355.0	364.5	9.6	6	45