*** GRID B 01 ***

VOLUME 68: CHAPTER 12. PHYSICAL PROPERTIES TABLES, WITH ADJUSTED SUB-BOTTOM DEPTHS.

The "Sub-Bottom Depth (m, adj.)" in the following tables differs in three significant respects from the convential method of estimating sub-bottom depth, which uses the depth to the top of the cored interval, 1.5 meters for each intervening section, and the depth in section. First, in the present case the depth specified for the top of the cored interval is not necessarily measured at the top of the first section. If in the estimation of the co-chief scientists the top of the core appears to reveal downhole contamination, the depth for the top of the cored interval is placed at the boundary in the core between the contaminants and the normal stratigraphic sequence. Second, voids within the core are subtracted from the total stratigraphic recovery. Finally, the calculation of the estimated sub-bottom depth takes into account the slight variations (1-2 cm) from the ideal section length of 150 cm.

Note: In requesting samples, make sure to use the standard leg, hole, core, and interval method. The adjusted sub-bottom depths are given only as an aid in doing high resolution stratigraphy and are not for use in sample or interval designation.

List of Tables

1) Shear Vane
2) Penetrometer
3) Sonic Velocity
4) Gravimetric Chemistry
5) Sediment Paleomagnetism
6) Carbon-Carbonate

*** GRID B 01 ***

*** GRID C 01 ***

Table 1: Shear Vane

Shear Vane Data, Leg 68

*** GRID C 01 ***

*** GRID D 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Shear Strength (gm/cm-cm)	Remolded Strength (gm/cm-cm)
502	1	CC	0	0.00	62.00	16.50
502	2	1	13	0.53	29.00	20.60
502	2	1	90	1.30	90.60	0.00
502	2	2	65	2.53	86.30	41.33
502	2	3	68	4.05	188.00	70.24
502	3	1	57	5.37	85.70	45.46
502	3	2	75	7.01	159.00	74.40
502	3	3	42	8.18	177.74	68.20
502	4	1	67	9.64	202.00	93.00
502	4	2	120	11.53	196.00	78.54
502	4	3	83	12.67	235.00	113.61
502	5	2	63	15.64	221.14	31.00
502	6	2	71	20.22	256.63	45.33
502	7	2	86	24.16	384.94	133.90
502	8	2	66	28.87	279.54	56.57
502	9	2	68	33.36	320.36	119.56
502	10	2	83	37.63	352.86	73.32
502	13	2	82	51.11	444.51	114.57
502	14	2	58	55.25	339.11	82.49
502	15	2	62	59.58	513.25	114.56
502	16	2	75	64.18	439.93	201.65
502	17	2	82	68.62	540.75	127.70
502	18	2	21	72.51	435.35	91.65
502	19	2	44	77.12	348.53	118.65
502	20	2	56	81.62	385.60	118.65
502	21	2	86	86.34	1093.79	510.99
502	22	2	61	90.50	793.46	378.19
502	22	3	55	91.54	608.07	185.39
502	23	3	77	95.18	437.52	103.82
502	24	2	70	99.39	645.15	244.71
502	25	2	86	103.88	526.50	222.46
502	26	2	61	107.88	764.49	196.90
502	27	2	49	111.33	972.99	277.99
502	28	2	33	116.63	625.49	428.58
502	29	2	60	119.40	1413.15	243.75
502	29	3	75	121.05	926.65	984.57
502	30	2	91	124.10	1290.30	793.46
502	31	2	92	128.52	1783.81	532.83
502	32	2	91	132.87	1969.14	382.24
502	33	2	22	136.56	1934.30	277.99
502	34	2	85	141.63	1811.72	187.66
502	35	2	63	145.83	7061.91	335.91
502	36	2	83	150.45	1888.06	718.16
502	37	2	86	154.73	2513.55	590.79
502	37	2	402	157.89	2374.55	845.57
502	38	2	62	159.00	2617.80	220.08
502	39	2	75	163.54	2223.97	266.41
502	40	2	38	167.40	2536.72	440.16
502	41	2	46	170.76	1471.06	57.92
502	42	2	75	176.09	1679.56	115.83
502	43	2	15	180.51	2142.89	289.58
502	44	2	10	184.83	1888.06	393.83
502	45	2	20	189.20	2490.39	220.00

*** GRID D 01 ***

*** GRID E 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Shear Strength (gm/cm-cm)	Remolded Strength (gm/cm-cm)
502	46	2	27	193.72	3185.38	602.32
502	47	2	47	198.32	3069.55	405.41
502A	1	1	97	0.97	62.00	12.40
502A	2	2	71	4.04	111.60	43.40
502A	3	2	80	8.50	190.14	57.87
502A	4	2	71	12.87	152.94	57.87
502A	5	2	71	17.26	283.14	47.53
502A	6	2	70	21.28	229.40	90.93
502A	7	2	90	26.04	349.27	90.95
502A	8	2	88	30.38	301.74	107.47
502A	10	2	76	39.36	339.11	50.40
502A	12	2	63	47.91	444.51	132.90
502A	16	2	68	65.67	476.59	215.38
502A	17	2	69	70.10	453.68	174.14
502A	19	2	84	78.77	472.01	64.16
502A	20	2	68	83.15	545.33	256.63
502A	21	2	59	87.55	815.70	164.97
502A	22	2	71	92.12	641.57	256.63
502A	23	2	83	96.59	632.40	151.23
502A	24	2	85	101.06	788.21	325.37
502A	25	2	82	105.34	763.80	215.05
502A	26	2	84	109.77	1394.12	504.26
502A	27	2	72	114.12	1401.54	578.41
502A	28	2	86	118.50	1319.97	778.63
502A	29	2	80	121.60	1572.09	1141.99
502A	30	2	85	125.13	1146.74	683.41
502A	32	2	85	130.67	1940.19	150.58
502A	33	2	85	133.62	1598.48	567.58
502A	34	2	77	136.57	1760.65	637.07
502A	35	2	85	139.20	1702.73	590.74
502A	36	2	62	142.80	1528.98	266.41
502A	36	2	63	142.81	2119.72	613.91
502A	38	2	24	147.22	1992.31	359.08
502A	39	2	76	149.36	2177.64	706.57
502A	40	2	65	152.33	1911.23	776.07
502A	41	2	85	154.55	2351.39	0.00
502A	42	2	66	157.96	2096.56	0.00
502A	43	2	70	160.45	1030.90	301.16
502A	44	2	61	163.01	2675.72	220.08
502A	45	2	64	165.83	2733.63	602.32
502A	46	2	56	167.97	2061.81	266.41
502A	47	2	87	170.35	1945.98	393.83
502A	48	2	18	172.81	2733.63	544.41
502A	50	2	53	177.19	1922.81	127.41
502A	51	2	38	180.18	2444.05	579.16
502A	52	2	12	182.26	1934.39	706.57
502A	54	2	61	186.71	0.00	0.00
502A	55	2	39	189.04	0.00	0.00
502A	56	2	27	190.75	0.00	0.00
502A	57	2	37	192.97	0.00	0.00
502A	58	2	41	195.01	0.00	0.00
502A	60	2	14	198.86	0.00	0.00
502A	62	1	44	201.54	0.00	0.00

*** GRID E 01 ***

*** GRID F 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Shear Strength (gm/cm-cm)	Remolded Strength (gm/cm-cm)
502A	63	1	97	204.06	0.00	0.00
502A	65	2	51	209.13	0.00	0.00
502A	66	2	8	210.63	0.00	0.00
502A	67	1	60	211.61	0.00	0.00
502A	68	2	25	214.53	0.00	0.00
503	1	2	85	2.35	74.00	0.00
503A	2	2	75	3.98	95.07	0.00
503A	4	3	12	12.36	0.00	0.00
503A	5	2	35	16.86	429.87	0.00
503A	7	2	65	25.40	164.97	0.00
503A	7	3	54	26.91	178.73	0.00
503A	9	2	72	34.67	142.06	0.00
503A	10	2	87	39.27	261.21	18.33
503A	11	2	63	43.46	384.94	0.00
503A	12	2	87	48.07	265.79	0.00
503A	13	2	75	52.35	485.76	82.49
503A	14	2	67	55.97	0.00	0.00
503A	14	2	96	56.26	224.55	0.00
503A	15	2	83	61.33	0.00	0.00
503A	16	2	108	65.52	0.00	0.00
503A	19	2	117	78.94	0.00	0.00
503A	20	2	105	83.38	0.00	0.00
503A	21	2	75	87.65	0.00	0.00
503A	23	2	104	96.64	0.00	0.00
503A	24	2	104	101.15	0.00	0.00
503A	29	2	81	122.91	0.00	0.00
503A	30	2	104	127.37	0.00	0.00
503A	31	2	84	131.69	0.00	0.00
503A	34	2	75	144.58	334.53	64.16
503A	36	2	96	153.79	197.05	29.79
503A	37	2	86	158.10	453.68	54.99
503A	39	2	47	166.37	430.77	50.41
503A	41	2	49	175.39	490.34	91.65
503A	42	2	84	180.15	398.65	36.66
503A	43	2	71	184.36	380.36	45.83
503A	44	2	70	188.81	403.27	119.15
503A	48	2	81	206.23	316.20	0.00
503A	49	1	75	209.35	238.30	22.91
503A	50	2	79	215.19	577.41	64.16
503A	51	2	64	219.42	719.47	64.16
503A	52	2	74	224.05	1686.40	513.25
503A	53	2	78	228.49	941.77	133.48
503A	54	2	101	233.12	1119.75	278.08
503B	1	1	75	0.75	45.47	24.80
503B	1	2	58	2.06	148.80	28.93
503B	2	2	75	5.04	163.27	37.20
503B	3	2	99	9.67	374.07	194.27
503B	4	2	82	13.80	334.53	18.33
503B	5	2	81	18.12	213.09	18.33
503B	6	2	86	22.62	224.55	0.00
503B	7	2	85	27.09	187.89	41.24
503B	8	2	58	31.18	233.71	0.00
503B	10	2	47	39.94	403.27	13.75

*** GRID F 01 ***

*** GRID G 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Shear Strength (gm/cm-cm)	Remolded Strength (gm/cm-cm)
503B	11	2	99	44.66	270.38	22.91
503B	12	2	43	48.73	311.62	36.66
503B	13	2	87	53.52	288.71	32.08
503B	14	2	103	57.74	513.26	132.90
503B	15	2	77	61.92	485.76	41.24
503B	16	2	86	66.60	219.97	41.24
503B	17	2	74	70.95	398.69	73.32
503B	18	2	66	75.36	426.18	64.16
503B	19	2	51	79.42	362.03	59.57
503B	20	2	100	83.00	252.04	54.99
503B	21	2	80	88.65	403.27	105.40
503B	22	2	110	93.15	485.76	100.82
503B	24	2	34	100.99	224.55	77.90
503B	25	2	4	105.08	279.54	54.99
503B	26	2	123	110.48	247.46	41.24

*** GRID G 01 ***

*** GRID H 01 ***

Table 2: Penetrometer

Penetrometer Data, Leg 68

*** GRID H 01 ***

*** GRID I 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502	1	CC	0	0.00	3.86
502	2	1	40	0.80	2.72
502	2	1	116	1.56	2.21
502	2	2	93	2.81	2.84
502	2	2	123	3.11	2.15
502	2	3	11	3.48	2.10
502	2	3	62	3.99	1.83
502	2	3	119	4.56	1.81
502	3	1	17	4.97	2.38
502	3	1	88	5.68	1.73
502	3	1	117	5.97	2.25
502	3	2	18	6.44	2.25
502	3	2	106	7.32	1.95
502	3	3	3	7.79	1.98
502	3	3	77	8.53	2.03
502	3	3	87	8.63	2.02
502	4	1	17	9.14	1.44
502	4	1	98	9.95	2.05
502	4	2	32	10.65	2.12
502	4	2	68	11.01	2.00
502	4	3	10	11.94	1.87
502	4	3	118	13.02	1.88
502	5	1	33	13.93	2.31
502	5	1	93	14.43	1.92
502	5	2	8	15.09	1.64
502	5	2	108	16.09	1.91
502	5	3	18	16.69	1.87
502	5	3	95	17.46	1.72
502	6	1	35	18.35	1.91
502	6	1	118	19.18	1.87
502	6	2	17	19.68	1.86
502	6	2	58	20.09	1.25
502	6	2	106	20.57	1.66
502	6	2	141	20.92	1.71
502	6	3	7	21.08	1.77
502	6	3	30	21.31	1.74
502	7	1	30	22.70	1.92
502	7	1	125	23.65	1.95
502	7	2	23	23.53	1.59
502	7	2	109	24.39	1.41
502	7	3	15	24.96	1.66
502	7	3	101	25.82	1.73
502	7	3	111	25.92	1.97
502	8	1	32	27.05	1.90
502	8	1	127	28.00	1.97
502	8	2	26	28.47	1.73
502	8	2	96	29.17	1.59
502	8	2	113	29.34	1.64
502	8	3	7	29.80	1.79
502	8	3	41	30.14	1.50
502	8	3	68	30.41	1.68
502	9	1	26	31.46	2.04
502	9	1	113	32.33	1.92

*** GRID I 01 ***

*** GRID J 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502	9	2	20	32.88	1.61
502	9	2	111	33.79	1.69
502	9	3	4	34.22	1.83
502	9	3	89	35.02	1.61
502	10	1	59	36.19	2.38
502	10	1	62	36.22	2.27
502	10	1	81	36.41	2.17
502	10	1	143	37.03	1.63
502	10	2	17	36.97	1.72
502	10	2	120	38.00	1.64
502	10	3	38	38.69	1.65
502	10	3	65	38.96	1.55
502	10	3	88	39.19	1.46
502	11	1	42	40.21	1.96
502	11	1	115	40.94	1.54
502	13	1	32	49.12	1.93
502	13	1	61	49.41	2.13
502	13	2	31	50.60	1.64
502	13	2	119	51.48	1.68
502	13	3	24	52.04	1.53
502	13	3	106	52.86	1.57
502	14	1	33	53.53	2.03
502	14	1	119	54.39	2.49
502	14	2	16	54.83	2.00
502	14	2	96	55.63	1.74
502	15	1	62	58.22	1.57
502	15	1	137	58.97	1.55
502	15	2	4	59.00	1.62
502	15	2	49	59.45	1.59
502	15	2	124	60.20	1.64
502	15	3	83	61.29	1.65
502	16	1	36	62.36	2.16
502	16	1	127	63.27	1.62
502	16	2	12	63.55	1.65
502	16	2	88	64.31	1.63
502	17	1	40	66.80	1.80
502	17	1	136	67.76	1.55
502	17	2	30	68.10	1.61
502	17	2	119	68.99	1.71
502	18	1	21	71.01	1.88
502	18	1	120	72.00	1.67
502	18	2	8	72.38	1.65
502	18	2	45	72.75	1.67
502	19	1	40	75.60	1.77
502	19	1	130	76.50	1.39
502	19	2	37	77.05	1.32
502	19	2	117	77.85	1.92
502	19	3	10	78.29	1.85
502	19	3	25	78.44	1.99
502	19	3	37	78.56	1.80
502	20	1	48	80.08	1.72
502	20	1	121	80.81	1.72
502	20	2	14	81.20	1.75

*** GRID J 01 ***

*** GRID K 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502	20	2	91	81.97	1.45
502	20	2	125	82.31	1.50
502	20	3	66	83.22	1.53
502	20	3	90	83.46	1.46
502	21	1	46	84.46	1.77
502	21	1	84	84.84	1.40
502	21	1	112	85.12	1.36
502	21	2	46	85.94	1.49
502	21	2	117	86.65	1.57
502	21	2	139	86.87	1.64
502	22	1	127	89.67	1.64
502	22	1	139	89.79	1.62
502	22	2	29	90.18	1.45
502	22	2	104	90.93	1.59
502	22	3	15	91.14	1.57
502	22	3	108	92.07	1.58
502	23	2	33	93.24	1.63
502	23	2	121	94.12	1.58
502	23	3	28	94.69	1.62
502	23	3	112	95.53	1.67
502	23	4	19	96.10	1.59
502	23	4	118	97.09	1.52
502	24	1	39	97.59	1.79
502	24	1	145	98.65	1.37
502	24	1	149	98.69	1.29
502	24	2	28	98.97	1.51
502	24	2	106	99.75	1.45
502	24	3	15	100.35	1.36
502	24	3	28	100.48	1.40
502	24	3	129	101.49	1.42
502	25	1	21	101.76	1.61
502	25	1	43	101.98	1.54
502	25	1	125	102.80	1.63
502	25	2	33	103.35	1.46
502	25	2	118	104.20	1.51
502	25	3	67	105.20	1.46
502	25	3	118	105.71	1.56
502	26	1	88	106.83	1.47
502	26	1	129	107.24	1.51
502	26	2	9	107.36	1.40
502	26	2	110	108.37	1.52
502	26	3	83	109.61	1.53
502	26	3	109	109.87	1.48
502	27	2	10	110.94	1.61
502	27	2	62	111.46	1.35
502	28	1	42	115.22	1.38
502	28	1	127	116.07	1.47
502	28	2	67	116.97	1.44
502	29	1	29	117.59	1.52
502	29	1	142	118.72	1.40
502	29	2	17	118.97	1.43
502	29	2	137	120.17	1.39
502	29	3	20	120.50	1.55

*** GRID K 01 ***

*** GRID L 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502	29	3	30	120.60	1.56
502	29	3	103	121.33	1.44
502	30	1	43	122.13	1.39
502	30	1	140	123.10	1.40
502	30	2	10	123.29	1.44
502	30	2	30	123.49	1.44
502	30	2	105	124.24	1.43
502	30	2	113	124.32	1.43
502	31	1	31	126.41	1.49
502	31	1	109	127.19	1.34
502	31	1	147	127.57	1.42
502	31	2	41	128.01	1.38
502	31	2	134	128.94	1.33
502	31	2	145	129.05	1.34
502	32	1	37	130.87	1.29
502	32	1	63	131.13	1.44
502	32	1	101	131.51	1.11
502	32	1	130	131.80	1.30
502	32	2	52	132.48	1.51
502	32	2	131	133.27	1.40
502	33	1	105	135.95	1.51
502	33	1	140	136.30	1.41
502	34	1	53	139.83	1.42
502	34	1	130	140.60	1.36
502	34	2	32	141.10	1.34
502	34	2	119	141.97	1.42
502	35	1	29	143.99	1.35
502	35	1	124	144.94	1.37
502	35	2	24	145.44	1.34
502	35	2	94	146.14	1.32
502	36	1	9	148.19	1.30
502	36	1	135	149.45	1.32
502	36	2	19	149.81	1.36
502	36	2	119	150.81	1.39
502	37	1	44	152.84	1.47
502	37	1	97	153.37	1.39
502	37	1	110	153.50	1.55
502	37	2	57	154.44	1.30
502	37	2	126	155.13	1.37
502	37	2	139	155.26	1.35
502	38	1	119	158.09	1.39
502	38	1	147	158.37	1.42
502	38	2	71	159.09	1.32
502	38	2	105	159.43	1.45
502	39	1	26	161.56	1.21
502	39	1	26	161.56	1.34
502	39	1	26	161.56	1.34
502	39	1	122	162.52	1.43
502	39	2	18	162.97	1.35
502	39	2	36	163.15	1.35
502	40	1	58	165.93	1.36
502	40	1	74	166.09	1.32
502	40	2	5	167.07	1.28

*** GRID L 01 ***

*** GRID M 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502	40	2	71	167.73	1.36
502	41	2	49	170.79	1.29
502	41	2	126	171.56	1.36
502	42	1	70	174.54	1.42
502	42	1	142	175.26	1.37
502	42	2	17	175.51	1.39
502	42	2	33	175.67	1.42
502	42	2	124	176.58	1.29
502	42	2	144	176.78	1.21
502	42	2	146	176.80	1.34
502	42	3	10	176.95	1.26
502	42	3	34	177.19	1.33
502	43	1	125	180.10	1.29
502	43	1	142	180.27	1.29
502	43	2	30	180.66	1.27
502	43	2	100	181.36	1.22
502	43	2	102	181.38	1.31
502	44	1	137	184.62	1.28
502	44	1	145	184.70	1.31
502	44	2	6	184.79	1.42
502	44	2	17	184.90	1.36
502	45	1	43	187.96	1.35
502	45	1	122	188.75	1.33
502	45	2	13	189.13	1.32
502	45	2	25	189.25	1.32
502	46	1	123	193.18	1.30
502	46	1	136	193.31	1.23
502	46	1	137	193.32	1.22
502	46	2	4	193.49	1.26
502	46	2	29	193.74	1.28
502	47	1	36	196.71	1.35
502	47	1	108	197.43	1.36
502	47	2	7	197.92	1.29
502	47	2	79	198.64	1.29
502	48	1	127	202.00	1.36
502	48	1	136	202.09	1.29
502	49	1	25	205.55	1.25
502	50	1	5	209.75	1.32
502	50	1	12	209.82	1.21
502	50	1	201	211.71	1.15
502A	1	1	16	0.16	3.32
502A	1	1	143	1.43	2.25
502A	2	1	52	2.37	1.98
502A	2	1	113	2.98	2.60
502A	2	2	20	3.53	2.17
502A	2	2	120	4.53	2.13
502A	2	3	68	5.51	2.14
502A	3	1	40	6.70	2.10
502A	3	1	131	7.61	2.21
502A	3	2	25	7.95	2.03
502A	3	2	126	8.96	1.88
502A	3	3	22	9.41	1.93
502A	3	3	95	10.14	1.96

*** GRID M 01 ***

*** GRID N 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502A	4	1	23	10.93	2.19
502A	4	1	130	12.00	1.93
502A	4	2	39	12.55	1.93
502A	4	2	128	13.44	1.98
502A	5	1	31	15.41	1.83
502A	5	1	110	16.20	1.93
502A	5	2	30	16.85	1.97
502A	5	2	110	17.65	1.94
502A	5	3	30	18.35	1.98
502A	5	3	110	19.15	1.94
502A	6	1	40	19.77	2.57
502A	6	1	111	20.48	1.83
502A	6	2	25	20.83	1.74
502A	6	2	45	21.03	1.79
502A	6	2	110	21.68	1.85
502A	6	3	50	22.58	1.76
502A	6	3	142	23.30	1.84
502A	7	1	75	24.60	2.27
502A	7	1	110	24.95	1.95
502A	7	2	35	25.49	2.10
502A	7	2	120	26.34	1.82
502A	7	3	30	26.94	1.76
502A	7	3	110	27.74	1.61
502A	8	1	40	28.58	2.32
502A	8	1	125	29.43	2.01
502A	8	2	30	29.80	1.72
502A	8	2	125	30.75	1.78
502A	8	3	15	31.16	1.72
502A	9	1	8	32.78	1.92
502A	10	1	30	37.40	2.33
502A	10	1	130	38.40	1.77
502A	10	2	40	39.00	1.66
502A	10	2	120	39.80	1.62
502A	10	3	30	40.40	1.68
502A	10	3	130	41.40	1.73
502A	12	1	20	46.00	2.53
502A	12	1	130	47.10	1.77
502A	12	2	30	47.58	1.71
502A	12	2	100	48.28	1.67
502A	12	3	30	49.08	1.69
502A	12	3	60	49.38	1.68
502A	16	1	50	64.00	2.04
502A	16	1	110	64.60	2.08
502A	16	2	40	65.39	1.62
502A	16	2	120	66.19	1.61
502A	16	3	20	66.70	1.55
502A	17	1	60	68.50	1.69
502A	17	1	110	69.00	1.68
502A	17	2	40	69.81	1.75
502A	17	2	120	70.61	1.76
502A	17	3	40	71.30	1.82
502A	17	3	110	72.00	1.76
502A	19	1	40	76.84	2.01

*** GRID N 01 ***

*** GRID B 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502A	19	1	110	77.54	1.92
502A	19	2	30	78.23	1.80
502A	19	2	120	79.13	1.78
502A	19	3	30	79.75	1.56
502A	19	3	90	80.35	1.68
502A	20	1	60	81.70	1.82
502A	20	1	120	82.30	1.79
502A	20	2	30	82.77	1.65
502A	20	2	110	83.57	1.66
502A	20	3	30	84.28	1.62
502A	20	3	120	85.18	1.48
502A	21	1	55	85.99	1.80
502A	21	1	120	86.64	1.66
502A	21	2	40	87.36	1.54
502A	21	2	120	88.16	1.60
502A	21	3	30	88.76	1.60
502A	21	3	110	89.23	1.65
502A	22	1	30	90.20	1.87
502A	22	1	120	91.10	1.65
502A	22	2	40	91.81	1.55
502A	22	2	130	92.68	1.65
502A	22	3	50	93.35	1.64
502A	22	3	120	94.11	1.47
502A	23	1	30	94.60	1.99
502A	23	1	120	95.50	1.52
502A	23	2	40	96.16	1.60
502A	23	2	110	96.86	1.65
502A	23	3	30	97.57	1.58
502A	23	3	110	98.37	1.53
502A	24	1	30	99.00	1.71
502A	24	1	110	99.80	1.62
502A	24	2	40	100.61	1.66
502A	24	2	130	101.51	1.61
502A	24	3	30	102.02	1.49
502A	24	3	120	102.92	1.60
502A	25	1	70	103.75	1.61
502A	25	1	130	104.35	1.65
502A	25	2	30	104.82	1.58
502A	25	2	120	105.72	1.57
502A	25	3	30	106.32	1.57
502A	25	3	110	107.12	1.61
502A	26	1	50	108.00	1.62
502A	26	1	120	108.70	1.53
502A	26	2	40	109.33	1.62
502A	26	2	130	110.23	1.37
502A	26	3	30	110.65	1.50
502A	26	3	100	111.35	1.49
502A	27	1	40	112.30	1.49
502A	27	1	120	113.10	1.53
502A	27	2	30	113.70	1.52
502A	27	2	120	114.60	1.49
502A	27	3	30	115.20	1.55
502A	27	3	110	116.00	1.49

*** GRID B 02 ***

*** GRID C 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502A	28	1	30	116.48	1.52
502A	28	1	120	117.38	1.40
502A	28	2	30	117.94	1.43
502A	28	2	120	118.84	1.38
502A	29	1	40	119.70	1.83
502A	29	1	130	120.60	1.46
502A	29	2	30	121.10	1.42
502A	29	2	110	121.90	1.45
502A	29	3	30	122.60	1.47
502A	30	1	40	123.20	1.60
502A	30	1	120	124.00	1.41
502A	30	2	30	124.58	1.43
502A	30	2	130	125.58	1.41
502A	32	1	40	128.70	1.40
502A	32	1	130	129.60	1.34
502A	32	2	27	130.09	1.15
502A	32	2	40	130.22	1.41
502A	32	2	120	131.02	1.39
502A	32	3	15	131.48	1.30
502A	33	1	50	131.80	1.37
502A	33	1	120	132.50	1.41
502A	33	2	30	133.07	1.33
502A	33	2	120	133.97	1.37
502A	34	1	40	134.70	1.41
502A	34	1	130	135.60	1.46
502A	34	2	40	136.20	1.44
502A	34	2	110	136.90	1.46
502A	35	1	50	137.35	1.49
502A	35	1	120	138.05	1.46
502A	35	2	30	138.65	1.42
502A	35	2	120	139.55	1.41
502A	35	3	20	140.05	1.42
502A	35	3	80	140.65	1.43
502A	36	1	30	140.98	1.45
502A	36	1	120	141.88	1.44
502A	36	2	30	142.48	1.45
502A	36	2	70	142.88	1.38
502A	37	1	70	143.20	1.62
502A	37	1	135	143.85	1.38
502A	37	2	30	144.24	1.41
502A	37	2	100	144.94	1.37
502A	38	1	40	145.88	1.41
502A	38	1	120	146.68	1.33
502A	38	2	20	147.18	1.31
502A	39	1	40	147.50	1.45
502A	39	1	120	148.30	1.39
502A	39	2	30	148.90	1.40
502A	39	2	110	149.70	1.34
502A	40	1	40	150.58	1.36
502A	40	1	120	151.38	1.40
502A	40	2	2	151.70	1.40
502A	40	2	100	152.68	1.29
502A	41	1	75	152.95	1.41

*** GRID C 02 ***

*** GRID D 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502A	41	1	130	153.50	1.43
502A	41	2	40	154.10	1.41
502A	41	2	120	154.90	1.35
502A	41	3	15	155.35	1.35
502A	42	1	40	156.20	1.35
502A	42	1	120	157.00	1.28
502A	42	2	30	157.60	1.35
502A	42	2	100	158.30	1.32
502A	43	1	30	158.60	1.41
502A	43	1	120	159.50	1.29
502A	43	2	30	160.05	1.44
502A	43	2	100	160.75	1.30
502A	44	1	60	161.61	1.35
502A	44	1	100	162.01	1.31
502A	44	1	131	162.32	1.32
502A	44	2	20	162.60	1.26
502A	44	2	95	163.35	1.31
502A	45	1	40	164.08	1.40
502A	45	1	110	164.78	1.28
502A	45	2	25	165.44	1.38
502A	45	2	70	165.89	1.35
502A	46	1	50	166.56	1.30
502A	46	1	120	167.26	1.27
502A	46	2	15	167.56	1.38
502A	46	2	60	168.01	1.34
502A	47	1	50	168.48	1.43
502A	47	1	120	169.18	1.37
502A	47	2	40	169.88	1.32
502A	47	2	120	170.68	1.31
502A	48	1	40	171.53	1.30
502A	48	1	110	172.23	1.30
502A	48	2	20	172.83	1.31
502A	50	1	30	175.50	1.51
502A	50	1	130	176.50	1.30
502A	50	2	40	177.06	1.38
502A	50	2	90	177.56	1.30
502A	51	1	40	178.70	1.35
502A	51	1	110	179.40	1.31
502A	51	2	15	179.95	1.25
502A	51	2	50	180.30	1.34
502A	52	1	40	181.02	1.28
502A	52	1	110	181.72	1.34
502A	52	2	10	182.24	1.28
502A	53	1	50	183.00	1.31
502A	53	1	120	183.70	1.27
502A	54	1	40	185.00	1.30
502A	54	1	120	185.80	1.34
502A	54	2	20	186.30	1.24
502A	54	2	70	186.80	1.36
502A	55	1	40	187.56	1.38
502A	55	1	120	188.36	1.33
502A	55	2	25	188.90	1.31
502A	56	1	50	189.47	1.34

*** GRID D 02 ***

*** GRID E 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502A	56	1	120	190.17	1.29
502A	56	2	30	190.78	1.31
502A	57	1	30	191.40	1.33
502A	57	1	110	192.20	1.61
502A	57	2	25	192.85	1.29
502A	58	1	50	193.56	1.35
502A	58	1	120	194.26	1.35
502A	58	2	18	194.78	1.58
502A	58	2	30	194.90	1.34
502A	60	1	40	197.65	1.25
502A	60	1	120	198.45	1.31
502A	60	2	10	198.82	1.33
502A	61	1	55	199.43	1.39
502A	61	1	100	199.88	1.33
502A	62	1	35	201.50	1.26
502A	63	1	40	203.49	1.31
502A	63	1	130	204.39	1.27
502A	65	1	50	207.60	1.28
502A	65	1	120	208.30	1.27
502A	65	2	20	208.82	1.31
502A	65	2	60	209.22	1.27
502A	66	1	70	209.85	1.27
502A	66	1	130	210.45	1.26
502A	66	2	20	210.75	1.28
502A	67	1	40	211.41	1.29
502A	67	1	80	211.81	1.34
502A	68	1	45	213.25	1.39
502A	68	1	120	214.00	1.18
502A	68	2	15	214.43	1.28
502A	68	2	50	214.78	1.22
502B	1	1	30	0.30	3.77
502B	1	1	120	1.16	2.88
502B	2	1	35	2.05	2.13
502B	2	1	120	2.90	2.00
502B	2	2	20	3.34	1.94
502B	2	2	95	4.09	2.11
502B	2	3	50	5.14	2.00
502B	3	1	30	6.45	2.54
502B	3	1	125	7.40	2.08
502B	3	2	25	7.85	1.81
502B	3	2	120	8.80	2.03
502B	3	3	30	9.40	1.94
502B	3	3	105	10.15	1.98
502B	4	1	45	11.00	2.25
502B	4	1	125	11.80	1.83
502B	4	2	30	12.34	1.93
502B	4	2	115	13.19	2.03
502B	4	3	30	13.84	1.99
502B	4	3	97	14.51	2.32
502B	5	1	30	15.15	2.68
502B	5	1	125	16.10	1.91
502B	5	2	15	16.45	1.81
502B	5	2	105	17.20	1.97

*** GRID E 02 ***

*** GRID F 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502B	5	3	22	17.75	1.86
502B	5	3	105	18.58	1.84
502B	6	1	25	19.60	2.07
502B	6	1	130	20.65	1.99
502B	6	2	10	20.96	2.11
502B	6	2	100	21.86	1.89
502B	6	3	24	22.58	1.88
502B	6	3	128	23.60	1.81
502B	7	2	25	24.28	1.85
502B	7	2	120	25.23	1.86
502B	7	3	25	25.77	1.76
502B	7	3	125	26.77	1.83
502B	7	4	15	27.18	1.73
502B	7	4	114	28.17	1.68
502B	8	1	30	28.45	2.49
502B	8	1	100	29.15	1.76
502B	8	2	25	29.79	1.71
502B	8	2	130	30.41	1.63
502B	8	3	28	30.85	1.85
502B	8	3	90	31.47	1.73
502B	9	1	25	32.65	2.15
502B	9	1	125	33.65	1.59
502B	9	2	18	34.04	1.73
502B	9	2	130	35.10	1.94
502B	9	3	10	35.39	1.87
502B	9	3	56	35.79	1.47
502B	10	1	114	38.09	2.22
502B	11	1	18	41.53	1.76
502B	11	1	125	42.60	1.72
502B	11	2	15	42.99	1.78
502B	11	2	123	44.07	1.65
502B	11	3	15	44.50	1.60
502B	11	3	113	45.48	1.67
502B	13	1	23	50.38	1.48
502B	13	1	125	51.40	1.81
502B	13	2	16	51.81	1.68
502B	13	2	122	52.87	1.75
502B	13	3	18	53.34	1.50
502B	13	3	106	54.22	1.50
502B	14	1	27	54.72	1.69
502B	14	1	132	55.77	1.46
502B	14	2	33	56.28	1.66
502B	14	2	123	57.16	1.64
502B	14	3	18	57.61	1.50
502B	14	3	94	58.37	1.69
502B	15	1	25	59.20	1.65
502B	15	1	120	60.15	1.68
502B	16	1	30	63.42	1.83
502B	16	1	87	63.99	1.54
502B	17	1	27	68.02	1.75
502B	17	1	122	68.97	1.63
502B	17	2	28	69.53	1.50
502B	17	2	113	70.38	1.62

*** GRID F 02 ***

*** GRID G 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502B	17	3	28	71.03	1.65
502B	17	3	93	71.68	1.83
502B	18	1	30	72.45	1.94
502B	18	1	128	73.43	1.49
502B	18	2	23	73.87	1.58
502B	18	2	96	74.60	1.62
502B	18	3	30	75.44	1.54
502B	18	3	101	76.15	1.51
502B	19	1	25	76.80	1.75
502B	19	1	117	77.72	1.45
502B	19	2	29	78.34	1.62
502B	19	2	126	79.31	1.53
502B	19	3	24	79.80	1.54
502B	19	3	97	80.53	1.61
502B	20	1	26	81.21	1.59
502B	20	1	127	82.22	1.48
502B	20	2	19	82.64	1.59
502B	20	2	102	83.47	1.52
502B	20	3	26	84.21	1.55
502B	20	3	111	85.06	1.38
502B	21	1	26	85.54	1.71
502B	21	1	122	86.50	1.57
502B	21	2	35	87.14	1.62
502B	21	2	122	88.01	1.55
502B	21	3	28	88.52	1.56
502B	21	3	92	89.16	1.55
502B	22	2	27	90.19	1.52
502B	22	2	107	90.99	1.40
502B	22	3	29	91.71	1.43
502B	22	3	101	92.43	1.51
502B	22	4	27	93.19	1.42
502B	22	4	136	94.28	1.02
502B	23	1	59	94.42	1.82
502B	23	1	130	95.13	1.56
502B	23	2	33	95.66	1.55
502B	23	2	109	96.42	1.45
502B	23	3	14	96.97	1.42
502C	1	2	33	32.45	1.58
502C	1	2	129	33.41	1.62
502C	1	3	42	33.88	1.79
502C	1	4	29	35.23	1.51
502C	1	4	103	35.97	1.64
502C	2	1	44	36.79	2.00
502C	2	1	116	37.51	1.79
502C	2	2	25	38.06	1.72
502C	2	2	104	38.85	1.66
502C	2	3	28	39.59	1.67
502C	2	3	114	40.45	1.59
502C	3	1	48	41.28	1.70
502C	3	1	127	42.07	1.60
502C	3	2	29	42.57	1.61
502C	3	2	123	43.51	1.70
502C	3	3	13	43.91	1.77

*** GRID G 02 ***

*** GRID H 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502C	3	3	43	44.21	1.74
502C	4	1	114	46.24	1.67
502C	4	2	37	46.49	1.73
502C	5	1	28	49.88	1.79
502C	5	1	125	50.85	1.58
502C	5	2	26	51.35	1.69
502C	5	2	117	52.26	1.56
502C	5	3	22	52.81	1.66
502C	5	3	87	53.46	1.50
502C	6	2	24	54.39	1.66
502C	6	2	127	55.42	1.64
502C	6	3	14	55.79	1.55
502C	6	3	21	55.86	1.72
502C	6	4	26	57.41	1.61
502C	6	4	88	58.03	1.57
502C	7	1	78	59.01	1.65
502C	8	1	40	63.20	1.84
502C	8	1	121	64.01	1.48
502C	8	2	22	64.46	1.58
502C	8	2	22	64.46	1.61
502C	8	3	24	65.98	1.62
502C	8	3	25	65.99	1.67
502C	9	1	52	67.72	1.73
502C	9	1	124	68.44	1.66
502C	9	2	34	69.04	1.59
502C	9	2	114	69.84	1.53
502C	9	3	25	70.45	1.58
502C	9	3	106	71.26	1.49
502C	10	1	46	72.06	1.63
502C	10	1	126	72.86	1.60
502C	10	2	25	73.33	1.56
502C	10	2	104	74.12	1.48
502C	10	3	27	74.86	1.57
502C	10	3	125	75.84	1.42
502C	11	1	18	76.18	1.71
502C	11	1	112	77.12	1.51
502C	11	2	17	77.64	1.46
502C	11	2	98	78.45	1.47
502C	11	3	25	79.22	1.44
502C	11	3	113	80.10	1.50
502C	12	1	117	81.12	1.65
502C	12	2	29	81.78	1.57
502C	13	1	41	85.21	1.65
502C	13	1	126	86.06	1.52
502C	13	2	25	86.53	1.55
502C	13	2	127	87.55	1.55
502C	13	3	24	88.02	1.53
502C	13	3	122	89.00	1.42
502C	14	1	26	89.46	1.72
502C	14	1	127	90.47	1.48
502C	14	2	27	90.94	1.47
502C	14	2	106	91.73	1.51
502C	14	3	23	92.40	1.49

*** GRID H 02 ***

*** GRID I 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502C	14	3	128	93.45	1.49
502C	15	1	23	93.83	1.50
502C	15	1	129	94.89	1.53
502C	15	2	40	95.48	1.57
502C	15	2	113	96.21	1.45
502C	15	3	30	96.88	1.42
502C	15	3	112	97.70	1.50
502C	16	1	24	98.24	1.55
502C	16	1	118	99.18	1.43
502C	16	2	37	99.86	1.61
502C	16	2	135	100.84	1.41
502C	16	3	26	101.25	1.46
502C	16	3	127	102.26	1.40
502C	17	1	51	102.61	1.73
502C	17	1	125	103.35	1.47
502C	17	2	36	103.96	1.55
502C	17	2	119	104.79	1.46
502C	17	3	27	105.37	1.40
502C	17	3	124	106.34	1.42
502C	18	1	49	107.36	1.38
502C	18	1	126	108.13	1.42
502C	18	2	31	108.54	1.45
502C	18	2	114	109.37	1.49
502C	18	3	21	109.94	1.42
502C	18	3	72	110.45	1.42
502C	19	1	21	111.41	1.49
502C	19	1	124	112.44	1.42
502C	19	2	11	112.81	1.50
502C	20	1	38	115.98	1.40
502C	20	1	114	116.74	1.57
502C	20	2	16	117.26	1.43
502C	20	2	89	117.99	1.52
502C	20	3	35	118.95	1.42
502C	21	1	24	120.24	1.58
502C	21	1	95	120.95	1.41
502C	21	2	26	121.76	1.44
502C	21	2	111	122.61	1.41
502C	21	3	46	122.97	1.53
502C	22	1	16	124.56	1.36
502C	22	1	60	125.00	1.49
502C	23	2	105	127.67	1.11
502C	23	2	123	127.85	1.30
502C	23	2	136	127.98	1.12
502C	23	3	17	128.29	1.31
502C	23	3	121	129.33	1.30
502C	24	1	44	130.24	2.00
502C	24	1	117	130.97	1.38
502C	24	2	42	131.67	1.40
502C	24	2	117	132.42	1.38
502C	24	3	19	132.94	1.33
502C	25	1	31	134.41	1.39
502C	25	1	93	135.03	1.50
502C	26	1	117	138.22	1.30

*** GRID I 02 ***

*** GRID J 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
502C	26	2	43	138.98	1.42
502C	26	2	130	139.85	1.37
502C	27	1	124	142.26	1.33
502C	27	2	11	141.96	1.28
502C	27	2	88	142.73	1.28
502C	28	1	44	210.64	1.38
502C	28	1	134	211.54	1.35
502C	28	2	32	212.03	1.45
502C	28	2	106	212.77	1.44
502C	29	1	21	213.41	1.63
502C	29	1	96	214.16	1.30
502C	29	2	16	214.86	1.31
502C	30	1	123	215.93	1.39
502C	31	1	52	216.92	1.57
502C	31	1	128	217.68	1.28
502C	31	2	13	217.93	1.31
502C	31	2	85	218.65	1.27
502C	32	1	35	219.45	1.58
502C	32	1	110	220.20	1.72
502C	33	1	57	222.27	1.38
502C	33	1	127	222.97	1.26
502C	33	2	40	223.57	1.23
502C	34	1	108	224.28	1.15
502C	34	2	23	224.93	1.12
503A	1	1	40	0.40	4.41
503A	1	1	75	0.75	2.61
503A	2	1	85	2.65	3.16
503A	2	1	105	2.85	3.27
503A	2	2	5	3.28	1.95
503A	2	3	50	5.11	2.33
503A	2	3	69	5.26	2.10
503A	4	1	35	10.85	2.20
503A	4	1	55	11.05	2.57
503A	4	2	48	11.52	2.60
503A	4	2	140	12.44	1.99
503A	4	3	2	12.26	1.77
503A	4	3	60	12.84	2.07
503A	5	1	23	15.23	1.55
503A	5	1	107	16.07	1.54
503A	5	2	12	16.63	1.70
503A	5	2	98	17.49	1.49
503A	5	3	5	18.06	1.53
503A	5	3	40	18.41	1.42
503A	7	1	143	24.78	2.36
503A	7	2	15	25.12	1.79
503A	7	2	130	26.05	1.84
503A	7	3	60	26.97	1.53
503A	7	3	113	27.50	2.21
503A	9	1	84	33.36	1.86
503A	9	1	113	33.65	1.53
503A	9	2	9	34.14	1.53
503A	9	2	121	35.06	1.89
503A	9	3	33	35.48	1.79

*** GRID J 02 ***

*** GRID K 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
503A	9	3	82	35.97	1.70
503A	10	1	24	37.24	1.94
503A	10	1	128	38.28	1.86
503A	10	2	49	38.89	1.60
503A	10	2	125	39.65	1.69
503A	10	3	10	40.03	1.58
503A	10	3	55	40.48	2.13
503A	11	1	90	42.20	2.05
503A	11	1	135	42.65	1.65
503A	11	2	10	42.93	1.90
503A	11	2	140	44.23	1.67
503A	11	3	10	44.43	1.54
503A	11	3	67	45.00	1.67
503A	12	1	82	46.51	1.97
503A	12	1	130	46.99	1.82
503A	12	2	22	47.42	2.27
503A	12	2	149	48.69	1.57
503A	12	3	10	48.80	1.55
503A	12	3	73	49.43	2.00
503A	13	1	114	51.34	2.10
503A	13	1	139	51.59	1.82
503A	13	2	8	51.68	1.83
503A	13	2	100	52.60	1.72
503A	13	3	13	53.23	1.33
503A	13	3	87	53.97	1.61
503A	14	2	26	55.56	1.66
503A	14	2	130	56.60	1.74
503A	14	3	12	56.92	1.67
503A	14	3	17	56.97	2.52
503A	14	3	83	57.63	1.85
503A	15	2	113	61.63	1.68
503A	15	3	9	62.09	1.76
503A	15	3	64	62.64	1.77
503A	16	1	139	64.79	2.52
503A	16	2	144	65.88	2.17
503A	16	3	13	66.04	2.03
503A	16	3	20	66.11	2.13
503A	17	2	4	68.99	2.26
503A	17	2	10	69.05	2.56
503A	19	1	35	76.95	1.79
503A	19	1	145	77.85	1.67
503A	19	2	48	78.25	2.04
503A	19	2	138	79.15	1.77
503A	19	3	5	79.04	1.93
503A	20	1	9	81.09	2.30
503A	20	1	135	82.10	1.54
503A	20	2	19	82.52	1.64
503A	20	2	147	83.80	1.75
503A	20	3	50	84.34	1.85
503A	20	3	128	85.12	1.69
503A	20	3	132	85.16	1.61
503A	21	1	9	85.49	2.10
503A	21	1	47	85.87	1.66

*** GRID K 02 ***

*** GRID L 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
503A	21	1	138	86.78	1.63
503A	21	2	17	87.07	1.54
503A	21	2	144	88.34	1.72
503A	21	3	12	88.53	1.68
503A	21	3	89	89.30	1.61
503A	23	1	35	94.55	1.82
503A	23	2	98	96.58	1.54
503A	23	2	110	96.70	1.32
503A	24	1	140	100.00	1.79
503A	24	2	20	100.31	1.72
503A	24	2	140	101.51	1.59
503A	24	3	45	102.08	1.60
503A	24	3	80	102.43	1.42
503A	29	1	72	121.32	1.62
503A	29	1	111	121.71	1.71
503A	29	2	26	122.36	1.54
503A	29	2	138	123.48	1.69
503A	29	3	60	124.21	1.42
503A	29	3	94	124.55	1.38
503A	30	1	103	125.95	1.59
503A	30	1	139	126.31	1.59
503A	30	2	39	126.72	1.70
503A	30	2	126	127.59	1.86
503A	31	1	90	130.30	1.71
503A	31	1	134	130.74	1.70
503A	31	2	63	131.48	1.81
503A	31	2	143	132.28	1.53
503A	31	3	40	132.75	1.67
503A	31	3	116	133.51	1.75
503A	32	1	58	134.38	1.86
503A	34	2	20	144.03	1.42
503A	34	2	138	145.21	1.71
503A	34	3	9	145.43	1.45
503A	34	3	46	145.80	1.54
503A	35	1	21	147.21	1.64
503A	35	1	77	147.67	1.61
503A	36	1	41	151.81	1.64
503A	36	1	137	152.69	1.47
503A	36	2	15	152.98	1.59
503A	36	2	101	153.84	1.82
503A	36	3	3	154.22	1.59
503A	36	3	33	154.52	1.49
503A	37	1	101	156.72	1.80
503A	37	1	140	157.11	1.52
503A	37	2	6	157.30	1.53
503A	37	2	110	158.34	1.52
503A	39	2	42	166.32	1.83
503A	39	2	136	167.26	1.64
503A	39	3	6	167.47	1.50
503A	40	1	76	169.52	1.74
503A	40	1	111	169.87	1.65
503A	41	1	30	173.70	1.52
503A	41	1	160	175.00	1.63

*** GRID L 02 ***

*** GRID M 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
503A	41	2	10	175.00	1.57
503A	41	2	145	176.35	1.34
503A	41	3	25	176.66	1.35
503A	41	3	98	177.39	1.45
503A	42	1	21	178.01	1.95
503A	42	1	73	178.53	1.58
503A	42	2	20	179.51	1.53
503A	42	2	81	180.12	1.52
503A	42	3	5	180.87	1.58
503A	42	3	50	181.28	1.69
503A	43	1	63	182.83	1.73
503A	43	1	105	183.25	1.52
503A	43	2	9	183.74	1.36
503A	43	2	129	184.94	1.60
503A	43	3	18	185.34	1.46
503A	43	3	41	185.57	1.64
503A	44	1	48	187.08	1.62
503A	44	1	131	187.91	1.53
503A	44	2	13	188.24	1.82
503A	44	2	94	189.05	1.44
503A	44	3	16	189.77	1.68
503A	44	3	76	190.37	1.72
503A	48	1	101	204.93	1.89
503A	48	1	138	205.30	1.51
503A	48	2	8	205.48	1.82
503A	48	2	146	206.88	1.42
503A	48	3	8	206.98	1.35
503A	48	3	59	207.49	1.51
503A	49	1	56	209.16	1.55
503A	49	1	139	209.99	1.52
503A	49	2	28	210.34	1.51
503A	50	1	79	213.79	1.46
503A	50	1	102	214.02	1.42
503A	50	2	11	214.51	1.51
503A	50	2	144	215.84	1.35
503A	50	3	20	216.10	1.37
503A	50	3	100	216.90	1.35
503A	51	1	31	217.71	1.39
503A	51	1	120	218.60	1.33
503A	51	2	8	218.86	1.36
503A	51	2	132	220.10	1.33
503A	51	3	4	220.32	1.46
503A	51	3	21	220.49	1.35
503A	52	1	10	221.90	1.44
503A	52	1	145	223.25	1.44
503A	52	2	23	223.54	1.44
503A	52	2	137	224.68	1.48
503A	52	3	10	224.91	1.33
503A	52	3	70	225.51	1.31
503A	53	1	40	226.60	1.23
503A	53	1	139	227.59	1.18
503A	53	2	53	228.24	1.40
503A	53	2	132	228.98	1.29

*** GRID M 02 ***

*** GRID N 02 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
503A	53	3	14	229.34	1.34
503A	53	3	67	229.87	1.40
503A	54	1	12	230.72	1.41
503A	54	1	140	232.00	1.36
503A	54	2	8	232.19	1.40
503A	54	2	141	233.52	1.35
503A	54	3	46	234.08	1.39
503A	54	3	89	234.51	1.38
503B	1	1	10	0.10	3.64
503B	1	1	37	0.37	3.32
503B	1	1	54	0.54	3.41
503B	1	1	68	0.68	2.93
503B	1	1	85	0.85	2.10
503B	1	1	119	1.19	2.62
503B	1	1	140	1.40	2.23
503B	1	2	10	1.58	2.08
503B	1	2	33	1.81	2.01
503B	1	2	53	2.01	2.07
503B	1	2	75	2.23	2.18
503B	1	2	85	2.33	1.94
503B	1	2	97	2.45	1.80
503B	2	1	75	3.53	2.33
503B	2	1	97	3.75	2.18
503B	2	2	28	4.57	2.14
503B	2	2	112	5.41	1.83
503B	3	1	37	7.55	1.69
503B	3	1	53	7.71	2.08
503B	3	1	70	7.88	1.86
503B	3	1	82	8.00	1.90
503B	3	1	107	8.25	2.12
503B	3	1	133	8.51	1.76
503B	3	2	10	8.78	1.44
503B	3	2	25	8.93	1.51
503B	3	3	26	10.44	1.65
503B	3	3	100	11.18	1.69
503B	4	1	105	12.65	1.59
503B	4	1	135	12.95	1.65
503B	4	2	8	13.06	1.59
503B	4	2	141	14.39	1.68
503B	4	3	13	14.62	1.52
503B	4	3	91	15.40	1.28
503B	5	1	85	16.85	1.67
503B	5	1	138	17.38	1.76
503B	5	2	12	17.43	1.50
503B	5	2	106	18.37	1.76
503B	5	3	4	18.85	2.06
503B	5	3	85	19.66	1.45
503B	6	1	33	20.62	2.30
503B	6	1	112	21.41	1.33
503B	6	2	82	22.58	1.49
503B	6	2	95	22.71	2.12
503B	6	3	14	23.41	1.93
503B	6	3	93	24.20	1.38

*** GRID N 02 ***

*** GRID B 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
503B	7	1	90	25.70	1.50
503B	7	1	138	26.18	1.83
503B	7	2	9	26.33	1.81
503B	7	2	131	27.55	1.66
503B	7	3	54	28.28	1.47
503B	7	3	103	28.77	1.84
503B	8	1	16	29.36	2.16
503B	8	1	138	30.58	1.44
503B	8	2	13	30.73	1.36
503B	8	2	146	32.06	1.63
503B	8	3	52	32.63	1.87
503B	8	3	80	32.91	1.71
503B	10	1	17	38.17	1.62
503B	10	1	126	39.26	1.68
503B	10	2	27	39.74	1.44
503B	10	2	137	40.84	1.52
503B	10	3	7	41.04	1.76
503B	10	3	85	41.82	1.64
503B	11	1	70	43.10	2.13
503B	11	1	109	43.49	1.98
503B	11	2	66	44.33	1.90
503B	11	2	144	45.11	2.02
503B	11	3	19	45.36	1.60
503B	11	3	91	46.08	1.78
503B	12	1	63	47.43	1.93
503B	12	1	141	48.21	1.69
503B	12	2	23	48.53	1.67
503B	12	2	136	49.66	1.75
503B	12	3	4	49.84	1.88
503B	12	3	80	50.54	1.48
503B	13	1	112	52.32	1.90
503B	13	1	140	52.60	1.76
503B	13	2	10	52.75	1.87
503B	13	2	140	54.05	1.53
503B	13	3	10	54.25	1.70
503B	13	3	49	54.64	1.46
503B	14	1	100	56.60	1.64
503B	14	1	138	56.98	1.59
503B	14	2	10	56.81	1.37
503B	14	2	140	58.11	1.59
503B	14	3	6	58.28	1.60
503B	14	3	78	59.00	1.77
503B	15	1	73	60.73	1.54
503B	15	1	146	61.46	1.64
503B	15	2	53	61.68	1.58
503B	15	2	136	62.51	1.44
503B	15	3	10	62.75	1.44
503B	15	3	75	63.40	1.45
503B	16	1	40	64.80	1.47
503B	16	1	137	65.77	1.69
503B	16	2	12	65.86	1.82
503B	16	2	135	67.09	1.55
503B	16	3	53	67.77	1.82

*** GRID B 03 ***

*** GRID C 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Penetration (x 0.1 mm)
503B	16	3	88	68.12	1.60
503B	17	1	37	69.17	1.73
503B	17	1	139	70.19	1.53
503B	17	2	13	70.34	1.45
503B	17	2	138	71.59	1.49
503B	17	3	22	71.93	1.85
503B	17	3	48	72.16	1.74
503B	18	1	23	73.43	1.51
503B	18	1	142	74.62	1.49
503B	18	2	10	74.80	1.51
503B	18	2	141	76.11	1.44
503B	18	3	13	76.34	1.53
503B	18	3	137	77.58	1.45
503B	19	1	102	78.62	1.69
503B	19	1	140	79.00	1.49
503B	19	2	42	79.33	1.52
503B	19	2	130	80.21	1.56
503B	19	3	6	80.47	1.66
503B	19	3	35	80.76	1.51
503B	20	2	50	82.50	1.64
503B	20	2	140	83.40	1.54
503B	20	3	15	83.62	1.43
503B	20	3	108	84.55	1.68
503B	21	1	95	87.35	1.93
503B	21	1	135	87.75	1.64
503B	21	2	10	87.95	1.59
503B	21	2	130	89.15	1.52
503B	21	3	43	89.78	1.49
503B	21	3	118	90.53	1.40
503B	22	2	22	92.27	1.58
503B	22	2	135	93.40	1.45
503B	22	3	5	93.60	1.60
503B	22	3	86	94.41	1.76
503B	24	1	85	100.45	1.88
503B	24	1	140	101.00	1.81
503B	24	2	25	100.90	1.61
503B	24	2	80	101.45	1.62
503B	25	2	7	105.11	1.58
503B	25	2	90	105.84	1.51
503B	26	2	18	109.43	1.56
503B	26	2	21	109.46	1.58
503B	26	2	96	110.21	1.62
503B	26	2	129	110.54	1.55

*** GRID C 03 ***

*** GRID D 03 ***

Table 3: Sonic Velocity

Sonic Velocity Data, Leg 68

*** GRID D 03 ***

*** GRID E 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502	1	CC	0	0.00	2.320
502	2	1	8	0.48	1.550
502	2	1	89	1.29	1.566
502	2	2	63	2.51	1.544
502	2	2	124	3.12	1.585
502	2	2	130	3.18	1.565
502	2	3	71	4.08	1.608
502	2	3	80	4.17	1.638
502	3	1	67	5.47	1.535
502	3	1	80	5.60	1.582
502	3	2	80	7.06	1.570
502	3	3	46	8.22	1.539
502	4	1	57	9.54	1.552
502	4	2	6	10.39	1.544
502	4	2	80	11.13	1.462
502	4	3	80	12.64	1.553
502	4	3	86	12.70	1.589
502	5	1	80	14.30	1.570
502	5	1	91	14.41	1.569
502	5	2	64	15.65	1.631
502	5	2	80	15.81	1.590
502	5	3	0	16.51	1.553
502	5	3	49	17.00	1.591
502	6	1	60	18.60	1.554
502	6	1	80	18.80	1.536
502	6	2	56	20.07	1.562
502	6	2	65	20.16	1.533
502	6	2	80	20.31	1.553
502	6	3	29	21.30	1.552
502	6	3	50	21.51	1.572
502	7	1	80	23.20	1.587
502	7	1	91	23.31	1.555
502	7	2	66	23.96	1.548
502	7	2	80	24.10	1.623
502	7	3	80	25.61	1.574
502	7	3	102	25.83	1.613
502	8	1	71	27.44	1.561
502	8	1	80	27.53	1.533
502	8	2	59	28.80	1.531
502	8	3	7	29.80	1.552
502	8	3	80	30.53	1.546
502	9	1	67	31.87	1.570
502	9	1	80	32.00	1.558
502	9	2	63	33.31	1.548
502	9	2	80	33.48	1.567
502	9	3	38	34.56	1.571
502	9	3	80	34.93	1.588
502	10	1	80	36.40	1.601
502	10	1	84	36.44	1.624
502	10	2	66	37.46	1.568
502	10	2	80	37.60	1.538
502	10	3	51	38.82	1.526
502	10	3	80	39.11	1.523

*** GRID E 03 ***

*** GRID F 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502	11	1	80	40.59	1.567
502	11	1	84	40.63	1.612
502	13	1	80	49.60	1.517
502	13	1	83	49.63	1.553
502	13	2	45	50.74	1.567
502	13	2	80	51.09	1.525
502	13	3	41	52.21	1.541
502	13	3	80	52.60	1.523
502	14	1	80	54.00	1.532
502	14	1	91	54.11	1.530
502	14	2	61	55.28	1.521
502	14	2	80	55.47	1.564
502	15	1	63	58.23	1.622
502	15	1	80	58.40	1.603
502	15	2	77	59.73	1.542
502	15	2	80	59.76	1.530
502	15	3	27	60.73	1.543
502	15	3	80	61.26	1.542
502	16	1	59	62.59	1.531
502	16	1	80	62.80	1.535
502	16	2	51	63.94	1.547
502	16	2	80	64.23	1.599
502	17	1	80	67.20	1.551
502	17	1	84	67.24	1.530
502	17	2	60	68.40	1.553
502	17	2	80	68.60	1.530
502	18	1	65	71.45	1.570
502	18	1	80	71.60	1.529
502	18	2	10	72.40	1.540
502	19	1	80	76.00	1.551
502	19	1	90	76.10	1.536
502	19	2	60	77.28	1.552
502	19	2	80	77.48	1.556
502	19	3	11	78.30	1.554
502	20	1	80	80.40	1.549
502	20	1	87	80.47	1.517
502	20	2	55	81.61	1.547
502	20	2	80	81.86	1.567
502	20	3	38	82.94	1.548
502	20	3	80	83.36	1.552
502	21	1	57	84.57	1.541
502	21	1	80	84.80	1.583
502	21	2	32	85.80	1.550
502	21	2	80	86.28	1.569
502	22	1	46	88.86	1.553
502	22	1	80	89.20	1.569
502	22	2	54	90.43	1.573
502	22	2	80	90.69	1.546
502	22	3	30	91.29	1.554
502	22	3	80	91.79	1.536
502	23	2	68	93.59	1.549
502	23	2	80	93.71	1.551
502	23	3	67	95.08	1.546

*** GRID F 03 ***

*** GRID G 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502	23	3	80	95.21	1.528
502	23	4	60	96.51	1.556
502	23	4	83	96.74	1.534
502	24	1	80	98.00	1.532
502	24	1	129	98.49	1.548
502	24	2	52	99.21	1.560
502	24	2	80	99.49	1.533
502	24	3	26	100.46	1.534
502	24	3	80	101.00	1.550
502	25	1	66	102.21	1.530
502	25	1	80	102.35	1.534
502	25	2	80	103.82	1.531
502	25	2	86	103.88	1.521
502	25	3	20	104.73	1.525
502	25	3	80	105.33	1.544
502	26	1	78	106.73	1.536
502	26	1	80	106.75	1.530
502	26	2	60	107.87	1.531
502	26	2	80	108.07	1.549
502	26	3	51	109.29	1.534
502	26	3	80	109.58	1.548
502	27	2	30	111.14	1.551
502	28	1	33	115.13	1.556
502	28	1	80	115.60	1.536
502	28	2	24	116.54	1.538
502	28	2	50	116.80	1.525
502	29	1	60	117.90	1.536
502	29	2	61	119.41	1.567
502	29	2	80	119.60	1.529
502	29	3	30	120.60	1.551
502	29	3	80	121.10	1.527
502	30	1	88	122.58	1.539
502	30	2	60	123.79	1.553
502	30	2	80	123.99	1.551
502	30	3	35	125.04	1.582
502	30	3	80	125.49	1.536
502	31	1	46	126.56	1.530
502	31	1	80	126.90	1.538
502	31	1	111	127.21	1.521
502	31	2	78	128.38	1.573
502	31	2	80	128.40	1.533
502	32	1	57	131.07	1.550
502	32	1	100	131.50	1.726
502	32	2	34	132.30	1.560
502	32	2	80	132.76	1.557
502	33	1	75	135.65	1.542
502	33	1	80	135.70	1.553
502	33	2	20	136.54	1.584
502	34	1	80	140.10	1.550
502	34	1	92	140.22	1.568
502	34	2	53	141.31	1.573
502	34	2	80	141.58	1.571
502	35	1	66	144.36	1.572

*** GRID G 03 ***

*** GRID H 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502	35	1	80	144.50	1.560
502	35	2	47	145.67	1.574
502	35	2	80	146.00	1.576
502	36	1	42	148.52	1.555
502	36	1	80	148.90	1.570
502	36	2	80	150.42	1.580
502	36	2	89	150.51	1.568
502	37	1	75	153.15	1.550
502	37	1	80	153.20	1.546
502	37	2	77	154.64	1.607
502	37	2	80	154.67	1.584
502	38	1	64	157.54	1.558
502	38	1	80	157.70	1.590
502	38	2	34	158.72	1.569
502	38	2	80	159.18	1.606
502	39	1	62	161.92	1.537
502	39	1	80	162.10	1.588
502	39	2	49	163.28	1.575
502	39	2	80	163.59	1.560
502	40	1	54	165.89	1.631
502	40	1	93	166.28	1.561
502	40	2	22	167.24	1.580
502	40	2	80	167.82	1.561
502	41	2	40	170.70	1.583
502	41	2	69	170.99	1.812
502	42	1	80	174.64	1.542
502	42	1	104	174.88	1.532
502	42	2	37	175.71	1.523
502	42	3	22	177.07	1.587
502	42	3	54	177.39	1.561
502	43	1	49	179.34	1.564
502	43	1	80	179.65	1.558
502	43	2	39	180.75	1.575
502	43	2	82	181.18	1.578
502	44	1	80	184.05	1.777
502	44	1	82	184.07	1.567
502	44	2	15	184.88	1.564
502	45	1	41	187.94	1.641
502	45	1	64	188.17	1.596
502	45	1	80	188.33	1.571
502	45	2	27	189.27	1.606
502	45	2	40	189.40	1.585
502	46	1	59	192.54	1.607
502	46	1	80	192.75	1.588
502	46	1	135	193.30	1.742
502	46	2	17	193.62	1.621
502	46	2	30	193.75	1.580
502	47	1	5	196.40	1.534
502	47	1	38	196.73	1.578
502	47	1	80	197.15	1.566
502	47	2	31	198.16	1.593
502	47	2	45	198.30	1.607
502	48	1	43	201.16	1.601

*** GRID H 03 ***

*** GRID I 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502	48	1	80	201.53	1.551
502	48	1	97	201.70	1.594
502	50	1	20	209.90	1.584
502A	1	1	14	0.14	1.539
502A	1	1	80	0.80	1.504
502A	1	1	97	0.97	1.518
502A	2	1	65	2.50	1.564
502A	2	1	80	2.65	1.571
502A	2	2	75	4.08	1.561
502A	2	2	80	4.13	1.555
502A	2	3	32	5.15	1.555
502A	2	3	80	5.63	1.587
502A	3	1	80	7.10	1.540
502A	3	1	81	7.11	1.539
502A	3	2	67	8.37	1.539
502A	3	2	80	8.50	1.524
502A	3	3	49	9.68	1.536
502A	3	3	80	9.99	1.517
502A	4	1	52	11.22	1.562
502A	4	1	80	11.50	1.548
502A	4	2	46	12.62	1.604
502A	4	2	80	12.96	1.616
502A	4	2	135	13.51	1.551
502A	4	3	36	14.02	1.571
502A	4	3	90	14.56	1.586
502A	5	1	80	15.90	1.555
502A	5	1	82	15.92	1.564
502A	5	2	59	17.14	1.574
502A	5	2	80	17.35	1.526
502A	5	3	15	18.20	2.161
502A	5	3	80	18.85	1.537
502A	6	1	72	20.09	1.549
502A	6	1	80	20.17	1.541
502A	6	2	42	21.00	1.565
502A	6	2	80	21.38	1.613
502A	6	2	83	21.41	1.591
502A	6	3	28	22.36	1.611
502A	6	3	80	22.88	1.634
502A	7	1	80	24.65	1.590
502A	7	2	76	25.90	1.589
502A	7	2	80	25.94	1.621
502A	7	3	42	27.06	1.567
502A	7	3	80	27.44	1.634
502A	8	1	80	28.98	1.584
502A	8	1	91	29.09	1.562
502A	8	2	64	30.14	1.567
502A	8	2	80	30.30	1.562
502A	9	1	10	32.80	1.544
502A	10	1	117	38.27	1.624
502A	10	2	65	39.25	1.604
502A	10	2	80	39.40	1.607
502A	10	3	44	40.54	1.557
502A	10	3	80	40.90	1.616

*** GRID I 03 ***

*** GRID J 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502A	11	1	15	41.65	1.532
502A	11	1	16	41.66	1.544
502A	12	1	80	46.60	1.543
502A	12	1	82	46.62	1.551
502A	12	1	107	46.87	1.575
502A	12	2	70	47.98	1.567
502A	12	2	80	48.08	1.576
502A	12	3	33	49.11	1.535
502A	12	3	38	49.16	1.545
502A	12	3	80	49.58	1.572
502A	13	1	12	50.42	1.525
502A	16	1	57	64.07	1.521
502A	16	1	80	64.30	1.520
502A	16	2	55	65.54	1.575
502A	16	2	80	65.79	1.560
502A	16	3	11	66.61	1.562
502A	16	3	30	66.80	1.571
502A	17	1	61	68.51	1.556
502A	17	1	80	68.70	1.510
502A	17	2	44	69.85	1.552
502A	17	2	80	70.21	1.559
502A	17	3	31	71.21	1.531
502A	17	3	80	71.70	1.519
502A	19	1	47	76.91	1.529
502A	19	1	80	77.24	1.514
502A	19	2	67	78.60	1.543
502A	19	2	80	78.73	1.530
502A	19	3	49	79.94	1.561
502A	19	3	80	80.25	1.587
502A	20	1	61	81.71	1.530
502A	20	1	80	81.90	1.557
502A	20	2	38	82.85	1.530
502A	20	2	80	83.27	1.536
502A	20	3	38	84.36	1.555
502A	20	3	80	84.78	1.547
502A	21	1	78	86.22	1.530
502A	21	1	80	86.24	1.539
502A	21	2	48	87.44	1.545
502A	21	2	80	87.76	1.554
502A	21	3	23	88.69	1.563
502A	21	3	80	88.93	1.539
502A	22	1	71	90.61	1.548
502A	22	1	80	90.70	1.532
502A	22	2	55	91.96	1.557
502A	22	2	80	92.21	1.517
502A	22	3	41	93.26	1.545
502A	22	3	80	93.71	1.544
502A	23	1	78	95.08	1.559
502A	23	1	80	95.10	1.543
502A	23	2	60	96.36	1.547
502A	23	2	80	96.56	1.531
502A	23	3	66	97.93	1.557
502A	23	3	80	98.07	1.549

*** GRID J 03 ***

*** GRID K 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502A	24	1	66	99.36	1.530
502A	24	1	80	99.50	1.526
502A	24	2	58	100.79	1.549
502A	24	2	80	101.01	1.549
502A	24	3	49	102.21	1.568
502A	24	3	80	102.52	1.554
502A	25	1	78	103.83	1.548
502A	25	1	80	103.85	1.548
502A	25	2	59	105.11	1.547
502A	25	2	80	105.32	1.558
502A	25	3	49	106.51	1.543
502A	25	3	80	106.82	1.541
502A	26	1	53	108.03	1.545
502A	26	1	80	108.30	1.546
502A	26	2	60	109.53	1.545
502A	26	2	80	109.73	1.522
502A	26	3	53	110.88	1.576
502A	26	3	80	111.15	1.542
502A	27	1	79	112.69	1.549
502A	27	1	80	112.70	1.541
502A	27	2	60	114.00	1.550
502A	27	2	80	114.20	1.509
502A	27	3	34	115.24	1.564
502A	27	3	80	115.70	1.553
502A	28	1	59	116.77	1.562
502A	28	1	80	116.98	1.540
502A	28	2	54	118.18	1.564
502A	28	2	80	118.44	1.560
502A	29	1	80	120.10	1.529
502A	29	1	81	120.11	1.540
502A	29	2	67	121.47	1.564
502A	29	2	80	121.60	1.553
502A	29	3	20	122.50	1.536
502A	30	1	90	123.70	1.521
502A	30	1	93	123.73	1.524
502A	30	2	61	124.89	1.547
502A	30	2	80	125.08	1.525
502A	32	1	64	128.94	1.570
502A	32	1	80	129.10	1.515
502A	32	1	92	129.22	1.541
502A	32	2	26	130.08	1.867
502A	32	2	37	130.19	1.521
502A	32	2	52	130.34	1.649
502A	32	2	70	130.52	1.555
502A	32	2	80	130.62	1.533
502A	32	3	11	131.44	1.578
502A	33	1	76	132.06	1.551
502A	33	1	80	132.10	1.547
502A	33	2	60	133.37	1.588
502A	33	2	80	133.57	1.560
502A	34	1	66	134.96	1.540
502A	34	1	80	135.10	1.530
502A	34	2	56	136.36	1.545

*** GRID K 03 ***

*** GRID L 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502A	34	2	80	136.60	1.567
502A	35	1	67	137.52	1.559
502A	35	1	80	137.65	1.554
502A	35	2	53	138.88	1.569
502A	35	2	80	139.15	1.542
502A	35	3	41	140.26	1.556
502A	35	3	80	140.65	1.520
502A	36	1	36	141.04	1.526
502A	36	1	80	141.48	1.521
502A	36	2	26	142.44	1.516
502A	36	2	80	142.98	1.536
502A	37	1	102	143.52	1.552
502A	37	2	39	144.33	1.552
502A	37	2	80	144.74	1.534
502A	38	1	58	146.06	1.559
502A	38	1	80	146.28	1.493
502A	38	2	16	147.14	1.586
502A	39	1	57	147.67	1.554
502A	39	1	80	147.90	1.564
502A	39	2	46	149.06	1.568
502A	39	2	80	149.40	1.558
502A	40	1	56	150.74	1.566
502A	40	1	80	150.98	1.558
502A	40	2	55	152.23	1.580
502A	40	2	80	152.48	1.549
502A	41	1	78	152.98	1.560
502A	41	2	57	154.27	1.579
502A	41	2	80	154.50	1.562
502A	41	3	12	155.32	1.574
502A	42	1	55	156.35	1.551
502A	42	1	80	156.60	1.529
502A	42	2	51	157.81	1.569
502A	42	2	80	158.10	1.516
502A	43	1	74	159.04	1.562
502A	43	1	80	159.10	1.061
502A	43	2	42	160.17	1.540
502A	44	1	63	161.64	1.575
502A	44	1	80	161.81	1.553
502A	44	1	130	162.31	1.615
502A	44	2	45	162.85	1.583
502A	44	2	78	163.18	1.567
502A	45	1	56	164.24	1.561
502A	45	1	80	164.48	1.583
502A	45	2	49	165.68	1.585
502A	45	2	78	165.96	1.565
502A	46	1	67	166.73	1.566
502A	46	1	80	166.86	1.553
502A	46	2	36	167.77	1.559
502A	46	2	60	168.01	1.547
502A	47	1	53	168.51	1.560
502A	47	2	66	170.14	1.572
502A	47	2	80	170.28	1.561
502A	48	1	52	171.65	1.584

*** GRID L 03 ***

*** GRID M 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502A	48	1	80	171.93	1.567
502A	48	2	25	172.88	1.597
502A	50	1	70	175.90	1.581
502A	50	1	88	176.08	1.569
502A	50	2	18	176.84	1.581
502A	50	2	60	177.26	1.524
502A	51	1	42	178.72	1.556
502A	51	1	80	179.10	1.553
502A	51	1	107	179.37	1.586
502A	51	2	25	180.05	1.579
502A	51	2	50	180.30	1.598
502A	52	1	60	181.22	1.555
502A	52	1	80	181.42	1.596
502A	52	2	13	182.27	1.583
502A	53	1	60	183.10	1.574
502A	53	1	80	183.30	1.553
502A	54	1	53	185.13	1.540
502A	54	1	80	185.40	1.549
502A	54	2	32	186.42	1.591
502A	54	2	80	186.90	1.556
502A	55	1	53	187.69	1.555
502A	55	1	80	187.96	1.561
502A	55	2	30	188.95	1.537
502A	55	2	48	189.13	1.565
502A	56	1	59	189.56	1.578
502A	56	1	80	189.77	1.558
502A	56	2	27	190.75	1.606
502A	56	2	45	190.93	1.573
502A	57	1	61	191.71	1.577
502A	57	1	79	191.89	1.693
502A	57	2	29	192.89	1.593
502A	57	2	40	193.00	1.652
502A	58	1	63	193.69	1.596
502A	58	1	80	193.86	1.569
502A	58	2	31	194.91	1.589
502A	58	2	50	195.10	1.592
502A	60	1	58	197.83	1.618
502A	60	1	80	198.05	1.640
502A	60	2	5	198.77	1.580
502A	61	1	63	199.51	1.574
502A	61	1	82	199.70	1.595
502A	62	1	36	201.50	1.632
502A	63	1	65	203.74	1.559
502A	63	1	80	203.89	1.583
502A	65	1	63	207.73	1.570
502A	65	2	20	208.82	1.554
502A	65	2	32	208.94	1.586
502A	66	1	80	209.95	1.581
502A	66	1	84	209.99	1.596
502A	66	2	13	210.68	1.585
502A	67	1	36	211.37	1.559
502A	68	1	57	213.37	1.556
502A	68	2	11	214.39	1.553

*** GRID M 03 ***

*** GRID N 03 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502B	1	1	35	0.35	1.535
502B	1	1	80	0.76	1.556
502B	1	1	80	0.76	1.567
502B	2	1	44	2.14	1.581
502B	2	2	48	3.62	1.544
502B	2	2	80	3.94	1.589
502B	2	3	25	4.89	1.599
502B	2	3	30	4.94	1.612
502B	3	1	60	6.75	1.564
502B	3	1	70	6.85	1.617
502B	3	2	52	8.12	1.575
502B	3	2	80	8.40	1.570
502B	3	3	42	9.52	1.594
502B	3	3	80	9.90	1.598
502B	4	1	80	11.35	1.589
502B	4	1	84	11.39	1.611
502B	4	2	58	12.62	1.557
502B	4	2	80	12.84	1.565
502B	4	3	75	14.29	1.591
502B	4	3	80	14.34	1.610
502B	5	1	80	15.65	1.609
502B	5	2	35	16.65	1.544
502B	5	2	75	17.05	1.558
502B	5	3	30	17.83	1.559
502B	5	3	80	18.33	1.599
502B	6	1	52	19.87	1.533
502B	6	1	80	20.15	1.614
502B	6	2	55	21.41	1.568
502B	6	2	80	21.66	1.622
502B	6	3	67	23.01	1.607
502B	6	3	80	23.14	1.567
502B	7	2	65	24.68	1.624
502B	7	2	80	24.83	1.598
502B	7	3	57	26.09	1.621
502B	7	3	80	26.32	1.591
502B	7	4	48	27.51	1.612
502B	7	4	80	27.83	1.630
502B	8	1	83	28.98	1.590
502B	8	1	95	29.10	1.585
502B	8	2	34	29.88	1.569
502B	8	2	100	30.11	1.606
502B	8	3	43	31.00	1.627
502B	8	3	80	31.37	1.586
502B	9	1	80	33.20	1.604
502B	9	1	83	33.23	1.585
502B	9	2	51	34.37	1.637
502B	9	2	85	34.71	1.599
502B	9	3	45	35.68	1.597
502B	9	3	45	35.68	1.597
502B	10	1	93	37.88	1.589
502B	11	1	62	41.97	1.545
502B	11	1	80	42.15	1.561
502B	11	2	64	43.48	1.560

*** GRID N 03 ***

*** GRID B 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502B	11	2	70	43.54	1.573
502B	11	3	35	44.70	1.586
502B	11	3	80	45.15	1.537
502B	12	3	19	48.54	1.535
502B	13	1	63	50.78	1.563
502B	13	1	80	50.95	1.575
502B	13	2	79	52.44	1.559
502B	13	2	80	52.45	1.570
502B	13	3	24	53.40	1.558
502B	13	3	80	53.96	1.545
502B	14	1	75	55.20	1.537
502B	14	1	80	55.25	1.569
502B	14	2	57	56.52	1.573
502B	14	2	63	56.58	1.621
502B	14	3	59	58.02	1.559
502B	14	3	80	58.23	1.581
502B	15	1	54	59.49	1.547
502B	15	1	62	59.57	1.589
502B	15	1	70	59.65	1.557
502B	16	1	70	63.82	1.554
502B	17	1	50	68.25	1.538
502B	17	2	46	69.71	1.550
502B	17	2	70	69.95	1.513
502B	17	3	32	71.07	1.569
502B	17	3	80	71.55	1.538
502B	18	1	74	72.89	1.560
502B	18	1	80	72.95	1.540
502B	18	2	54	74.18	1.539
502B	18	2	80	74.44	1.596
502B	18	3	50	75.64	1.557
502B	18	3	80	75.94	1.581
502B	19	1	41	76.96	1.562
502B	19	1	80	77.35	1.551
502B	19	2	74	78.79	1.571
502B	19	2	80	78.85	1.588
502B	19	3	37	79.93	1.535
502B	19	3	80	80.36	1.560
502B	20	1	64	81.59	1.548
502B	20	1	80	81.75	1.549
502B	20	2	71	83.16	1.554
502B	20	2	80	83.25	1.580
502B	20	3	72	84.67	1.565
502B	20	3	80	84.75	1.560
502B	21	1	67	85.95	1.562
502B	21	1	80	86.08	1.546
502B	21	2	57	87.36	1.550
502B	21	2	80	87.59	1.556
502B	21	3	80	89.04	1.560
502B	22	2	58	90.50	1.565
502B	22	2	80	90.72	1.572
502B	22	3	80	92.22	1.586
502B	22	3	85	92.27	1.584
502B	22	4	39	93.31	1.571

*** GRID B 04 ***

*** GRID C 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502B	22	4	80	93.72	1.557
502B	23	1	82	94.65	1.539
502B	23	2	80	96.13	1.541
502B	23	3	11	96.94	1.559
502B	23	3	15	96.98	1.547
502C	1	2	74	32.86	1.572
502C	1	3	45	33.91	1.543
502C	1	3	50	33.96	1.559
502C	1	4	57	35.51	1.570
502C	1	4	80	35.74	1.538
502C	2	1	73	37.08	1.553
502C	2	1	80	37.15	1.562
502C	2	2	80	38.61	1.580
502C	2	2	83	38.64	1.560
502C	2	3	33	39.64	1.575
502C	2	3	80	40.11	1.579
502C	3	1	70	41.50	1.545
502C	3	1	80	41.60	1.513
502C	3	2	59	42.87	1.579
502C	3	2	80	43.08	1.561
502C	3	3	20	43.98	1.580
502C	3	3	22	44.00	1.559
502C	4	1	93	46.03	1.555
502C	4	1	130	46.40	1.603
502C	4	2	12	46.24	1.583
502C	4	2	35	46.47	1.543
502C	5	1	52	50.12	1.554
502C	5	1	80	50.40	1.575
502C	5	2	49	51.58	1.568
502C	5	2	80	51.89	1.563
502C	5	3	45	53.04	1.615
502C	5	3	80	53.39	1.576
502C	6	2	69	54.84	1.563
502C	6	2	80	54.95	1.564
502C	6	3	65	56.30	1.574
502C	6	3	80	56.45	1.586
502C	6	4	45	57.60	1.565
502C	6	4	80	57.95	1.555
502C	7	1	48	58.71	1.537
502C	7	1	70	58.93	1.543
502C	8	1	71	63.51	1.554
502C	8	1	80	63.60	1.553
502C	8	2	46	64.70	1.555
502C	8	2	80	65.04	1.593
502C	8	3	41	66.15	1.551
502C	8	3	80	66.54	1.558
502C	9	1	80	68.00	1.544
502C	9	1	84	68.04	1.564
502C	9	2	44	69.14	1.587
502C	9	2	80	69.50	1.552
502C	9	3	48	70.68	1.561
502C	9	3	80	71.00	1.657
502C	10	1	100	72.60	1.573

*** GRID C 04 ***

*** GRID D 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502C	10	1	101	72.61	1.566
502C	10	2	59	73.67	1.522
502C	10	2	80	73.88	1.576
502C	10	3	40	74.99	1.570
502C	10	3	80	75.39	1.571
502C	11	1	80	76.80	1.568
502C	11	1	82	76.82	1.563
502C	11	2	75	78.22	1.584
502C	11	2	80	78.27	1.569
502C	11	3	27	79.24	1.578
502C	11	3	80	79.77	1.580
502C	12	1	78	80.73	1.540
502C	12	1	80	80.75	1.551
502C	12	2	19	81.68	1.544
502C	12	2	20	81.69	1.568
502C	13	1	80	85.60	1.544
502C	13	1	103	85.83	1.548
502C	13	2	56	86.84	1.532
502C	13	2	80	87.08	1.551
502C	13	3	52	88.30	1.538
502C	13	3	80	88.58	1.656
502C	14	1	47	89.67	1.547
502C	14	1	80	90.00	1.586
502C	14	2	45	91.12	1.560
502C	14	2	80	91.47	1.553
502C	14	3	45	92.62	1.565
502C	14	3	80	92.97	1.556
502C	15	1	52	94.12	1.533
502C	15	1	80	94.40	1.553
502C	15	2	42	95.50	1.563
502C	15	2	80	95.88	1.562
502C	15	3	48	97.06	1.546
502C	15	3	80	97.38	1.572
502C	16	1	67	98.67	1.537
502C	16	1	80	98.80	1.523
502C	16	2	51	100.00	1.523
502C	16	2	80	100.29	1.549
502C	16	3	40	101.39	1.556
502C	16	3	80	101.79	1.552
502C	17	1	79	102.89	1.544
502C	17	1	80	102.90	1.525
502C	17	2	47	104.07	1.548
502C	17	2	80	104.40	1.551
502C	17	3	75	105.85	1.544
502C	18	1	65	107.52	1.556
502C	18	1	80	107.67	1.539
502C	18	2	51	108.74	1.556
502C	18	2	80	109.03	1.549
502C	18	3	27	110.00	1.579
502C	18	3	50	110.23	1.566
502C	19	1	42	111.62	1.538
502C	19	1	80	112.00	1.547
502C	19	2	10	112.80	1.533

*** GRID D 04 ***

*** GRID E 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
502C	19	2	14	112.84	1.529
502C	20	1	69	116.29	1.557
502C	20	1	80	116.40	1.536
502C	20	2	69	117.79	1.531
502C	20	2	80	117.90	1.559
502C	20	3	20	118.80	1.552
502C	20	3	28	118.88	1.548
502C	21	1	35	120.35	1.532
502C	21	1	80	120.80	1.526
502C	21	2	68	122.18	1.530
502C	21	2	80	122.30	1.458
502C	21	3	45	122.96	1.540
502C	21	3	50	123.01	1.510
502C	22	1	26	124.66	1.550
502C	22	1	50	124.90	1.540
502C	23	2	80	127.42	1.551
502C	23	2	89	127.51	1.533
502C	23	2	106	127.68	1.760
502C	23	2	117	127.79	1.561
502C	23	2	131	127.93	1.721
502C	23	3	88	129.00	1.577
502C	24	1	70	130.50	1.541
502C	24	1	80	130.60	1.564
502C	24	2	46	131.71	1.548
502C	24	2	80	132.05	1.557
502C	24	3	20	132.95	1.564
502C	25	1	48	134.58	1.571
502C	25	1	80	134.90	1.538
502C	26	1	125	138.30	1.563
502C	26	1	135	138.40	1.553
502C	26	2	38	138.93	1.570
502C	26	2	80	139.35	1.558
502C	27	1	80	141.82	1.568
502C	27	1	84	141.86	1.551
502C	27	2	68	142.53	1.574
502C	28	1	90	211.10	1.543
502C	28	2	17	211.88	1.551
502C	29	1	68	213.88	1.553
502C	29	2	25	214.95	1.571
502C	30	1	129	215.99	1.540
502C	31	2	37	218.17	1.572
502C	33	1	90	222.60	1.556
502C	33	2	17	223.34	1.585
502C	33	2	48	223.65	1.623
502C	34	1	83	224.03	1.553
502C	35	1	74	226.26	1.551
503	1	1	32	0.32	1.485
503	1	2	65	2.15	1.510
503	1	3	67	3.66	1.521
503A	1	1	10	0.10	1.523
503A	1	1	60	0.60	1.522
503A	1	1	122	1.22	1.510
503A	2	1	80	2.60	1.518

*** GRID E 04 ***

*** GRID F 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
503A	2	1	80	2.60	1.506
503A	2	1	113	2.93	1.511
503A	2	1	130	3.10	1.528
503A	2	2	39	3.62	1.511
503A	2	2	78	4.01	1.514
503A	2	3	53	5.14	1.510
503A	2	3	68	5.25	1.490
503A	4	1	39	10.89	1.511
503A	4	2	98	12.02	1.524
503A	4	2	126	12.30	1.523
503A	4	3	21	12.45	1.499
503A	5	1	18	15.18	1.507
503A	5	1	80	15.80	1.509
503A	5	1	96	15.96	1.530
503A	5	2	34	16.85	1.532
503A	5	2	125	17.76	1.511
503A	5	3	26	18.27	1.516
503A	5	3	41	18.42	1.533
503A	5	3	56	18.57	1.516
503A	7	1	130	24.65	1.546
503A	7	1	139	24.74	1.534
503A	7	2	68	25.43	1.518
503A	7	3	38	26.75	1.521
503A	7	3	80	27.17	1.499
503A	7	3	99	27.36	1.508
503A	9	1	80	33.32	1.531
503A	9	1	85	33.37	1.530
503A	9	2	74	34.69	1.531
503A	9	3	57	35.72	1.535
503A	9	3	63	35.78	1.541
503A	10	1	82	37.82	3.133
503A	10	1	96	37.96	1.515
503A	10	1	97	37.97	1.509
503A	10	2	50	38.90	1.524
503A	10	3	30	40.23	1.554
503A	10	3	60	40.53	1.514
503A	11	1	92	42.22	1.519
503A	11	2	67	43.50	1.533
503A	11	2	80	43.63	1.524
503A	11	3	39	44.72	1.513
503A	11	3	80	45.13	1.505
503A	12	1	80	46.49	1.540
503A	12	1	83	46.52	1.521
503A	12	2	76	47.96	1.518
503A	12	3	48	49.18	1.528
503A	12	3	80	49.50	1.531
503A	13	1	124	51.44	1.511
503A	13	1	130	51.50	1.507
503A	13	2	72	52.32	1.516
503A	13	3	57	53.67	1.508
503A	13	3	80	53.90	1.518
503A	14	2	72	56.02	1.508
503A	14	3	40	57.20	1.523

*** GRID F 04 ***

*** GRID G 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
503A	14	3	80	57.60	1.525
503A	15	2	89	61.39	1.516
503A	15	3	41	62.41	1.510
503A	15	3	80	62.80	1.528
503A	16	1	131	64.71	1.521
503A	16	2	118	65.62	1.535
503A	16	3	26	66.17	1.504
503A	19	1	80	77.20	1.520
503A	19	1	86	77.26	1.516
503A	19	2	121	78.98	1.519
503A	19	3	3	79.02	1.521
503A	20	1	91	81.66	1.526
503A	20	1	128	82.03	1.509
503A	20	2	107	83.40	1.520
503A	20	2	140	83.73	1.503
503A	20	3	25	84.09	1.496
503A	20	3	80	84.64	1.502
503A	20	3	137	85.21	1.525
503A	21	1	80	86.20	1.525
503A	21	1	131	86.71	1.520
503A	21	2	83	87.73	1.515
503A	21	3	78	89.19	1.516
503A	21	3	80	89.21	1.511
503A	23	1	31	94.51	1.503
503A	23	2	75	96.35	1.510
503A	24	1	130	99.90	1.509
503A	24	1	137	99.97	1.505
503A	24	2	78	100.89	1.522
503A	24	2	107	101.18	1.503
503A	24	3	17	101.80	1.503
503A	24	3	80	102.43	1.515
503A	29	1	80	121.40	1.524
503A	29	1	86	121.46	1.504
503A	29	2	75	122.85	1.502
503A	29	3	33	123.94	1.525
503A	29	3	80	124.41	1.517
503A	30	1	80	125.72	1.496
503A	30	1	89	125.81	1.508
503A	30	2	53	126.86	1.495
503A	31	1	80	130.20	1.522
503A	31	1	87	130.27	1.513
503A	31	2	38	131.23	1.513
503A	31	3	65	133.00	1.505
503A	31	3	80	133.15	1.519
503A	34	2	131	145.14	1.523
503A	34	3	15	145.49	1.513
503A	35	1	79	147.67	1.555
503A	36	1	80	152.12	1.504
503A	36	1	81	152.13	1.504
503A	36	2	80	153.63	1.509
503A	36	3	22	154.41	1.503
503A	37	1	103	156.74	1.498
503A	37	2	53	157.77	1.500

*** GRID G 04 ***

*** GRID H 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
503A	39	2	10	166.00	1.500
503A	40	1	62	169.38	1.510
503A	40	1	80	169.56	1.503
503A	41	1	68	174.08	1.505
503A	41	1	80	174.20	1.507
503A	41	2	91	175.81	1.502
503A	41	3	49	176.90	1.503
503A	41	3	80	177.21	1.524
503A	42	1	100	178.80	1.527
503A	42	1	107	178.87	1.530
503A	42	2	75	180.06	1.508
503A	42	3	40	181.22	1.507
503A	42	3	44	181.23	1.522
503A	43	1	80	183.00	1.526
503A	43	1	86	183.06	1.524
503A	43	2	99	184.64	1.530
503A	43	3	17	185.33	1.506
503A	44	1	80	187.40	1.516
503A	44	1	89	187.49	1.529
503A	44	2	69	188.80	1.514
503A	44	3	33	189.94	1.516
503A	44	3	80	190.41	1.524
503A	48	1	80	204.72	1.525
503A	48	1	83	204.75	1.505
503A	48	2	87	206.29	1.521
503A	48	3	40	207.30	1.511
503A	49	1	88	209.48	1.508
503A	49	2	19	210.25	1.507
503A	49	2	20	210.26	1.512
503A	50	1	80	213.80	1.532
503A	50	1	110	214.10	1.510
503A	50	2	90	215.30	1.514
503A	50	3	56	216.46	1.536
503A	51	1	67	218.07	1.522
503A	51	1	80	218.20	1.516
503A	51	2	77	219.55	1.519
503A	51	3	12	220.40	1.523
503A	52	1	79	222.59	1.540
503A	52	1	80	222.60	1.533
503A	52	2	30	223.61	1.566
503A	52	3	38	225.19	1.533
503A	53	1	83	227.03	1.530
503A	53	2	105	228.71	1.535
503A	53	3	20	229.40	1.535
503A	54	1	73	231.33	1.557
503A	54	2	67	232.78	1.535
503A	54	3	14	233.76	1.515
503A	54	3	80	234.42	1.516
503B	1	1	78	0.78	1.510
503B	1	1	84	0.84	1.502
503B	1	2	51	1.99	1.501
503B	1	2	83	2.31	1.515
503B	2	1	44	3.22	1.514

*** GRID H 04 ***

*** GRID I 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
503B	2	1	70	3.48	1.509
503B	2	1	81	3.59	1.503
503B	2	2	61	4.90	1.512
503B	2	2	81	5.10	1.522
503B	3	1	81	7.99	1.517
503B	3	1	83	8.01	1.516
503B	3	2	19	8.87	1.527
503B	3	2	108	9.76	1.514
503B	3	3	31	10.49	1.541
503B	4	1	73	12.33	1.512
503B	4	2	81	13.79	1.527
503B	4	3	31	14.80	1.532
503B	4	3	81	15.30	1.535
503B	5	1	81	16.81	1.538
503B	5	1	107	17.07	1.525
503B	5	2	34	17.65	1.528
503B	5	3	70	19.51	1.543
503B	5	3	81	19.62	1.518
503B	6	1	112	21.41	1.536
503B	6	1	131	21.60	1.544
503B	6	2	59	22.35	1.526
503B	6	3	80	24.07	1.545
503B	6	3	83	24.10	1.541
503B	7	1	91	25.71	1.501
503B	7	1	93	25.73	1.556
503B	7	2	81	27.05	1.519
503B	7	3	24	27.98	1.525
503B	7	3	61	28.35	1.528
503B	8	1	81	30.01	1.539
503B	8	1	101	30.21	1.519
503B	8	2	61	31.21	1.536
503B	8	3	20	32.31	1.521
503B	8	3	81	32.92	1.531
503B	10	1	81	38.81	1.542
503B	10	1	98	38.98	1.515
503B	10	2	48	39.95	1.521
503B	10	3	58	41.55	1.528
503B	10	3	81	41.78	1.515
503B	11	1	81	43.21	1.518
503B	11	1	103	43.43	1.527
503B	11	2	103	44.70	1.542
503B	11	3	47	45.64	1.511
503B	12	1	81	47.61	1.535
503B	12	1	122	48.02	1.548
503B	12	2	125	49.55	1.516
503B	12	3	51	50.31	1.521
503B	12	3	81	50.55	1.531
503B	13	1	118	52.38	1.522
503B	13	1	121	52.41	1.515
503B	13	2	88	53.53	1.516
503B	13	3	19	54.34	1.525
503B	13	3	24	54.39	1.539
503B	14	1	81	56.41	1.517

*** GRID I 04 ***

*** GRID J 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Velocity (km/s)
503B	14	1	119	56.79	1.512
503B	14	2	99	57.70	1.535
503B	14	3	42	58.64	1.530
503B	14	3	81	59.03	1.532
503B	15	1	81	60.81	1.532
503B	15	1	101	61.01	1.524
503B	15	2	55	61.70	1.513
503B	15	3	58	63.23	1.519
503B	15	3	81	63.46	1.540
503B	16	1	81	65.21	1.530
503B	16	1	118	65.58	1.503
503B	16	2	127	67.01	1.497
503B	16	3	28	67.52	1.518
503B	16	3	81	68.05	1.531
503B	17	1	81	69.61	1.521
503B	17	1	81	69.61	1.519
503B	17	2	58	70.79	1.516
503B	17	3	34	72.05	1.521
503B	18	1	81	74.01	1.524
503B	18	1	96	74.16	1.520
503B	18	2	69	75.39	1.503
503B	18	2	81	75.51	1.520
503B	18	3	86	77.07	1.525
503B	18	3	93	77.14	1.514
503B	18	3	93	77.14	1.514
503B	19	1	122	78.82	1.520
503B	19	1	131	78.91	1.522
503B	19	1	131	78.91	1.522
503B	19	1	131	78.91	1.522
503B	19	2	59	79.50	1.527
503B	19	2	68	79.59	1.525
503B	19	3	30	80.71	1.524
503B	20	2	90	82.90	1.528
503B	20	3	46	83.93	1.530
503B	20	3	81	84.28	1.502
503B	20	3	100	84.47	1.514
503B	21	1	81	87.21	1.510
503B	21	1	127	87.67	1.525
503B	21	2	58	88.43	1.523
503B	21	3	87	90.22	1.518
503B	22	2	104	93.09	1.517
503B	22	3	8	93.63	1.508
503B	22	3	65	94.20	1.508
503B	22	3	71	94.26	1.520
503B	24	1	81	100.41	1.521
503B	24	1	130	100.90	1.526
503B	25	2	17	105.21	1.522
503B	25	2	17	105.21	1.522
503B	26	2	119	110.44	1.500

*** GRID J 04 ***

*** GRID K 04 ***

Table 4: Gravimetric Chemistry

Gravimetric Chemistry Data, Leg 68

*** GRID K 04 ***

*** GRID L 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Water Content	Porosity	Density (gm/cc)	Grain Density (gm/cc)
502	2	1	75 - 77	1.16	49.01	72.65	1.482	2.763
502	2	2	80 - 82	2.69	48.12	72.10	1.498	2.786
502	2	3	80 - 82	4.18	45.98	69.87	1.520	2.724
502	3	1	80 - 82	5.61	49.55	73.08	1.475	2.764
502	3	2	80 - 82	7.07	45.80	69.68	1.521	2.719
502	3	3	80 - 82	8.57	46.84	70.63	1.508	2.730
502	4	1	80 - 82	9.78	47.46	71.28	1.502	2.748
502	4	2	80 - 82	11.14	46.33	70.21	1.515	2.730
502	4	3	80 - 82	12.65	43.72	68.13	1.558	2.752
502	5	1	80 - 82	14.31	48.67	72.16	1.483	2.734
502	5	2	80 - 82	15.82	40.46	65.35	1.615	2.776
502	5	3	80 - 82	17.32	43.44	67.97	1.565	2.763
502	6	1	80 - 82	18.81	46.18	70.32	1.523	2.760
502	6	2	80 - 82	20.32	46.29	70.28	1.518	2.745
502	6	3	50 - 52	21.52	46.94	70.79	1.508	2.738
502	7	1	80 - 82	23.21	45.14	69.36	1.537	2.751
502	7	2	80 - 82	24.11	47.13	70.79	1.502	2.718
502	7	3	80 - 82	25.62	43.39	67.74	1.561	2.740
502	8	1	80 - 82	27.54	44.47	68.61	1.543	2.728
502	8	2	78 - 80	29.00	44.82	68.86	1.536	2.722
502	8	3	80 - 82	30.54	46.65	70.81	1.518	2.773
502	9	1	80 - 82	32.01	47.53	71.55	1.505	2.776
502	9	2	80 - 82	33.49	44.24	68.59	1.550	2.752
502	9	3	80 - 82	34.94	47.59	70.94	1.491	2.688
502	10	1	80 - 82	36.41	50.39	73.53	1.459	2.735
502	10	2	80 - 82	37.61	52.79	75.23	1.425	2.716
502	10	3	80 - 82	39.12	49.51	72.69	1.468	2.715
502	11	1	80 - 82	40.60	47.42	70.84	1.494	2.694
502	13	1	80 - 82	49.61	46.11	69.83	1.514	2.705
502	13	2	80 - 82	51.10	41.68	66.13	1.586	2.731
502	13	3	80 - 82	52.61	46.11	69.92	1.516	2.717
502	14	1	80 - 82	54.01	45.10	69.63	1.544	2.791
502	14	2	80 - 82	55.48	46.05	69.71	1.514	2.695
502	15	1	80 - 82	58.41	45.54	68.99	1.515	2.661
502	15	2	80 - 82	59.77	44.73	69.18	1.547	2.775
502	15	3	80 - 82	61.27	46.72	70.21	1.503	2.687
502	16	1	80 - 82	62.81	42.84	66.67	1.556	2.669
502	16	2	80 - 82	64.24	41.69	65.86	1.580	2.698
502	17	1	80 - 82	67.21	43.56	68.08	1.563	2.763
502	17	2	80 - 82	68.61	41.37	65.29	1.578	2.665
502	18	1	80 - 82	71.61	42.04	66.28	1.577	2.710
502	19	1	80 - 82	76.01	45.70	69.27	1.516	2.679
502	19	2	80 - 82	77.49	41.87	66.25	1.582	2.725
502	20	1	80 - 82	80.41	41.06	65.43	1.594	2.717
502	20	2	80 - 82	81.87	41.94	66.38	1.583	2.733
502	20	3	80 - 82	83.37	40.42	65.26	1.614	2.768
502	21	1	80 - 82	84.81	39.24	64.06	1.633	2.761
502	21	2	80 - 82	86.29	37.54	62.10	1.654	2.726
502	22	1	80 - 82	89.21	39.29	63.77	1.623	2.720
502	22	2	80 - 82	90.70	42.60	67.05	1.574	2.742
502	22	3	80 - 82	91.80	40.62	65.09	1.603	2.726
502	23	2	80 - 82	93.72	40.46	64.95	1.605	2.728
502	23	3	80 - 82	95.22	41.85	66.21	1.582	2.722

*** GRID L 04 ***

*** GRID M 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Water Content	Porosity	Density (gm/cc)	Grain Density (gm/cc)
502	23	4	80 - 82	96.72	41.27	65.06	1.576	2.649
502	24	1	80 - 82	98.01	43.06	67.22	1.561	2.712
502	24	2	80 - 82	99.50	41.49	65.66	1.582	2.696
502	24	3	80 - 82	101.01	38.24	62.64	1.638	2.708
502	25	1	80 - 82	102.36	40.85	65.14	1.595	2.706
502	25	2	80 - 82	103.83	38.90	63.50	1.632	2.732
502	25	3	80 - 82	105.34	39.52	63.65	1.610	2.679
502	26	1	80 - 82	106.76	41.28	65.71	1.592	2.727
502	26	2	80 - 82	108.08	41.79	66.25	1.585	2.734
502	26	3	80 - 82	109.59	38.92	62.76	1.612	2.644
502	28	1	80 - 82	115.61	40.06	64.65	1.614	2.737
502	28	2	50 - 52	116.81	38.29	63.04	1.646	2.749
502	29	2	80 - 82	119.61	40.51	65.30	1.612	2.763
502	29	3	80 - 82	121.11	39.43	63.98	1.623	2.728
502	30	1	80 - 82	122.51	38.78	63.59	1.640	2.757
502	30	2	80 - 82	124.00	38.15	62.79	1.646	2.736
502	30	3	80 - 82	125.50	40.61	65.09	1.603	2.726
502	31	1	80 - 82	126.91	39.71	64.40	1.622	2.747
502	31	1	111 - 113	127.22	48.73	72.87	1.495	2.826
502	31	2	80 - 82	128.41	41.24	65.00	1.576	2.647
502	32	1	80 - 82	131.31	46.64	70.76	1.517	2.768
502	32	1	100 - 101	131.51	48.05	72.03	1.499	2.785
502	32	2	80 - 82	132.77	41.62	67.02	1.610	2.851
502	33	1	80 - 82	135.71	41.06	65.63	1.598	2.741
502	33	2	20 - 22	136.55	39.77	64.31	1.617	2.730
502	34	1	80 - 82	140.11	39.62	64.38	1.625	2.754
502	34	2	80 - 82	141.59	37.57	62.42	1.661	2.760
502	35	1	80 - 82	144.51	41.11	65.85	1.602	2.762
502	35	2	80 - 82	146.01	39.22	63.50	1.619	2.697
502	36	1	80 - 82	148.91	41.59	66.30	1.594	2.763
502	36	2	80 - 82	150.43	43.20	67.57	1.564	2.740
502	37	1	80 - 82	153.21	42.33	67.27	1.589	2.800
502	37	2	80 - 82	154.68	39.11	64.07	1.638	2.776
502	38	1	80 - 82	157.71	40.22	64.29	1.598	2.676
502	38	2	80 - 82	159.19	39.70	64.42	1.623	2.750
502	39	1	80 - 82	162.11	40.42	64.85	1.605	2.720
502	39	2	80 - 82	163.60	40.17	64.53	1.606	2.709
502	40	1	80 - 82	166.16	47.05	70.76	1.504	2.723
502	40	2	80 - 82	167.83	40.59	65.09	1.604	2.730
502	41	2	80 - 82	171.11	39.88	64.41	1.615	2.729
502	42	1	80 - 82	174.65	43.47	67.79	1.559	2.736
502	42	2	80 - 82	176.15	41.10	65.69	1.598	2.744
502	42	3	54 - 56	177.40	40.80	65.48	1.605	2.752
502	43	1	80 - 82	179.66	39.20	63.31	1.615	2.676
502	43	2	82 - 84	181.19	41.57	65.99	1.588	2.728
502	44	1	80 - 82	184.06	40.04	64.55	1.612	2.726
502	44	2	10 - 12	184.84	43.23	67.30	1.557	2.702
502	45	1	80 - 82	188.34	38.05	62.81	1.651	2.750
502	45	2	40 - 42	189.41	38.39	62.86	1.637	2.715
502	46	1	80 - 82	192.76	40.96	65.34	1.595	2.718
502	46	1	136 - 138	193.32	32.27	56.45	1.749	2.720
502	46	2	30 - 32	193.76	41.73	67.18	1.610	2.858
502	47	1	80 - 82	197.16	36.97	61.75	1.670	2.753

*** GRID M 04 ***

*** GRID N 04 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Water Content	Porosity	Density (gm/cc)	Grain Density (gm/cc)
502	47	2	45 - 47	198.31	38.19	63.13	1.653	2.770
502	48	1	80 - 82	201.54	44.93	68.91	1.534	2.717
502	50	1	27 - 29	209.98	41.30	65.59	1.588	2.710
502A	1	1	80 - 82	0.81	48.11	71.87	1.494	2.756
502A	2	1	80 - 82	2.66	47.78	71.41	1.494	2.729
502A	2	2	80 - 82	4.14	50.74	73.48	1.448	2.690
502A	2	3	80 - 82	5.64	43.92	68.05	1.549	2.719
502A	3	1	80 - 82	7.11	43.88	67.28	1.533	2.629
502A	3	2	80 - 82	8.51	43.12	67.48	1.565	2.738
502A	3	3	80 - 82	10.00	45.81	69.40	1.515	2.683
502A	4	1	80 - 82	11.51	44.65	68.62	1.537	2.711
502A	4	2	80 - 82	12.97	42.62	67.11	1.575	2.747
502A	4	3	90 - 92	14.57	44.28	67.94	1.534	2.667
502A	5	1	80 - 82	15.91	41.07	65.90	1.605	2.773
502A	5	2	80 - 82	17.36	42.67	67.18	1.574	2.750
502A	5	3	80 - 82	18.86	43.50	68.14	1.566	2.778
502A	6	1	80 - 82	20.18	43.03	67.23	1.563	2.717
502A	6	2	80 - 82	21.39	46.10	69.87	1.516	2.711
502A	6	3	80 - 82	22.89	44.50	68.39	1.537	2.698
502A	7	1	80 - 82	24.66	43.84	68.11	1.553	2.735
502A	7	2	80 - 82	25.95	40.62	64.88	1.597	2.700
502A	7	3	80 - 82	27.45	47.04	70.67	1.502	2.712
502A	8	1	80 - 82	28.99	46.28	69.79	1.508	2.681
502A	8	2	80 - 82	30.31	42.87	67.31	1.570	2.744
502A	9	1	10 - 12	32.81	46.84	70.59	1.507	2.724
502A	10	1	80 - 82	37.91	48.88	72.17	1.476	2.711
502A	10	2	80 - 82	39.41	46.77	70.05	1.498	2.661
502A	10	3	80 - 82	40.91	42.07	66.30	1.576	2.709
502A	11	1	15 - 17	41.66	47.29	70.80	1.497	2.703
502A	12	1	80 - 82	46.61	41.98	66.33	1.580	2.722
502A	12	2	80 - 82	48.09	43.06	67.39	1.565	2.733
502A	12	3	80 - 82	49.59	45.68	69.48	1.521	2.708
502A	13	1	12 - 14	50.43	47.59	71.28	1.498	2.733
502A	16	1	80 - 82	64.31	43.22	67.32	1.558	2.707
502A	16	2	80 - 82	65.80	45.80	69.42	1.516	2.686
502A	16	3	30 - 32	66.81	45.14	69.35	1.536	2.750
502A	17	1	80 - 82	68.71	45.00	69.23	1.538	2.750
502A	17	2	80 - 82	70.22	44.17	68.49	1.550	2.747
502A	17	3	80 - 82	71.71	42.78	67.42	1.576	2.767
502A	19	1	80 - 82	77.25	44.91	69.27	1.542	2.765
502A	19	2	80 - 82	78.74	44.07	68.43	1.553	2.751
502A	19	3	80 - 82	80.26	44.09	68.57	1.555	2.767
502A	20	1	80 - 82	81.91	44.51	68.92	1.549	2.765
502A	20	2	80 - 82	83.28	41.20	65.73	1.596	2.738
502A	20	3	80 - 82	84.79	42.22	66.67	1.579	2.738
502A	21	1	80 - 82	86.25	41.53	66.26	1.596	2.765
502A	21	2	80 - 82	87.77	41.75	66.46	1.592	2.764
502A	21	3	80 - 82	88.94	43.49	68.06	1.565	2.768
502A	22	1	80 - 82	90.71	41.95	66.50	1.585	2.748
502A	22	2	80 - 82	92.22	42.27	66.94	1.584	2.765
502A	22	3	80 - 82	93.72	44.37	69.39	1.564	2.842
502A	23	1	80 - 82	95.11	40.02	65.10	1.627	2.796
502A	23	2	80 - 82	96.57	43.56	68.22	1.566	2.780

*** GRID N 04 ***

*** GRID B 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Water Content	Porosity	Density (gm/cc)	Grain Density (gm/cc)
502A	23	3	80 - 82	98.08	39.68	64.51	1.626	2.763
502A	24	1	80 - 82	99.51	45.45	70.47	1.550	2.864
502A	24	2	80 - 82	101.02	40.65	65.75	1.618	2.803
502A	24	3	80 - 82	102.53	38.52	63.80	1.657	2.814
502A	25	1	80 - 82	103.86	39.03	64.10	1.642	2.789
502A	25	2	80 - 82	105.33	40.64	65.40	1.609	2.761
502A	25	3	80 - 82	106.83	42.05	66.82	1.589	2.774
502A	26	1	80 - 82	108.31	41.57	65.61	1.578	2.682
502A	26	2	80 - 82	109.74	48.00	70.80	1.475	2.626
502A	26	3	80 - 82	111.16	38.09	61.96	1.627	2.648
502A	27	1	80 - 82	112.71	39.83	63.69	1.599	2.650
502A	27	2	80 - 82	114.21	39.61	63.95	1.614	2.704
502A	27	3	80 - 82	115.71	38.64	63.17	1.635	2.724
502A	28	1	80 - 82	116.99	37.73	62.13	1.647	2.708
502A	28	2	80 - 82	118.45	36.86	61.34	1.664	2.718
502A	29	1	80 - 82	120.11	38.05	62.11	1.632	2.669
502A	29	2	80 - 82	121.61	38.94	63.01	1.618	2.670
502A	30	1	90 - 92	123.71	39.32	64.16	1.632	2.764
502A	30	2	80 - 82	125.09	37.92	62.35	1.644	2.711
502A	32	1	80 - 82	129.11	38.42	62.67	1.631	2.691
502A	32	2	80 - 82	130.63	44.08	67.45	1.530	2.629
502A	33	1	80 - 82	132.11	37.59	62.35	1.659	2.750
502A	33	2	80 - 82	133.58	37.28	61.43	1.648	2.680
502A	34	1	80 - 82	135.11	39.12	63.77	1.630	2.740
502A	34	2	80 - 82	136.61	35.67	59.54	1.669	2.654
502A	35	1	80 - 82	137.66	38.59	63.26	1.639	2.740
502A	35	2	80 - 82	139.16	38.41	63.23	1.646	2.757
502A	35	3	80 - 82	140.66	40.59	64.99	1.601	2.717
502A	36	1	80 - 82	141.49	41.45	66.67	1.608	2.825
502A	36	2	80 - 82	142.99	38.15	62.88	1.648	2.746
502A	37	2	80 - 82	144.75	40.24	65.22	1.621	2.784
502A	38	1	80 - 82	146.29	41.37	65.68	1.587	2.712
502A	39	1	80 - 82	147.91	40.00	64.62	1.615	2.739
502A	39	2	80 - 82	149.41	39.52	63.97	1.619	2.717
502A	40	1	80 - 82	150.99	40.64	65.21	1.604	2.737
502A	40	2	80 - 82	152.49	41.14	65.37	1.589	2.700
502A	41	1	80 - 82	153.01	44.30	68.40	1.544	2.722
502A	41	2	80 - 82	154.51	41.75	66.67	1.597	2.790
502A	42	1	80 - 82	156.61	41.35	66.19	1.601	2.777
502A	42	2	80 - 82	158.11	41.37	66.29	1.602	2.787
502A	43	1	80 - 82	159.11	44.10	68.25	1.548	2.725
502A	43	2	80 - 82	160.56	40.54	64.38	1.588	2.651
502A	44	1	80 - 82	161.82	40.47	64.86	1.603	2.715
502A	44	2	80 - 82	163.21	40.90	65.82	1.609	2.783
502A	45	1	80 - 82	164.49	40.68	64.87	1.595	2.693
502A	45	2	80 - 82	165.96	39.36	63.89	1.623	2.725
502A	46	1	80 - 82	166.87	39.17	63.64	1.625	2.717
502A	46	2	80 - 82	168.22	42.86	66.14	1.543	2.605
502A	47	1	80 - 82	168.79	40.59	64.19	1.581	2.624
502A	47	2	80 - 82	170.29	41.41	65.38	1.579	2.673
502A	48	1	80 - 82	171.94	39.39	63.60	1.615	2.689
502A	50	1	70 - 72	175.91	40.13	64.64	1.611	2.727
502A	50	2	60 - 62	177.27	43.26	68.08	1.574	2.797

*** GRID B 05 ***

*** GRID C 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Water Content	Porosity	Density (gm/cc)	Grain Density (gm/cc)
502A	51	1	80 - 82	179.11	39.32	64.02	1.628	2.746
502A	51	2	50 - 52	180.31	38.54	63.66	1.652	2.794
502A	52	1	80 - 82	181.43	38.41	63.35	1.649	2.772
502A	53	1	80 - 82	183.31	38.33	63.34	1.653	2.781
502A	54	1	80 - 82	185.41	39.78	64.74	1.627	2.780
502A	54	2	80 - 82	186.91	37.70	64.16	1.702	2.957
502A	55	1	80 - 82	187.97	39.43	64.66	1.640	2.810
502A	55	2	48 - 50	189.14	38.00	62.95	1.657	2.773
502A	56	1	80 - 82	189.78	38.31	63.33	1.653	2.781
502A	56	2	45 - 47	190.94	37.08	61.89	1.669	2.756
502A	57	1	80 - 82	191.91	39.82	64.84	1.628	2.786
502A	57	2	40 - 42	193.01	37.74	62.81	1.664	2.786
502A	58	1	80 - 82	193.87	37.38	62.30	1.667	2.768
502A	58	2	50 - 52	195.11	35.46	60.23	1.699	2.757
502A	60	1	80 - 82	198.06	33.72	58.90	1.747	2.817
502A	61	1	82 - 84	199.71	37.97	63.10	1.662	2.794
502A	63	1	80 - 82	203.90	36.98	61.97	1.676	2.777
502A	65	1	80 - 82	207.91	44.57	69.23	1.553	2.798
502A	65	2	20 - 22	208.83	40.34	65.06	1.613	2.754
502A	66	1	80 - 82	209.96	41.56	66.10	1.590	2.742
502A	66	2	50 - 52	211.06	45.17	69.43	1.537	2.757
502A	68	1	70 - 72	213.51	53.13	75.47	1.421	2.714
502B	1	1	80 - 82	0.77	49.62	73.05	1.472	2.752
502B	2	1	80 - 82	2.51	44.77	69.42	1.550	2.800
502B	2	2	80 - 82	3.95	43.14	67.50	1.565	2.738
502B	2	3	30 - 32	4.95	42.91	67.43	1.572	2.755
502B	3	1	70 - 72	6.86	42.96	69.55	1.619	3.032
502B	3	2	80 - 82	8.41	43.02	67.82	1.577	2.792
502B	3	3	80 - 82	9.91	46.97	71.23	1.516	2.795
502B	4	1	80 - 82	11.36	46.25	70.09	1.515	2.722
502B	4	2	80 - 82	12.85	46.91	70.73	1.508	2.734
502B	4	3	80 - 82	14.35	42.46	66.81	1.574	2.728
502B	5	1	80 - 82	15.66	43.04	67.25	1.563	2.719
502B	5	1	80 - 82	15.66	43.04	67.25	1.563	2.719
502B	5	2	75 - 77	17.06	52.70	74.72	1.418	2.652
502B	5	3	80 - 82	18.34	42.34	66.38	1.568	2.688
502B	6	1	80 - 82	20.16	47.74	71.28	1.493	2.717
502B	6	2	80 - 82	21.67	43.56	67.57	1.551	2.700
502B	6	3	80 - 82	23.15	43.34	67.47	1.557	2.712
502B	7	2	80 - 82	24.84	43.50	67.31	1.547	2.675
502B	7	3	80 - 82	26.33	41.36	65.53	1.584	2.695
502B	7	4	80 - 82	27.84	46.35	69.91	1.509	2.690
502B	8	1	95 - 97	29.11	41.36	65.70	1.588	2.715
502B	8	2	100 - 102	30.12	44.40	68.35	1.540	2.705
502B	8	3	80 - 82	31.38	44.04	68.01	1.544	2.702
502B	9	1	80 - 82	33.21	45.52	69.22	1.521	2.692
502B	9	2	85 - 87	34.72	47.89	71.26	1.488	2.698
502B	9	3	45 - 47	35.69	46.21	69.90	1.512	2.702
502B	11	1	80 - 82	42.16	46.07	69.96	1.519	2.727
502B	11	2	70 - 72	43.55	42.29	66.36	1.569	2.692
502B	11	3	80 - 82	45.16	46.75	70.24	1.502	2.688
502B	13	1	80 - 82	50.96	44.16	68.05	1.541	2.694
502B	13	2	80 - 82	52.46	43.32	67.21	1.552	2.683

*** GRID C 05 ***

*** GRID D 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Water Content	Porosity	Density (gm/cc)	Grain Density (gm/cc)
502B	13	3	80 - 82	53.97	44.51	68.44	1.538	2.703
502B	14	1	80 - 82	55.26	42.27	66.77	1.579	2.744
502B	14	2	63 - 65	56.59	43.03	67.23	1.562	2.716
502B	14	3	80 - 82	58.24	42.35	66.61	1.573	2.716
502B	15	1	70 - 72	59.66	44.47	69.77	1.569	2.882
502B	16	1	70 - 72	63.83	45.28	69.63	1.538	2.770
502B	17	1	80 - 82	68.56	40.65	65.34	1.608	2.753
502B	17	2	70 - 72	69.96	42.87	67.52	1.575	2.770
502B	17	3	80 - 82	71.56	42.13	66.61	1.581	2.740
502B	18	1	80 - 82	72.96	44.47	68.86	1.548	2.761
502B	18	2	80 - 82	74.45	43.29	67.70	1.564	2.746
502B	18	3	80 - 82	75.95	43.50	67.79	1.558	2.734
502B	19	1	80 - 82	77.36	41.69	65.63	1.574	2.671
502B	19	2	80 - 82	78.86	43.82	69.65	1.590	2.943
502B	19	3	80 - 82	80.37	41.68	66.14	1.587	2.733
502B	20	1	80 - 82	81.76	39.24	64.04	1.632	2.757
502B	20	2	80 - 82	83.26	40.27	64.80	1.609	2.730
502B	20	3	80 - 82	84.76	38.28	63.07	1.648	2.754
502B	21	1	80 - 82	86.09	41.35	65.95	1.595	2.747
502B	21	2	80 - 82	87.60	41.94	66.48	1.585	2.745
502B	21	3	80 - 82	89.05	42.13	66.59	1.581	2.737
502B	22	2	80 - 82	90.73	41.12	66.20	1.610	2.805
502B	22	3	80 - 82	92.23	42.11	84.56	2.008	7.531
502B	22	4	80 - 82	93.73	38.54	63.38	1.644	2.760
502B	23	1	80 - 82	94.64	40.63	65.45	1.611	2.769
502B	23	2	15 - 17	95.49	38.69	63.41	1.639	2.746
502B	23	3	15 - 17	96.99	39.59	64.76	1.636	2.804
503A	2	1	80 - 82	2.61	73.62	88.45	1.202	2.745
503A	2	3	68 - 70	5.26	62.70	81.72	1.303	2.659
503A	5	1	80 - 82	15.81	73.55	88.09	1.198	2.661
503A	5	3	80 - 82	18.82	54.03	76.62	1.418	2.788
503A	7	1	130 - 132	24.66	76.87			
503A	7	3	80 - 82	27.18	77.04	90.04	1.169	2.694
503A	9	1	80 - 82	33.33	80.54			
503A	9	3	63 - 65	35.79	78.78	91.40	1.160	2.862
503A	10	1	96 - 98	37.97	78.47	90.61	1.155	2.646
503A	10	3	60 - 62	40.54	68.72	85.00	1.237	2.579
503A	11	1	80 - 82	42.11	78.24	90.45	1.156	2.634
503A	11	2	80 - 82	43.64	79.04	90.73	1.148	2.595
503A	11	3	80 - 82	45.14	65.11	83.93	1.289	2.798
503A	12	1	80 - 82	46.50	75.78			
503A	12	3	80 - 82	49.51	79.92	91.22	1.141	2.609
503A	13	1	130 - 132	51.51	74.77	89.34	1.195	2.829
503A	13	3	80 - 82	53.91	69.57	85.43	1.228	2.565
503A	14	3	80 - 82	57.61	78.87	89.34	1.133	2.245
503A	15	3	80 - 82	62.81	76.67	89.27	1.164	2.531
503A	19	1	80 - 82	77.21	74.13			
503A	20	1	91 - 93	81.67	81.10	91.33	1.126	2.455
503A	20	3	80 - 82	84.65	61.13	80.43	1.316	2.614
503A	21	1	80 - 82	86.21	74.63			
503A	21	3	80 - 82	89.22	75.76	88.42	1.167	2.442
503A	24	1	130 - 132	99.91	69.92	85.24	1.219	2.485
503A	24	3	80 - 82	102.44	67.63	83.89	1.240	2.492

*** GRID D 05 ***

*** GRID E 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Water Content	Porosity	Density (gm/cc)	Grain Density (gm/cc)
503A	29	1	80 - 82	121.41	66.64	83.74	1.257	2.578
503A	29	3	80 - 82	124.42	65.53	82.47	1.259	2.475
503A	30	1	80 - 82	125.73	62.88	80.84	1.286	2.491
503A	31	1	80 - 82	130.21	67.41	83.52	1.239	2.450
503A	31	3	80 - 82	133.16	68.43	83.88	1.226	2.401
503A	36	1	80 - 82	152.13	58.42	78.62	1.346	2.617
503A	36	1	80 - 82	152.13	55.45	76.58	1.381	2.627
503A	40	1	80 - 82	169.57	63.63	81.57	1.282	2.531
503A	41	1	80 - 82	174.21	64.93	82.27	1.267	2.507
503A	41	3	80 - 82	177.22	62.81	81.20	1.293	2.557
503A	42	1	100 - 102	178.81	64.70	81.82	1.265	2.456
503A	42	3	40 - 42	181.23	61.51	80.33	1.306	2.555
503A	43	1	80 - 82	183.01	62.48	80.40	1.287	2.463
503A	44	1	80 - 82	187.41	64.09	81.05	1.265	2.397
503A	44	3	80 - 82	190.42	65.74	82.15	1.250	2.398
503A	48	1	80 - 82	204.73	50.79	72.88	1.435	2.604
503A	49	2	20 - 22	210.27	56.98	77.02	1.352	2.531
503A	50	1	80 - 82	213.81	56.57	76.67	1.355	2.523
503A	51	1	80 - 82	218.21	53.72	74.34	1.384	2.496
503A	52	1	80 - 82	222.61	63.29	80.40	1.270	2.379
503A	53	1	80 - 82	227.01	62.82	80.88	1.287	2.503
503A	54	1	80 - 82	231.41	70.41	85.24	1.211	2.427
503A	54	3	80 - 82	234.43	61.10	80.22	1.313	2.582
503B	1	1	84 - 86	0.85	61.26	80.45	1.313	2.603
503B	1	2	83 - 85	2.32	70.08	85.89	1.226	2.600
503B	2	1	81 - 83	3.60	64.87	83.38	1.285	2.717
503B	2	2	81 - 83	5.11	73.69	88.16	1.196	2.658
503B	3	1	81 - 83	8.00	66.74	83.67	1.254	2.554
503B	3	3	81 - 83	11.00	79.54	90.82	1.142	2.543
503B	4	1	81 - 83	12.42	77.19			
503B	4	3	81 - 83	15.31	64.57	82.68	1.281	2.620
503B	5	1	81 - 83	16.82	64.84	82.95	1.279	2.638
503B	5	3	81 - 83	19.63	72.29	87.18	1.206	2.607
503B	6	1	131 - 133	21.61	74.80	88.51	1.183	2.596
503B	6	3	81 - 83	24.09	79.29	90.56	1.142	2.505
503B	7	1	93 - 95	25.74	65.31	83.48	1.278	2.685
503B	7	3	61 - 63	28.36	78.64	90.93	1.156	2.721
503B	8	1	81 - 83	30.02	78.62	90.81	1.155	2.688
503B	8	3	71 - 73	32.83	81.03	91.88	1.134	2.650
503B	10	1	81 - 83	38.82	69.60	85.27	1.225	2.528
503B	10	3	81 - 83	41.79	78.09			
503B	11	1	81 - 83	43.22	76.56	90.06	1.176	2.775
503B	11	3	81 - 83	45.99	78.12	90.65	1.160	2.714
503B	12	1	81 - 83	47.62	80.63			
503B	12	3	81 - 83	50.56	80.93	92.15	1.139	2.767
503B	13	1	121 - 123	52.42	76.37	89.56	1.173	2.654
503B	13	3	24 - 26	54.40	75.16	89.30	1.188	2.759
503B	14	1	81 - 83	56.42	72.55	87.80	1.210	2.723
503B	14	3	81 - 83	59.04	71.70	87.56	1.221	2.778
503B	15	1	81 - 83	60.82	74.53	88.43	1.187	2.612
503B	15	3	81 - 83	63.47	78.00	90.33	1.158	2.634
503B	16	1	81 - 83	65.22	68.54	85.38	1.246	2.681
503B	16	3	81 - 83	68.06	70.84	86.72	1.224	2.688

*** GRID E 05 ***

*** GRID F 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Water Content	Porosity	Density (gm/cc)	Grain Density (gm/cc)
503B	17	1	81 - 83	69.62	69.24	85.87	1.240	2.699
503B	17	3	48 - 50	72.16	75.57	89.23	1.181	2.677
503B	18	1	81 - 83	74.02	80.26	91.60	1.141	2.684
503B	18	2	81 - 83	75.52	74.32	88.74	1.194	2.723
503B	18	3	86 - 88	77.08	74.87	88.89	1.187	2.686
503B	19	1	131 - 133	78.92	75.55	89.01	1.178	2.622
503B	19	2	68 - 70	79.60	76.65	89.80	1.172	2.683
503B	20	3	81 - 83	84.29	67.09	84.64	1.262	2.704
503B	21	1	81 - 83	87.22	73.62			
503B	21	3	81 - 83	90.17	67.70			
503B	22	3	71 - 73	94.27	66.24	84.16	1.271	2.709
503B	24	1	81 - 83	100.42	61.52	80.95	1.316	2.659

*** GRID F 05 ***

*** GRID G 05 ***

Table 5: Sediment Paleomagnetism

Sediment Paleomagnetism
Long-Core Spinner Magnetometer

Note: The RC column is used to indicate the repeat factor for the measurement. A "0" indicates the first measurement, whereas successive repeat measurements are indicated by "1," "2," and so on. Also note that "phi" under the "Sedimentological Notes" column is the designation for the rotation angle measured from the orientation ring of each core.

*** GRID G 05 ***

*** GRID H 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	3	1	15	4.95	0	BROKEN LINER MIDDLE OF ST	114.847	350.9
502	3	1	30	5.10	0		362.312	298.8
502	3	1	45	5.25	0		151.129	12.6
502	3	1	60	5.40	0		1154.618	359.0
502	3	1	75	5.55	0		212.587	108.6
502	3	1	90	5.70	0		38.498	329.2
502	3	1	105	5.85	0		259.631	326.5
502	3	1	120	6.00	0		278.841	346.5
502	3	1	135	6.15	0		97.801	3.5
502	3	1	145	6.25	0		75.466	11.5
502	3	2	17	6.43	0		209.342	342.1
502	3	2	30	6.56	0		259.763	348.9
502	3	2	45	6.71	0		270.298	345.9
502	3	2	60	6.86	0		128.655	326.3
502	3	2	75	7.01	0		183.469	358.5
502	3	2	90	7.16	0		577.325	346.5
502	3	2	105	7.31	0		408.564	9.0
502	3	2	120	7.46	0		205.513	348.7
502	3	2	135	7.61	0		271.551	13.8
502	3	2	145	7.71	0		475.131	27.3
502	3	2	145	7.71	1	REPEAT	472.540	27.2
502	3	3	17	7.93	0		237.194	158.5
502	3	3	30	8.06	0		322.296	179.1
502	3	3	45	8.21	0		517.520	182.8
502	3	3	60	8.36	0		242.027	195.5
502	3	3	75	8.51	0		269.193	174.6
502	3	3	90	8.66	0		355.088	164.4
502	3	3	96	8.72	0		243.068	188.0
502	4	1	17	9.14	0		737.510	24.1
502	4	1	30	9.27	0		679.324	49.3
502	4	1	45	9.42	0		217.642	62.7
502	4	1	60	9.57	0		116.399	190.6
502	4	1	75	9.72	0		345.463	67.1
502	4	1	90	9.87	0		396.882	65.6
502	4	1	105	10.02	0		374.607	56.6
502	4	1	120	10.17	0		127.027	36.3
502	4	1	135	10.32	0		286.080	82.0
502	4	1	145	10.42	0		345.736	94.1
502	4	2	17	10.50	0		246.054	77.2
502	4	2	17	10.50	1	POST VIBRATOR REPEAT	249.854	76.5
502	4	2	30	10.63	0		300.029	99.3
502	4	2	45	10.78	0		251.337	78.3
502	4	2	60	10.93	0		411.032	74.7
502	4	2	75	11.08	0		438.823	70.2
502	4	2	90	11.23	0		223.735	78.8
502	4	2	105	11.38	0		317.734	78.9
502	4	2	120	11.53	0		328.442	69.6
502	4	2	135	11.68	0		358.815	80.5
502	4	2	145	11.78	0		254.046	77.7
502	4	3	17	12.01	0		416.024	88.5
502	4	3	30	12.14	0		332.554	68.9
502	4	3	45	12.29	0		457.231	82.6
502	4	3	60	12.44	0		472.226	91.3

*** GRID H 05 ***

*** GRID I 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	4	3	75	12.59	0		574.753	90.3
502	4	3	90	12.74	0		364.219	99.1
502	4	3	105	12.89	0		240.727	97.0
502	4	3	120	13.04	0		200.576	115.0
502	4	3	129	13.13	0		63.876	108.8
502	5	1	18	13.78	0	REPEAT BECAUSE OF SLIP	207.097	77.4
502	5	1	30	13.90	0		97.333	64.2
502	5	1	45	14.05	0		58.804	80.4
502	5	1	60	14.15	0	VOID	8.331	280.5
502	5	1	75	14.25	0		354.083	338.4
502	5	1	90	14.40	0		404.254	315.1
502	5	1	105	14.55	0		80.278	84.2
502	5	1	120	14.70	0		249.122	349.5
502	5	1	135	14.85	0		525.492	354.1
502	5	1	145	14.95	0		505.889	18.6
502	5	2	18	15.19	0		336.957	24.6
502	5	2	30	15.31	0		290.671	12.9
502	5	2	45	15.46	0		256.645	20.0
502	5	2	60	15.61	0		195.515	36.5
502	5	2	75	15.76	0		233.699	17.0
502	5	2	90	15.91	0		414.927	21.1
502	5	2	105	16.06	0		91.032	19.3
502	5	2	120	16.21	0		284.908	35.1
502	5	2	135	16.36	0		276.684	44.7
502	5	2	145	16.46	0		191.118	64.1
502	5	3	17	16.68	0		174.778	63.5
502	5	3	30	16.81	0		156.656	64.4
502	5	3	45	16.96	0		130.211	76.5
502	5	3	60	17.11	0		131.767	254.6
502	5	3	75	17.26	0		34.832	145.8
502	5	3	90	17.41	0		165.371	141.1
502	5	3	105	17.56	0		111.046	179.8
502	5	3	107	17.58	0		186.298	180.6
502	6	1	17	18.17	0	PHI=195 DEGREES	139.748	246.6
502	6	1	30	18.30	0		98.090	47.5
502	6	1	45	18.45	0		29.213	93.8
502	6	1	60	18.60	0		190.764	202.4
502	6	1	75	18.75	0		188.861	187.0
502	6	1	90	18.90	0		124.046	203.5
502	6	1	105	19.05	0		327.472	213.8
502	6	1	120	19.20	0		57.630	53.7
502	6	1	120	19.20	1	REPEAT	53.760	50.6
502	6	1	135	19.35	0		48.762	235.2
502	6	1	144	19.44	0		70.035	59.6
502	6	2	17	19.68	0		100.389	24.2
502	6	2	30	19.81	0		94.161	46.4
502	6	2	45	19.96	0		174.500	23.1
502	6	2	60	20.11	0		606.888	28.2
502	6	2	75	20.26	0		63.387	315.5
502	6	2	90	20.41	0		311.683	20.2
502	6	2	105	20.56	0		215.463	16.6
502	6	2	120	20.71	0		79.497	23.2
502	6	2	135	20.86	0		78.568	31.9

*** GRID I 05 ***

*** GRID J 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 a-6)	NRM Declination (deg.)
502	6	2	144	20.95	0		88.151	23.9
502	6	3	15	21.16	0		89.819	17.6
502	6	3	25	21.26	0		41.539	358.3
502	6	3	35	21.36	0		75.259	12.0
502	6	3	45	21.46	0		15.136	8.5
502	6	3	55	21.56	0		27.046	60.4
502	6	3	65	21.66	0		531.856	323.5
502	6	3	74	21.75	0		90.867	296.9
502	6	3	75	21.76	0	BASE	191.696	177.2
502	7	1	18	22.58	0	PHI=088 DEGREES	384.578	206.0
502	7	1	30	22.70	0		188.685	344.3
502	7	1	45	22.85	0		94.546	99.0
502	7	1	60	23.00	0		58.624	162.2
502	7	1	75	23.15	0		10.448	83.2
502	7	1	90	23.30	0		57.297	345.2
502	7	1	105	23.45	0		108.594	275.1
502	7	1	120	23.60	0		117.947	217.0
502	7	1	135	23.75	0		35.564	324.3
502	7	1	144	23.84	0		32.018	276.8
502	7	2	22	23.52	0		16.438	56.8
502	7	2	30	23.60	0		37.806	41.8
502	7	2	45	23.75	0		149.104	42.7
502	7	2	60	23.90	0		100.585	89.5
502	7	2	75	24.05	0		170.969	242.9
502	7	2	90	24.20	0		79.517	213.4
502	7	2	105	24.35	0		284.224	218.9
502	7	2	120	24.50	0		128.343	221.6
502	7	2	135	24.65	0		79.231	39.6
502	7	2	144	24.74	0		125.322	52.3
502	7	3	17	24.98	0		19.774	224.9
502	7	3	25	25.06	0		5.956	235.7
502	7	3	35	25.16	0		86.268	230.2
502	7	3	45	25.26	0		176.282	233.2
502	7	3	55	25.36	0		98.015	235.7
502	7	3	65	25.46	0		170.118	230.4
502	7	3	75	25.56	0		81.371	215.2
502	7	3	85	25.66	0		220.471	231.0
502	7	3	95	25.76	0		153.752	236.3
502	7	3	105	25.86	0		156.813	230.9
502	7	3	115	25.96	0		162.329	245.9
502	8	1	17	26.90	0	PHI=132 DEGREES	413.027	339.2
502	8	1	30	27.03	0		200.994	9.4
502	8	1	45	27.18	0		156.051	325.7
502	8	1	60	27.33	0		119.611	327.1
502	8	1	75	27.48	0		42.723	283.5
502	8	1	90	27.63	0		88.890	301.0
502	8	1	105	27.78	0		168.538	330.7
502	8	1	120	27.93	0		285.520	308.8
502	8	1	135	28.08	0		458.308	312.1
502	8	1	144	28.17	0		158.054	301.3
502	8	2	16	28.37	0		280.487	359.8
502	8	2	30	28.51	0		39.184	0.7
502	8	2	45	28.66	0		173.049	307.4

*** GRID J 05 ***

*** GRID K 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	8	2	60	28.81	0		125.052	296.7
502	8	2	75	28.96	0		83.665	304.2
502	8	2	90	29.11	0		87.198	334.2
502	8	2	105	29.26	0		34.739	223.7
502	8	2	120	29.41	0		71.172	299.5
502	8	2	135	29.56	0		138.676	12.8
502	8	2	140	29.61	0		70.264	339.2
502	8	2	144	29.65	0		119.212	306.1
502	8	3	17	29.90	0		172.754	322.1
502	8	3	30	30.03	0		224.247	308.2
502	8	3	45	30.18	0		232.944	327.2
502	8	3	60	30.33	0		204.528	355.8
502	8	3	75	30.48	0		372.995	351.7
502	8	3	90	30.63	0		181.515	7.4
502	8	3	95	30.68	0		154.023	330.8
502	8	3	98	30.71	0		156.489	311.2
502	8	3	100	30.73	0		93.404	218.5
502	8	3	102	30.75	0		113.674	185.0
502	9	1	17	31.37	0	PHI=165 DEGREES	738.722	131.0
502	9	1	30	31.50	0	REDO FROM TOP,SLIPPED	139.956	203.1
502	9	1	45	31.65	0		202.586	134.6
502	9	1	60	31.80	0		81.475	170.5
502	9	1	75	31.95	0		222.106	71.5
502	9	1	90	32.10	0		326.471	161.7
502	9	1	105	32.25	0		119.832	264.3
502	9	1	120	32.40	0		9.740	198.8
502	9	1	135	32.55	0		232.867	217.8
502	9	1	143	32.63	0		197.996	63.5
502	9	2	16	32.84	0		183.978	242.5
502	9	2	30	32.98	0		381.029	262.8
502	9	2	45	33.13	0		356.966	90.1
502	9	2	60	33.28	0		252.682	203.4
502	9	2	75	33.43	0		150.430	207.8
502	9	2	90	33.58	0		127.784	201.0
502	9	2	105	33.73	0		122.357	240.1
502	9	2	120	33.88	0		252.708	249.1
502	9	2	135	34.03	0		370.491	208.3
502	9	2	145	34.13	0		111.231	267.4
502	9	3	16	34.34	0	DAMAGED LINER	76.307	248.1
502	9	3	30	34.48	0		105.758	234.5
502	9	3	45	34.63	0		60.307	302.9
502	9	3	60	34.73	0		196.096	298.1
502	9	3	75	34.88	0		228.782	261.7
502	9	3	90	35.03	0		303.556	319.6
502	9	3	95	35.08	0		22.694	256.2
502	10	1	60	36.20	0	PHI=008 DEGREES	117.526	194.8
502	10	1	75	36.35	0	MOSTLY VOID ABOVE 50CM	169.438	233.3
502	10	1	90	36.50	0		323.492	259.8
502	10	1	105	36.65	0		125.567	277.2
502	10	1	120	36.80	0		109.828	276.0
502	10	1	135	36.95	0		107.190	307.7
502	10	1	142	37.02	0		324.431	277.9
502	10	2	17	36.97	0		209.857	237.5

*** GRID K 05 ***

*** GRID L 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	10	2	30	37.10	0		183.883	259.2
502	10	2	45	37.25	0		211.163	271.6
502	10	2	60	37.40	0		327.968	175.0
502	10	2	75	37.55	0		94.588	248.9
502	10	2	90	37.70	0		799.814	268.7
502	10	2	105	37.85	0		222.442	257.3
502	10	2	120	38.00	0		144.881	269.3
502	10	2	135	38.15	0		27.441	352.2
502	10	2	140	38.20	0		19.951	132.7
502	10	2	144	38.24	0		97.195	83.7
502	10	3	16	38.47	0		399.286	96.9
502	10	3	20	38.51	0		423.021	94.0
502	10	3	30	38.61	0		308.647	113.8
502	10	3	40	38.71	0		231.837	83.9
502	10	3	50	38.81	0		24.287	139.0
502	10	3	60	38.91	0		435.478	86.3
502	10	3	70	39.01	0		336.357	99.4
502	10	3	80	39.11	0		364.586	85.7
502	10	3	90	39.21	0		410.326	108.4
502	10	3	100	39.31	0		231.770	67.3
502	10	3	110	39.41	0		122.314	113.2
502	10	3	120	39.51	0		367.147	162.0
502	10	3	127	39.58	0		229.804	84.8
502	11	1	16	39.95	0	PHI=239 DEGREES	656.130	9.1
502	11	1	30	40.09	0		295.862	109.9
502	11	1	45	40.24	0		492.630	140.7
502	11	1	60	40.39	0		428.917	17.5
502	11	1	75	40.54	0		474.828	216.6
502	11	1	90	40.69	0		298.266	112.2
502	11	1	105	40.84	0		381.347	102.3
502	11	1	120	40.99	0		595.562	139.9
502	11	1	149	41.28	0		231.419	232.7
502	13	1	17	48.97	0	PHI=200 DEGREES	845.603	11.1
502	13	1	30	49.10	0	LOOKS SOMEWHAT DISTURBED	286.876	230.2
502	13	1	45	49.25	0		233.634	74.1
502	13	1	60	49.40	0		196.114	100.7
502	13	1	75	49.55	0		244.523	177.1
502	13	1	90	49.70	0		100.783	209.8
502	13	1	105	49.85	0		121.877	265.9
502	13	1	120	50.00	0		87.317	174.8
502	13	1	135	50.15	0		489.813	279.7
502	13	1	144	50.24	0		147.691	358.2
502	13	2	17	50.46	0		124.891	25.1
502	13	2	30	50.59	0		66.834	341.9
502	13	2	45	50.74	0		301.922	358.2
502	13	2	60	50.89	0		359.158	351.0
502	13	2	75	51.04	0		207.300	7.5
502	13	2	90	51.19	0		116.649	58.8
502	13	2	90	51.19	1	REPEAT	90.648	46.0
502	13	2	90	51.19	2	REPEAT	92.128	45.6
502	13	2	105	51.34	0		110.154	349.7
502	13	2	120	51.49	0		233.930	3.9
502	13	2	135	51.64	0		194.864	11.2

*** GRID L 05 ***

*** GRID M 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	13	2	146	51.75	0		345.604	343.8
502	13	3	17	51.97	0		427.177	332.7
502	13	3	30	52.10	0		569.123	31.5
502	13	3	45	52.25	0		399.224	27.7
502	13	3	60	52.40	0		241.272	1.5
502	13	3	75	52.55	0		251.897	9.1
502	13	3	90	52.70	0		191.022	7.3
502	13	3	94	52.74	0		186.301	22.1
502	13	3	97	52.77	0		186.135	357.2
502	13	3	100	52.80	0		163.578	33.1
502	13	3	102	52.82	0		120.980	67.0
502	13	3	104	52.84	0		133.091	137.3
502	13	3	104	52.84	1	REVERSAL BETWEEN 104 &	138.654	146.5
502	13	3	106	52.86	0	106	202.778	181.4
502	13	3	106	52.86	1		208.144	182.3
502	14	1	17	53.37	0	PHI=188 DEGREES	526.209	94.5
502	14	1	30	53.50	0	VERY DISTURBED	455.742	193.8
502	14	1	45	53.65	0		29.896	313.3
502	14	1	60	53.80	0		34.001	174.9
502	14	1	75	53.95	0		265.650	313.4
502	14	1	90	54.10	0		274.891	269.6
502	14	1	105	54.25	0		299.875	151.4
502	14	1	120	54.40	0		159.846	141.7
502	14	1	135	54.55	0		292.868	239.1
502	14	1	144	54.64	0		432.764	228.2
502	14	2	17	54.84	0		345.775	312.7
502	14	2	30	54.97	0		203.348	39.7
502	14	2	45	55.12	0		337.746	310.9
502	14	2	60	55.27	0		161.939	14.9
502	14	2	75	55.42	0		166.930	22.3
502	14	2	90	55.57	0		370.272	18.7
502	14	2	105	55.72	0		134.760	346.1
502	15	1	20	57.80	0	PHI=170 DEGREES	689.751	203.2
502	15	1	30	57.90	0	0-15 VOID	694.173	131.8
502	15	1	45	58.05	0		533.080	36.4
502	15	1	60	58.20	0		333.407	313.2
502	15	1	75	58.35	0		281.289	358.5
502	15	1	90	58.50	0		369.172	359.2
502	15	1	105	58.65	0		354.131	351.9
502	15	1	120	58.80	0		271.785	38.6
502	15	1	135	58.95	0		76.541	345.4
502	15	1	145	59.05	0		146.490	29.6
502	15	2	17	59.13	0		241.423	349.1
502	15	2	30	59.26	0		336.600	268.7
502	15	2	45	59.41	0		176.502	4.2
502	15	2	60	59.56	0		165.731	350.3
502	15	2	75	59.71	0		306.169	19.0
502	15	2	90	59.86	0		174.956	0.2
502	15	2	105	60.01	0		47.245	300.8
502	15	2	105	60.01	1		37.988	300.0
502	15	2	110	60.06	1		73.838	342.6
502	15	2	115	60.11	1		73.165	16.6
502	15	2	120	60.16	0		107.279	48.2

*** GRID M 05 ***

*** GRID N 05 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	15	2	120	60.16	1		110.528	54.0
502	15	2	125	60.21	1		81.544	105.8
502	15	2	130	60.26	1		129.083	193.1
502	15	2	135	60.31	0		138.979	178.7
502	15	2	135	60.31	1		144.482	177.6
502	15	2	144	60.40	0		184.984	179.9
502	15	3	17	60.63	0		295.282	186.6
502	15	3	30	60.76	0		215.036	172.9
502	15	3	45	60.91	0		190.160	169.9
502	15	3	60	61.06	0		204.671	64.4
502	15	3	60	61.06	0		207.947	61.5
502	15	3	67	61.13	0		283.727	153.1
502	15	3	75	61.21	0		254.829	175.4
502	15	3	81	61.27	0		233.289	276.4
502	16	1	17	62.17	0	PHI=045 DEGREES	223.226	350.7
502	16	1	30	62.30	0	0-8 VOID	85.802	98.9
502	16	1	45	62.45	0		266.643	334.7
502	16	1	60	62.60	0		208.479	187.0
502	16	1	75	62.75	0		348.537	167.3
502	16	1	90	62.90	0		125.707	230.4
502	16	1	105	63.05	0		367.185	144.4
502	16	1	120	63.20	0		564.098	186.2
502	16	1	135	63.35	0		326.150	165.1
502	16	1	144	63.44	0		313.447	177.3
502	16	2	17	63.60	0		179.910	170.4
502	16	2	30	63.73	0		76.851	171.2
502	16	2	45	63.88	0		176.740	170.2
502	16	2	60	64.03	0		538.056	165.9
502	16	2	75	64.18	0		759.640	142.6
502	16	2	80	64.23	0		458.861	169.7
502	16	2	85	64.28	0		143.807	204.2
502	16	2	90	64.33	0		184.573	205.4
502	16	2	104	64.47	0		86.524	238.9
502	17	1	17	66.57	0	PHI=340 DEGREES	443.218	342.4
502	17	1	30	66.70	0		1174.703	253.4
502	17	1	45	66.85	0		317.051	268.5
502	17	1	60	67.00	0		103.513	174.3
502	17	1	75	67.15	0		232.691	201.7
502	17	1	90	67.30	0		748.470	335.7
502	17	1	105	67.45	0		392.352	189.7
502	17	1	120	67.60	0		561.036	198.0
502	17	1	135	67.75	0		1167.591	105.5
502	17	1	144	67.84	0		259.774	190.5
502	17	2	17	67.97	0		206.589	207.3
502	17	2	30	68.10	0		288.553	200.7
502	17	2	45	68.25	0		349.972	197.7
502	17	2	60	68.40	0		422.652	199.0
502	17	2	75	68.55	0		448.070	199.0
502	17	2	90	68.70	0		513.562	207.7
502	17	2	105	68.85	0		236.898	200.4
502	17	2	120	69.00	0		256.218	208.7
502	17	2	135	69.15	0		265.019	204.0
502	17	2	144	69.24	0		265.829	183.2

*** GRID N 05 ***

*** GRID B 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	18	1	16	70.96	0	PHI=215 DEGREES	119.004	235.5
502	18	1	30	71.10	0		62.282	267.3
502	18	1	45	71.25	0		212.743	236.7
502	18	1	60	71.40	0		404.095	253.1
502	18	1	75	71.55	0		255.624	230.4
502	18	1	90	71.70	0		361.186	236.4
502	18	1	105	71.85	0		913.390	189.1
502	18	1	120	72.00	0		433.484	197.5
502	18	1	135	72.15	0		342.933	264.6
502	18	1	144	72.24	0		215.663	134.7
502	18	2	5	72.35	0		639.213	185.8
502	18	2	20	72.50	0		691.239	119.0
502	18	2	35	72.65	0		142.477	245.6
502	18	2	50	72.80	0		402.365	223.6
502	18	2	63	72.93	0		281.860	177.3
502	19	1	17	75.37	0	PHI=085 DEGREES	409.009	13.8
502	19	1	30	75.50	0		203.251	282.7
502	19	1	45	75.65	0		106.297	160.5
502	19	1	60	75.80	0		215.597	185.8
502	19	1	75	75.95	0		220.458	282.0
502	19	1	75	75.95	1	REPEAT	175.160	292.0
502	19	1	90	76.10	0		71.747	104.6
502	19	1	105	76.25	0		77.299	275.2
502	19	1	120	76.40	0		65.590	239.4
502	19	1	135	76.55	0		437.598	317.9
502	19	1	144	76.64	0		105.460	227.7
502	19	2	17	76.85	0		70.568	187.4
502	19	2	30	76.98	0		4468.296	121.6
502	19	2	30	76.98	1	REPEAT	2954.222	123.4
502	19	2	35	77.03	1		229.569	144.9
502	19	2	45	77.13	0		187.670	159.0
502	19	2	60	77.28	0		65.865	249.4
502	19	2	75	77.43	0		52.640	315.8
502	19	2	90	77.58	0		135.976	175.0
502	19	2	105	77.73	0		80.226	199.6
502	19	2	120	77.88	0		61.463	176.6
502	19	2	135	78.03	0		102.817	159.3
502	19	2	144	78.12	0		63.494	162.5
502	19	3	5	78.24	0	SLIPPED IN HOLDER,REPEAT	38.162	231.0
502	19	3	15	78.34	0		101.309	241.6
502	19	3	25	78.44	0		83.520	228.1
502	19	3	35	78.54	0		91.422	330.6
502	19	3	45	78.64	0		24.359	280.3
502	19	3	51	78.70	0		247.483	266.6
502	20	1	17	79.77	0	PHI=010 DEGREES	47.952	279.2
502	20	1	30	79.90	0		112.241	356.9
502	20	1	45	80.05	0		175.219	324.6
502	20	1	60	80.20	0		104.605	324.0
502	20	1	75	80.35	0		69.923	4.5
502	20	1	90	80.50	0		48.910	314.2
502	20	1	105	80.65	0		79.421	135.0
502	20	1	120	80.80	0		68.074	142.1
502	20	1	135	80.95	0		89.422	154.5

*** GRID B 06 ***

*** GRID C 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	20	1	144	81.04	0		170.220	169.0
502	20	2	17	81.23	0		143.335	98.6
502	20	2	30	81.36	0		56.818	151.4
502	20	2	45	81.51	0		93.559	160.4
502	20	2	60	81.66	0		111.942	148.2
502	20	2	75	81.81	0		363.983	147.5
502	20	2	90	81.96	0		272.266	181.1
502	20	2	105	82.11	0		195.005	175.8
502	20	2	120	82.26	0		246.289	166.5
502	20	2	135	82.41	0		150.677	174.7
502	20	2	144	82.50	0		22.851	176.7
502	20	3	16	82.72	0		59.114	2.3
502	20	3	25	82.81	0		255.074	351.9
502	20	3	35	82.91	0		278.987	357.3
502	20	3	45	83.01	0		298.706	355.3
502	20	3	55	83.11	0		244.417	352.4
502	20	3	65	83.21	0		232.665	357.1
502	20	3	75	83.31	0		222.604	2.0
502	20	3	85	83.41	0		74.461	47.1
502	20	3	93	83.49	0		77.778	96.8
502	21	1	17	84.17	0	PHI=105 DEGREES	204.552	153.2
502	21	1	30	84.30	0		100.089	225.2
502	21	1	45	84.45	0		190.047	59.4
502	21	1	60	84.60	0		157.656	63.4
502	21	1	75	84.75	0		167.716	135.0
502	21	1	90	84.90	0		521.957	123.6
502	21	1	105	85.05	0		230.611	144.3
502	21	1	120	85.20	0		341.055	120.5
502	21	1	135	85.35	0		286.684	142.5
502	21	1	144	85.44	0		287.715	128.8
502	21	2	16	85.64	0		298.156	145.9
502	21	2	30	85.78	0		361.112	143.1
502	21	2	45	85.93	0		459.195	147.3
502	21	2	60	86.08	0		454.356	141.7
502	21	2	75	86.23	0		405.995	139.8
502	21	2	90	86.38	0		293.527	143.5
502	21	2	105	86.53	0		265.978	146.8
502	21	2	120	86.68	0		321.464	151.1
502	21	2	135	86.83	0		334.644	152.0
502	21	2	144	86.92	0		346.845	152.2
502	22	1	17	88.57	0	PHI=095 DEGREES	106.530	166.0
502	22	1	30	88.70	0		156.051	123.5
502	22	1	45	88.85	0		192.484	144.8
502	22	1	60	89.00	0		136.301	140.3
502	22	1	75	89.15	0		53.781	195.0
502	22	1	90	89.30	0		70.283	155.6
502	22	1	105	89.45	0		69.735	26.4
502	22	1	120	89.60	0		119.060	296.0
502	22	1	135	89.75	0		16.243	304.5
502	22	1	144	89.84	0		58.143	272.2
502	22	2	17	90.06	0	VOID BOTTOM 20CM	84.347	307.8
502	22	2	30	90.19	0		88.222	317.1
502	22	2	45	90.34	0		83.429	320.7

*** GRID C 06 ***

*** GRID D 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	22	2	60	90.49	0		153.344	315.1
502	22	2	75	90.64	0		44.811	301.3
502	22	2	90	90.79	0		232.095	333.0
502	22	2	105	90.94	0		146.066	327.8
502	22	3	17	91.16	0		155.949	355.4
502	22	3	30	91.29	0		48.106	327.4
502	22	3	45	91.44	0		43.376	295.1
502	22	3	60	91.59	0		129.430	300.8
502	22	3	75	91.74	0		181.508	341.6
502	22	3	90	91.89	0		59.754	250.3
502	23	2	17	93.08	0	PHI=138 DEGREES	152.422	268.7
502	23	2	30	93.21	0		55.200	277.0
502	23	2	45	93.36	0		269.575	330.2
502	23	2	60	93.51	0		226.740	325.3
502	23	2	75	93.66	0		193.923	329.9
502	23	2	90	93.81	0		196.247	317.9
502	23	2	105	93.96	0		291.993	333.9
502	23	2	120	94.11	0		158.359	268.2
502	23	2	135	94.26	0		225.131	304.5
502	23	2	144	94.35	0		202.687	308.1
502	23	3	17	94.58	0		220.285	269.0
502	23	3	30	94.71	0		196.750	288.0
502	23	3	45	94.86	0		188.492	274.5
502	23	3	60	95.01	0		197.891	272.6
502	23	3	75	95.16	0		152.044	269.9
502	23	3	90	95.31	0		123.233	271.9
502	23	3	105	95.46	0		168.472	272.1
502	23	3	120	95.61	0		178.798	271.5
502	23	3	135	95.76	0		173.881	259.5
502	23	3	144	95.85	0		276.958	259.9
502	23	4	17	96.08	0		303.173	300.6
502	23	4	30	96.21	0		170.269	315.3
502	23	4	45	96.36	0		191.007	309.8
502	23	4	60	96.51	0		228.643	305.7
502	23	4	75	96.66	0		224.958	302.4
502	23	4	90	96.81	0		131.321	302.9
502	23	4	105	96.96	0		274.721	288.1
502	23	4	120	97.11	0		330.951	283.0
502	23	4	127	97.18	0		260.828	301.8
502	24	1	17	97.37	0	PHI=144 DEGREES	464.884	268.7
502	24	1	30	97.50	0	LINER CRACKED IN MIDDLE	314.261	273.4
502	24	1	45	97.65	0		193.893	259.6
502	24	1	60	97.80	0		43.933	307.7
502	24	1	75	97.95	0		413.990	266.7
502	24	1	90	98.10	0	CORE DISTURBED AT 90 CM	413.846	157.6
502	24	1	105	98.25	0		74.647	318.9
502	24	1	120	98.40	0		178.051	295.6
502	24	1	135	98.55	0		238.470	297.5
502	24	1	144	98.64	0		263.046	308.0
502	24	2	17	98.86	0		281.743	291.4
502	24	2	30	98.99	0		307.498	289.4
502	24	2	45	99.14	0		373.460	288.0
502	24	2	60	99.29	0		282.340	281.3

*** GRID D 06 ***

*** GRID E 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	24	2	75	99.44	0		240.013	297.1
502	24	2	90	99.59	0		320.825	296.6
502	24	2	105	99.74	0		216.450	291.1
502	24	2	120	99.89	0		235.540	288.8
502	24	2	135	100.04	0		263.548	292.1
502	24	2	144	100.13	0		227.191	291.0
502	24	3	17	100.37	0		285.647	295.2
502	24	3	30	100.50	0		254.910	293.2
502	24	3	45	100.65	0		335.199	290.5
502	24	3	60	100.80	0		261.410	281.4
502	24	3	75	100.95	0		198.001	293.8
502	24	3	90	101.10	0		180.737	289.7
502	24	3	105	101.25	0		200.825	290.5
502	24	3	120	101.40	0		169.653	281.9
502	24	3	128	101.48	0		293.709	280.9
502	25	1	17	101.72	0	PHI=082 DEGREES	239.832	218.6
502	25	1	30	101.85	0		166.856	8.9
502	25	1	45	102.00	0		363.237	358.2
502	25	1	60	102.15	0		180.371	4.9
502	25	1	75	102.30	0		353.157	344.2
502	25	1	90	102.45	0		349.808	354.2
502	25	1	105	102.60	0		91.535	347.0
502	25	1	120	102.75	0		152.033	1.0
502	25	1	135	102.90	0		202.845	336.4
502	25	1	144	102.99	0		412.555	334.8
502	25	2	17	103.19	0		314.433	317.3
502	25	2	30	103.32	0		219.793	8.4
502	25	2	45	103.47	0		206.243	327.9
502	25	2	60	103.62	0		215.220	320.7
502	25	2	75	103.77	0		241.414	353.2
502	25	2	90	103.92	0		162.779	275.8
502	25	2	105	104.07	0		81.572	16.0
502	25	2	120	104.22	0		169.681	9.2
502	25	2	135	104.37	0		248.927	350.8
502	25	2	144	104.46	0		120.778	5.1
502	25	3	17	104.70	0		222.852	326.6
502	25	3	30	104.83	0		256.026	349.1
502	25	3	45	104.98	0		256.088	347.3
502	25	3	45	104.98	0		254.296	349.2
502	25	3	50	105.03	0		266.301	337.4
502	25	3	55	105.08	0		125.040	30.5
502	25	3	60	105.13	0		157.101	348.4
502	25	3	60	105.13	0		147.179	348.2
502	25	3	65	105.18	0		173.506	354.6
502	25	3	70	105.23	0		100.146	357.7
502	25	3	75	105.28	0		47.530	357.7
502	25	3	75	105.28	0		37.327	9.4
502	25	3	80	105.33	0		28.153	228.6
502	25	3	85	105.38	0		129.846	180.8
502	25	3	90	105.43	0		84.193	163.8
502	25	3	90	105.43	0		82.133	167.8
502	25	3	95	105.48	0		100.500	169.7
502	25	3	100	105.53	0		207.139	185.5

*** GRID E 06 ***

*** GRID F 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	25	3	105	105.58	0		129.602	200.0
502	25	3	105	105.58	0		136.630	204.7
502	25	3	110	105.63	0		166.717	243.8
502	25	3	115	105.68	0		363.083	240.0
502	25	3	120	105.73	0		110.548	197.8
502	25	3	120	105.73	0		113.937	192.7
502	25	3	125	105.78	0		125.609	184.1
502	26	1	16	106.11	0	PHI=161 DEGREES	140.621	154.5
502	26	1	30	106.25	0	ASH LAYER AT 30-50 CM?	630.684	276.1
502	26	1	45	106.40	0		2644.610	286.5
502	26	1	60	106.55	0		193.864	7.9
502	26	1	75	106.70	0		43.267	104.0
502	26	1	90	106.85	0		236.149	122.6
502	26	1	105	107.00	0		14.761	19.6
502	26	1	120	107.15	0		403.414	142.6
502	26	1	135	107.30	0		211.568	114.6
502	26	2	17	107.44	0		234.954	145.0
502	26	2	30	107.57	0		89.215	126.9
502	26	2	45	107.72	0		145.595	160.8
502	26	2	60	107.87	0		251.289	113.7
502	26	2	75	108.02	0		290.327	137.1
502	26	2	90	108.17	0		321.527	136.0
502	26	2	105	108.32	0		164.069	104.0
502	26	2	120	108.47	0		134.698	140.7
502	26	2	135	108.62	0		107.926	122.4
502	26	2	144	108.71	0		81.846	179.7
502	26	3	17	108.95	0		92.671	156.2
502	26	3	30	109.08	0		107.609	358.7
502	26	3	45	109.23	0		16.990	19.4
502	26	3	60	109.38	0		151.325	314.5
502	26	3	75	109.53	0		196.550	316.8
502	26	3	90	109.68	0		252.658	304.8
502	26	3	105	109.83	0		194.750	116.6
502	26	3	106	109.84	0		242.549	122.1
502	29	1	17	117.47	0	PHI=275 DEGREES	147.454	354.8
502	29	1	30	117.60	0		356.825	267.3
502	29	1	45	117.75	0		117.833	193.7
502	29	1	60	117.90	0		183.909	199.5
502	29	1	75	118.05	0		141.905	216.1
502	29	1	90	118.20	0		130.449	172.3
502	29	1	105	118.35	0		31.758	231.8
502	29	1	120	118.50	0		256.544	199.1
502	29	1	135	118.65	0		181.606	195.1
502	29	1	144	118.74	0		260.573	207.8
502	29	2	17	118.97	0		131.036	209.2
502	29	2	30	119.10	0		95.854	202.6
502	29	2	45	119.25	0		395.289	219.3
502	29	2	60	119.40	0		82.007	193.3
502	29	2	75	119.55	0		30.190	206.8
502	29	2	90	119.70	0		123.886	214.6
502	29	2	105	119.85	0		246.157	224.3
502	29	2	120	120.00	0		208.940	227.6
502	29	2	135	120.15	0		223.635	227.4

*** GRID F 06 ***

*** GRID G 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	29	2	144	120.24	0		158.820	231.7
502	29	3	17	120.47	0		172.955	224.9
502	29	3	30	120.60	0		336.899	248.3
502	29	3	45	120.75	0		127.198	240.2
502	29	3	60	120.90	0		59.252	154.7
502	29	3	75	121.05	0		56.435	123.2
502	29	3	90	121.20	0		76.271	110.8
502	29	3	105	121.35	0		34.522	104.6
502	29	3	107	121.37	0		55.827	112.7
502	30	1	17	121.87	0	PHI=139 DEGREES	380.750	231.8
502	30	1	30	122.00	0		469.687	278.0
502	30	1	45	122.15	0		478.968	297.5
502	30	1	60	122.30	0		97.384	306.3
502	30	1	75	122.45	0		230.746	274.0
502	30	1	90	122.60	0		336.698	264.8
502	30	1	105	122.75	0		310.163	266.2
502	30	1	120	122.90	0		375.353	284.3
502	30	1	134	123.04	0		185.689	266.9
502	30	1	135	123.05	0		214.379	279.4
502	30	2	17	123.36	0		342.742	284.0
502	30	2	30	123.49	0		508.406	287.2
502	30	2	45	123.64	0		331.692	283.7
502	30	2	60	123.79	0		392.806	281.4
502	30	2	75	123.94	0		251.889	283.2
502	30	2	90	124.09	0		218.824	289.0
502	30	2	105	124.24	0		130.680	294.3
502	30	2	120	124.39	0		87.324	285.3
502	30	2	135	124.54	0		117.089	284.0
502	30	2	144	124.63	0		65.967	290.4
502	30	3	17	124.86	0		59.940	0.9
502	30	3	30	124.99	0		29.129	201.0
502	30	3	45	125.14	0		493.707	120.6
502	30	3	60	125.29	0		189.507	126.3
502	30	3	75	125.44	0		203.019	112.0
502	30	3	90	125.59	0		110.667	103.0
502	30	3	104	125.73	0		252.705	134.0
502	31	1	17	126.27	0	PHI=250 DEGREES	232.011	186.5
502	31	1	30	126.40	0		13.856	292.7
502	31	1	45	126.55	0		58.410	256.7
502	31	1	60	126.70	0		166.697	161.4
502	31	1	75	126.85	0		232.937	312.4
502	31	1	90	127.00	0		169.468	323.4
502	31	1	105	127.15	0		429.258	330.7
502	31	1	120	127.30	0		335.090	329.4
502	31	1	135	127.45	0		270.800	280.3
502	31	1	144	127.54	0		160.458	318.5
502	31	2	17	127.77	0		314.821	300.1
502	31	2	30	127.90	0		245.834	292.0
502	31	2	45	128.05	0		40.131	260.2
502	31	2	60	128.20	0		88.937	136.9
502	31	2	75	128.35	0		9.327	97.6
502	31	2	90	128.50	0		106.837	144.3
502	31	2	105	128.65	0		282.467	137.0

*** GRID G 06 ***

*** GRID H 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	31	2	120	128.80	0		415.731	135.6
502	31	2	135	128.95	0		283.216	147.2
502	31	2	144	129.04	0		299.564	146.4
502	32	1	17	130.67	0	PHI=075 DEGREES	460.139	134.9
502	32	1	30	130.80	0		54.478	17.9
502	32	1	45	130.95	0		713.737	221.4
502	32	1	60	131.10	0		664.314	122.9
502	32	1	75	131.25	0		682.217	117.4
502	32	1	90	131.40	0		627.585	157.4
502	32	1	105	131.55	0		1237.177	133.0
502	32	1	120	131.70	0		561.698	153.3
502	32	1	135	131.85	0		762.690	153.8
502	32	1	144	131.94	0		724.797	148.6
502	32	2	17	132.13	0		322.572	155.3
502	32	2	30	132.26	0		438.383	154.3
502	32	2	45	132.41	0		487.238	145.9
502	32	2	60	132.56	0		495.085	142.7
502	32	2	75	132.71	0		476.664	141.5
502	32	2	90	132.86	0		531.965	148.2
502	32	2	105	133.01	0		397.357	154.8
502	32	2	120	133.16	0		256.883	149.7
502	32	2	135	133.31	0		428.576	149.1
502	32	2	144	133.40	0		404.880	150.5
502	33	1	17	135.07	0	PHI=025 DEGREES	1513.138	204.4
502	33	1	30	135.20	0		635.354	249.6
502	33	1	45	135.35	0		624.249	26.0
502	33	1	60	135.50	0		215.280	92.1
502	33	1	75	135.65	0		257.310	33.0
502	33	1	90	135.80	0		281.486	26.3
502	33	1	105	135.95	0		171.956	26.7
502	33	1	120	136.10	0		374.962	31.1
502	33	1	135	136.25	0		191.678	22.7
502	33	1	144	136.34	0		262.257	49.6
502	34	1	55	139.85	0	PHI=200 DEGREES	181.141	185.6
502	34	1	60	139.90	0	UPPER 45 CM MANGLED	126.063	178.6
502	34	1	75	140.05	0		128.325	181.1
502	34	1	90	140.20	0		84.818	180.6
502	34	1	105	140.35	0		60.034	183.1
502	34	1	120	140.50	0		32.148	163.4
502	34	1	142	140.72	0		33.247	226.2
502	34	2	17	140.95	0		41.815	197.2
502	34	2	30	141.08	0		52.663	182.1
502	34	2	45	141.23	0		30.282	167.3
502	34	2	60	141.38	0		14.804	166.0
502	34	2	75	141.53	0		10.754	65.9
502	34	2	90	141.68	0		26.369	173.2
502	34	2	120	141.98	0		18.668	201.1
502	34	2	135	142.13	0		17.956	199.5
502	34	2	144	142.22	0		17.312	225.8
502	34	3	17	142.47	0		3.223	165.2
502	34	3	25	142.55	0		3.137	184.4
502	34	3	35	142.65	0		9.401	205.9
502	34	3	45	142.75	0		7.603	192.9

*** GRID H 06 ***

*** GRID I 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	34	3	55	142.85	0		7.738	190.0
502	34	3	65	142.95	0		7.419	212.6
502	34	3	75	143.05	0		10.947	235.3
502	34	3	89	143.19	0		15.023	248.3
502	35	1	17	143.87	0	PHI=175 DEGREES	219.578	259.3
502	35	1	30	144.00	0		75.315	49.7
502	35	1	45	144.15	0		257.797	129.8
502	35	1	60	144.30	0		31.579	109.5
502	35	1	75	144.45	0		59.084	245.0
502	35	1	90	144.60	0		28.836	323.4
502	35	1	105	144.75	0		84.105	210.3
502	35	1	120	144.90	0		7.401	115.0
502	35	1	135	145.05	0		32.886	300.5
502	35	1	144	145.14	0		34.013	72.7
502	35	2	17	145.37	0		8.961	79.1
502	35	2	17	145.37	1	REPEAT	7.821	76.1
502	35	2	30	145.50	0		63.080	321.2
502	35	2	30	145.50	1		60.871	8.0
502	35	2	45	145.65	0		23.366	81.2
502	35	2	45	145.65	1		42.693	86.4
502	35	2	60	145.80	0		8.372	63.0
502	35	2	60	145.80	1		11.915	66.6
502	35	2	75	145.95	0		34.059	64.4
502	35	2	75	145.95	1		28.510	62.6
502	35	2	90	146.10	0		6.081	290.6
502	35	2	90	146.10	1		2.896	281.5
502	35	2	105	146.25	0		14.631	162.5
502	35	2	105	146.25	1		12.061	152.6
502	35	2	120	146.40	0		3.813	226.9
502	35	2	120	146.40	1		3.711	212.1
502	35	2	132	146.52	0		87.997	133.2
502	35	2	132	146.52	1		89.511	132.8
502	36	1	17	148.27	0	PHI=257 DEGREES	1101.906	11.4
502	36	1	30	148.40	0		92.817	188.8
502	36	1	45	148.55	0		33.460	185.8
502	36	1	60	148.70	0		124.964	16.9
502	36	1	75	148.85	0		65.175	246.6
502	36	1	90	149.00	0		14.797	278.9
502	36	1	105	149.15	0		43.477	21.0
502	36	1	120	149.30	0		39.242	176.4
502	36	1	135	149.45	0		102.210	332.4
502	36	1	144	149.54	0		85.059	243.2
502	36	2	17	149.79	0		27.221	241.5
502	36	2	30	149.92	0		36.186	133.6
502	36	2	45	150.07	0		32.321	323.5
502	36	2	60	150.22	0		37.493	353.2
502	36	2	75	150.37	0		24.071	48.5
502	36	2	90	150.52	0		73.625	138.6
502	36	2	105	150.67	0		86.444	114.9
502	36	2	120	150.82	0		64.300	230.9
502	36	2	135	150.97	0		15.466	263.6
502	36	2	144	151.06	0		11.705	234.4
502	37	1	17	152.57	0	PHI=243 DEGREES	2930.584	13.3

*** GRID I 06 ***

*** GRID J 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	37	1	30	152.70	0		972.891	245.6
502	37	1	45	152.85	0		1049.469	61.4
502	37	1	60	153.00	0		324.587	271.4
502	37	1	75	153.15	0		570.328	112.7
502	37	1	90	153.30	0		248.463	316.1
502	37	1	105	153.45	0		562.139	331.7
502	37	1	120	153.60	0		52.904	299.9
502	37	1	135	153.75	0		309.631	29.3
502	37	1	144	153.84	0		526.587	97.2
502	37	2	17	154.04	0		210.029	110.4
502	37	2	30	154.17	0		234.903	329.6
502	37	2	45	154.32	0		196.261	251.5
502	37	2	60	154.47	0		37.368	325.6
502	37	2	75	154.62	0		228.356	227.8
502	37	2	90	154.77	0		21.849	140.6
502	37	2	105	154.92	0		2.073	202.3
502	37	2	120	155.07	0		6.158	230.5
502	37	2	135	155.22	0		10.043	350.6
502	37	2	144	155.31	0		7.873	290.1
502	38	1	17	157.07	0	PHI=243 DEGREES	73.027	54.3
502	38	1	30	157.20	0		138.300	200.9
502	38	1	45	157.35	0		93.889	192.9
502	38	1	60	157.50	0		49.837	163.6
502	38	1	75	157.65	0		48.528	178.2
502	38	1	90	157.80	0		11.360	32.7
502	38	1	105	157.95	0		38.304	91.8
502	38	1	120	158.10	0		21.588	216.8
502	38	1	135	158.25	0		81.011	239.9
502	38	1	144	158.34	0		95.592	253.3
502	38	2	17	158.55	0		83.265	330.6
502	38	2	30	158.68	0		10.301	207.9
502	38	2	45	158.83	0		46.943	278.7
502	38	2	60	158.98	0		58.584	284.0
502	38	2	90	159.28	0		31.268	256.8
502	38	2	105	159.43	0		21.910	243.4
502	38	2	114	159.52	0		32.175	240.1
502	39	1	17	161.47	0	PHI=335 DEGREES	588.144	348.4
502	39	1	30	161.60	0		128.595	330.5
502	39	1	45	161.75	0		29.942	298.5
502	39	1	60	161.90	0		171.126	351.5
502	39	1	75	162.05	0		158.812	200.0
502	39	1	90	162.20	0		156.268	303.5
502	39	1	105	162.35	0		139.596	315.3
502	39	1	120	162.50	0		79.985	304.9
502	39	1	135	162.65	0		45.732	334.9
502	39	1	144	162.74	0		52.924	290.8
502	39	2	17	162.96	0		55.444	272.8
502	39	2	30	163.09	0		33.115	267.8
502	39	2	45	163.24	0		36.726	227.4
502	39	2	60	163.39	0		88.213	344.1
502	39	2	75	163.54	0		69.641	297.4
502	39	2	90	163.69	0		91.470	326.5
502	39	2	103	163.82	0		59.786	288.8

*** GRID J 06 ***

*** GRID K 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	40	1	17	165.52	0	PHI=233 DEGREES	2454.877	42.3
502	40	1	30	165.65	0	DRILLING MUD	3328.396	66.0
502	40	1	45	165.80	0		594.742	200.5
502	40	1	60	165.95	0		161.205	59.2
502	40	1	75	166.10	0		1107.570	92.6
502	40	1	90	166.25	0		435.619	236.9
502	40	1	105	166.40	0		231.227	231.5
502	40	1	120	166.55	0		154.443	228.0
502	40	1	135	166.70	0		182.779	238.0
502	40	1	144	166.79	0		105.689	228.3
502	40	2	17	167.19	0		117.471	225.5
502	40	2	30	167.32	0		388.307	226.9
502	40	2	40	167.42	0		174.469	239.0
502	40	2	50	167.52	0		88.390	233.8
502	40	2	60	167.62	0		26.749	244.1
502	40	2	75	167.77	0		109.226	263.8
502	40	2	78	167.80	0		131.799	271.9
502	41	1	17	169.11	0	PHI=185 DEGREES	459.597	112.4
502	41	1	30	169.24	0	VERY DISTURBED,SPLIT CORE	3549.572	68.0
502	41	1	45	169.39	0		176.771	188.4
502	41	1	60	169.54	0		3096.137	339.7
502	41	1	75	169.69	0		101.393	103.7
502	41	1	90	169.84	0		85.918	68.2
502	41	1	105	169.99	0		49.582	167.9
502	41	1	120	170.14	0		280.625	323.1
502	41	1	135	170.29	0		302.428	310.7
502	41	1	144	170.38	0		119.263	15.5
502	41	2	17	170.47	0		489.572	5.2
502	41	2	30	170.60	0		383.170	6.6
502	41	2	45	170.75	0		451.873	5.2
502	41	2	60	170.90	0		738.422	17.9
502	41	2	75	171.05	0		748.421	21.9
502	41	2	90	171.20	0		63.295	19.7
502	41	2	105	171.35	0		52.649	20.1
502	41	2	120	171.50	0		43.810	18.4
502	41	2	135	171.65	0		57.094	15.0
502	41	2	144	171.74	0		57.812	28.6
502	42	1	17	174.01	0	PHI=002 DEGREES	8416.645	103.1
502	42	1	30	174.14	0		953.533	291.7
502	42	1	45	174.29	0		5380.732	116.2
502	42	1	60	174.44	0		3534.015	189.3
502	42	1	75	174.59	0		216.653	181.5
502	42	1	90	174.74	0		1869.806	200.7
502	42	1	105	174.89	0		257.464	132.2
502	42	1	120	175.04	0		211.156	0.4
502	42	1	135	175.19	0		115.315	340.2
502	42	1	144	175.28	0		47.028	257.6
502	42	2	17	175.51	0		16.780	247.5
502	42	2	30	175.64	0		30.796	259.1
502	42	2	45	175.79	0		20.245	176.4
502	42	2	60	175.94	0		101.405	157.0
502	42	2	75	176.09	0		207.772	199.6
502	42	2	90	176.24	0		129.716	215.4

*** GRID K 06 ***

*** GRID L 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	42	2	105	176.39	0		135.509	218.0
502	42	2	120	176.54	0		62.000	236.7
502	42	2	135	176.69	0		54.354	226.8
502	42	2	144	176.78	0		78.339	249.1
502	43	1	17	179.02	0	UNORIENTED	128.474	53.6
502	43	1	30	179.15	0		124.910	57.8
502	43	1	45	179.30	0		159.921	48.3
502	43	1	60	179.45	0		138.491	59.9
502	43	1	75	179.60	0		122.906	65.9
502	43	1	90	179.75	0		162.694	59.4
502	43	1	105	179.90	0		176.796	56.9
502	43	1	120	180.05	0		157.167	47.4
502	43	1	135	180.20	0		25.339	74.5
502	43	1	144	180.29	0		62.459	53.5
502	43	2	17	180.53	0	UNORIENTED	79.853	36.3
502	43	2	30	180.66	0		55.879	57.1
502	43	2	45	180.81	0		292.603	48.5
502	43	2	60	180.96	0		138.219	46.5
502	43	2	75	181.11	0		175.712	43.7
502	43	2	90	181.26	0		188.146	61.7
502	43	2	103	181.39	0		96.936	48.7
502	44	1	17	183.42	0	PHI=259 DEGREES	1259.459	106.4
502	44	1	30	183.55	0		445.558	177.6
502	44	1	45	183.70	0		100.452	44.1
502	44	1	60	183.85	0		178.059	251.1
502	44	1	75	184.00	0		171.681	357.1
502	44	1	90	184.15	0		103.023	354.6
502	44	1	105	184.30	0		83.115	2.6
502	44	1	120	184.45	0		112.560	15.6
502	44	1	135	184.60	0		402.935	6.9
502	44	1	144	184.69	0		107.409	13.0
502	45	1	17	187.70	0	PHI=105 DEGREES	272.115	18.2
502	45	1	30	187.83	0		7650.609	107.4
502	45	1	45	187.98	0		175.652	67.1
502	45	1	45	187.98	0		176.720	66.5
502	45	1	46	187.99	0		64.278	252.3
502	45	1	47	188.00	0		398.993	253.8
502	45	1	50	188.03	0		309.342	251.0
502	45	1	60	188.13	0		185.341	249.5
502	45	1	75	188.28	0		277.061	247.6
502	45	1	90	188.43	0		254.096	246.0
502	45	1	105	188.58	0		127.083	236.2
502	45	1	120	188.73	0		141.369	256.7
502	45	1	135	188.88	0		375.497	255.8
502	45	1	144	188.97	0		219.434	259.1
502	46	1	17	192.12	0	PHI=043 DEGREES	136.434	274.4
502	46	1	30	192.25	0		694.361	209.1
502	46	1	45	192.40	0		241.152	193.5
502	46	1	60	192.55	0		692.418	182.3
502	46	1	75	192.70	0		1058.604	180.8
502	46	1	90	192.85	0		736.237	182.1
502	46	1	105	193.00	0		648.796	181.0
502	46	1	120	193.15	0		357.862	169.7

*** GRID L 06 ***

*** GRID M 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502	46	1	135	193.30	0		295.713	187.8
502	46	1	144	193.39	0		350.359	188.7
502	47	1	17	196.52	0	PHI=055 DEGREES	401.988	223.0
502	47	1	30	196.65	0		333.466	181.4
502	47	1	45	196.80	0		126.983	315.9
502	47	1	60	196.95	0		174.376	306.9
502	47	1	75	197.10	0		185.803	253.4
502	47	1	90	197.25	0		163.056	292.3
502	47	1	105	197.40	0		149.286	310.2
502	47	1	120	197.55	0		195.572	288.0
502	47	1	135	197.70	0		225.070	281.4
502	47	1	144	197.79	0		226.830	291.4
502	47	2	17	198.02	0	SLOWEST RPM-ON LOWEST	165.180	298.6
502	47	2	17	198.02	1	PULLEY	162.603	303.3
502	47	2	30	198.15	0	REPEAT,NEXT PULLEY UP,	364.999	275.1
502	47	2	30	198.15	1	(FASTER)	353.055	278.1
502	47	2	45	198.30	0		326.928	282.0
502	47	2	45	198.30	1		341.721	287.4
502	47	2	60	198.45	0		336.839	290.2
502	47	2	60	198.45	1		321.130	294.6
502	47	2	75	198.60	0		166.657	198.3
502	47	2	75	198.60	1		157.699	203.0
502	48	1	17	200.90	0	PHI=035 DEGREES	358.374	293.0
502	48	1	30	201.03	0	MIDDLE PULLEY SEEMS OK,	256.941	163.3
502	48	1	45	201.18	0	WILL USE ON SUBSEQUENT	120.038	145.2
502	48	1	60	201.33	0	RUNS	93.785	185.8
502	48	1	75	201.48	0		240.224	157.1
502	48	1	90	201.63	0		473.239	152.1
502	48	1	105	201.78	0		435.441	153.0
502	48	1	120	201.93	0		164.713	158.6
502	48	1	135	202.08	0		100.517	159.7
502	48	1	144	202.17	0		122.232	138.8
502A	1	1	20	0.20	0	PHI=205 DEGREES	462.543	129.8
502A	1	1	30	0.30	0		93.610	213.4
502A	1	1	40	0.40	0		181.088	168.0
502A	1	1	50	0.50	0		553.015	209.8
502A	1	1	60	0.60	0		392.498	154.9
502A	1	1	70	0.70	0		115.177	140.7
502A	1	1	80	0.80	0		305.199	175.4
502A	1	1	90	0.90	0		210.233	112.2
502A	1	1	100	1.00	0		73.103	213.7
502A	1	1	110	1.10	0		95.698	145.8
502A	1	1	120	1.20	0		83.387	218.2
502A	1	1	130	1.30	0		196.205	153.8
502A	1	1	140	1.40	0		240.959	186.0
502A	1	1	145	1.45	0		218.064	184.5
502A	2	1	20	2.05	0	PHI=058 DEGREES	228.927	264.0
502A	2	1	30	2.15	0		164.758	242.5
502A	2	1	40	2.25	0		182.815	247.6
502A	2	1	50	2.35	0		157.333	243.3
502A	2	1	60	2.45	0		119.320	274.4
502A	2	1	70	2.55	0		147.321	249.5
502A	2	1	80	2.65	0		267.628	225.9

*** GRID M 06 ***

*** GRID N 06 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 a-6)	NRM Declination (deg.)
502A	2	1	90	2.75	0		389.099	185.2
502A	2	1	100	2.85	0		196.868	155.8
502A	2	1	110	2.95	0		510.701	195.3
502A	2	1	120	3.05	0		186.853	175.9
502A	2	1	130	3.15	0		260.503	225.8
502A	2	1	140	3.25	0		308.012	209.0
502A	2	1	144	3.29	0		315.659	212.7
502A	2	2	20	3.53	0		358.672	270.3
502A	2	2	30	3.63	0		401.160	284.1
502A	2	2	40	3.73	0		432.292	258.1
502A	2	2	50	3.83	0		654.530	268.7
502A	2	2	60	3.93	0		345.087	273.8
502A	2	2	70	4.03	0		311.171	270.4
502A	2	2	80	4.13	0		440.855	278.7
502A	2	2	90	4.23	0		137.123	279.8
502A	2	2	100	4.33	0		87.079	280.6
502A	2	2	110	4.43	0		120.454	261.4
502A	2	2	120	4.53	0		162.874	280.1
502A	2	2	130	4.63	0		185.493	288.4
502A	2	2	140	4.73	0		186.532	301.0
502A	2	2	145	4.78	0		206.304	329.1
502A	2	3	20	5.03	0		271.502	260.4
502A	2	3	30	5.13	0		403.956	269.1
502A	2	3	40	5.23	0		491.432	271.1
502A	2	3	50	5.33	0		298.966	302.0
502A	2	3	60	5.43	0		257.409	285.0
502A	2	3	70	5.53	0		196.186	274.4
502A	2	3	75	5.58	0		166.138	278.6
502A	3	1	20	6.50	0	PHI=342 DEGREES	579.985	157.3
502A	3	1	30	6.60	0		453.277	273.4
502A	3	1	40	6.70	0		179.444	78.4
502A	3	1	50	6.80	0		241.355	356.0
502A	3	1	60	6.90	0		613.111	225.6
502A	3	1	70	7.00	0		595.612	214.2
502A	3	1	80	7.10	0		245.534	220.3
502A	3	1	90	7.20	0		328.139	224.3
502A	3	1	100	7.30	0		224.324	261.0
502A	3	1	110	7.40	0		303.666	206.7
502A	3	1	120	7.50	0		400.612	227.2
502A	3	1	130	7.60	0		424.971	251.5
502A	3	1	140	7.70	0		385.840	228.6
502A	3	1	145	7.75	0		165.826	165.2
502A	3	2	20	7.90	0		565.093	251.3
502A	3	2	30	8.00	0		605.624	217.8
502A	3	2	40	8.10	0		291.398	272.3
502A	3	2	50	8.20	0		317.665	162.2
502A	3	2	60	8.30	0		178.800	244.0
502A	3	2	70	8.40	0		302.127	242.2
502A	3	2	80	8.50	0		362.230	252.2
502A	3	2	90	8.60	0		361.588	250.9
502A	3	2	100	8.70	0		269.567	253.1
502A	3	2	110	8.80	0		285.726	267.5
502A	3	2	120	8.90	0		316.522	263.1

*** GRID N 06 ***

*** GRID B 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	3	2	130	9.00	0		391.423	258.5
502A	3	2	140	9.10	0		512.465	274.3
502A	3	2	144	9.14	0	CORE SLIPPING IN LINER	505.394	274.2
502A	3	3	20	9.39	0	CORE SLIPPING IN LINER	332.276	292.7
502A	3	3	30	9.49	0	CORE SLIPPING IN LINER	369.200	282.0
502A	3	3	40	9.59	0	CORE SLIPPING IN LINER	282.609	280.8
502A	3	3	50	9.69	0		234.532	286.8
502A	3	3	60	9.79	0		97.827	298.6
502A	3	3	70	9.89	0		177.063	305.0
502A	3	3	80	9.99	0		327.782	290.5
502A	3	3	90	10.09	0		362.932	297.1
502A	3	3	100	10.19	0		133.088	289.1
502A	3	3	110	10.29	0		66.129	264.9
502A	3	3	119	10.38	0		175.877	300.1
502A	4	1	20	10.90	0	PHI=063 DEGREES	99.977	101.5
502A	4	1	30	11.00	0		165.208	141.8
502A	4	1	40	11.10	0		317.974	127.9
502A	4	1	50	11.20	0		149.066	80.1
502A	4	1	60	11.30	0		293.190	157.5
502A	4	1	70	11.40	0		590.745	32.6
502A	4	1	80	11.50	0		508.389	94.7
502A	4	1	90	11.60	0		204.351	175.4
502A	4	1	100	11.70	0		455.469	195.5
502A	4	1	110	11.80	0		590.704	146.4
502A	4	1	120	11.90	0		264.959	138.2
502A	4	1	130	12.00	0		244.429	165.2
502A	4	1	140	12.10	0		180.297	150.9
502A	4	1	144	12.14	0		314.436	140.4
502A	4	2	20	12.36	0		513.426	173.9
502A	4	2	30	12.46	0		464.782	154.8
502A	4	2	40	12.56	0		293.097	148.0
502A	4	2	50	12.66	0		317.910	151.6
502A	4	2	60	12.76	0		342.882	140.2
502A	4	2	70	12.86	0		513.836	146.5
502A	4	2	80	12.96	0		332.759	152.3
502A	4	2	90	13.06	0		531.998	143.3
502A	4	2	100	13.16	0		508.663	134.5
502A	4	2	110	13.26	0		450.351	136.7
502A	4	2	120	13.36	0		466.026	133.9
502A	4	2	130	13.46	0		320.580	176.7
502A	4	2	140	13.56	0		303.217	130.3
502A	4	2	144	13.60	0		267.369	112.0
502A	4	3	20	13.86	0	CORE LOOSE & SHIFTY IN	210.366	226.0
502A	4	3	30	13.96	0	LINER	221.723	246.5
502A	4	3	40	14.06	0		179.380	239.7
502A	4	3	50	14.16	0		171.088	264.3
502A	4	3	60	14.26	0		259.518	256.3
502A	4	3	70	14.36	0		200.925	275.8
502A	4	3	80	14.46	0		257.335	219.6
502A	4	3	90	14.56	0		68.524	120.0
502A	4	3	101	14.67	0		187.684	227.3
502A	5	1	20	15.30	0	PHI=222 DEGREES	141.905	160.7
502A	5	1	30	15.40	0		255.991	142.6

*** GRID B 07 ***

*** GRID C 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 e-6)	NRM Declination (deg.)
502A	5	1	40	15.50	0		239.199	160.1
502A	5	1	50	15.60	0		294.415	163.0
502A	5	1	60	15.70	0		240.690	166.2
502A	5	1	70	15.80	0		231.692	24.3
502A	5	1	80	15.90	0		247.223	161.0
502A	5	1	90	16.00	0		325.932	162.2
502A	5	1	100	16.10	0		50.725	168.3
502A	5	1	110	16.20	0		83.315	180.7
502A	5	1	120	16.30	0		299.389	205.3
502A	5	1	130	16.40	0		158.487	204.5
502A	5	1	140	16.50	0		281.092	224.8
502A	5	1	144	16.54	0		251.145	224.1
502A	5	2	20	16.75	0		201.904	190.7
502A	5	2	30	16.85	0		181.613	200.8
502A	5	2	40	16.95	0		291.810	205.9
502A	5	2	50	17.05	0		264.746	219.2
502A	5	2	60	17.15	0		36.106	223.2
502A	5	2	70	17.25	0		77.442	47.9
502A	5	2	80	17.35	0		168.336	61.2
502A	5	2	90	17.45	0		15.823	66.4
502A	5	2	100	17.55	0		34.666	300.3
502A	5	2	110	17.65	0		75.776	83.9
502A	5	2	120	17.75	0		19.058	266.2
502A	5	2	130	17.85	0		51.710	113.3
502A	5	2	140	17.95	0		158.447	122.3
502A	5	2	144	17.99	0		168.706	139.2
502A	5	3	20	18.25	0		219.958	9.9
502A	5	3	30	18.35	0		253.257	9.4
502A	5	3	40	18.45	0		364.115	13.4
502A	5	3	50	18.55	0		420.625	15.8
502A	5	3	60	18.65	0		54.886	8.2
502A	5	3	70	18.75	0		22.754	347.3
502A	5	3	80	18.85	0		58.693	181.0
502A	5	3	90	18.95	0		93.073	220.7
502A	5	3	100	19.05	0		14.841	270.8
502A	5	3	110	19.15	0		93.015	30.1
502A	5	3	120	19.25	0		218.975	33.9
502A	5	3	124	19.29	0		186.880	37.7
502A	6	1	20	19.57	0	PHI=152 DEGREES	12.973	331.0
502A	6	1	30	19.67	0		1012.378	165.0
502A	6	1	40	19.77	0		748.064	159.2
502A	6	1	50	19.87	0	CORE TWISTED INSIDE THE	119.899	199.2
502A	6	1	60	19.97	0	LINER FROM HERE TO 6-3,	74.417	270.6
502A	6	1	70	20.07	0	50 CM	90.819	299.5
502A	6	1	80	20.17	0		56.840	220.8
502A	6	1	90	20.27	0		52.912	352.3
502A	6	1	100	20.37	0		39.077	352.3
502A	6	1	110	20.47	0		47.463	353.6
502A	6	1	120	20.57	0		113.727	341.4
502A	6	1	129	20.66	0		294.149	54.1
502A	6	2	20	20.78	0		73.252	92.1
502A	6	2	30	20.88	0		149.852	85.3
502A	6	2	40	20.98	0		479.904	82.8

*** GRID C 07 ***

*** GRID D 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	6	2	50	21.08	0		322.785	86.8
502A	6	2	60	21.18	0		190.792	75.4
502A	6	2	70	21.28	0		222.934	80.5
502A	6	2	80	21.38	0		170.663	72.1
502A	6	2	90	21.48	0		201.882	69.9
502A	6	2	100	21.58	0		141.184	65.5
502A	6	2	110	21.68	0		138.266	68.2
502A	6	2	120	21.78	0		68.280	335.3
502A	6	2	130	21.88	0		75.304	63.9
502A	6	2	140	21.98	0		121.355	73.3
502A	6	2	144	22.02	0		109.653	63.9
502A	6	3	20	22.28	0		9.529	0.6
502A	6	3	30	22.38	0		49.781	306.0
502A	6	3	50	22.58	0		35.300	254.2
502A	6	3	60	22.68	0		10.648	258.5
502A	6	3	70	22.78	0		20.534	325.8
502A	6	3	80	22.88	0		57.530	261.8
502A	6	3	90	22.98	0		141.101	250.6
502A	6	3	100	23.08	0		100.387	246.9
502A	6	3	110	23.18	0		54.618	227.6
502A	6	3	120	23.22	0		11.900	191.1
502A	6	3	130	23.22	0		13.069	235.8
502A	6	3	140	23.28	0		158.211	178.4
502A	6	3	144	23.32	0		106.877	202.9
502A	7	1	20	24.05	0	PHI=230 DEGREES	249.730	171.7
502A	7	1	30	24.15	0		620.432	335.2
502A	7	1	40	24.25	0		439.253	35.7
502A	7	1	50	24.35	0		102.560	31.6
502A	7	1	60	24.45	0		1762.870	293.9
502A	7	1	70	24.55	0		247.964	330.8
502A	7	1	80	24.65	0		246.995	281.4
502A	7	1	90	24.75	0		110.401	48.4
502A	7	1	100	24.85	0		47.181	87.0
502A	7	1	110	24.95	0		13.298	68.0
502A	7	1	120	25.05	0		115.511	133.5
502A	7	1	130	25.15	0		55.687	103.4
502A	7	2	60	25.74	0	BASE OF SEC. 1 AND TOP	157.561	246.7
502A	7	2	70	25.84	0	OF SEC. 2 DISTURBED	196.005	249.3
502A	7	2	80	25.94	0		29.849	269.3
502A	7	2	90	26.04	0		67.408	85.7
502A	7	2	100	26.14	0		92.832	102.6
502A	7	2	110	26.24	0		108.731	86.9
502A	7	2	120	26.34	0		61.935	82.9
502A	7	2	130	26.44	0		13.574	154.5
502A	7	2	140	26.54	0		49.223	245.4
502A	7	2	144	26.58	0		81.816	240.3
502A	7	3	20	26.84	0		128.047	247.4
502A	7	3	30	26.94	0		223.680	246.4
502A	7	3	40	27.04	0		52.372	248.4
502A	7	3	50	27.14	0		23.794	127.8
502A	7	3	60	27.24	0		26.168	173.8
502A	7	3	70	27.34	0		149.546	249.2
502A	7	3	80	27.44	0		165.646	249.5

*** GRID D 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	7	3	90	27.54	0		115.682	250.1
502A	7	3	100	27.64	0		243.224	254.9
502A	7	3	110	27.74	0		175.447	247.2
502A	7	3	120	27.84	0		101.410	270.4
502A	7	3	130	27.94	0		67.161	245.4
502A	7	3	140	28.04	0		72.281	236.2
502A	7	3	144	28.08	0		29.290	215.0
502A	8	1	30	28.48	0	PHI=301 DEGREES	211.462	182.5
502A	8	1	40	28.58	0	CORE IS SOUPY & SLOSHING	378.765	238.6
502A	8	1	50	28.68	0	AROUND IN LINER	134.033	234.0
502A	8	1	60	28.78	0		116.407	297.1
502A	8	1	70	28.88	0		196.879	49.4
502A	8	1	80	28.98	0		183.494	166.3
502A	8	1	90	29.08	0		124.541	138.3
502A	8	1	100	29.18	0		84.865	84.2
502A	8	1	110	29.28	0		140.131	234.6
502A	8	1	120	29.38	0		154.139	247.8
502A	8	1	130	29.48	0		186.817	258.4
502A	8	1	140	29.58	0		206.579	257.1
502A	8	1	144	29.62	0		118.372	272.0
502A	8	2	20	29.70	0	REPEAT DUE TO SLIP IN	173.978	243.7
502A	8	2	30	29.80	0	HOLDER	162.051	252.8
502A	8	2	40	29.90	0		37.849	274.8
502A	8	2	50	30.00	0		86.280	262.1
502A	8	2	60	30.10	0		182.594	238.9
502A	8	2	70	30.20	0		141.726	242.7
502A	8	2	80	30.30	0		123.377	253.0
502A	8	2	90	30.40	0		180.007	240.9
502A	8	2	100	30.50	0		89.456	257.6
502A	8	2	110	30.60	0		75.466	243.6
502A	8	2	120	30.70	0		40.482	264.4
502A	8	2	130	30.80	0		99.502	251.8
502A	8	2	144	30.94	0		14.608	219.8
502A	8	3	5	31.06	0		138.001	143.7
502A	8	3	10	31.11	0		106.852	130.9
502A	8	3	15	31.16	0		112.124	133.4
502A	9	1	6	32.76	0	PHI=040 DEGREES	150.323	178.7
502A	9	1	16	32.86	0		76.245	136.6
502A	10	1	20	37.30	0	PHI=061 DEGREES	217.573	35.4
502A	10	1	30	37.40	0		44.449	188.8
502A	10	1	40	37.50	0		348.380	51.0
502A	10	1	50	37.60	0		908.083	66.0
502A	10	1	60	37.70	0		93.168	134.9
502A	10	1	70	37.80	0		70.833	30.5
502A	10	1	80	37.90	0		106.768	50.0
502A	10	1	90	38.00	0		36.515	10.9
502A	10	1	100	38.10	0		166.513	12.9
502A	10	1	110	38.20	0		180.865	340.4
502A	10	1	120	38.30	0		179.432	341.4
502A	10	1	130	38.40	0		229.890	0.4
502A	10	1	140	38.50	0		139.646	293.7
502A	10	1	150	38.60	0		153.572	341.5
502A	10	2	20	38.80	0		230.123	337.9

*** GRID F 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	10	2	30	38.90	0		91.803	350.3
502A	10	2	40	39.00	0		160.211	335.3
502A	10	2	50	39.10	0		154.839	173.8
502A	10	2	60	39.20	0		201.727	337.1
502A	10	2	70	39.30	0		209.969	335.9
502A	10	2	80	39.40	0		169.943	338.8
502A	10	2	90	39.50	0		68.440	342.7
502A	10	2	100	39.60	0		23.049	347.6
502A	10	2	110	39.70	0		31.010	75.8
502A	10	2	120	39.80	0		112.770	127.5
502A	10	2	130	39.90	0		278.150	148.8
502A	10	2	140	40.00	0		333.168	150.6
502A	10	2	145	40.05	0		338.606	149.9
502A	10	3	20	40.30	0		93.957	145.9
502A	10	3	30	40.40	0		206.147	138.1
502A	10	3	40	40.50	0		388.253	144.3
502A	10	3	50	40.60	0		349.951	144.2
502A	10	3	60	40.70	0		352.900	147.0
502A	10	3	70	40.80	0		282.237	149.7
502A	10	3	80	40.90	0		191.185	145.5
502A	10	3	90	41.00	0		130.581	142.2
502A	10	3	100	41.10	0		255.195	144.3
502A	10	3	110	41.20	0		283.043	144.7
502A	10	3	120	41.30	0		88.759	144.6
502A	11	1	5	41.55	0	PHI=045 DEGREES	221.698	311.2
502A	11	1	10	41.60	0		1196.834	0.8
502A	11	1	15	41.65	0		3924.073	323.7
502A	11	1	17	41.67	0		1759.954	306.9
502A	12	1	20	46.00	0	PHI=240 DEGREES	483.075	248.6
502A	12	1	30	46.10	0		127.889	10.4
502A	12	1	40	46.20	0		72.975	350.9
502A	12	1	50	46.30	0		79.030	86.0
502A	12	1	60	46.40	0		243.154	98.4
502A	12	1	70	46.50	0		61.419	98.7
502A	12	1	80	46.60	0		61.411	77.6
502A	12	1	90	46.70	0		288.346	122.5
502A	12	1	100	46.80	0		156.951	259.1
502A	12	1	110	46.90	0		97.382	330.3
502A	12	1	120	47.00	0		237.004	260.2
502A	12	1	130	47.10	0		203.857	250.5
502A	12	1	140	47.20	0		61.328	259.3
502A	12	1	145	47.25	0		140.512	226.2
502A	12	2	20	47.48	0		320.945	251.5
502A	12	2	30	47.58	0		296.699	252.4
502A	12	2	40	47.68	0		224.040	249.5
502A	12	2	50	47.78	0		139.160	259.8
502A	12	2	60	47.88	0		106.573	245.0
502A	12	2	70	47.98	0		124.427	239.0
502A	12	2	80	48.08	0		168.726	232.6
502A	12	2	90	48.18	0		343.256	298.8
502A	12	2	100	48.28	0		385.083	236.6
502A	12	2	110	48.38	0		171.985	229.4
502A	12	2	120	48.48	0		217.271	255.9

*** GRID F 07 ***

*** GRID G 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	12	2	130	48.58	0		357.760	260.6
502A	12	2	140	48.68	0		197.429	258.9
502A	12	2	145	48.73	0		281.122	230.7
502A	12	3	20	48.98	0		68.350	261.2
502A	12	3	30	49.08	0		22.837	129.6
502A	12	3	40	49.18	0		34.736	75.0
502A	12	3	50	49.28	0		153.663	60.9
502A	12	3	60	49.38	0		339.996	14.8
502A	12	3	70	49.48	0		271.901	46.2
502A	12	3	80	49.58	0		34.734	257.4
502A	12	3	85	49.63	0		4.572	164.4
502A	16	1	20	63.70	0	PHI=209 DEGREES	105.216	201.7
502A	16	1	30	63.80	0		110.955	225.9
502A	16	1	40	63.90	0		92.813	175.0
502A	16	1	50	64.00	0		178.497	217.3
502A	16	1	60	64.10	0		35.931	240.7
502A	16	1	70	64.20	0		113.747	76.6
502A	16	1	80	64.30	0		89.423	43.1
502A	16	1	90	64.40	0		116.261	340.6
502A	16	1	100	64.50	0		174.270	354.2
502A	16	1	110	64.60	0		30.053	83.7
502A	16	1	120	64.70	0		261.646	322.2
502A	16	1	130	64.80	0		306.081	336.2
502A	16	1	140	64.90	0		206.853	284.8
502A	16	1	145	64.95	0		257.698	266.6
502A	16	2	20	65.19	0		55.943	50.9
502A	16	2	30	65.29	0		118.543	15.7
502A	16	2	40	65.39	0		220.341	19.5
502A	16	2	50	65.49	0		427.945	19.1
502A	16	2	60	65.59	0		219.746	21.3
502A	16	2	70	65.69	0		139.747	9.0
502A	16	2	80	65.79	0		220.987	13.8
502A	16	2	90	65.89	0		190.122	19.5
502A	16	2	100	65.99	0		118.910	20.2
502A	16	2	110	66.09	0		158.670	21.5
502A	16	2	120	66.19	0		152.504	23.8
502A	16	2	130	66.29	0		263.475	24.3
502A	16	2	140	66.39	0		318.639	20.4
502A	16	2	144	66.43	0		286.140	20.0
502A	16	3	5	66.55	0		296.616	10.2
502A	16	3	15	66.65	0		264.511	9.4
502A	16	3	25	66.75	0		236.980	11.5
502A	16	3	29	66.79	0		194.116	13.2
502A	17	1	20	68.10	0	PHI=239 DEGREES	117.986	272.7
502A	17	1	30	68.20	0	TOP 40CM CRUMBLY	130.718	59.2
502A	17	1	40	68.30	0		153.923	96.0
502A	17	1	50	68.40	0		122.019	61.0
502A	17	1	60	68.50	0		11.146	111.2
502A	17	1	70	68.60	0		143.365	86.2
502A	17	1	80	68.70	0		184.498	112.0
502A	17	1	90	68.80	0		281.919	108.1
502A	17	1	100	68.90	0		371.005	98.5
502A	17	1	110	69.00	0		354.695	108.7

*** GRID G 07 ***

*** GRID H 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	17	1	120	69.10	0		332.518	102.5
502A	17	1	130	69.20	0		315.395	103.3
502A	17	1	140	69.30	0		353.737	107.0
502A	17	1	144	69.34	0		341.940	105.3
502A	17	2	20	69.61	0		347.362	98.5
502A	17	2	30	69.71	0		373.243	100.2
502A	17	2	40	69.81	0		409.321	99.7
502A	17	2	50	69.91	0		359.928	94.4
502A	17	2	60	70.01	0		330.718	93.1
502A	17	2	70	70.11	0		315.555	97.9
502A	17	2	80	70.21	0		361.940	99.0
502A	17	2	90	70.31	0		375.789	99.3
502A	17	2	100	70.41	0		361.512	99.6
502A	17	2	110	70.51	0		260.587	99.4
502A	17	2	130	70.71	0		210.763	97.2
502A	17	2	140	70.81	0		278.699	94.5
502A	17	2	145	70.86	0		281.439	98.8
502A	17	3	20	71.10	0		375.978	111.5
502A	17	3	30	71.20	0		400.899	101.5
502A	17	3	40	71.30	0		443.464	98.0
502A	17	3	50	71.40	0		368.800	102.5
502A	17	3	60	71.50	0		254.292	94.1
502A	17	3	70	71.60	0		200.163	94.7
502A	17	3	80	71.70	0		135.907	91.4
502A	17	3	90	71.80	0		233.722	97.3
502A	17	3	100	71.90	0		268.247	97.0
502A	17	3	110	72.00	0		210.481	97.6
502A	17	3	120	72.10	0		113.430	309.7
502A	17	3	129	72.19	0		228.074	234.5
502A	19	1	20	76.64	0	PHI=241 DEGREES	90.372	229.5
502A	19	1	30	76.74	0		15.964	176.6
502A	19	1	40	76.84	0		71.405	34.9
502A	19	1	50	76.94	0		16.943	72.8
502A	19	1	60	77.04	0		30.432	237.0
502A	19	1	70	77.14	0		8.023	240.2
502A	19	1	80	77.24	0		129.063	249.9
502A	19	1	90	77.34	0		63.503	218.9
502A	19	1	100	77.44	0		4.709	8.1
502A	19	1	110	77.54	0		103.945	263.8
502A	19	1	120	77.64	0		69.350	238.6
502A	19	1	130	77.74	0		35.747	306.9
502A	19	1	140	77.84	0		111.715	233.5
502A	19	1	145	77.89	0		90.755	227.9
502A	19	2	20	78.13	0		191.123	226.6
502A	19	2	30	78.23	0		156.979	75.6
502A	19	2	40	78.33	0		539.270	70.5
502A	19	2	50	78.43	0		243.916	28.1
502A	19	2	60	78.53	0		287.727	34.4
502A	19	2	70	78.63	0		208.830	40.8
502A	19	2	80	78.73	0		283.465	21.6
502A	19	2	90	78.83	0		195.084	40.0
502A	19	2	100	78.93	0		200.076	29.0
502A	19	2	110	79.03	0		283.729	19.3

*** GRID H 07 ***

*** GRID I 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 a-6)	NRM Declination (deg.)
502A	19	2	120	79.13	0		146.763	57.5
502A	19	2	130	79.23	0		173.447	70.1
502A	19	2	140	79.33	0		37.746	5.7
502A	19	2	145	79.38	0		92.881	222.7
502A	19	3	20	79.65	0		147.437	239.2
502A	19	3	30	79.75	0		142.760	110.9
502A	19	3	40	79.85	0		45.306	255.0
502A	19	3	50	79.95	0		45.790	72.9
502A	19	3	60	80.05	0		86.430	65.3
502A	19	3	70	80.15	0		56.743	31.2
502A	19	3	80	80.25	0		48.411	324.3
502A	19	3	90	80.35	0		82.421	42.6
502A	19	3	100	80.45	0		79.052	329.5
502A	20	1	110	82.20	0	PHI=310 DEGREES	264.004	94.7
502A	20	1	120	82.30	0	TOP PART OF CORE DAMAGED	142.068	330.4
502A	20	1	130	82.40	0		214.878	15.7
502A	20	1	140	82.50	0		221.270	43.9
502A	20	1	145	82.55	0		226.230	286.7
502A	20	2	20	82.67	0		828.140	18.3
502A	20	2	30	82.77	0		794.646	236.0
502A	20	2	40	82.87	0		137.240	332.7
502A	20	2	50	82.97	0		107.725	357.6
502A	20	2	60	83.07	0		83.783	29.3
502A	20	2	70	83.17	0		28.996	289.7
502A	20	2	80	83.27	0		50.991	12.4
502A	20	2	90	83.37	0		24.577	316.1
502A	20	2	100	83.47	0		63.810	179.0
502A	20	2	110	83.57	0		128.893	212.3
502A	20	2	120	83.67	0		91.632	214.4
502A	20	2	130	83.77	0		25.645	48.5
502A	20	2	140	83.87	0		74.854	260.4
502A	20	2	145	83.92	0		56.904	229.6
502A	20	3	20	84.18	0		108.227	193.1
502A	20	3	30	84.28	0		88.237	206.9
502A	20	3	40	84.38	0		16.285	120.5
502A	20	3	50	84.48	0		423.172	136.4
502A	20	3	60	84.58	0		136.480	135.9
502A	20	3	70	84.68	0		33.231	237.0
502A	20	3	80	84.78	0		53.022	193.8
502A	20	3	90	84.88	0		62.728	201.5
502A	20	3	100	84.98	0		83.825	180.3
502A	20	3	110	85.08	0		181.142	189.6
502A	20	3	120	85.18	0		240.236	182.4
502A	20	3	130	85.28	0		261.339	188.1
502A	20	3	140	85.38	0		227.062	161.7
502A	20	3	142	85.40	0		91.476	214.4
502A	21	1	20	85.64	0	PHI=101 DEGREES	293.391	25.8
502A	21	1	30	85.74	0		260.064	354.5
502A	21	1	40	85.84	0		1505.477	357.9
502A	21	1	50	85.94	0		130.508	352.1
502A	21	1	60	86.04	0		203.559	25.0
502A	21	1	70	86.14	0		277.270	43.8
502A	21	1	80	86.24	0		85.064	255.3

*** GRID I 07 ***

*** GRID J 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	21	1	90	86.34	0		72.337	57.9
502A	21	1	100	86.44	0		128.413	5.4
502A	21	1	110	86.54	0		116.652	25.3
502A	21	1	120	86.64	0		298.870	10.7
502A	21	1	130	86.74	0		313.131	23.0
502A	21	1	140	86.84	0		220.795	20.7
502A	21	1	143	86.87	0		239.832	16.6
502A	21	1	143	86.87	1	REPEAT	243.678	16.2
502A	21	2	20	87.16	0	VOID 43-70CM	313.050	32.6
502A	21	2	30	87.26	0		344.100	28.9
502A	21	2	40	87.36	0		205.288	21.6
502A	21	2	50	87.46	0		37.299	46.6
502A	21	2	60	87.56	0		149.366	0.2
502A	21	2	70	87.66	0		4.364	20.5
502A	21	2	80	87.76	0		103.624	95.4
502A	21	2	90	87.86	0		329.974	30.9
502A	21	2	100	87.96	0		421.152	28.4
502A	21	2	110	88.06	0		374.195	22.7
502A	21	2	120	88.16	0		376.095	35.1
502A	21	2	130	88.26	0		429.444	23.5
502A	21	2	136	88.32	0		340.175	350.5
502A	21	3	20	88.66	0		364.283	17.7
502A	21	3	30	88.76	0		396.649	22.0
502A	21	3	40	88.86	0		358.785	27.5
502A	21	3	50	88.88	0		423.577	23.4
502A	21	3	60	88.88	0		454.485	25.5
502A	21	3	70	88.88	0		654.257	60.8
502A	21	3	80	88.93	0		250.608	22.7
502A	21	3	90	89.03	0		253.428	26.8
502A	21	3	100	89.13	0		408.040	27.6
502A	21	3	110	89.23	0		398.064	20.7
502A	21	3	120	89.33	0		325.759	36.9
502A	21	3	130	89.43	0		254.636	32.5
502A	21	3	140	89.53	0		265.804	27.1
502A	21	3	145	89.58	0		228.096	30.1
502A	22	1	20	90.10	0	PHI=197 DEGREES	297.879	323.2
502A	22	1	30	90.20	0		398.269	325.1
502A	22	1	40	90.30	0		364.397	330.3
502A	22	1	50	90.40	0		339.090	333.5
502A	22	1	60	90.50	0		363.342	323.9
502A	22	1	70	90.60	0		191.161	326.2
502A	22	1	80	90.70	0		661.973	343.4
502A	22	1	90	90.80	0		273.723	344.0
502A	22	1	100	90.90	0		366.905	339.4
502A	22	1	110	91.00	0		405.514	350.8
502A	22	1	120	91.10	0		401.099	347.0
502A	22	1	130	91.20	0		342.509	19.2
502A	22	1	140	91.30	0		361.995	345.9
502A	22	1	145	91.35	0		352.039	341.9
502A	22	2	20	91.61	0		392.557	340.4
502A	22	2	30	91.71	0		225.450	341.5
502A	22	2	40	91.81	0		351.815	218.4
502A	22	2	50	91.91	0		63.263	347.7

*** GRID J 07 ***

*** GRID K 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	22	2	60	92.01	0		111.236	213.2
502A	22	2	70	92.11	0		128.305	195.2
502A	22	2	80	92.21	0		123.435	183.9
502A	22	2	90	92.31	0		73.914	185.8
502A	22	2	100	92.41	0		28.876	202.2
502A	22	2	110	92.51	0		54.840	163.2
502A	22	2	120	92.58	0		60.697	162.8
502A	22	2	130	92.68	0		114.692	157.8
502A	22	2	140	92.78	0		65.617	159.7
502A	22	2	145	92.83	0		295.103	42.4
502A	22	3	20	93.09	0		146.810	175.7
502A	22	3	30	93.19	0		113.220	189.4
502A	22	3	40	93.25	0		49.176	183.2
502A	22	3	50	93.35	0		89.103	185.2
502A	22	3	60	93.51	0		32.098	54.9
502A	22	3	70	93.61	0		26.057	139.8
502A	22	3	80	93.71	0		9.804	194.3
502A	22	3	90	93.81	0		3.805	198.2
502A	22	3	100	93.91	0		138.072	185.9
502A	22	3	110	94.01	0		148.577	186.9
502A	22	3	120	94.11	0		122.239	183.1
502A	22	3	130	94.21	0		151.086	179.3
502A	22	3	140	94.31	0		73.380	179.8
502A	22	3	145	94.36	0		12.725	150.7
502A	23	1	20	94.50	0	PHI=135 DEGREES	884.893	31.0
502A	23	1	30	94.60	0	TOP 50 CM DAMAGED	1051.496	271.3
502A	23	1	40	94.70	0	ORIENTATION MAY BE LOST	152.977	241.1
502A	23	1	50	94.80	0		84.631	257.3
502A	23	1	60	94.90	0		237.350	19.6
502A	23	1	70	95.00	0		552.200	253.6
502A	23	1	80	95.10	0		183.259	12.7
502A	23	1	90	95.20	0		176.012	29.9
502A	23	1	100	95.30	0		206.010	29.6
502A	23	1	110	95.40	0		130.956	25.5
502A	23	1	120	95.50	0		173.581	42.2
502A	23	1	130	95.60	0		136.064	53.8
502A	23	1	140	95.70	0		133.140	25.0
502A	23	1	145	95.75	0		132.579	15.3
502A	23	2	20	95.96	0		206.100	11.5
502A	23	2	30	96.06	0		175.691	9.9
502A	23	2	40	96.16	0		213.597	18.9
502A	23	2	50	96.26	0		189.091	24.4
502A	23	2	60	96.36	0		278.021	22.7
502A	23	2	70	96.46	0		184.809	21.0
502A	23	2	80	96.56	0		152.150	15.4
502A	23	2	90	96.66	0		132.688	9.1
502A	23	2	100	96.76	0		193.410	21.5
502A	23	2	110	96.86	0		307.399	28.0
502A	23	2	120	96.96	0		169.517	28.2
502A	23	2	130	97.06	0		162.998	25.3
502A	23	2	140	97.16	0		160.282	29.6
502A	23	2	145	97.21	0		146.177	29.4
502A	23	3	20	97.47	0	MISORIENTED IN SPINNER	266.272	43.9

*** GRID K 07 ***

*** GRID L 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	23	3	30	97.57	0	ABOUT 5 TO 6 DEGREES	237.742	41.7
502A	23	3	40	97.67	0		153.812	39.1
502A	23	3	50	97.77	0		177.336	39.1
502A	23	3	60	97.87	0		198.617	43.1
502A	23	3	70	97.97	0		221.901	36.9
502A	23	3	80	98.07	0		271.750	41.4
502A	23	3	90	98.17	0		191.828	34.6
502A	23	3	100	98.27	0		126.247	24.7
502A	23	3	110	98.37	0		183.296	38.0
502A	23	3	120	98.47	0		266.130	34.6
502A	23	3	130	98.57	0		310.490	44.3
502A	23	3	140	98.67	0		264.350	40.8
502A	23	3	145	98.72	0		243.065	44.2
502A	24	1	32	99.02	0	PHI=237 DEGREES	175.865	302.0
502A	24	1	40	99.10	0	TOP 20CM DAMAGED	239.555	349.5
502A	24	1	50	99.20	0		233.439	12.5
502A	24	1	60	99.30	0		162.930	5.8
502A	24	1	70	99.40	0		291.307	353.5
502A	24	1	80	99.50	0		281.259	357.3
502A	24	1	90	99.60	0		204.820	0.5
502A	24	1	100	99.70	0		185.790	12.8
502A	24	1	110	99.80	0		220.541	356.3
502A	24	1	120	99.90	0		223.675	24.7
502A	24	1	130	100.00	0		276.894	1.0
502A	24	1	140	100.10	0		333.898	357.6
502A	24	1	144	100.14	0		311.822	350.8
502A	24	2	20	100.41	0		249.370	356.7
502A	24	2	30	100.51	0		177.400	331.9
502A	24	2	40	100.61	0		246.890	4.3
502A	24	2	50	100.71	0		232.744	342.5
502A	24	2	60	100.81	0		268.579	1.7
502A	24	2	70	100.91	0		117.416	338.8
502A	24	2	80	101.01	0		151.258	4.3
502A	24	2	90	101.11	0		189.291	345.2
502A	24	2	100	101.21	0		253.117	350.9
502A	24	2	110	101.31	0		147.048	349.5
502A	24	2	120	101.41	0		165.919	347.2
502A	24	2	130	101.51	0		141.912	316.7
502A	24	2	140	101.61	0		207.688	356.4
502A	24	2	144	101.65	0		337.209	356.7
502A	24	3	20	101.92	0		314.556	333.9
502A	24	3	30	102.02	0		162.426	358.5
502A	24	3	40	102.12	0		141.452	312.1
502A	24	3	50	102.22	0		176.977	318.8
502A	24	3	60	102.32	0		186.169	333.2
502A	24	3	70	102.42	0		158.015	339.2
502A	24	3	80	102.52	0		147.935	328.0
502A	24	3	90	102.62	0		100.168	32.2
502A	24	3	100	102.72	0		124.149	337.4
502A	24	3	110	102.82	0		125.212	346.2
502A	24	3	120	102.92	0		359.175	311.9
502A	24	3	130	103.02	0		32.694	344.7
502A	24	3	140	103.12	0		78.463	140.4

*** GRID L 07 ***

*** GRID M 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	24	3	145	103.17	0		239.759	242.2
502A	25	1	20	103.25	0	PHI=031 DEGREES	1607.287	1.3
502A	25	1	20	103.25	0		1607.287	1.3
502A	25	1	30	103.35	0		1972.952	68.9
502A	25	1	40	103.45	0		162.713	50.4
502A	25	1	50	103.55	0		340.916	22.7
502A	25	1	60	103.65	0		407.258	257.1
502A	25	1	70	103.75	0		396.139	199.6
502A	25	1	80	103.85	0		298.601	146.0
502A	25	1	90	103.95	0		49.493	193.1
502A	25	1	100	104.05	0		108.613	200.2
502A	25	1	110	104.15	0		131.096	281.1
502A	25	1	120	104.25	0		226.926	240.9
502A	25	1	130	104.35	0		182.539	244.3
502A	25	1	140	104.45	0		143.030	247.2
502A	25	1	145	104.50	0		193.964	248.9
502A	25	2	20	104.72	0		162.451	205.3
502A	25	2	30	104.82	0		228.903	254.9
502A	25	2	40	104.92	0		205.409	234.9
502A	25	2	50	105.02	0		120.220	240.3
502A	25	2	60	105.12	0		270.447	348.6
502A	25	2	70	105.22	0		84.956	261.7
502A	25	2	80	105.32	0		119.606	252.3
502A	25	2	90	105.42	0		250.116	249.1
502A	25	2	100	105.52	0		266.162	243.5
502A	25	2	110	105.62	0		197.570	244.4
502A	25	2	120	105.72	0		188.000	240.1
502A	25	2	130	105.82	0		118.108	227.7
502A	25	2	140	105.92	0		80.335	234.2
502A	25	2	145	105.97	0		112.034	242.8
502A	25	3	20	106.22	0		225.210	242.7
502A	25	3	30	106.32	0		224.697	244.6
502A	25	3	40	106.42	0		106.812	246.0
502A	25	3	50	106.52	0		13.367	241.2
502A	25	3	60	106.62	0		73.262	254.9
502A	25	3	70	106.72	0		77.443	236.2
502A	25	3	80	106.82	0		84.070	250.6
502A	25	3	90	106.92	0		158.482	249.1
502A	25	3	100	107.02	0		188.230	251.7
502A	25	3	110	107.12	0		179.561	252.3
502A	25	3	120	107.22	0		194.216	253.7
502A	25	3	128	107.30	0		9.712	257.6
502A	26	1	40	107.90	0	PHI=040 DEGREES	214.633	234.5
502A	26	1	50	108.00	0	TOP OF CORE DAMAGED	197.793	158.2
502A	26	1	60	108.10	0		42.027	327.8
502A	26	1	70	108.20	0		113.227	147.8
502A	26	1	80	108.30	0		166.455	154.0
502A	26	1	90	108.40	0		221.748	16.4
502A	26	1	100	108.50	0		71.039	99.8
502A	26	1	110	108.60	0		145.726	277.3
502A	26	1	120	108.70	0		49.234	30.9
502A	26	1	130	108.80	0		226.786	325.7
502A	26	1	140	108.90	0		88.112	24.5

*** GRID M 07 ***

*** GRID N 07 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	26	1	144	108.94	0		76.892	38.8
502A	26	2	20	109.13	0		198.796	60.2
502A	26	2	30	109.23	0		242.875	37.5
502A	26	2	40	109.33	0		235.308	45.7
502A	26	2	50	109.43	0		181.359	44.6
502A	26	2	60	109.53	0		204.142	40.7
502A	26	2	70	109.63	0		472.441	73.3
502A	26	2	80	109.73	0		543.798	26.2
502A	26	2	90	109.83	0		424.094	43.5
502A	26	2	100	109.93	0		329.852	24.8
502A	26	2	110	110.03	0		194.254	29.5
502A	26	2	120	110.13	0		108.427	18.1
502A	26	2	130	110.23	0		250.473	11.3
502A	26	2	140	110.33	0		195.664	34.7
502A	26	2	144	110.37	0		210.852	28.6
502A	26	3	20	110.55	0		295.427	353.1
502A	26	3	30	110.65	0		347.182	348.4
502A	26	3	40	110.75	0		315.938	342.6
502A	26	3	50	110.85	0		362.202	339.8
502A	26	3	60	110.95	0		233.049	329.5
502A	26	3	70	111.05	0		183.455	332.9
502A	26	3	80	111.15	0		96.524	324.1
502A	26	3	90	111.25	0		377.360	342.8
502A	26	3	100	111.35	0		91.387	306.3
502A	26	3	110	111.45	0		82.825	330.8
502A	26	3	120	111.55	0		107.410	324.8
502A	26	3	130	111.65	0		55.700	296.3
502A	26	3	140	111.75	0		124.242	218.5
502A	26	3	144	111.79	0		20.215	193.1
502A	27	1	20	112.10	0	PHI=080 DEGREES	59.690	176.6
502A	27	1	30	112.20	0		365.939	17.1
502A	27	1	40	112.30	0		212.879	113.5
502A	27	1	50	112.40	0		190.316	127.4
502A	27	1	60	112.50	0		237.048	129.4
502A	27	1	70	112.60	0		270.072	126.0
502A	27	1	80	112.70	0		264.955	128.5
502A	27	1	90	112.80	0		598.885	77.3
502A	27	1	90	112.80	1	REPEAT	601.774	77.1
502A	27	1	100	112.90	0		310.225	136.2
502A	27	1	110	113.00	0		258.489	132.1
502A	27	1	120	113.10	0		181.104	118.7
502A	27	1	130	113.20	0		107.863	134.9
502A	27	1	140	113.30	0		112.199	120.2
502A	27	1	144	113.34	0		94.464	125.5
502A	27	2	20	113.60	0		220.736	131.0
502A	27	2	30	113.70	0		224.254	138.5
502A	27	2	40	113.80	0		187.788	128.1
502A	27	2	50	113.90	0		228.760	132.6
502A	27	2	60	114.00	0		269.656	132.2
502A	27	2	70	114.10	0		231.967	128.5
502A	27	2	80	114.20	0		119.638	114.2
502A	27	2	90	114.30	0		184.760	127.6
502A	27	2	100	114.40	0		242.926	124.8

*** GRID N 07 ***

*** GRID B 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	27	2	110	114.50	0		141.744	126.8
502A	27	2	120	114.60	0		67.733	124.9
502A	27	2	130	114.70	0		73.429	130.1
502A	27	2	140	114.80	0		82.267	106.2
502A	27	2	144	114.84	0		89.572	109.5
502A	27	3	20	115.10	0		311.689	117.0
502A	27	3	30	115.20	0		252.740	112.1
502A	27	3	40	115.30	0		343.535	125.6
502A	27	3	50	115.40	0		248.899	118.7
502A	27	3	60	115.50	0		333.597	110.5
502A	27	3	70	115.60	0		273.490	116.1
502A	27	3	80	115.70	0		170.944	116.8
502A	27	3	90	115.80	0		195.039	117.6
502A	27	3	100	115.90	0		232.751	119.8
502A	27	3	110	116.00	0		220.141	124.4
502A	27	3	120	116.07	0	VOID	20.893	166.8
502A	27	3	123	116.09	0	VOID	70.603	208.4
502A	28	1	20	116.38	0	PHI=052 DEGREES	200.223	174.9
502A	28	1	30	116.48	0		713.148	290.8
502A	28	1	40	116.58	0		448.129	261.8
502A	28	1	50	116.68	0		272.130	249.4
502A	28	1	60	116.78	0		38.963	202.6
502A	28	1	70	116.88	0		393.843	235.6
502A	28	1	80	116.98	0		10.761	25.2
502A	28	1	90	117.08	0		270.101	72.8
502A	28	1	100	117.18	0		440.567	68.4
502A	28	1	110	117.28	0		324.104	71.1
502A	28	1	120	117.38	0		472.642	64.6
502A	28	1	130	117.48	0		247.935	64.6
502A	28	1	140	117.58	0		181.892	74.4
502A	28	1	144	117.62	0		250.933	72.5
502A	28	2	20	117.84	0		495.725	59.7
502A	28	2	30	117.94	0		476.581	60.7
502A	28	2	40	118.04	0		370.333	69.8
502A	28	2	50	118.14	0		244.658	73.0
502A	28	2	60	118.24	0		151.019	58.7
502A	28	2	70	118.34	0		313.860	57.3
502A	28	2	80	118.44	0		200.905	42.0
502A	28	2	90	118.54	0		438.204	55.8
502A	28	2	100	118.64	0		478.888	48.5
502A	28	2	110	118.74	0		405.889	52.9
502A	28	2	120	118.84	0		284.120	58.7
502A	28	2	130	118.94	0		429.292	45.9
502A	28	2	140	119.04	0		388.895	50.9
502A	28	2	144	119.08	0		300.840	47.6
502A	28	3	5	119.19	0		293.159	65.5
502A	29	1	20	119.50	0	PHI=247 DEGREES	119.899	70.1
502A	29	1	30	119.60	0		347.894	235.7
502A	29	1	40	119.70	0		307.712	169.1
502A	29	1	50	119.80	0		414.277	113.6
502A	29	1	60	119.90	0		399.997	145.4
502A	29	1	70	120.00	0		336.574	157.1
502A	29	1	80	120.10	0		247.800	159.9

*** GRID B 08 ***

*** GRID C 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	29	1	90	120.20	0		197.795	156.9
502A	29	1	100	120.30	0		161.971	163.2
502A	29	1	110	120.40	0		37.812	243.6
502A	29	1	120	120.50	0		83.581	320.0
502A	29	1	130	120.60	0		238.657	326.3
502A	29	1	140	120.70	0		252.719	316.3
502A	29	1	144	120.74	0		301.231	323.1
502A	29	2	20	121.00	0		76.039	329.0
502A	29	2	30	121.10	0		193.396	336.9
502A	29	2	40	121.20	0		335.562	340.7
502A	29	2	50	121.30	0		310.977	331.4
502A	29	2	60	121.40	0		269.857	336.3
502A	29	2	70	121.50	0		17.369	141.6
502A	29	2	80	121.60	0		87.964	351.5
502A	29	2	90	121.70	0		84.976	330.8
502A	29	2	100	121.80	0		237.516	332.6
502A	29	2	110	121.90	0		237.480	349.0
502A	29	2	130	122.10	0		189.950	342.5
502A	29	2	140	122.20	0		235.984	347.6
502A	29	2	144	122.24	0		193.088	305.3
502A	29	3	5	122.35	0		253.144	350.9
502A	29	3	15	122.45	0		150.244	0.1
502A	29	3	25	122.55	0		87.022	31.3
502A	29	3	35	122.65	0		193.745	36.4
502A	29	3	45	122.75	0		224.339	8.6
502A	29	3	55	122.85	0		202.780	11.5
502A	30	1	20	123.00	0	PHI=270 DEGREES	204.140	327.8
502A	30	1	30	123.10	0		733.391	87.6
502A	30	1	40	123.20	0		290.903	90.2
502A	30	1	50	123.30	0		308.067	16.5
502A	30	1	60	123.40	0		512.482	325.7
502A	30	1	70	123.50	0		170.969	13.3
502A	30	1	80	123.60	0		378.668	267.1
502A	30	1	90	123.70	0		494.369	302.2
502A	30	1	100	123.80	0		329.407	12.7
502A	30	1	110	123.90	0		208.527	4.7
502A	30	1	120	124.00	0		168.947	358.2
502A	30	1	130	124.10	0		78.169	316.5
502A	30	1	140	124.20	0		150.656	340.0
502A	30	1	145	124.25	0		78.266	15.4
502A	30	2	20	124.48	0		240.987	329.6
502A	30	2	30	124.58	0		249.582	331.5
502A	30	2	40	124.68	0		233.992	316.1
502A	30	2	50	124.78	0		262.407	323.0
502A	30	2	60	124.88	0		245.390	318.3
502A	30	2	70	124.98	0		238.990	313.0
502A	30	2	80	125.08	0		227.201	326.7
502A	30	2	90	125.18	0		362.320	322.5
502A	30	2	100	125.28	0		256.155	325.5
502A	30	2	110	125.38	0		112.468	337.0
502A	30	2	120	125.48	0		141.078	315.1
502A	30	2	130	125.58	0		231.505	328.4
502A	30	2	140	125.68	0		217.190	321.5

*** GRID C 08 ***

*** GRID D 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	30	2	145	125.73	0		232.377	324.1
502A	30	3	10	125.88	0		192.025	335.4
502A	30	3	20	125.98	0		140.685	329.6
502A	30	3	25	126.03	0	RATHER VOID HERE	4.560	356.6
502A	32	1	20	128.50	0	PHI=295 DEGREES	715.089	307.1
502A	32	1	30	128.60	0		523.734	26.2
502A	32	1	40	128.70	0		350.792	43.1
502A	32	1	50	128.80	0		453.261	47.6
502A	32	1	60	128.90	0		461.939	42.4
502A	32	1	70	129.00	0		227.761	44.7
502A	32	1	80	129.10	0		375.632	42.4
502A	32	1	90	129.20	0		297.784	43.8
502A	32	1	100	129.30	0		359.585	38.9
502A	32	1	110	129.40	0		485.582	42.7
502A	32	1	120	129.50	0		485.346	41.0
502A	32	1	130	129.60	0		546.189	46.0
502A	32	1	140	129.70	0		645.729	46.8
502A	32	1	145	129.75	0		556.329	45.1
502A	32	2	20	130.02	0		922.371	40.4
502A	32	2	30	130.12	0		3154.325	20.3
502A	32	2	40	130.22	0		474.614	38.5
502A	32	2	50	130.32	0		416.352	34.3
502A	32	2	60	130.42	0		650.620	34.4
502A	32	2	70	130.52	0		668.140	40.3
502A	32	2	80	130.62	0		550.819	36.4
502A	32	2	90	130.72	0		318.679	52.5
502A	32	2	100	130.82	0		388.954	43.8
502A	32	2	110	130.92	0		465.542	42.2
502A	32	2	120	131.02	0		456.005	38.5
502A	32	2	130	131.12	0		393.297	37.1
502A	32	2	140	131.22	0		380.454	34.7
502A	32	2	145	131.27	0		407.164	33.5
502A	32	3	5	131.38	0		409.755	45.6
502A	32	3	10	131.43	0		536.888	39.8
502A	32	3	15	131.48	0		590.929	40.7
502A	32	3	20	131.53	0		494.666	47.2
502A	32	3	25	131.58	0		119.999	172.6
502A	33	1	20	131.50	0	PHI=145 DEGREES	470.129	283.6
502A	33	1	30	131.60	0		258.031	33.2
502A	33	1	40	131.70	0		312.846	357.8
502A	33	1	50	131.80	0		232.983	328.1
502A	33	1	60	131.90	0		280.861	352.0
502A	33	1	70	132.00	0		328.259	7.6
502A	33	1	80	132.10	0		342.775	6.8
502A	33	1	90	132.20	0		311.844	9.8
502A	33	1	100	132.30	0		440.244	0.6
502A	33	1	110	132.40	0		339.894	15.6
502A	33	1	120	132.50	0		321.524	3.0
502A	33	1	130	132.60	0		281.512	5.4
502A	33	1	140	132.70	0		282.669	10.2
502A	33	1	145	132.75	0		287.585	4.4
502A	33	2	20	132.97	0		547.688	17.4
502A	33	2	30	133.07	0		461.951	12.7

*** GRID D 08 ***

*** GRID E 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	33	2	40	133.17	0		173.247	14.5
502A	33	2	50	133.27	0		242.835	14.2
502A	33	2	60	133.37	0		229.478	17.8
502A	33	2	70	133.47	0		352.090	12.8
502A	33	2	80	133.57	0		435.303	22.4
502A	33	2	90	133.67	0		405.000	19.9
502A	33	2	100	133.77	0		360.571	22.6
502A	33	2	110	133.87	0		451.531	23.0
502A	33	2	120	133.97	0		483.750	22.5
502A	33	2	130	134.07	0		416.045	17.3
502A	33	2	140	134.17	0		357.549	22.4
502A	33	2	145	134.22	0		323.643	22.2
502A	34	1	20	134.50	0	PHI=000 DEGREES	1856.212	272.5
502A	34	1	30	134.60	0		267.791	22.3
502A	34	1	40	134.70	0		189.863	26.9
502A	34	1	50	134.80	0		186.391	59.5
502A	34	1	60	134.90	0		157.096	42.8
502A	34	1	70	135.00	0		95.100	30.6
502A	34	1	80	135.10	0		136.363	23.5
502A	34	1	90	135.20	0		64.578	13.9
502A	34	1	100	135.30	0		23.544	141.4
502A	34	1	110	135.40	0		93.365	218.3
502A	34	1	120	135.50	0		139.217	206.3
502A	34	1	130	135.60	0		99.736	202.9
502A	34	1	140	135.70	0		7.687	165.2
502A	34	1	145	135.75	0		22.715	196.2
502A	34	2	20	136.00	0		148.521	232.1
502A	34	2	30	136.10	0		93.326	220.5
502A	34	2	40	136.20	0		105.005	208.5
502A	34	2	50	136.30	0		72.550	227.1
502A	34	2	60	136.40	0		128.740	236.1
502A	34	2	70	136.50	0		54.883	253.5
502A	34	2	80	136.60	0		46.171	208.2
502A	34	2	90	136.70	0		92.333	213.3
502A	34	2	100	136.80	0		87.385	217.3
502A	34	2	110	136.90	0		46.327	230.5
502A	34	2	120	137.00	0		38.598	234.6
502A	34	2	130	137.10	0		84.463	227.2
502A	34	2	140	137.20	0		99.521	225.1
502A	34	2	145	137.25	0		123.142	227.0
502A	35	1	20	137.05	0	PHI=100 DEGREES	206.827	69.7
502A	35	1	30	137.15	0		1184.768	335.7
502A	35	1	40	137.25	0		653.463	207.8
502A	35	1	50	137.35	0		180.441	124.6
502A	35	1	60	137.45	0		214.738	132.4
502A	35	1	70	137.55	0		172.276	124.2
502A	35	1	80	137.65	0		213.341	103.1
502A	35	1	90	137.75	0		140.875	116.5
502A	35	1	100	137.85	0		132.753	121.8
502A	35	1	110	137.95	0		91.921	140.8
502A	35	1	120	138.05	0		86.428	109.6
502A	35	1	130	138.15	0		101.872	137.6
502A	35	1	140	138.25	0		49.929	117.9

*** GRID E 08 ***

*** GRID F 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	35	1	145	138.30	0		58.326	121.0
502A	35	2	20	138.55	0		123.383	125.0
502A	35	2	30	138.65	0		75.375	113.1
502A	35	2	40	138.75	0		117.022	113.5
502A	35	2	50	138.85	0		98.441	110.0
502A	35	2	60	138.95	0		58.892	112.6
502A	35	2	70	139.05	0		41.186	133.3
502A	35	2	80	139.15	0		33.736	139.2
502A	35	2	90	139.25	0		10.204	237.9
502A	35	2	100	139.35	0		37.793	134.7
502A	35	2	110	139.45	0		35.293	101.2
502A	35	2	120	139.55	0		42.885	122.6
502A	35	2	130	139.65	0		55.254	135.5
502A	35	2	140	139.75	0		56.909	115.0
502A	35	2	145	139.80	0		54.390	91.2
502A	35	3	20	140.05	0		26.262	316.3
502A	35	3	30	140.15	0		39.706	124.1
502A	35	3	40	140.25	0		4.702	94.2
502A	35	3	50	140.35	0		14.240	92.2
502A	35	3	60	140.45	0		26.210	130.8
502A	35	3	70	140.55	0		10.367	123.6
502A	35	3	80	140.65	0		3.496	256.7
502A	35	3	89	140.72	0		11.244	111.6
502A	36	1	20	140.88	0	PHI=175 DEGREES	59.345	285.0
502A	36	1	30	140.98	0	TENTATIVE ORIENTATION	32.411	262.1
502A	36	1	40	141.08	0	W.R.T.DOUBLE BLACK LINE	8.237	353.5
502A	36	1	50	141.18	0		12.942	196.3
502A	36	1	60	141.28	0		956.855	218.7
502A	36	1	70	141.38	0		352.368	227.4
502A	36	1	80	141.48	0		20.136	326.3
502A	36	1	90	141.58	0		7.472	279.2
502A	36	1	100	141.68	0		0.633	299.2
502A	36	1	110	141.78	0		26.969	232.7
502A	36	1	120	141.88	0		11.899	18.1
502A	36	1	130	141.98	0		13.104	246.1
502A	36	1	140	142.08	0		5.115	158.8
502A	36	1	145	142.13	0		16.756	256.0
502A	36	2	20	142.38	0	TENTATIVE ORIENTATION	9.583	282.1
502A	36	2	20	142.38	1	REPEAT AGAIN	7.129	284.4
502A	36	2	25	142.43	1	REPEAT	13.130	250.6
502A	36	2	30	142.48	0	W.R.T.DOUBLE BLACK LINE	7.533	311.1
502A	36	2	30	142.48	1		8.001	300.6
502A	36	2	35	142.53	1		6.794	233.2
502A	36	2	40	142.58	0		137.637	188.2
502A	36	2	40	142.58	1		186.188	191.6
502A	36	2	45	142.63	1		163.723	16.5
502A	36	2	50	142.68	0		22.613	41.1
502A	36	2	50	142.68	1		20.730	38.1
502A	36	2	55	142.73	1		25.872	290.4
502A	36	2	60	142.78	0		55.457	98.7
502A	36	2	60	142.78	1		49.927	97.3
502A	36	2	65	142.83	1		11.275	5.2
502A	36	2	70	142.88	0		3.742	253.7

*** GRID F 08 ***

*** GRID G 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	36	2	70	142.88	1		5.792	206.7
502A	36	2	75	142.93	1		23.817	33.5
502A	36	2	80	142.98	0		18.114	18.8
502A	36	2	80	142.98	1		17.449	20.4
502A	36	2	84	143.02	0		14.693	6.6
502A	36	2	84	143.02	1		14.353	10.3
502A	36	2	84	143.02	2		13.663	19.5
502A	37	1	20	142.70	0	PHI=315 DEGREES	1350.137	339.1
502A	37	1	30	142.80	0		1020.254	184.4
502A	37	1	40	142.90	0		324.547	98.6
502A	37	1	50	143.00	0		895.979	8.3
502A	37	1	60	143.10	0		842.713	171.0
502A	37	1	70	143.20	0		171.007	84.1
502A	37	1	80	143.30	0		575.935	246.0
502A	37	1	90	143.40	0		70.664	53.3
502A	37	1	100	143.50	0		132.385	220.2
502A	37	1	110	143.60	0		112.717	220.8
502A	37	1	120	143.70	0		303.959	336.1
502A	37	1	130	143.80	0		57.236	334.7
502A	37	1	140	143.90	0		60.182	344.4
502A	37	1	145	143.95	0		665.700	325.6
502A	37	2	20	144.14	0		106.319	284.6
502A	37	2	30	144.24	0		223.636	240.1
502A	37	2	40	144.34	0		14.730	99.8
502A	37	2	50	144.44	0		7.551	261.3
502A	37	2	60	144.54	0		2.172	183.7
502A	37	2	70	144.64	0		10.882	315.2
502A	37	2	80	144.74	0		7.636	328.3
502A	37	2	90	144.84	0		5.807	325.7
502A	37	2	100	144.94	0		1.364	254.0
502A	37	2	110	145.04	0		48.808	117.4
502A	37	2	114	145.08	0		78.197	122.9
502A	38	1	20	145.68	0	PHI=285 DEGREES	708.730	357.5
502A	38	1	30	145.78	0		60.878	180.8
502A	38	1	40	145.88	0		73.762	292.9
502A	38	1	50	145.98	0		39.631	350.1
502A	38	1	60	146.08	0		10.626	234.2
502A	38	1	70	146.18	0		10.870	318.3
502A	38	1	80	146.28	0		7.408	280.2
502A	38	1	90	146.38	0		12.808	13.1
502A	38	1	100	146.48	0		27.314	332.1
502A	38	1	110	146.58	0		3.374	144.2
502A	38	1	120	146.68	0		7.064	299.4
502A	38	1	130	146.78	0		3.904	178.3
502A	38	1	140	146.88	0		6.122	194.1
502A	38	1	144	146.92	0		7.789	255.6
502A	38	2	0	146.98	0		10.074	289.8
502A	38	2	10	147.08	0		31.905	247.1
502A	38	2	20	147.18	0		3.163	4.9
502A	38	2	30	147.28	0		9.659	250.9
502A	38	2	34	147.32	0	LAST 10 CM VOID	32.226	223.1
502A	39	1	20	147.30	0	PHI=110 DEGREES	1221.034	350.5
502A	39	1	30	147.40	0		93.786	271.4

*** GRID G 08 ***

*** GRID H 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	39	1	40	147.50	0		148.415	246.3
502A	39	1	50	147.60	0		37.912	269.5
502A	39	1	60	147.70	0		135.567	91.7
502A	39	1	70	147.80	0		83.097	70.6
502A	39	1	80	147.90	0		25.349	170.5
502A	39	1	90	148.00	0		53.054	103.9
502A	39	1	100	148.10	0		38.633	19.1
502A	39	1	110	148.20	0		31.470	353.8
502A	39	1	120	148.30	0		18.203	53.4
502A	39	1	130	148.40	0		26.619	353.8
502A	39	1	140	148.50	0		18.081	336.2
502A	39	1	144	148.54	0		5.846	151.0
502A	39	2	20	148.80	0		17.189	213.3
502A	39	2	30	148.90	0		0.978	208.0
502A	39	2	40	149.00	0		4.979	153.8
502A	39	2	50	149.10	0		76.284	294.1
502A	39	2	60	149.20	0		12.620	340.3
502A	39	2	70	149.30	0		15.311	214.3
502A	39	2	80	149.40	0		36.040	275.2
502A	39	2	90	149.50	0		18.275	180.9
502A	39	2	100	149.60	0		44.330	189.5
502A	39	2	110	149.70	0		89.403	60.7
502A	39	2	120	149.80	0		10.992	178.9
502A	39	2	130	149.90	0		18.668	341.3
502A	40	1	20	150.38	0	PHI=300 DEGREES	444.739	176.5
502A	40	1	30	150.48	0		1114.269	287.7
502A	40	1	40	150.58	0		70.615	192.5
502A	40	1	50	150.68	0		17.444	107.0
502A	40	1	60	150.78	0		8.988	297.3
502A	40	1	70	150.88	0		67.342	69.5
502A	40	1	80	150.98	0		40.622	174.1
502A	40	1	90	151.08	0		32.870	138.8
502A	40	1	100	151.18	0		37.464	142.7
502A	40	1	110	151.28	0		8.620	238.4
502A	40	1	120	151.38	0		45.080	31.6
502A	40	1	130	151.48	0		18.428	51.6
502A	40	1	140	151.58	0		18.140	219.2
502A	40	1	144	151.62	0		17.163	218.8
502A	40	2	20	151.88	0		12.295	294.2
502A	40	2	30	151.98	0		6.468	260.6
502A	40	2	40	152.08	0		1.798	295.7
502A	40	2	50	152.18	0		4.844	198.4
502A	40	2	60	152.28	0		21.378	170.2
502A	40	2	70	152.38	0		12.387	70.3
502A	40	2	80	152.48	0		20.504	139.3
502A	40	2	90	152.58	0		3.933	33.9
502A	40	2	100	152.68	0		3.280	102.8
502A	40	2	110	152.78	0		17.335	268.2
502A	41	1	20	152.40	0	PHI=245 DEGREES	185.218	129.3
502A	41	1	30	152.50	0		145.930	16.0
502A	41	1	40	152.60	0		1168.840	91.7
502A	41	1	50	152.70	0		367.596	174.2
502A	41	1	60	152.80	0		2525.806	134.2

*** GRID H 08 ***

*** GRID I 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	41	1	70	152.90	0		255.078	204.8
502A	41	1	80	153.00	0		29.990	319.3
502A	41	1	90	153.10	0		45.759	342.4
502A	41	1	100	153.20	0		44.443	250.6
502A	41	1	110	153.30	0		110.506	70.8
502A	41	1	120	153.40	0		38.544	178.5
502A	41	1	130	153.50	0		86.013	151.8
502A	41	1	140	153.60	0		70.775	229.0
502A	41	1	144	153.64	0		26.377	130.3
502A	41	2	20	153.90	0		472.204	47.0
502A	41	2	30	154.00	0		40.056	253.7
502A	41	2	40	154.10	0		27.326	291.7
502A	41	2	50	154.20	0		15.738	140.3
502A	41	2	60	154.30	0		14.792	348.5
502A	41	2	70	154.40	0		1.933	159.7
502A	41	2	80	154.50	0		19.716	64.9
502A	41	2	90	154.60	0		8.697	296.5
502A	41	2	100	154.70	0		7.274	153.1
502A	41	2	110	154.80	0		3.953	74.0
502A	41	2	120	154.90	0		6.604	246.5
502A	41	2	130	155.00	0		16.713	332.0
502A	41	2	140	155.10	0		38.104	326.4
502A	41	2	145	155.15	0		13.479	309.5
502A	41	3	5	155.25	0		28.525	357.3
502A	41	3	10	155.30	0		41.316	10.9
502A	41	3	15	155.35	0		49.987	27.0
502A	41	3	20	155.40	0		15.435	290.2
502A	42	1	20	156.00	0	PHI=103 DEGREES	64.459	359.5
502A	42	1	30	156.10	0		133.155	22.4
502A	42	1	40	156.20	0		170.204	213.2
502A	42	1	50	156.30	0		2.846	72.9
502A	42	1	60	156.40	0		26.014	36.1
502A	42	1	70	156.50	0		123.250	267.6
502A	42	1	80	156.60	0		23.151	261.0
502A	42	1	90	156.70	0		58.860	50.5
502A	42	1	100	156.80	0		21.135	316.5
502A	42	1	110	156.90	0		39.936	7.2
502A	42	1	120	157.00	0		12.791	252.5
502A	42	1	130	157.10	0		32.937	334.8
502A	42	1	140	157.20	0		3.694	126.0
502A	42	1	145	157.25	0		2.726	42.5
502A	42	2	20	157.50	0		47.767	318.7
502A	42	2	30	157.60	0		29.576	341.6
502A	42	2	40	157.70	0		17.484	0.7
502A	42	2	50	157.80	0		16.572	319.8
502A	42	2	60	157.90	0		12.786	17.8
502A	42	2	70	158.00	0		22.788	358.0
502A	42	2	80	158.10	0		67.787	323.6
502A	42	2	90	158.20	0		26.509	355.3
502A	42	2	100	158.30	0		23.149	7.4
502A	42	2	110	158.40	0	BASE DAMAGED AND VOID	22.843	265.3
502A	43	1	20	158.50	0	PHI=203 DEGREES	23.288	341.4
502A	43	1	30	158.60	0		7.405	140.2

*** GRID I 08 ***

*** GRID J 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	43	1	40	158.70	0		5.632	60.3
502A	43	1	50	158.80	0		73.417	95.1
502A	43	1	60	158.90	0		43.869	60.3
502A	43	1	70	159.00	0		92.685	10.6
502A	43	1	80	159.10	0		85.822	117.0
502A	43	1	90	159.20	0		71.737	87.4
502A	43	1	100	159.30	0		33.627	108.0
502A	43	1	110	159.40	0		16.007	99.0
502A	43	1	120	159.50	0		3.342	107.9
502A	43	1	130	159.60	0		33.943	138.9
502A	43	1	140	159.65	0		25.063	29.1
502A	43	1	145	159.70	0		24.767	131.6
502A	43	2	20	159.95	0		48.331	123.3
502A	43	2	30	160.05	0		72.111	99.2
502A	43	2	40	160.15	0		65.462	136.2
502A	43	2	50	160.25	0		25.570	132.4
502A	43	2	60	160.35	0		59.408	124.0
502A	43	2	70	160.45	0		64.882	158.9
502A	43	2	80	160.55	0		113.747	113.2
502A	43	2	90	160.65	0		318.639	119.8
502A	43	2	100	160.75	0		406.837	104.6
502A	43	2	110	160.85	0		166.902	103.6
502A	43	2	120	160.93	0		48.881	272.6
502A	44	1	20	161.21	0	PHI=305 DEGREES	1790.991	226.5
502A	44	1	30	161.31	0		224.098	347.4
502A	44	1	40	161.41	0		144.724	173.3
502A	44	1	50	161.51	0		39.305	255.0
502A	44	1	60	161.61	0		24.918	113.1
502A	44	1	70	161.71	0		9.255	73.6
502A	44	1	80	161.81	0		41.046	172.0
502A	44	1	90	161.91	0		14.814	125.5
502A	44	1	100	162.01	0		54.952	265.3
502A	44	1	110	162.11	0		11.460	268.0
502A	44	1	120	162.21	0		185.342	11.7
502A	44	1	130	162.31	0		746.442	15.7
502A	44	1	140	162.41	0		311.576	20.2
502A	44	1	144	162.45	0		360.845	14.6
502A	44	2	20	162.60	0		193.977	13.5
502A	44	2	30	162.70	0		132.396	18.6
502A	44	2	40	162.80	0		141.326	16.4
502A	44	2	50	162.90	0		141.910	15.3
502A	44	2	60	163.00	0		188.772	13.2
502A	44	2	70	163.10	0		98.979	21.8
502A	44	2	80	163.20	0		88.577	26.6
502A	44	2	90	163.30	0		203.470	22.5
502A	44	2	100	163.40	0		323.736	17.9
502A	44	2	104	163.43	0		61.229	335.6
502A	45	1	20	163.88	0	PHI=326 DEGREES	108.529	299.4
502A	45	1	30	163.98	0		37.226	9.7
502A	45	1	40	164.08	0		26.215	351.1
502A	45	1	50	164.18	0		40.678	351.6
502A	45	1	60	164.28	0		48.784	316.5
502A	45	1	70	164.38	0		48.070	314.7

*** GRID J 08 ***

*** GRID K 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	45	1	80	164.48	0		73.746	323.6
502A	45	1	90	164.58	0		63.684	302.0
502A	45	1	100	164.68	0		95.105	308.3
502A	45	1	110	164.78	0		173.465	303.7
502A	45	1	120	164.88	0		263.792	309.1
502A	45	1	130	164.98	0		397.001	314.0
502A	45	1	140	165.08	0		361.224	310.0
502A	45	1	144	165.12	0		353.928	312.3
502A	45	2	20	165.39	0		83.399	324.9
502A	45	2	30	165.49	0		60.582	305.7
502A	45	2	40	165.59	0		58.351	324.5
502A	45	2	50	165.69	0		36.064	318.8
502A	45	2	60	165.79	0		30.703	329.3
502A	45	2	70	165.89	0		37.430	321.6
502A	45	2	80	165.96	0		14.373	356.8
502A	45	2	86	166.00	0		34.127	243.7
502A	46	1	20	166.26	0	PHI=128 DEGREES	285.634	29.5
502A	46	1	30	166.36	0		66.832	244.8
502A	46	1	40	166.46	0		47.713	104.7
502A	46	1	50	166.56	0		170.542	8.2
502A	46	1	60	166.66	0		135.403	37.0
502A	46	1	70	166.76	0		71.014	40.0
502A	46	1	80	166.86	0		17.438	342.9
502A	46	1	90	166.96	0		69.106	5.7
502A	46	1	100	167.06	0		139.997	11.4
502A	46	1	110	167.16	0		176.477	26.4
502A	46	1	120	167.26	0		163.749	31.5
502A	46	1	130	167.36	0		112.947	28.2
502A	46	1	140	167.46	0		128.723	32.8
502A	46	1	144	167.50	0		105.307	50.0
502A	46	2	20	167.61	0		144.450	36.3
502A	46	2	30	167.71	0		309.833	35.2
502A	46	2	40	167.81	0		277.126	43.2
502A	46	2	50	167.91	0		393.063	37.8
502A	46	2	60	168.01	0		220.360	27.4
502A	46	2	72	168.13	0		65.696	31.0
502A	46	2	80	168.21	0		17.438	342.9
502A	46	2	90	168.31	0		69.106	5.7
502A	46	2	100	168.41	0		139.997	11.4
502A	46	2	110	168.51	0		176.477	26.4
502A	46	2	120	168.61	0		163.749	31.5
502A	46	2	130	168.71	0		112.947	28.2
502A	46	2	140	168.81	0		128.723	32.8
502A	46	2	144	168.85	0		105.307	50.0
502A	47	1	20	168.18	0	PHI=007 DEGREES	125.995	105.1
502A	47	1	30	168.28	0		115.787	298.1
502A	47	1	40	168.38	0		388.497	69.5
502A	47	1	50	168.48	0		68.655	46.5
502A	47	1	60	168.58	0		376.876	28.5
502A	47	1	70	168.68	0		27.119	115.7
502A	47	1	80	168.78	0		36.601	106.3
502A	47	1	90	168.88	0		44.891	111.5
502A	47	1	100	168.98	0		17.391	242.1

*** GRID K 08 ***

*** GRID L 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	47	1	110	169.08	0		11.138	89.7
502A	47	1	120	169.18	0		31.630	111.9
502A	47	1	130	169.28	0		21.738	156.2
502A	47	1	140	169.38	0		61.225	206.2
502A	47	1	144	169.42	0		65.201	166.1
502A	47	2	20	169.68	0		30.466	54.4
502A	47	2	30	169.78	0		13.949	166.6
502A	47	2	40	169.88	0		13.977	77.4
502A	47	2	50	169.98	0		93.861	186.0
502A	47	2	60	170.08	0		20.945	144.6
502A	47	2	70	170.18	0		29.492	138.6
502A	47	2	80	170.28	0		35.867	99.3
502A	47	2	90	170.38	0		88.432	235.9
502A	47	2	100	170.48	0		19.803	181.5
502A	47	2	110	170.58	0		72.863	99.3
502A	47	2	120	170.68	0		61.637	37.6
502A	47	2	130	170.78	0		169.794	126.2
502A	47	2	140	170.88	0		174.977	130.5
502A	47	2	144	170.92	0		86.619	137.6
502A	48	1	20	171.33	0	PHI=049 DEGREES	1380.636	238.8
502A	48	1	30	171.43	0		533.881	335.0
502A	48	1	40	171.53	0		236.611	83.6
502A	48	1	50	171.63	0		191.308	147.0
502A	48	1	60	171.73	0		53.730	269.5
502A	48	1	70	171.83	0		49.803	211.4
502A	48	1	80	171.93	0		94.416	289.8
502A	48	1	90	172.03	0		74.007	140.9
502A	48	1	100	172.13	0		27.842	250.1
502A	48	1	110	172.23	0		59.806	270.1
502A	48	1	120	172.33	0		93.721	247.2
502A	48	1	130	172.43	0		31.609	261.7
502A	48	1	140	172.53	0		44.430	275.0
502A	48	1	144	172.57	0		38.776	217.7
502A	50	1	20	175.40	0	PHI=345 DEGREES	127.588	220.8
502A	50	1	30	175.50	0	SLIPPED IN HOLDER	149.735	325.9
502A	50	1	40	175.60	0		120.947	357.9
502A	50	1	50	175.70	0		158.638	90.2
502A	50	1	60	175.80	0		247.180	62.6
502A	50	1	70	175.90	0		76.809	34.1
502A	50	1	80	176.00	0		2.179	230.4
502A	50	1	90	176.10	0		59.288	104.1
502A	50	1	100	176.20	0		51.145	282.5
502A	50	1	110	176.30	0		30.689	261.4
502A	50	1	120	176.40	0		128.317	211.0
502A	50	1	130	176.50	0		103.647	35.9
502A	50	1	140	176.60	0		36.603	74.2
502A	50	1	145	176.65	0		17.041	115.6
502A	50	2	20	176.86	0		32.749	331.4
502A	50	2	30	176.96	0		107.544	7.3
502A	50	2	40	177.06	0		87.021	189.7
502A	50	2	50	177.16	0		253.235	27.4
502A	50	2	60	177.26	0		70.719	0.3
502A	50	2	70	177.36	0		266.603	182.5

*** GRID L 08 ***

*** GRID M 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	50	2	80	177.46	0		630.674	103.1
502A	50	2	90	177.56	0		137.999	44.1
502A	50	2	100	177.66	0		71.295	282.0
502A	50	2	108	177.74	0		130.057	135.6
502A	51	1	20	178.50	0	PHI=175 DEGREES	321.331	217.8
502A	51	1	30	178.60	0		161.390	52.6
502A	51	1	40	178.70	0		143.197	81.4
502A	51	1	50	178.80	0		37.422	324.0
502A	51	1	60	178.90	0		34.286	273.2
502A	51	1	70	179.00	0		26.583	346.4
502A	51	1	80	179.10	0		73.239	15.5
502A	51	1	90	179.20	0		168.969	3.0
502A	51	1	100	179.30	0		250.380	337.0
502A	51	1	110	179.40	0		137.205	3.8
502A	51	1	120	179.50	0		119.487	351.9
502A	51	1	130	179.60	0		155.085	350.1
502A	51	1	140	179.70	0		78.385	348.0
502A	51	1	145	179.75	0		59.387	355.8
502A	51	2	10	179.90	0		73.546	333.2
502A	51	2	20	180.00	0		31.890	358.0
502A	51	2	30	180.10	0		56.343	329.2
502A	51	2	40	180.20	0		29.222	312.6
502A	51	2	50	180.30	0		7.650	318.4
502A	51	2	58	180.38	0		9.239	358.0
502A	52	1	20	180.82	0	PHI=275 DEGREES	1212.513	278.3
502A	52	1	30	180.92	0		395.496	345.1
502A	52	1	40	181.02	0		230.960	216.7
502A	52	1	50	181.12	0		274.948	225.6
502A	52	1	60	181.22	0		217.634	223.1
502A	52	1	70	181.32	0		228.343	213.7
502A	52	1	80	181.42	0		187.989	227.0
502A	52	1	100	181.62	0		106.261	226.1
502A	52	1	110	181.72	0		105.966	200.7
502A	52	1	120	181.82	0		145.707	227.7
502A	52	1	130	181.92	0		172.244	237.2
502A	52	1	140	182.02	0		355.731	232.0
502A	52	1	145	182.07	0		334.651	229.8
502A	52	2	5	182.19	0		177.288	239.2
502A	52	2	15	182.29	0		75.977	224.2
502A	53	1	20	182.70	0	PHI=325 DEGREES	2987.745	145.2
502A	53	1	30	182.80	0		521.255	163.3
502A	53	1	40	182.90	0		64.317	245.5
502A	53	1	50	183.00	0		46.536	252.5
502A	53	1	60	183.10	0		73.184	248.2
502A	53	1	70	183.20	0		85.715	246.4
502A	53	1	80	183.30	0		111.419	245.9
502A	53	1	90	183.40	0		132.216	253.7
502A	53	1	100	183.50	0		99.484	249.8
502A	53	1	110	183.60	0		34.143	132.5
502A	53	1	120	183.70	0		143.152	252.5
502A	53	1	130	183.80	0		130.003	248.0
502A	53	1	140	183.90	0		36.467	16.2
502A	54	1	20	184.80	0	PHI=275 DEGREES	491.854	326.6

*** GRID M 08 ***

*** GRID N 08 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	54	1	30	184.90	0		160.569	342.3
502A	54	1	40	185.00	0		159.628	33.7
502A	54	1	50	185.10	0		175.117	21.6
502A	54	1	60	185.20	0		104.857	30.2
502A	54	1	70	185.30	0		86.747	26.9
502A	54	1	80	185.40	0		169.327	24.4
502A	54	1	90	185.50	0		161.915	31.4
502A	54	1	100	185.60	0		125.270	19.0
502A	54	1	110	185.70	0		186.157	22.5
502A	54	1	120	185.80	0		197.967	28.6
502A	54	1	130	185.90	0		273.003	23.3
502A	54	1	140	186.00	0		241.894	26.9
502A	54	1	145	186.05	0		233.537	25.8
502A	54	2	20	186.30	0		189.415	22.5
502A	54	2	30	186.40	0		158.375	22.6
502A	54	2	40	186.50	0		88.872	16.7
502A	54	2	50	186.60	0		73.893	33.8
502A	54	2	60	186.70	0		49.120	21.3
502A	54	2	70	186.80	0		28.469	36.3
502A	54	2	80	186.90	0		42.201	20.2
502A	54	2	87	186.97	0		91.984	209.8
502A	55	1	20	187.36	0	PHI=260 DEGREES	110.166	103.5
502A	55	1	30	187.46	0		145.042	62.6
502A	55	1	40	187.56	0		115.454	84.0
502A	55	1	50	187.66	0		138.954	52.3
502A	55	1	60	187.76	0		173.449	57.7
502A	55	1	70	187.86	0		89.753	53.5
502A	55	1	80	187.96	0		151.577	41.8
502A	55	1	90	188.06	0		113.996	40.6
502A	55	1	100	188.16	0		99.691	64.9
502A	55	1	110	188.26	0		145.843	63.4
502A	55	1	120	188.36	0		132.709	44.8
502A	55	1	130	188.46	0		182.513	50.4
502A	55	1	140	188.56	0		179.995	39.8
502A	55	1	145	188.61	0		105.008	34.9
502A	55	2	10	188.75	0		329.029	92.2
502A	55	2	20	188.85	0		307.459	87.5
502A	55	2	30	188.95	0		355.125	76.4
502A	55	2	40	189.05	0		54.636	142.0
502A	55	2	45	189.10	0		297.072	78.3
502A	56	1	20	189.17	0	PHI=005 DEGREES	245.219	53.8
502A	56	1	30	189.27	0		588.072	87.7
502A	56	1	40	189.37	0		89.876	285.4
502A	56	1	50	189.47	0		155.263	280.5
502A	56	1	60	189.57	0		210.215	291.3
502A	56	1	70	189.67	0		137.221	275.4
502A	56	1	80	189.77	0		54.052	268.5
502A	56	1	90	189.87	0		68.103	284.3
502A	56	1	100	189.97	0		163.891	279.0
502A	56	1	110	190.07	0		170.040	283.9
502A	56	1	120	190.17	0		205.099	288.7
502A	56	1	130	190.27	0		135.612	309.8
502A	56	1	140	190.37	0		55.168	279.3

*** GRID N 08 ***

*** GRID B 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	56	1	145	190.42	0		2.591	325.4
502A	56	2	10	190.58	0		97.566	281.0
502A	56	2	20	190.68	0		127.186	279.3
502A	56	2	30	190.78	0		153.101	287.0
502A	56	2	40	190.88	0		241.876	276.8
502A	56	2	50	190.98	0		273.704	286.1
502A	57	1	20	191.30	0	PHI=265 DEGREES	818.676	320.6
502A	57	1	30	191.40	0		112.654	238.6
502A	57	1	40	191.50	0		387.731	153.9
502A	57	1	50	191.60	0		507.465	225.5
502A	57	1	60	191.70	0		163.338	121.8
502A	57	1	70	191.80	0		203.215	191.6
502A	57	1	80	191.90	0		158.501	169.5
502A	57	1	90	192.00	0		428.217	132.9
502A	57	1	100	192.10	0		226.286	174.1
502A	57	1	110	192.20	0		259.438	165.1
502A	57	1	120	192.30	0		303.117	172.1
502A	57	1	130	192.40	0		262.177	182.1
502A	57	1	140	192.50	0		183.775	207.4
502A	57	1	145	192.55	0		101.805	170.6
502A	57	2	10	192.70	0		246.754	159.5
502A	57	2	20	192.80	0		461.880	176.7
502A	57	2	30	192.90	0		266.147	173.4
502A	57	2	40	193.00	0		251.550	169.2
502A	57	2	48	193.08	0		94.719	175.4
502A	58	1	20	193.26	0	PHI=165 DEGREES	942.010	314.3
502A	58	1	30	193.36	0		859.594	128.6
502A	58	1	40	193.46	0		456.020	318.6
502A	58	1	50	193.56	0		381.520	293.4
502A	58	1	60	193.66	0		295.049	293.2
502A	58	1	70	193.76	0		166.996	292.6
502A	58	1	80	193.86	0		200.682	296.5
502A	58	1	90	193.96	0		237.674	308.9
502A	58	1	100	194.06	0		225.702	297.6
502A	58	1	110	194.16	0		288.660	293.6
502A	58	1	120	194.26	0		351.451	298.7
502A	58	1	130	194.36	0		382.018	298.8
502A	58	1	140	194.46	0		590.253	298.4
502A	58	1	145	194.51	0		488.633	300.2
502A	58	2	10	194.70	0		111.723	280.3
502A	58	2	20	194.80	0		195.551	251.3
502A	58	2	30	194.90	0		96.187	288.4
502A	58	2	40	195.00	0		98.096	292.6
502A	58	2	46	195.06	0		67.924	291.7
502A	60	1	20	197.45	0	PHI=075 DEGREES	311.419	61.5
502A	60	1	30	197.55	0		242.533	212.4
502A	60	1	40	197.65	0		562.108	245.2
502A	60	1	50	197.75	0		810.761	222.3
502A	60	1	60	197.85	0		895.944	221.8
502A	60	1	70	197.95	0		541.145	223.8
502A	60	1	80	198.05	0		313.256	212.2
502A	60	1	90	198.15	0		19.932	256.6
502A	60	1	100	198.25	0		62.346	249.7

*** GRID B 09 ***

*** GRID C 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	60	1	110	198.35	0		100.358	187.9
502A	60	1	120	198.45	0		89.266	235.4
502A	60	1	130	198.55	0		61.151	211.8
502A	60	1	140	198.65	0		80.779	200.2
502A	60	1	144	198.69	0		177.130	238.4
502A	60	2	5	198.77	0		71.303	245.5
502A	60	2	10	198.82	0		189.523	222.1
502A	60	2	20	198.92	0		897.012	96.7
502A	60	2	25	198.97	0		280.502	327.0
502A	61	1	20	199.08	0	PHI=055 DEGREES	3544.190	350.9
502A	61	1	30	199.18	0	TOP DISTURBED	2301.838	87.8
502A	61	1	40	199.28	0		558.477	194.5
502A	61	1	50	199.38	0		93.176	233.6
502A	61	1	60	199.48	0		135.926	209.4
502A	61	1	70	199.58	0		293.499	224.7
502A	61	1	80	199.68	0		201.195	230.1
502A	61	1	90	199.78	0		187.058	222.5
502A	61	1	100	199.88	0		138.837	198.3
502A	61	1	110	199.98	0		107.231	225.8
502A	61	1	120	200.08	0		98.350	225.2
502A	61	1	130	200.18	0		20.6[illegible]	310.7
502A	61	1	136	200.24	0		128.0[illegible]	330.8
502A	63	1	40	203.49	0	PHI=213 DEGREES	343.[illegible]13	246.0
502A	63	1	50	203.59	0		151.464	260.8
502A	63	1	60	203.69	0		126.260	272.3
502A	63	1	70	203.79	0		202.053	289.6
502A	63	1	80	203.89	0		596.009	75.8
502A	63	1	90	203.99	0		286.525	266.1
502A	63	1	100	204.09	0		234.666	269.3
502A	63	1	110	204.19	0		219.441	292.2
502A	63	1	120	204.29	0		173.407	282.5
502A	63	1	125	204.34	1	REPEAT	173.600	285.3
502A	63	1	130	204.39	0		116.985	285.1
502A	63	1	130	204.39	1		128.677	286.4
502A	63	1	135	204.44	1		61.855	108.9
502A	63	1	140	204.49	0		93.002	112.6
502A	63	1	140	204.49	1		142.973	113.6
502A	63	1	145	204.54	0		164.848	114.8
502A	63	1	145	204.54	1		160.213	115.3
502A	63	CC	5	204.62	0	LABELED CORE CATCHER	181.020	129.7
502A	65	1	30	207.40	0	PHI=246 DEGREES	20.555	314.5
502A	65	1	40	207.50	0	TOP DAMAGED	132.000	243.0
502A	65	1	50	207.60	0		224.701	309.3
502A	65	1	60	207.70	0		177.400	304.2
502A	65	1	70	207.80	0		64.663	315.4
502A	65	1	80	207.90	0		40.696	359.1
502A	65	1	90	208.00	0		125.907	271.7
502A	65	1	100	208.10	0		64.600	304.5
502A	65	1	110	208.20	0		95.613	291.0
502A	65	1	120	208.30	0		62.945	12.5
502A	65	1	130	208.40	0		1212.516	169.9
502A	65	1	140	208.50	0		64.848	254.7
502A	65	1	145	208.55	0		112.280	275.7

*** GRID C 09 ***

*** GRID D 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502A	65	2	20	208.82	0		250.471	338.4
502A	65	2	30	208.92	0		96.410	299.7
502A	65	2	40	209.02	0		80.046	316.5
502A	65	2	50	209.12	0		105.876	301.5
502A	65	2	60	209.22	0		215.852	313.6
502A	65	2	70	209.32	0		57.545	310.5
502A	66	1	20	209.35	0	PHI=250 DEGREES	83.823	80.8
502A	66	1	30	209.45	0	TOP LOOKS BAD	105.332	319.2
502A	66	1	40	209.55	0		640.135	322.7
502A	66	1	50	209.65	0		221.213	143.4
502A	66	1	60	209.75	0		30.915	184.9
502A	66	1	70	209.85	0		58.132	191.7
502A	66	1	80	209.95	0		64.029	153.0
502A	66	1	90	210.05	0		346.018	96.6
502A	66	1	100	210.15	0		8.129	213.1
502A	66	1	110	210.25	0		13.324	218.3
502A	66	1	120	210.35	0		27.104	215.6
502A	66	1	130	210.45	0		38.579	214.1
502A	66	1	140	210.55	0		22.463	183.6
502A	66	1	145	210.60	0		45.203	207.4
502A	66	2	5	210.60	0		44.823	224.0
502A	66	2	10	210.65	0		34.076	199.0
502A	66	2	20	210.75	0		24.018	205.0
502A	66	2	25	210.80	0		45.977	314.6
502A	67	1	20	211.21	0	PHI=248 DEGREES	643.722	68.0
502A	67	1	30	211.31	0		335.425	187.3
502A	67	1	40	211.41	0		53.152	297.4
502A	67	1	50	211.51	0		70.291	353.9
502A	67	1	60	211.61	0		18.267	288.0
502A	67	1	70	211.71	0		17.104	288.6
502A	67	1	80	211.81	0		16.701	35.6
502A	67	1	86	211.87	0		7.774	85.9
502A	68	1	30	213.10	0	PHI=030 DEGREES	236.924	47.0
502A	68	1	40	213.20	0	TOP DAMAGED	113.338	159.7
502A	68	1	50	213.30	0		198.414	141.2
502A	68	1	60	213.40	0		95.319	166.3
502A	68	1	70	213.50	0		53.817	313.2
502A	68	1	80	213.60	0		39.958	159.7
502A	68	1	90	213.70	0		35.296	250.8
502A	68	1	100	213.80	0		55.509	190.5
502A	68	1	110	213.90	0		58.679	310.7
502A	68	1	120	214.00	0		32.064	177.9
502A	68	1	144	214.24	0		12.471	61.3
502A	68	2	20	214.48	0		44.204	110.1
502A	68	2	30	214.58	0		53.147	208.8
502A	68	2	40	214.68	0		15.141	146.6
502A	68	2	50	214.78	0		6.781	150.3
502A	68	2	60	214.88	0		7.817	215.0
502A	68	2	139	215.67	0		15.350	19.7
502B	1	1	20	0.20	0	PHI=008 DEGREES	944.457	53.0
502B	1	1	30	0.30	0		478.481	92.6
502B	1	1	40	0.40	0		396.775	85.7
502B	1	1	50	0.50	0		315.022	90.6

*** GRID D 09 ***

*** GRID E 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	1	1	60	0.58	0		528.442	105.3
502B	1	1	70	0.66	0		380.208	101.9
502B	1	1	80	0.76	0		332.657	99.1
502B	1	1	90	0.86	0		112.734	101.6
502B	1	1	100	0.96	0		80.556	121.2
502B	1	1	110	1.06	0		99.125	109.4
502B	1	1	120	1.16	0		105.257	111.1
502B	1	1	130	1.26	0		254.038	287.3
502B	1	1	140	1.36	0		183.212	101.5
502B	1	1	145	1.41	0		231.700	108.3
502B	1	2	5	1.53	0		271.756	121.9
502B	1	2	15	1.63	0		254.293	128.5
502B	2	1	20	1.90	0	PHI=338 DEGREES	83.263	47.1
502B	2	1	30	2.00	0		170.881	52.7
502B	2	1	40	2.10	0		353.281	55.7
502B	2	1	50	2.20	0		232.285	112.5
502B	2	1	60	2.30	0		437.520	61.7
502B	2	1	70	2.40	0		483.727	63.4
502B	2	1	80	2.50	0		430.903	77.0
502B	2	1	90	2.60	0		208.443	61.0
502B	2	1	100	2.70	0		342.016	92.5
502B	2	1	110	2.80	0		226.936	73.5
502B	2	1	120	2.90	0		258.133	75.6
502B	2	1	130	3.00	0		372.472	63.4
502B	2	1	140	3.10	0		379.879	68.3
502B	2	1	145	3.15	0		202.837	54.6
502B	2	2	20	3.34	0		200.013	78.3
502B	2	2	30	3.44	0		229.786	77.5
502B	2	2	40	3.54	0		202.590	83.5
502B	2	2	50	3.64	0		328.537	78.3
502B	2	2	60	3.74	0		311.102	75.5
502B	2	2	70	3.84	0		286.025	74.0
502B	2	2	80	3.94	0		373.036	72.1
502B	2	2	90	4.04	0		295.440	63.6
502B	2	2	100	4.14	0		481.021	72.1
502B	2	2	110	4.24	0		276.794	71.9
502B	2	2	120	4.34	0		176.300	71.9
502B	2	2	130	4.44	0		226.720	67.8
502B	2	2	140	4.54	0		426.337	69.4
502B	2	2	145	4.59	0		447.771	71.6
502B	2	3	15	4.79	0		252.422	72.8
502B	2	3	20	4.84	0		331.381	69.1
502B	2	3	30	4.94	0		409.387	74.7
502B	2	3	40	5.04	0		344.059	85.2
502B	2	3	50	5.14	0		336.318	81.5
502B	2	3	60	5.24	0		159.305	78.5
502B	2	3	70	5.34	0		217.842	54.8
502B	2	3	72	5.36	0		231.019	86.1
502B	3	1	20	6.35	0	PHI=220 DEGREES	268.515	25.5
502B	3	1	30	6.45	0		272.955	61.4
502B	3	1	40	6.55	0		729.689	53.5
502B	3	1	50	6.65	0		308.041	74.9
502B	3	1	60	6.75	0		367.464	49.8

*** GRID E 09 ***

*** GRID F 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	3	1	70	6.85	0		506.978	53.6
502B	3	1	80	6.95	0		721.582	47.8
502B	3	1	90	7.05	0		376.499	47.2
502B	3	1	100	7.15	0		168.982	59.9
502B	3	1	110	7.25	0		218.849	59.9
502B	3	1	120	7.35	0		239.349	49.0
502B	3	1	130	7.45	0		243.519	40.6
502B	3	1	140	7.55	0		345.952	45.6
502B	3	1	145	7.60	0		323.686	38.0
502B	3	2	20	7.80	0		225.617	39.3
502B	3	2	30	7.90	0		398.024	36.0
502B	3	2	40	8.00	0		586.270	43.3
502B	3	2	50	8.10	0		443.774	34.6
502B	3	2	60	8.20	0		299.833	30.5
502B	3	2	70	8.30	0		290.214	28.8
502B	3	2	80	8.40	0		263.598	29.3
502B	3	2	90	8.50	0		193.099	40.3
502B	3	2	100	8.60	0		276.589	27.9
502B	3	2	110	8.70	0		189.502	34.4
502B	3	2	120	8.80	0		323.571	26.7
502B	3	2	130	8.90	0		307.140	32.5
502B	3	2	140	9.00	0		107.645	33.4
502B	3	2	145	9.05	0		218.784	35.3
502B	3	3	20	9.30	0		328.600	35.8
502B	3	3	40	9.50	0		371.296	37.0
502B	3	3	50	9.60	0		294.030	36.5
502B	3	3	60	9.70	0		266.456	42.8
502B	3	3	70	9.80	0		193.691	39.8
502B	3	3	80	9.90	0		246.054	44.2
502B	3	3	90	10.00	0		321.279	42.4
502B	3	3	100	10.10	0		226.155	46.4
502B	3	3	110	10.20	0		250.259	52.3
502B	3	3	120	10.30	0		351.564	53.4
502B	3	3	125	10.35	0		322.445	48.7
502B	4	1	20	10.75	0	PHI=180 DEGREES	43.669	11.6
502B	4	1	30	10.85	0		198.559	355.7
502B	4	1	40	10.95	0		157.602	22.3
502B	4	1	50	11.05	0		287.465	345.0
502B	4	1	60	11.15	0		275.006	33.6
502B	4	1	70	11.25	0		378.659	12.3
502B	4	1	80	11.35	0		360.957	10.4
502B	4	1	90	11.45	0		309.670	11.7
502B	4	1	100	11.55	0		348.121	26.0
502B	4	1	110	11.65	0		392.150	24.8
502B	4	1	120	11.75	0		386.582	19.0
502B	4	1	130	11.85	0		449.375	16.2
502B	4	1	140	11.95	0		584.066	26.7
502B	4	1	145	12.00	0		506.773	22.8
502B	4	2	20	12.24	0		572.810	18.6
502B	4	2	30	12.34	0		500.631	16.7
502B	4	2	40	12.44	0		384.156	18.6
502B	4	2	50	12.54	0		207.143	2.3
502B	4	2	60	12.64	0		196.195	22.1

*** GRID F 09 ***

*** GRID G 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	4	2	70	12.74	0		300.393	14.9
502B	4	2	80	12.84	0		448.216	14.1
502B	4	2	90	12.94	0		237.221	16.0
502B	4	2	100	13.04	0		275.533	6.4
502B	4	2	110	13.14	0		180.310	43.6
502B	4	2	120	13.24	0		184.878	42.8
502B	4	2	130	13.34	0		354.932	22.2
502B	4	2	140	13.44	0		375.601	47.5
502B	4	2	145	13.49	0		379.332	24.3
502B	4	3	20	13.74	0		278.499	352.4
502B	4	3	30	13.84	0		380.650	7.5
502B	4	3	40	13.94	0		315.278	11.2
502B	4	3	50	14.04	0		428.163	8.1
502B	4	3	60	14.14	0		553.323	11.2
502B	4	3	70	14.24	0		425.892	10.1
502B	4	3	80	14.34	0		415.717	9.8
502B	4	3	90	14.44	0		292.103	7.8
502B	4	3	100	14.54	0		229.419	358.5
502B	4	3	110	14.64	0		128.627	26.9
502B	4	3	120	14.74	0		325.748	27.4
502B	4	3	127	14.81	0		321.083	33.7
502B	5	1	20	15.05	0	PHI=050 DEGREES	471.498	202.4
502B	5	1	20	15.05	0		471.498	202.4
502B	5	1	30	15.15	0		141.121	270.2
502B	5	1	40	15.25	0		93.820	14.7
502B	5	1	50	15.35	0		311.328	238.6
502B	5	1	60	15.45	0		72.594	310.4
502B	5	1	70	15.55	0		157.946	254.5
502B	5	1	80	15.65	0		213.572	255.6
502B	5	1	90	15.75	0		209.830	244.6
502B	5	1	100	15.85	0		215.761	246.0
502B	5	1	110	15.95	0		168.387	249.2
502B	5	1	120	16.05	0		148.421	263.5
502B	5	1	130	16.15	0		223.076	252.9
502B	5	1	140	16.25	0		135.031	251.6
502B	5	1	145	16.30	0		149.984	341.3
502B	5	2	20	16.50	0		59.235	160.3
502B	5	2	30	16.60	0		81.486	80.6
502B	5	2	40	16.70	0		3.992	81.2
502B	5	2	50	16.80	0		75.352	254.0
502B	5	2	60	16.90	0		105.472	237.1
502B	5	2	70	17.00	0		25.549	62.5
502B	5	2	80	17.07	0		17.518	60.6
502B	5	2	80	17.07	0	NEAR VOID	17.518	60.6
502B	5	2	90	17.07	0		5.354	42.5
502B	5	2	100	17.15	0		194.262	79.3
502B	5	2	100	17.15	0	PIECE BETWEEN VOIDS	194.262	79.3
502B	5	2	110	17.25	0		174.407	74.0
502B	5	2	120	17.22	0		152.043	76.1
502B	5	2	130	17.32	0		267.592	80.3
502B	5	2	140	17.42	0		222.558	69.0
502B	5	2	145	17.47	0		196.673	79.1
502B	5	3	18	17.71	0		224.075	69.6

*** GRID G 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	5	3	18	17.71	1	REPEAT FOR DETAIL	224.075	69.6
502B	5	3	20	17.73	0		169.051	68.7
502B	5	3	20	17.73	1		161.522	68.6
502B	5	3	25	17.78	1		49.073	81.8
502B	5	3	30	17.83	0		10.225	164.0
502B	5	3	30	17.83	1		17.817	209.4
502B	5	3	35	17.88	1		75.660	231.3
502B	5	3	40	17.93	0		77.793	236.3
502B	5	3	40	17.93	1		92.042	235.4
502B	5	3	45	17.98	1		88.010	247.6
502B	5	3	50	18.03	0		51.551	286.4
502B	5	3	50	18.03	1		52.223	274.9
502B	5	3	55	18.08	1		60.084	120.6
502B	5	3	60	18.13	0		49.874	62.5
502B	5	3	60	18.13	1		36.428	63.5
502B	5	3	65	18.18	1		110.848	83.3
502B	5	3	70	18.23	0		143.261	72.6
502B	5	3	70	18.23	1		139.707	71.9
502B	5	3	75	18.28	1		160.096	58.2
502B	5	3	80	18.33	0		184.986	58.2
502B	5	3	80	18.33	1		178.258	58.9
502B	5	3	90	18.43	0		198.045	63.7
502B	5	3	100	18.53	0		96.896	77.6
502B	5	3	110	18.63	0		75.022	82.6
502B	5	3	120	18.73	0		414.882	200.1
502B	5	3	122	18.75	0		985.002	178.5
502B	6	1	20	19.55	0	PHI=275 DEGREES	64.968	305.3
502B	6	1	30	19.65	0		84.523	349.1
502B	6	1	40	19.75	0		38.158	341.9
502B	6	1	50	19.85	0		4.708	2.7
502B	6	1	60	19.95	0		205.842	16.6
502B	6	1	70	20.05	0		440.284	7.2
502B	6	1	80	20.15	0		162.219	353.4
502B	6	1	90	20.25	0		114.698	29.7
502B	6	1	100	20.35	0		183.145	346.6
502B	6	1	110	20.45	0		132.723	353.4
502B	6	1	120	20.55	0		124.557	356.7
502B	6	1	130	20.65	0		107.146	19.1
502B	6	1	140	20.75	0		58.335	1.9
502B	6	1	145	20.80	0		67.057	349.4
502B	6	2	20	21.06	0		71.481	331.1
502B	6	2	30	21.16	0		24.569	30.9
502B	6	2	40	21.26	0		33.721	351.3
502B	6	2	50	21.36	0		18.647	99.8
502B	6	2	60	21.46	0		49.713	167.3
502B	6	2	70	21.56	0		65.661	252.3
502B	6	2	80	21.66	0		11.490	196.6
502B	6	2	90	21.76	0		24.376	302.5
502B	6	2	100	21.86	0		37.342	220.3
502B	6	2	110	21.96	0		115.497	187.2
502B	6	2	120	22.06	0		107.644	177.7
502B	6	2	130	22.16	0		57.054	174.0
502B	6	2	140	22.26	0		101.833	176.7

*** GRID I 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	6	2	145	22.31	0		87.179	183.0
502B	6	3	20	22.54	0		96.442	178.9
502B	6	3	30	22.64	0		71.074	179.3
502B	6	3	40	22.74	0		125.814	149.6
502B	6	3	50	22.84	0		151.697	204.7
502B	6	3	60	22.94	0		77.143	163.2
502B	6	3	70	23.04	0		96.113	178.1
502B	6	3	80	23.14	0		34.746	178.7
502B	6	3	90	23.24	0		19.644	1.1
502B	6	3	100	23.34	0		39.457	352.2
502B	6	3	110	23.44	0		31.711	342.3
502B	6	3	120	23.54	0		65.033	17.4
502B	6	3	127	23.59	0		127.281	4.5
502B	6	3	145	23.77	0		87.179	183.0
502B	7	2	20	24.23	0	PHI=080 DEGREES	191.594	298.6
502B	7	2	30	24.33	0		336.404	262.7
502B	7	2	40	24.43	0		94.320	217.7
502B	7	2	50	24.53	0		630.479	304.6
502B	7	2	60	24.63	0		162.097	201.1
502B	7	2	70	24.73	0		106.974	86.7
502B	7	2	80	24.83	0		420.823	352.2
502B	7	2	90	24.93	0		31.290	40.1
502B	7	2	100	25.03	0		319.065	246.7
502B	7	2	110	25.13	0		30.387	183.3
502B	7	2	120	25.23	0		73.952	129.5
502B	7	2	130	25.33	0		65.986	115.7
502B	7	2	140	25.43	0		177.012	180.8
502B	7	2	145	25.48	0		212.434	172.7
502B	7	3	20	25.72	0		81.736	257.0
502B	7	3	30	25.82	0		2.290	135.2
502B	7	3	40	25.92	0		163.219	173.9
502B	7	3	50	26.02	0		142.757	162.1
502B	7	3	60	26.12	0		338.875	244.2
502B	7	3	70	26.22	0		119.029	173.8
502B	7	3	80	26.32	0		206.395	164.8
502B	7	3	90	26.42	0		158.721	150.9
502B	7	3	100	26.52	0		153.323	149.1
502B	7	3	110	26.62	0		267.942	104.2
502B	7	3	120	26.72	0		119.539	180.5
502B	7	3	130	26.82	0		140.403	207.7
502B	7	3	140	26.92	0		133.669	192.4
502B	7	3	145	26.97	0		114.889	165.7
502B	7	4	20	27.23	0		89.161	173.0
502B	7	4	30	27.33	0		111.064	192.3
502B	7	4	40	27.43	0		82.685	151.0
502B	7	4	50	27.53	0		159.850	177.6
502B	7	4	60	27.63	0		159.914	203.3
502B	7	4	70	27.73	0		212.511	181.3
502B	7	4	80	27.83	0		206.976	185.2
502B	7	4	90	27.93	0		121.412	178.2
502B	7	4	100	28.03	0		170.620	190.4
502B	7	4	110	28.13	0		90.494	177.9
502B	7	4	126	28.29	0		180.736	315.5

*** GRID I 09 ***

*** GRID J 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	8	1	20	28.35	0	PHI=220 DEGREES	530.205	72.0
502B	8	1	30	28.45	0		46.312	132.6
502B	8	1	40	28.55	0		80.712	162.0
502B	8	1	50	28.65	0		44.084	223.7
502B	8	1	60	28.75	0		26.835	213.0
502B	8	1	70	28.85	0		58.992	259.1
502B	8	1	80	28.95	0		133.667	266.0
502B	8	1	90	29.05	0		42.761	27.9
502B	8	1	100	29.15	0		50.874	28.8
502B	8	1	110	29.25	0		16.662	203.7
502B	8	1	120	29.35	0		30.861	58.8
502B	8	1	130	29.45	0		45.847	12.9
502B	8	1	140	29.55	0		37.908	346.2
502B	8	1	145	29.60	0		114.546	29.6
502B	8	2	20	29.74	0	VOID BETWEEN 45 & 85CM	37.294	69.1
502B	8	2	30	29.84	0		186.251	89.7
502B	8	2	40	29.94	0		305.937	105.6
502B	8	2	50	30.04	0		53.713	96.2
502B	8	2	60	30.01	0		4.521	62.2
502B	8	2	70	30.01	0		7.291	203.2
502B	8	2	80	30.01	0		14.282	81.2
502B	8	2	90	30.01	0		127.770	64.8
502B	8	2	100	30.11	0		186.002	100.9
502B	8	2	110	30.21	0		265.778	112.6
502B	8	2	120	30.31	0		401.245	102.1
502B	8	2	130	30.41	0		152.175	84.0
502B	8	2	140	30.51	0		141.258	102.1
502B	8	2	145	30.56	0		170.381	107.5
502B	8	3	20	30.77	0		139.823	100.8
502B	8	3	30	30.87	0		160.858	101.4
502B	8	3	40	30.97	0		220.758	70.6
502B	8	3	50	31.07	0		268.254	94.0
502B	8	3	60	31.17	0		231.514	92.5
502B	8	3	70	31.27	0		322.773	100.2
502B	8	3	80	31.37	0		140.983	104.9
502B	8	3	90	31.47	0		157.662	92.1
502B	8	3	100	31.57	0		182.866	53.8
502B	8	3	102	31.59	0		30.727	260.3
502B	9	1	20	32.60	0	PHI=158 DEGREES	409.434	86.2
502B	9	1	30	32.70	0		420.233	232.9
502B	9	1	40	32.80	0		79.960	215.6
502B	9	1	50	32.90	0		63.747	259.9
502B	9	1	60	33.00	0		111.282	241.8
502B	9	1	70	33.10	0		60.548	67.8
502B	9	1	80	33.20	0		62.409	259.0
502B	9	1	90	33.30	0		179.614	213.9
502B	9	1	100	33.40	0		92.566	198.4
502B	9	1	110	33.50	0		91.712	210.4
502B	9	1	120	33.60	0		131.005	219.8
502B	9	1	130	33.70	0		138.420	229.2
502B	9	1	140	33.80	0		63.939	220.3
502B	9	1	145	33.85	0		81.322	119.5
502B	9	2	20	34.06	0		104.710	240.3

*** GRID J 09 ***

*** GRID K 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	9	2	30	34.16	0		131.610	229.0
502B	9	2	40	34.26	0		177.107	224.9
502B	9	2	50	34.36	0		309.116	214.2
502B	9	2	60	34.46	0		156.132	243.9
502B	9	2	70	34.56	0		511.298	218.0
502B	9	2	80	34.66	0		252.995	237.5
502B	9	2	90	34.76	0		158.367	224.0
502B	9	2	100	34.86	0		100.842	233.6
502B	9	2	110	34.96	0		74.776	227.6
502B	9	2	120	35.00	0		130.722	212.0
502B	9	2	130	35.10	0		160.882	221.0
502B	9	2	140	35.20	0		145.117	216.1
502B	9	3	10	35.39	0		89.609	185.7
502B	9	3	20	35.48	0		80.558	302.7
502B	9	3	30	35.53	0		279.128	205.6
502B	9	3	40	35.63	0		226.286	222.1
502B	9	3	50	35.73	0		132.787	175.4
502B	9	3	60	35.83	0		186.312	240.5
502B	10	1	20	37.15	0	PHI=162 DEGREES	831.802	152.3
502B	10	1	30	37.25	0		359.085	266.4
502B	10	1	40	37.35	0		157.960	155.7
502B	10	1	50	37.45	0		624.398	164.3
502B	10	1	60	37.55	0		164.568	335.4
502B	10	1	70	37.65	0		230.311	249.9
502B	10	1	80	37.75	0		285.366	32.4
502B	10	1	90	37.85	0		145.289	276.2
502B	10	1	100	37.95	0		11.364	243.4
502B	10	1	110	38.05	0		95.054	260.6
502B	10	1	120	38.15	0		52.021	296.2
502B	10	1	130	38.25	0		370.104	223.8
502B	10	1	140	38.35	0		92.650	352.7
502B	10	2	20	38.35	0		179.083	107.1
502B	10	2	30	38.35	0		91.282	108.8
502B	10	2	40	38.35	0		102.978	87.9
502B	10	2	50	38.35	0		64.543	57.2
502B	10	2	60	38.45	0		65.711	50.4
502B	10	2	70	38.55	0		283.359	49.7
502B	10	2	80	38.65	0		822.979	215.3
502B	10	2	90	38.75	0		106.679	283.2
502B	10	2	100	38.85	0		65.772	9.4
502B	10	2	110	38.95	0		67.579	272.6
502B	10	2	120	39.05	0		163.702	329.6
502B	10	2	130	39.15	0		227.968	332.2
502B	10	2	140	39.25	0		139.934	342.1
502B	11	1	20	41.55	0	PHI=302 DEGREES	185.309	72.9
502B	11	1	30	41.65	0		268.157	140.5
502B	11	1	40	41.75	0		344.923	61.5
502B	11	1	50	41.85	0		262.622	37.6
502B	11	1	60	41.95	0		299.317	133.0
502B	11	1	70	42.05	0		90.396	72.4
502B	11	1	80	42.15	0		1426.507	23.1
502B	11	1	90	42.25	0		85.445	153.1
502B	11	1	100	42.35	0		56.375	191.9

*** GRID K 09 ***

*** GRID L 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	11	1	110	42.45	0		70.517	207.1
502B	11	1	120	42.55	0		93.791	289.6
502B	11	1	130	42.65	0		60.012	199.5
502B	11	1	140	42.75	0		185.549	239.5
502B	11	2	20	43.04	0		80.575	216.6
502B	11	2	30	43.14	0		105.331	264.7
502B	11	2	40	43.24	0		82.768	252.6
502B	11	2	50	43.34	0		172.558	270.0
502B	11	2	60	43.44	0		15.259	288.2
502B	11	2	70	43.54	0		109.597	238.3
502B	11	2	80	43.64	0		112.880	225.9
502B	11	2	90	43.74	0		127.660	232.0
502B	11	2	100	43.84	0		133.869	228.4
502B	11	2	110	43.94	0		108.942	231.5
502B	11	2	120	44.04	0		167.998	234.0
502B	11	2	130	44.14	0		117.517	245.1
502B	11	2	140	44.24	0		228.140	232.2
502B	11	3	20	44.55	0		132.807	231.2
502B	11	3	30	44.65	0		207.156	227.9
502B	11	3	40	44.75	0		142.824	231.4
502B	11	3	50	44.85	0		91.184	229.3
502B	11	3	60	44.95	0		151.646	226.4
502B	11	3	70	45.05	0		246.149	225.3
502B	11	3	80	45.15	0		301.159	223.3
502B	11	3	90	45.25	0		80.688	247.5
502B	11	3	100	45.35	0		111.817	235.3
502B	11	3	110	45.45	0		166.908	232.5
502B	11	3	120	45.55	0		157.015	238.7
502B	11	3	127	45.62	0		115.573	120.4
502B	12	1	20	45.70	0	PHI=149 DEGREES	2341.443	223.1
502B	12	1	30	45.80	0		830.153	353.1
502B	12	1	40	45.90	0		329.583	206.8
502B	12	1	50	46.00	0		576.818	320.4
502B	12	1	60	46.10	0		539.948	204.7
502B	12	1	70	46.20	0		425.599	67.1
502B	12	1	80	46.30	0		875.543	202.2
502B	12	1	90	46.40	0		653.173	10.0
502B	12	1	100	46.50	0		388.947	90.8
502B	12	1	110	46.60	0		183.316	103.8
502B	12	1	120	46.70	0		853.456	250.1
502B	12	1	130	46.80	0		793.603	39.4
502B	12	1	140	46.84	0		265.546	232.8
502B	12	2	20	47.04	0		3174.802	249.5
502B	12	2	30	47.14	0		790.313	231.5
502B	12	2	40	47.24	0		504.154	267.8
502B	12	2	50	47.34	0		1253.945	211.3
502B	12	2	60	47.44	0		259.915	71.5
502B	12	2	70	47.54	0		439.573	37.3
502B	12	2	80	47.64	0		1157.426	336.2
502B	12	2	90	47.74	0		255.870	250.9
502B	12	2	100	47.84	0		804.772	267.0
502B	12	2	110	47.94	0		444.206	0.1
502B	12	2	120	48.04	0		297.924	327.1

*** GRID L 09 ***

*** GRID M 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	12	2	130	48.14	0		31.644	38.5
502B	12	2	140	48.24	0		120.894	240.0
502B	12	2	144	48.28	0		60.897	265.6
502B	12	3	10	48.45	0		150.693	255.8
502B	12	3	20	48.55	0		155.462	231.6
502B	12	3	30	48.65	0		101.577	223.5
502B	12	3	40	48.75	0		62.227	108.7
502B	12	3	50	48.85	0		358.473	175.0
502B	13	1	20	50.35	0	PHI=134 DEGREES	431.596	100.6
502B	13	1	30	50.45	0		351.061	67.5
502B	13	1	40	50.55	0		198.276	77.3
502B	13	1	50	50.65	0		90.265	59.3
502B	13	1	60	50.75	0		262.191	344.4
502B	13	1	70	50.85	0		112.658	110.6
502B	13	1	80	50.95	0		201.869	116.5
502B	13	1	90	51.05	0		150.202	67.0
502B	13	1	100	51.15	0		206.444	100.4
502B	13	1	110	51.25	0		184.825	355.0
502B	13	1	120	51.35	0		123.209	75.1
502B	13	1	130	51.45	0		38.554	186.8
502B	13	1	140	51.55	0		144.138	104.7
502B	13	2	20	51.85	0		281.335	115.2
502B	13	2	30	51.95	0		284.814	100.7
502B	13	2	40	52.05	0		253.323	102.4
502B	13	2	50	52.15	0		233.303	100.9
502B	13	2	60	52.25	0		312.092	105.8
502B	13	2	70	52.35	0		329.530	106.1
502B	13	2	80	52.45	0		226.236	104.0
502B	13	2	90	52.55	0		274.878	115.9
502B	13	2	100	52.65	0		220.405	106.9
502B	13	2	110	52.75	0		237.400	126.4
502B	13	2	120	52.85	0		222.939	114.9
502B	13	2	130	52.95	0		239.115	116.7
502B	13	2	140	53.05	0		148.171	133.6
502B	13	3	20	53.36	0		164.868	127.9
502B	13	3	30	53.46	0		315.667	126.5
502B	13	3	40	53.56	0		403.828	141.9
502B	13	3	50	53.66	0		319.004	145.9
502B	13	3	60	53.76	0		291.696	138.1
502B	13	3	70	53.86	0		267.598	147.7
502B	13	3	80	53.96	0		193.934	121.7
502B	13	3	90	54.06	0		241.855	154.5
502B	13	3	100	54.16	0		238.568	158.8
502B	13	3	110	54.26	0		337.370	174.8
502B	13	3	120	54.36	0		252.009	60.6
502B	14	1	20	54.65	0	PHI=025 DEGREES	517.231	134.4
502B	14	1	30	54.75	0		192.322	100.2
502B	14	1	40	54.85	0		674.946	82.2
502B	14	1	50	54.95	0		217.170	226.8
502B	14	1	60	55.05	0		80.874	167.3
502B	14	1	70	55.15	0		108.041	176.8
502B	14	1	80	55.25	0		174.394	122.3
502B	14	1	90	55.35	0		387.072	121.9

*** GRID M 09 ***

*** GRID N 09 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	14	1	100	55.45	0		215.790	121.6
502B	14	1	110	55.55	0		206.962	127.7
502B	14	1	120	55.65	0		140.353	77.8
502B	14	1	130	55.75	0		272.907	193.7
502B	14	1	140	55.85	0		254.863	141.8
502B	14	1	145	55.90	0		504.110	177.0
502B	14	2	20	56.15	0		278.487	121.3
502B	14	2	30	56.25	0		334.887	117.4
502B	14	2	40	56.35	0		300.951	109.1
502B	14	2	50	56.45	0		234.537	113.7
502B	14	2	60	56.55	0		261.613	112.7
502B	14	2	70	56.65	0		210.834	128.3
502B	14	2	80	56.73	0		402.727	122.7
502B	14	2	90	56.83	0		285.203	119.8
502B	14	2	100	56.93	0		262.695	119.4
502B	14	2	110	57.03	0		364.101	120.5
502B	14	2	120	57.13	0		219.817	117.8
502B	14	2	130	57.23	0		149.704	132.0
502B	14	2	140	57.33	0		141.041	151.0
502B	14	3	20	57.63	0		229.755	133.1
502B	14	3	30	57.73	0		298.323	135.2
502B	14	3	40	57.83	0		133.788	124.5
502B	14	3	50	57.93	0		140.164	140.3
502B	14	3	60	58.03	0		227.435	133.8
502B	14	3	70	58.13	0		239.806	138.6
502B	14	3	80	58.23	0		220.755	133.1
502B	14	3	90	58.33	0		235.596	140.5
502B	14	3	100	58.43	0		76.126	124.4
502B	14	3	109	58.48	0		253.175	32.6
502B	15	1	20	59.15	0	PHI=108 DEGREES	121.963	261.5
502B	15	1	30	59.25	0		98.369	83.1
502B	15	1	40	59.35	0		175.095	353.7
502B	15	1	50	59.45	0		165.056	325.8
502B	15	1	60	59.55	0		214.288	355.7
502B	15	1	70	59.65	0		253.451	38.5
502B	15	1	80	59.75	0		287.984	3.0
502B	15	1	90	59.85	0		126.827	5.7
502B	15	1	100	59.95	0		123.323	36.1
502B	15	1	110	60.05	0		105.215	48.7
502B	15	1	120	60.15	0		93.478	0.5
502B	15	1	130	60.25	0		200.746	11.4
502B	15	1	140	60.35	0		278.833	243.3
502B	16	1	20	63.32	0	PHI=255 DEGREES	413.091	127.2
502B	16	1	30	63.42	0		253.845	27.1
502B	16	1	40	63.52	0		200.861	46.7
502B	16	1	50	63.62	0		207.189	75.2
502B	16	1	60	63.72	0		163.569	109.4
502B	16	1	70	63.82	0		133.003	56.7
502B	16	1	80	63.92	0		316.261	75.6
502B	16	1	90	64.02	0		469.107	65.7
502B	16	1	97	64.09	0		140.851	75.5
502B	18	1	20	72.35	0	PHI=240 DEGREES	221.829	357.2
502B	18	1	30	72.45	0		212.183	1.9

*** GRID N 09 ***

*** GRID B 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 a-6)	NRM Declination (deg.)
502B	18	1	40	72.55	0		335.693	7.4
502B	18	1	50	72.65	0		369.092	12.2
502B	18	1	60	72.75	0		448.111	24.3
502B	18	1	70	72.85	0		277.306	24.9
502B	18	1	80	72.95	0		319.172	21.7
502B	18	1	90	73.05	0		296.082	16.1
502B	18	1	100	73.15	0		189.362	7.2
502B	18	1	110	73.25	0		436.159	10.5
502B	18	1	120	73.35	0		220.683	5.2
502B	18	1	130	73.45	0		128.850	0.0
502B	18	1	140	73.55	0		54.526	36.3
502B	18	2	20	73.84	0		46.981	256.6
502B	18	2	30	73.94	0		55.411	295.1
502B	18	2	40	74.04	0		44.456	66.1
502B	18	2	50	74.14	0		53.330	329.3
502B	18	2	60	74.24	0		97.188	34.7
502B	18	2	70	74.34	0		39.633	78.8
502B	18	2	80	74.44	0		15.258	359.6
502B	18	2	90	74.54	0		48.503	127.9
502B	18	2	100	74.64	0		62.171	65.2
502B	18	2	110	74.74	0		33.779	136.7
502B	18	2	120	74.84	0		73.016	182.8
502B	18	2	130	74.94	0		41.909	149.5
502B	18	2	140	75.04	0		54.232	176.9
502B	18	3	20	75.34	0		19.868	229.6
502B	18	3	30	75.44	0		37.119	199.7
502B	18	3	40	75.54	0		141.549	225.4
502B	18	3	50	75.64	0		17.874	54.8
502B	18	3	60	75.74	0		25.299	72.8
502B	18	3	70	75.84	0		52.531	44.6
502B	18	3	80	75.94	0		84.958	25.2
502B	18	3	90	76.04	0		80.978	28.6
502B	18	3	100	76.14	0		112.817	50.1
502B	18	3	110	76.24	0		171.106	25.5
502B	18	3	120	76.34	0		315.783	38.5
502B	18	3	128	76.42	0		46.447	24.0
502B	19	1	20	76.75	0	PHI=240 DEGREES	517.602	52.6
502B	19	1	30	76.85	0		305.661	319.2
502B	19	1	40	76.95	0		261.372	322.5
502B	19	1	50	77.05	0		182.022	357.3
502B	19	1	60	77.15	0		153.153	338.2
502B	19	1	70	77.25	0		279.792	333.8
502B	19	1	80	77.35	0		397.171	321.5
502B	19	1	90	77.45	0		251.540	327.7
502B	19	1	100	77.55	0		305.314	321.8
502B	19	1	110	77.65	0		384.348	337.9
502B	19	1	120	77.75	0		397.722	337.2
502B	19	1	130	77.85	0		318.397	339.2
502B	19	1	140	77.95	0		201.342	349.2
502B	19	2	20	78.25	0		183.824	330.2
502B	19	2	30	78.35	0		194.066	356.4
502B	19	2	40	78.45	0		173.233	3.1
502B	19	2	50	78.55	0		113.238	338.8

*** GRID B 10 ***

*** GRID C 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	19	2	60	78.65	0		92.462	318.4
502B	19	2	70	78.75	0		84.886	15.5
502B	19	2	80	78.85	0		45.443	354.4
502B	19	2	90	78.95	0		80.780	350.9
502B	19	2	100	79.05	0		66.389	49.0
502B	19	2	110	79.15	0		41.184	75.2
502B	19	2	120	79.25	0		186.882	150.5
502B	19	2	130	79.35	0		120.835	154.3
502B	19	2	135	79.40	0		177.775	114.0
502B	19	2	140	79.45	0		43.239	205.2
502B	19	2	145	79.50	0		107.432	211.1
502B	19	3	20	79.76	0		165.103	145.1
502B	19	3	30	79.86	0		158.065	200.7
502B	19	3	40	79.96	0		192.296	121.5
502B	19	3	50	80.06	0		57.652	357.6
502B	19	3	60	80.16	0		129.288	233.4
502B	19	3	70	80.26	0		149.988	175.2
502B	19	3	80	80.36	0		80.185	138.7
502B	19	3	90	80.46	0		84.535	152.6
502B	19	3	100	80.56	0		347.683	41.6
502B	19	3	110	80.66	0		90.240	293.0
502B	20	1	20	81.15	0	PHI=063 DEGREES	197.896	202.2
502B	20	1	30	81.25	0		438.736	196.7
502B	20	1	40	81.35	0		200.980	332.9
502B	20	1	50	81.45	0		506.310	150.6
502B	20	1	60	81.55	0		197.019	52.5
502B	20	1	70	81.65	0		686.878	328.2
502B	20	1	80	81.75	0		350.759	194.1
502B	20	1	90	81.85	0		399.923	127.9
502B	20	1	100	81.95	0		109.968	48.2
502B	20	1	110	82.05	0		207.189	339.6
502B	20	1	120	82.15	0		256.201	346.0
502B	20	1	130	82.25	0		239.546	62.7
502B	20	1	140	82.35	0		300.492	18.4
502B	20	2	20	82.65	0		137.851	32.2
502B	20	2	30	82.75	0		342.092	356.3
502B	20	2	40	82.85	0		328.623	25.5
502B	20	2	50	82.95	0		49.880	157.6
502B	20	2	60	83.05	0		37.335	126.6
502B	20	2	70	83.15	0		348.367	52.3
502B	20	2	80	83.25	0		193.384	11.2
502B	20	2	90	83.35	0		342.207	24.1
502B	20	2	100	83.45	0		168.540	25.9
502B	20	2	110	83.55	0		436.402	2.0
502B	20	2	120	83.65	0		258.984	340.3
502B	20	2	130	83.75	0		540.213	62.3
502B	20	2	140	83.85	0		323.159	353.1
502B	20	3	20	84.15	0		151.444	201.8
502B	20	3	30	84.25	0		376.606	342.7
502B	20	3	40	84.35	0		580.682	23.7
502B	20	3	50	84.45	0		585.070	24.8
502B	20	3	60	84.55	0		156.559	2.0
502B	20	3	70	84.65	0		324.925	40.8

*** GRID C 10 ***

*** GRID D 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	20	3	80	84.75	0		423.565	12.7
502B	20	3	90	84.85	0		201.687	10.4
502B	20	3	100	84.95	0		69.532	288.0
502B	20	3	110	85.05	0		250.595	355.7
502B	20	3	120	85.15	0		270.263	9.3
502B	20	3	129	85.24	0		161.795	245.9
502B	21	1	20	85.48	0	PHI=210 DEGREES	2253.954	341.6
502B	21	1	30	85.58	0		563.903	77.9
502B	21	1	40	85.68	0		1095.054	82.5
502B	21	1	50	85.78	0		412.417	341.6
502B	21	1	60	85.88	0		231.944	26.5
502B	21	1	70	85.98	0		150.575	61.9
502B	21	1	80	86.08	0		106.045	217.7
502B	21	1	90	86.18	0		607.835	336.7
502B	21	1	100	86.28	0		147.966	258.5
502B	21	1	110	86.38	0		273.010	18.8
502B	21	1	140	86.68	0		563.469	71.7
502B	21	2	20	86.99	0		365.359	49.0
502B	21	2	30	87.09	0		353.534	43.8
502B	21	2	40	87.19	0		532.059	30.8
502B	21	2	50	87.29	0		561.111	35.0
502B	21	2	60	87.39	0		463.474	19.8
502B	21	2	70	87.49	0		266.787	47.0
502B	21	2	80	87.59	0		360.477	48.4
502B	21	2	90	87.69	0		349.214	43.3
502B	21	2	100	87.79	0		424.222	43.7
502B	21	2	110	87.89	0		447.203	26.1
502B	21	2	120	87.99	0		306.972	34.7
502B	21	2	130	88.09	0		377.938	35.7
502B	21	2	140	88.19	0		396.750	37.5
502B	21	3	20	88.44	0		480.493	45.9
502B	21	3	30	88.54	0		320.539	58.7
502B	21	3	40	88.64	0		287.179	46.2
502B	21	3	50	88.74	0		312.807	41.1
502B	21	3	60	88.84	0		161.806	273.8
502B	21	3	70	88.94	0		113.710	48.4
502B	21	3	80	89.04	0		171.857	51.4
502B	21	3	90	89.14	0		139.480	44.7
502B	21	3	100	89.24	0		85.815	9.0
502B	21	3	110	89.34	0		58.690	25.3
502B	22	2	20	90.12	0	PHI=330 DEGREES	16.869	315.1
502B	22	2	30	90.22	0		139.194	110.1
502B	22	2	40	90.32	0		110.687	16.2
502B	22	2	50	90.42	0		248.941	358.3
502B	22	2	60	90.52	0		2383.133	346.6
502B	22	2	70	90.62	0		104.830	63.2
502B	22	2	80	90.72	0		68.949	84.4
502B	22	2	90	90.82	0		98.643	1.0
502B	22	2	100	90.92	0		139.221	343.5
502B	22	2	110	91.02	0		42.210	343.3
502B	22	2	120	91.12	0		43.936	226.8
502B	22	2	140	91.32	0		293.927	331.8
502B	22	3	20	91.62	0		110.473	346.6

*** GRID D 10 ***

*** GRID E 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	22	3	30	91.72	0		174.350	349.8
502B	22	3	40	91.82	0		92.301	6.0
502B	22	3	50	91.92	0		75.372	352.6
502B	22	3	60	92.02	0		78.346	100.2
502B	22	3	70	92.12	0		48.872	35.5
502B	22	3	80	92.22	0		31.413	33.1
502B	22	3	90	92.32	0		98.610	20.9
502B	22	3	100	92.42	0		232.019	349.8
502B	22	3	110	92.52	0		204.930	356.0
502B	22	3	120	92.62	0		138.331	333.0
502B	22	3	130	92.72	0		112.507	346.4
502B	22	3	140	92.82	0		99.685	9.2
502B	22	4	20	93.12	0		103.128	340.4
502B	22	4	30	93.22	0		117.522	322.1
502B	22	4	40	93.32	0		153.338	332.1
502B	22	4	50	93.42	0		236.262	328.9
502B	22	4	60	93.52	0		203.928	338.0
502B	22	4	70	93.62	0		142.184	347.5
502B	22	4	80	93.72	0		159.637	335.6
502B	22	4	90	93.82	0		179.908	1.4
502B	22	4	100	93.92	0		152.890	334.6
502B	22	4	110	94.02	0		187.843	338.7
502B	22	4	120	94.12	0		176.359	332.2
502B	22	4	128	94.20	0		33.890	298.8
502B	23	1	20	94.03	0	PHI=350 DEGREES	3428.458	92.9
502B	23	1	30	94.13	0		1211.459	183.4
502B	23	1	40	94.23	0		1892.340	272.0
502B	23	1	50	94.33	0		62.638	136.9
502B	23	1	60	94.43	0		752.099	53.3
502B	23	1	70	94.53	0		260.443	76.3
502B	23	1	80	94.63	0		247.182	68.2
502B	23	1	90	94.73	0		790.117	42.7
502B	23	1	100	94.83	0		191.753	62.8
502B	23	1	110	94.93	0		110.917	351.1
502B	23	1	120	95.03	0		520.204	31.8
502B	23	1	130	95.13	0		324.731	58.5
502B	23	1	140	95.23	0		227.913	83.2
502B	23	2	20	95.53	0		382.828	223.6
502B	23	2	30	95.63	0		368.764	48.3
502B	23	2	40	95.73	0		519.775	91.1
502B	23	2	50	95.83	0		269.135	50.9
502B	23	2	60	95.93	0		81.188	41.3
502B	23	2	70	96.03	0		35.910	292.0
502B	23	2	80	96.13	0		191.845	34.5
502B	23	2	90	96.23	0		136.994	339.9
502B	23	2	100	96.33	0		1321.271	74.0
502B	23	2	110	96.43	0		149.884	98.7
502B	23	2	120	96.53	0		83.173	301.5
502B	23	2	130	96.63	0		82.696	67.8
502B	23	2	140	96.73	0		393.494	245.3
502B	23	3	10	96.93	0		298.943	59.8
502B	23	3	20	97.03	0		291.615	60.9
502B	23	3	30	97.13	0		101.067	52.7

*** GRID E 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502B	23	3	40	97.19	0	VOID NEAR BASE	265.012	126.2
502C	1	2	20	32.32	0	PHI=045 DEGREES	2112.372	261.7
502C	1	2	30	32.42	0		2068.606	129.4
502C	1	2	40	32.52	0		6268.438	138.0
502C	1	2	50	32.62	0		2613.143	131.1
502C	1	2	60	32.72	0		2005.308	123.9
502C	1	2	70	32.82	0		1538.390	45.7
502C	1	2	80	32.92	0		1515.190	20.4
502C	1	2	90	33.02	0		134.011	34.1
502C	1	2	100	33.12	0		569.498	262.7
502C	1	2	110	33.22	0		2187.990	15.5
502C	1	2	120	33.32	0		298.738	340.5
502C	1	2	130	33.42	0		244.584	284.8
502C	1	2	140	33.52	0		427.097	309.3
502C	1	3	25	33.71	0		733.855	148.5
502C	1	3	30	33.76	0		3200.556	82.2
502C	1	3	40	33.86	0		20.778	42.7
502C	1	3	50	33.96	0		413.827	123.0
502C	1	3	60	34.06	0		302.804	336.0
502C	1	3	70	34.16	0		993.080	127.3
502C	1	3	80	34.26	0		2353.819	140.3
502C	1	3	90	34.36	0		3576.849	138.8
502C	1	3	100	34.46	0		411.445	170.4
502C	1	3	110	34.56	0		152.834	73.9
502C	1	3	120	34.66	0		243.213	157.9
502C	1	3	130	34.76	0		410.052	153.1
502C	1	3	140	34.86	0		390.207	156.0
502C	1	4	20	35.14	0		161.260	139.9
502C	1	4	30	35.24	0		150.726	149.3
502C	1	4	40	35.34	0		197.677	147.7
502C	1	4	50	35.44	0		273.702	153.0
502C	1	4	60	35.54	0		214.690	127.4
502C	1	4	70	35.64	0		404.074	149.0
502C	1	4	80	35.74	0		278.888	149.6
502C	1	4	90	35.84	0		281.311	165.7
502C	1	4	100	35.94	0		330.276	161.6
502C	1	4	110	36.04	0		433.925	154.5
502C	1	4	120	36.14	0		326.993	175.3
502C	2	1	10	36.45	0	PHI=310 DEGREES	529.580	312.4
502C	2	1	20	36.55	0		304.779	48.1
502C	2	1	30	36.65	0		1902.123	307.8
502C	2	1	40	36.75	0		916.024	22.4
502C	2	1	50	36.85	0		269.857	230.0
502C	2	1	60	36.95	0		98.322	108.9
502C	2	1	70	37.05	0		1968.961	108.3
502C	2	1	80	37.15	0		3986.788	26.6
502C	2	1	90	37.25	0		654.042	22.0
502C	2	1	100	37.35	0		704.507	100.3
502C	2	1	110	37.45	0		15115.15	84.1
502C	2	1	120	37.55	0		4128.152	46.0
502C	2	1	130	37.65	0		1137.264	192.3
502C	2	1	140	37.75	0		560.248	52.9
502C	2	2	20	38.01	0		2612.004	248.6

*** GRID G 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	2	2	30	38.11	0		6546.904	101.7
502C	2	2	40	38.21	0		4740.954	58.2
502C	2	2	50	38.31	0		293.867	72.8
502C	2	2	60	38.41	0		1202.978	137.7
502C	2	2	70	38.51	0		350.620	308.6
502C	2	2	80	38.61	0		2783.263	197.8
502C	2	2	90	38.71	0		612.734	44.4
502C	2	2	100	38.81	0		290.827	274.5
502C	2	2	110	38.91	0		902.484	221.9
502C	2	2	120	39.01	0		231.977	234.1
502C	2	2	130	39.11	0		216.447	193.9
502C	2	2	140	39.21	0		72.117	293.8
502C	2	3	20	39.51	0		233.208	265.2
502C	2	3	30	39.61	0		94.878	208.6
502C	2	3	40	39.71	0		108.881	290.7
502C	2	3	50	39.81	0		54.133	72.6
502C	2	3	60	39.91	0		190.735	274.9
502C	2	3	70	40.01	0		342.022	271.3
502C	2	3	90	40.21	0		90.125	294.7
502C	2	3	100	40.31	0		113.015	154.3
502C	2	3	110	40.41	0		641.030	247.0
502C	2	3	120	40.51	0		233.858	231.6
502C	2	3	130	40.61	0		1416.980	330.7
502C	3	1	20	41.00	0	PHI=158 DEGREES	1314.724	325.7
502C	3	1	30	41.10	0		273.738	109.2
502C	3	1	40	41.20	0		79.313	14.9
502C	3	1	50	41.30	0		1077.552	114.3
502C	3	1	60	41.40	0		359.695	318.5
502C	3	1	70	41.50	0		517.652	60.3
502C	3	1	80	41.60	0		251.968	237.3
502C	3	1	90	41.70	0		131.398	250.4
502C	3	1	100	41.80	0		43.768	297.4
502C	3	1	110	41.90	0		54.526	38.2
502C	3	1	120	42.00	0		147.881	185.1
502C	3	1	130	42.10	0		255.462	161.2
502C	3	1	140	42.20	0		114.207	184.7
502C	3	2	20	42.48	0		108.454	328.5
502C	3	2	30	42.58	0		283.541	359.8
502C	3	2	40	42.68	0		154.896	19.6
502C	3	2	50	42.78	0		195.608	342.1
502C	3	2	60	42.88	0		258.685	341.2
502C	3	2	70	42.98	0		144.877	241.1
502C	3	2	80	43.08	0		34.833	341.9
502C	3	2	90	43.18	0		158.950	24.1
502C	3	2	100	43.28	0		129.769	10.4
502C	3	2	110	43.38	0		246.160	325.1
502C	3	2	120	43.48	0		325.953	346.5
502C	3	2	130	43.58	0		124.320	72.6
502C	3	2	140	43.68	0		30.160	171.4
502C	3	3	10	43.88	0		196.299	5.6
502C	3	3	20	43.98	0		276.172	344.3
502C	3	3	30	44.08	0		512.428	330.9
502C	3	3	40	44.18	0		186.632	358.9

*** GRID G 10 ***

*** GRID H 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 a-6)	NRM Declination (deg.)
502C	3	3	48	44.26	0		83.394	33.2
502C	4	1	70	45.80	0	PHI=355 DEGREES	719.073	342.7
502C	4	1	80	45.90	0	VERY DISTURBED	714.214	118.5
502C	4	1	90	46.00	0		266.310	13.1
502C	4	1	100	46.10	0		368.292	253.0
502C	4	1	110	46.20	0		815.384	345.3
502C	4	1	120	46.30	0		217.622	273.5
502C	4	1	130	46.40	0		217.678	225.6
502C	4	1	140	46.50	0		300.935	254.7
502C	4	2	5	46.17	0		127.311	265.3
502C	4	2	10	46.22	0		383.645	251.8
502C	4	2	20	46.32	0		727.365	262.4
502C	4	2	30	46.42	0		477.742	256.7
502C	4	2	42	46.54	0		205.469	268.3
502C	5	1	20	49.80	0	PHI=215 DEGREES	74.613	279.5
502C	5	1	30	49.90	0		930.806	37.6
502C	5	1	40	50.00	0		366.192	185.9
502C	5	1	50	50.10	0		75.924	161.2
502C	5	1	60	50.20	0		363.960	19.4
502C	5	1	70	50.30	0		234.838	112.9
502C	5	1	80	50.40	0		302.581	126.1
502C	5	1	90	50.50	0		242.914	119.9
502C	5	1	100	50.60	0		289.131	124.2
502C	5	1	110	50.70	0		326.865	116.2
502C	5	1	120	50.80	0		176.796	131.4
502C	5	1	130	50.90	0		364.381	127.0
502C	5	1	140	51.00	0		288.283	135.0
502C	5	2	20	51.29	0		194.263	79.4
502C	5	2	30	51.39	0		60.551	106.8
502C	5	2	40	51.49	0		127.786	155.2
502C	5	2	50	51.59	0		287.033	156.9
502C	5	2	60	51.69	0		201.838	158.5
502C	5	2	70	51.79	0		222.217	166.8
502C	5	2	80	51.89	0		201.670	160.4
502C	5	2	90	51.99	0		328.284	163.9
502C	5	2	100	52.09	0		205.141	170.1
502C	5	2	110	52.19	0		291.927	166.6
502C	5	2	120	52.29	0		280.231	166.6
502C	5	2	130	52.39	0		256.351	161.4
502C	5	2	140	52.49	0		383.778	160.3
502C	5	3	20	52.79	0		189.633	150.9
502C	5	3	30	52.89	0		240.253	147.7
502C	5	3	40	52.99	0		289.701	145.1
502C	5	3	50	53.09	0		334.624	155.7
502C	5	3	60	53.19	0		334.584	156.9
502C	5	3	70	53.29	0		318.301	153.4
502C	5	3	80	53.39	0		241.759	149.2
502C	5	3	90	53.49	0		89.868	101.9
502C	5	3	100	53.59	0		121.664	146.6
502C	6	2	20	54.35	0	PHI=290 DEGREES	63.843	34.3
502C	6	2	30	54.45	0		340.715	161.1
502C	6	2	40	54.55	0		99.902	316.0
502C	6	2	50	54.65	0		53.660	51.4

*** GRID H 10 ***

*** GRID I 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 a-6)	NRM Declination (deg.)
502C	6	2	60	54.75	0		719.685	25.5
502C	6	2	70	54.85	0		416.485	336.8
502C	6	2	80	54.95	0		126.964	330.5
502C	6	2	90	55.05	0		115.829	326.8
502C	6	2	100	55.15	0		269.889	316.4
502C	6	2	110	55.25	0		136.470	345.7
502C	6	2	120	55.35	0		142.645	330.6
502C	6	2	125	55.40	0		116.175	347.4
502C	6	2	130	55.45	0		57.887	198.4
502C	6	2	135	55.50	0		48.599	266.6
502C	6	2	140	55.55	0		5.026	104.4
502C	6	2	144	55.59	0		23.903	66.8
502C	6	3	5	55.70	0		179.837	141.2
502C	6	3	10	55.75	0		271.944	137.1
502C	6	3	15	55.80	0		375.668	137.4
502C	6	3	20	55.85	0		243.134	127.3
502C	6	3	30	55.95	0		284.697	111.3
502C	6	3	40	56.05	0		124.678	98.7
502C	6	3	50	56.15	0		344.004	138.7
502C	6	3	60	56.25	0		212.547	130.9
502C	6	3	70	56.35	0		143.830	122.5
502C	6	3	80	56.45	0		160.411	113.4
502C	6	3	90	56.55	0		155.731	123.6
502C	6	3	100	56.65	0		139.742	114.5
502C	6	3	110	56.75	0		105.148	117.1
502C	6	3	120	56.85	0		104.176	136.6
502C	6	3	130	56.95	0		84.486	118.6
502C	6	3	140	57.05	0		264.001	107.6
502C	6	4	20	57.35	0		343.736	111.3
502C	6	4	30	57.45	0		234.345	58.2
502C	6	4	40	57.55	0		263.975	102.1
502C	6	4	50	57.65	0		248.248	109.7
502C	6	4	60	57.75	0		267.517	106.2
502C	6	4	70	57.85	0		314.927	106.0
502C	6	4	80	57.95	0		312.193	104.3
502C	6	4	90	58.05	0		223.764	88.1
502C	6	4	100	58.15	0		135.015	90.0
502C	6	4	110	58.25	0		207.431	58.6
502C	7	1	20	58.43	0	PHI=085 DEGREES	353.611	38.4
502C	7	1	30	58.53	0	UNORIENTED	662.947	176.3
502C	7	1	40	58.63	0		1623.444	268.4
502C	7	1	50	58.73	0		388.034	353.8
502C	7	1	60	58.83	0		225.151	24.5
502C	7	1	70	58.93	0		197.165	5.0
502C	7	1	80	59.03	0		174.687	350.9
502C	7	1	87	59.10	0		171.725	335.1
502C	8	1	45	63.25	0	PHI=118 DEGREES	298.727	26.7
502C	8	1	50	63.30	0	TOP 28 CM CUT OFF	1562.394	97.9
502C	8	1	60	63.40	0		374.455	120.4
502C	8	1	70	63.50	0		163.282	158.6
502C	8	1	80	63.60	0		237.817	148.0
502C	8	1	90	63.70	0		462.354	151.6
502C	8	1	100	63.80	0		310.661	155.4

*** GRID I 10 ***

*** GRID J 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	8	1	110	63.90	0		448.870	97.5
502C	8	1	120	64.00	0		403.082	148.4
502C	8	1	130	64.10	0		392.575	143.8
502C	8	1	140	64.20	0		425.787	139.2
502C	8	2	20	64.44	0		389.083	145.6
502C	8	2	30	64.54	0		275.917	128.3
502C	8	2	40	64.64	0		409.433	112.7
502C	8	2	50	64.74	0		346.579	137.0
502C	8	2	60	64.84	0		186.940	129.9
502C	8	2	70	64.94	0		209.508	122.6
502C	8	2	80	65.04	0		186.386	169.6
502C	8	2	90	65.14	0		207.994	152.2
502C	8	2	100	65.24	0		354.683	135.1
502C	8	2	110	65.34	0		300.714	130.2
502C	8	2	120	65.44	0		228.106	132.5
502C	8	2	130	65.54	0		258.225	135.2
502C	8	2	140	65.64	0		351.601	150.9
502C	8	3	20	65.94	0		358.813	130.1
502C	8	3	30	66.04	0		276.700	128.6
502C	8	3	40	66.14	0		279.687	129.0
502C	8	3	50	66.24	0		320.992	127.5
502C	8	3	60	66.34	0		324.333	129.5
502C	8	3	70	66.44	0		357.803	127.1
502C	8	3	80	66.54	0		282.989	122.0
502C	8	3	90	66.64	0	VOID 90-110 CM	170.091	110.3
502C	8	3	100	66.69	0		472.276	40.5
502C	8	3	110	66.69	0		216.598	112.8
502C	8	3	120	66.79	0		172.913	119.3
502C	8	3	130	66.89	0		186.294	133.4
502C	8	3	140	66.99	0		259.182	119.6
502C	9	1	20	67.40	0	PHI=021 DEGREES	138.304	109.1
502C	9	1	30	67.50	0		224.240	156.4
502C	9	1	40	67.60	0		320.899	149.9
502C	9	1	50	67.70	0		408.592	88.9
502C	9	1	60	67.80	0		307.194	153.2
502C	9	1	70	67.90	0		407.192	151.6
502C	9	1	80	68.00	0		318.591	135.1
502C	9	1	90	68.10	0		128.401	156.3
502C	9	1	100	68.20	0		165.796	150.2
502C	9	1	110	68.30	0		67.198	335.6
502C	9	1	120	68.40	0		41.281	184.5
502C	9	1	130	68.50	0		158.356	28.8
502C	9	1	140	68.60	0		84.254	51.3
502C	9	1	145	68.65	0		66.688	330.3
502C	9	2	20	68.90	0		102.363	117.3
502C	9	2	30	69.00	0		16.904	142.7
502C	9	2	40	69.10	0		10.645	269.0
502C	9	2	50	69.20	0		61.962	288.9
502C	9	2	60	69.30	0		30.215	279.0
502C	9	2	70	69.40	0		19.966	11.0
502C	9	2	80	69.50	0		15.768	230.3
502C	9	2	90	69.60	0		69.271	316.7
502C	9	2	100	69.70	0		23.047	89.8

*** GRID J 10 ***

*** GRID K 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	9	2	110	69.80	0		27.659	263.4
502C	9	2	120	69.90	0		45.869	310.1
502C	9	2	130	70.00	0		89.686	325.1
502C	9	2	140	70.10	0		507.111	286.0
502C	9	2	145	70.15	0		127.787	314.5
502C	9	3	5	70.25	1	REPEAT TOP OF SECTION	89.913	326.9
502C	9	3	10	70.30	1		53.520	339.7
502C	9	3	15	70.35	1		13.308	337.1
502C	9	3	20	70.40	0		11.043	196.3
502C	9	3	20	70.40	1		13.303	217.9
502C	9	3	25	70.45	1		81.976	18.7
502C	9	3	30	70.50	0		58.125	159.7
502C	9	3	30	70.50	1		53.698	168.5
502C	9	3	40	70.60	0		85.572	154.3
502C	9	3	50	70.70	0		106.832	129.9
502C	9	3	60	70.80	0		82.091	131.3
502C	9	3	70	70.90	0		79.502	138.8
502C	9	3	80	71.00	0		131.323	139.1
502C	9	3	90	71.10	0		235.740	147.2
502C	9	3	100	71.20	0		234.100	155.6
502C	9	3	110	71.30	0		214.720	147.8
502C	9	3	120	71.40	0		135.859	153.1
502C	9	3	128	71.48	0		107.326	86.2
502C	10	1	40	72.00	0	PHI=290 DEGREES	82.564	227.7
502C	10	1	50	72.10	0	TOP 20CM UNORIENTED	363.984	257.3
502C	10	1	60	72.20	0		561.438	294.8
502C	10	1	70	72.30	0		133.318	303.7
502C	10	1	80	72.40	0		424.468	341.2
502C	10	1	90	72.50	0		337.387	299.1
502C	10	1	100	72.60	0		282.259	296.5
502C	10	1	110	72.70	0		286.920	269.3
502C	10	1	120	72.80	0		216.075	284.6
502C	10	1	130	72.90	0		137.886	281.5
502C	10	1	140	73.00	0		128.331	277.4
502C	10	1	145	73.05	0		148.939	278.2
502C	10	2	20	73.28	0		123.804	277.4
502C	10	2	30	73.38	0		65.722	270.0
502C	10	2	40	73.48	0		80.156	292.5
502C	10	2	50	73.58	0		26.084	295.5
502C	10	2	50	73.58	1	REPEAT	18.584	286.2
502C	10	2	55	73.63	1		569.273	111.6
502C	10	2	60	73.68	0		506.128	272.1
502C	10	2	60	73.68	1		522.708	271.9
502C	10	2	65	73.73	1		31.379	255.0
502C	10	2	70	73.78	0		28.749	23.6
502C	10	2	70	73.78	1		27.545	9.7
502C	10	2	75	73.83	1		79.550	3.3
502C	10	2	80	73.88	0		78.603	5.5
502C	10	2	80	73.88	1		79.815	1.9
502C	10	2	85	73.93	1		32.193	341.7
502C	10	2	90	73.98	0		17.852	18.3
502C	10	2	90	73.98	1		16.770	14.9
502C	10	2	95	74.03	1		31.302	98.3

*** GRID K 10 ***

*** GRID L 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	10	2	100	74.08	0		135.642	157.3
502C	10	2	100	74.08	1		131.605	157.8
502C	10	2	105	74.13	1		110.661	109.2
502C	10	2	110	74.18	0		175.332	103.9
502C	10	2	110	74.18	1		176.427	104.7
502C	10	2	120	74.28	0		142.111	101.9
502C	10	2	130	74.38	0		96.422	102.5
502C	10	2	140	74.48	0		83.164	101.7
502C	10	2	145	74.53	0		127.645	102.9
502C	10	3	20	74.79	0		102.518	101.4
502C	10	3	30	74.89	0		54.213	65.8
502C	10	3	40	74.99	0		491.001	140.5
502C	10	3	50	75.09	0		59.078	93.6
502C	10	3	60	75.19	0		59.515	86.5
502C	10	3	70	75.29	0		101.847	81.6
502C	10	3	80	75.39	0		57.300	86.3
502C	10	3	90	75.49	0		104.174	89.1
502C	10	3	100	75.59	0		120.028	162.9
502C	10	3	110	75.69	0		225.396	98.2
502C	10	3	120	75.79	0		299.752	93.8
502C	10	3	130	75.89	0		272.322	92.9
502C	10	3	140	75.99	0		319.149	96.8
502C	10	3	145	76.04	0		273.608	93.5
502C	11	1	20	76.20	0	PHI=165 DEGREES	121.456	290.9
502C	11	1	30	76.30	0		188.307	185.6
502C	11	1	40	76.40	0		32.247	140.7
502C	11	1	50	76.50	0		145.495	262.8
502C	11	1	60	76.60	0		168.317	66.3
502C	11	1	70	76.70	0		180.869	194.6
502C	11	1	80	76.80	0		187.559	252.3
502C	11	1	90	76.90	0		221.692	167.0
502C	11	1	100	77.00	0		287.863	177.1
502C	11	1	110	77.10	0		352.571	165.8
502C	11	1	120	77.20	0		293.352	167.5
502C	11	1	130	77.30	0		342.836	164.6
502C	11	1	140	77.40	0		249.897	172.5
502C	11	2	20	77.67	0		132.454	155.0
502C	11	2	30	77.77	0		33.068	153.1
502C	11	2	40	77.87	0		141.099	158.7
502C	11	2	50	77.97	0		182.861	156.7
502C	11	2	60	78.07	0		250.262	163.3
502C	11	2	70	78.17	0		346.120	156.9
502C	11	2	80	78.27	0		353.140	151.7
502C	11	2	90	78.37	0		352.880	145.4
502C	11	2	100	78.47	0		343.547	153.5
502C	11	2	110	78.57	0		390.566	155.7
502C	11	2	130	78.77	0		335.621	153.1
502C	11	2	140	78.87	0		220.029	158.0
502C	11	3	20	79.17	0		325.895	158.4
502C	11	3	30	79.27	0		281.884	155.1
502C	11	3	40	79.37	0		356.464	152.4
502C	11	3	50	79.47	0		284.192	159.1
502C	11	3	60	79.57	0		252.231	160.2

*** GRID L 10 ***

*** GRID M 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	11	3	70	79.67	0		278.385	155.5
502C	11	3	80	79.77	0		310.142	158.3
502C	11	3	90	79.87	0		259.696	159.5
502C	11	3	100	79.97	0		349.280	159.5
502C	11	3	110	80.07	0		424.673	158.3
502C	11	3	120	80.17	0		376.579	159.3
502C	12	1	20	80.15	0	PHI=247 DEGREES	757.119	276.9
502C	12	1	30	80.25	0		957.819	291.0
502C	12	1	40	80.35	0	ASH?	24336.60	292.6
502C	12	1	50	80.45	0		5627.150	295.2
502C	12	1	60	80.55	0		682.943	294.0
502C	12	1	70	80.65	0		334.014	261.8
502C	12	1	80	80.75	0		451.318	278.7
502C	12	1	90	80.85	0		766.288	318.7
502C	12	1	100	80.95	0		240.938	252.9
502C	12	1	110	81.05	0		100.672	193.8
502C	12	1	120	81.15	0		377.550	231.7
502C	12	1	130	81.25	0		404.539	264.2
502C	12	1	140	81.35	0		295.560	212.8
502C	12	2	10	81.59	0		350.871	270.2
502C	12	2	20	81.69	0		419.306	272.8
502C	12	2	30	81.79	0		287.906	274.8
502C	12	2	40	81.89	0		310.271	255.7
502C	13	1	40	85.20	0	PHI=119 DEGREES	97.673	9.4
502C	13	1	50	85.30	0	20CM FROM TOP UNORIENTED	199.357	261.0
502C	13	1	60	85.40	0		3016.516	146.5
502C	13	1	70	85.50	0		176.329	152.4
502C	13	1	80	85.60	0		114.175	210.4
502C	13	1	90	85.70	0		68.389	170.5
502C	13	1	100	85.80	0		51.936	216.2
502C	13	1	110	85.90	0		364.477	253.1
502C	13	1	120	86.00	0		4.032	240.6
502C	13	1	130	86.10	0		55.398	188.5
502C	13	1	140	86.20	0		96.066	149.5
502C	13	2	20	86.48	0		106.066	170.8
502C	13	2	30	86.58	0		90.228	157.2
502C	13	2	40	86.68	0		73.995	244.8
502C	13	2	50	86.78	0		103.933	157.5
502C	13	2	60	86.88	0		110.910	146.1
502C	13	2	70	86.98	0		142.018	155.5
502C	13	2	80	87.08	0		138.538	150.5
502C	13	2	90	87.18	0		201.155	160.1
502C	13	2	100	87.28	0		180.593	156.2
502C	13	2	110	87.38	0		88.187	163.4
502C	13	2	120	87.48	0		2.936	61.0
502C	13	2	130	87.58	0		49.625	184.8
502C	13	2	140	87.68	0		18.564	301.0
502C	13	3	20	87.98	0		193.528	169.7
502C	13	3	30	88.08	0		121.161	173.8
502C	13	3	40	88.18	0		127.837	170.3
502C	13	3	50	88.28	0		109.566	172.1
502C	13	3	60	88.38	0		148.307	172.9
502C	13	3	70	88.48	0		191.069	167.2

*** GRID M 10 ***

*** GRID N 10 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	13	3	80	88.58	0		127.581	169.4
502C	13	3	90	88.68	0		106.685	173.2
502C	13	3	100	88.78	0		188.856	164.3
502C	13	3	110	88.88	0		107.764	176.7
502C	13	3	120	88.98	0		222.008	170.9
502C	13	3	130	89.08	0		190.053	175.2
502C	13	3	140	89.18	0		199.959	167.6
502C	14	1	20	89.40	0	PHI=285 DEGREES	464.751	139.4
502C	14	1	30	89.50	0		25541.05	121.2
502C	14	1	40	89.60	0		246.404	302.2
502C	14	1	50	89.70	0		388.692	175.8
502C	14	1	60	89.80	0		361.449	87.9
502C	14	1	70	89.90	0		342.075	131.6
502C	14	1	80	90.00	0		82.528	155.6
502C	14	1	90	90.10	0		206.178	162.3
502C	14	1	100	90.20	0		241.865	176.5
502C	14	1	110	90.30	0		249.799	178.6
502C	14	1	120	90.40	0		185.522	205.0
502C	14	1	130	90.50	0		221.188	175.5
502C	14	1	140	90.60	0		213.196	169.9
502C	14	2	20	90.87	0		106.532	150.9
502C	14	2	30	90.97	0		99.600	183.0
502C	14	2	40	91.07	0		93.955	173.0
502C	14	2	50	91.17	0		165.757	177.2
502C	14	2	60	91.27	0		169.682	181.4
502C	14	2	70	91.37	0		169.161	175.1
502C	14	2	80	91.47	0		168.697	178.3
502C	14	2	90	91.57	0		227.673	170.7
502C	14	2	100	91.67	0		254.266	175.5
502C	14	2	110	91.77	0		308.032	170.0
502C	14	2	120	91.87	0		244.311	179.0
502C	14	2	130	91.97	0		128.102	182.2
502C	14	2	140	92.07	0		168.804	194.6
502C	14	3	20	92.37	0		225.830	212.6
502C	14	3	30	92.47	0		250.579	186.0
502C	14	3	40	92.57	0		159.714	190.1
502C	14	3	50	92.67	0		200.170	216.7
502C	14	3	60	92.77	0		288.210	191.9
502C	14	3	70	92.87	0		304.407	189.0
502C	14	3	80	92.97	0		360.034	190.7
502C	14	3	90	93.07	0		316.259	190.7
502C	14	3	100	93.17	0		194.879	190.3
502C	14	3	110	93.27	0		95.042	190.2
502C	14	3	120	93.37	0		34.869	192.5
502C	14	3	130	93.47	0		60.671	196.6
502C	14	3	140	93.57	0		144.661	193.3
502C	14	4	5	93.72	0		169.782	189.9
502C	14	4	10	93.77	0		173.476	122.3
502C	15	1	20	93.80	0	PHI=046 DEGREES	408.787	82.6
502C	15	1	30	93.90	0		245.994	154.6
502C	15	1	40	94.00	0		273.722	122.6
502C	15	1	50	94.10	0		183.179	85.2
502C	15	1	60	94.20	0		1228.278	80.2

*** GRID N 10 ***

*** GRID B 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	15	1	70	94.30	0		305.211	107.6
502C	15	1	80	94.40	0		329.059	110.1
502C	15	1	90	94.50	0		379.620	114.1
502C	15	1	100	94.60	0		210.145	115.0
502C	15	1	110	94.70	0		264.005	117.6
502C	15	1	120	94.80	0		320.575	114.6
502C	15	1	130	94.90	0		274.994	103.5
502C	15	1	140	95.00	0		262.194	92.6
502C	15	2	20	95.28	0		264.576	106.7
502C	15	2	30	95.38	0		230.191	114.0
502C	15	2	40	95.48	0		223.499	115.1
502C	15	2	50	95.58	0		303.263	112.3
502C	15	2	60	95.68	0		308.402	112.1
502C	15	2	70	95.78	0		272.620	110.0
502C	15	2	80	95.88	0		289.560	113.6
502C	15	2	90	95.98	0		339.320	108.2
502C	15	2	100	96.08	0		289.938	109.2
502C	15	2	110	96.18	0		275.655	108.7
502C	15	2	120	96.28	0		235.194	124.7
502C	15	2	130	96.38	0		183.341	104.4
502C	15	2	140	96.48	0		185.513	103.4
502C	15	3	20	96.78	0		102.915	111.1
502C	15	3	30	96.88	0		125.929	101.3
502C	15	3	40	96.98	0		264.301	113.9
502C	15	3	50	97.08	0		315.010	110.7
502C	15	3	60	97.18	0		559.774	156.4
502C	15	3	70	97.28	0		184.336	122.2
502C	15	3	80	97.38	0		153.845	111.4
502C	15	3	90	97.48	0		213.495	107.7
502C	15	3	100	97.58	0		220.515	112.2
502C	15	3	110	97.68	0		227.058	111.4
502C	15	3	120	97.78	0		215.838	112.7
502C	15	3	130	97.88	0		165.175	115.7
502C	15	3	140	97.98	0		178.799	111.4
502C	15	3	144	98.02	0		164.803	113.8
502C	16	1	20	98.20	0	PHI=089 DEGREES	78.200	75.9
502C	16	1	30	98.30	0		94.671	17.3
502C	16	1	40	98.40	0		50.601	16.9
502C	16	1	50	98.50	0		241.788	19.5
502C	16	1	60	98.60	0		243.279	18.5
502C	16	1	70	98.70	0		163.262	5.0
502C	16	1	80	98.80	0		243.996	20.2
502C	16	1	90	98.90	0		127.277	10.3
502C	16	1	100	99.00	0		12.070	176.9
502C	16	1	110	99.10	0		168.207	348.6
502C	16	1	120	99.20	0		351.856	312.2
502C	16	1	130	99.30	0		274.170	23.8
502C	16	1	140	99.40	0		372.330	5.5
502C	16	2	20	99.69	0		193.864	181.5
502C	16	2	20	99.69	1	REMEASURE	211.527	182.2
502C	16	2	30	99.79	0		104.361	35.0
502C	16	2	30	99.79	1		120.852	30.6
502C	16	2	40	99.89	0		227.349	37.2

*** GRID B 11 ***

*** GRID C 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	16	2	40	99.89	1		249.614	35.0
502C	16	2	50	99.99	0		362.262	37.0
502C	16	2	50	99.99	1		358.832	28.5
502C	16	2	60	100.09	0		220.469	30.8
502C	16	2	60	100.09	1		258.151	20.0
502C	16	2	70	100.19	0		252.482	25.4
502C	16	2	70	100.19	1		256.428	15.8
502C	16	2	80	100.29	0		213.194	27.4
502C	16	2	80	100.29	1		218.092	19.7
502C	16	2	90	100.39	0		196.399	39.1
502C	16	2	90	100.39	1		195.402	30.4
502C	16	2	100	100.49	0		209.428	31.8
502C	16	2	100	100.49	1		206.727	23.2
502C	16	2	110	100.59	0		273.742	30.8
502C	16	2	110	100.59	1		263.789	22.2
502C	16	2	120	100.69	0		214.735	24.2
502C	16	2	120	100.69	1		214.996	15.3
502C	16	2	130	100.79	0		120.842	32.3
502C	16	2	130	100.79	1		124.467	23.5
502C	16	2	140	100.89	0		120.163	46.4
502C	16	2	140	100.89	1		122.545	37.8
502C	16	2	145	100.94	1		85.142	26.4
502C	16	3	20	101.19	0	MISALIGNED	111.851	136.9
502C	16	3	30	101.29	0		31.097	119.1
502C	16	3	40	101.39	0		182.210	192.2
502C	16	3	50	101.49	0		204.388	196.0
502C	16	3	60	101.59	0		149.656	198.1
502C	16	3	70	101.69	0		91.361	201.0
502C	16	3	80	101.79	0		81.028	174.4
502C	16	3	90	101.89	0		66.967	182.5
502C	16	3	100	101.99	0		127.298	192.2
502C	16	3	110	102.09	0		174.217	192.4
502C	16	3	120	102.19	0		227.810	196.7
502C	16	3	130	102.29	0		240.333	197.3
502C	16	3	140	102.39	0		188.188	205.0
502C	16	3	145	102.44	0		134.231	205.6
502C	17	1	20	102.30	0	PHI=252 DEGREES	12322.13	11.3
502C	17	1	30	102.40	0		5274.953	119.0
502C	17	1	40	102.50	0		779.978	158.7
502C	17	1	50	102.60	0		894.732	210.5
502C	17	1	60	102.70	0		3361.731	273.9
502C	17	1	70	102.80	0		1457.898	331.1
502C	17	1	80	102.90	0		463.241	270.0
502C	17	1	90	103.00	0		353.224	311.2
502C	17	1	100	103.10	0		348.388	307.0
502C	17	1	110	103.20	0		465.686	291.3
502C	17	1	120	103.30	0		23.333	82.5
502C	17	1	130	103.40	0		112.055	215.3
502C	17	1	140	103.50	0		497.596	321.4
502C	17	2	20	103.80	0		319.592	289.3
502C	17	2	30	103.90	0		290.824	287.1
502C	17	2	40	104.00	0		260.619	284.4
502C	17	2	50	104.10	0		198.651	287.1

*** GRID C 11 ***

*** GRID D 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	17	2	60	104.20	0		165.290	281.7
502C	17	2	70	104.30	0		125.093	287.2
502C	17	2	80	104.40	0		97.522	307.2
502C	17	2	90	104.50	0		56.032	292.4
502C	17	2	100	104.60	0		95.467	295.3
502C	17	2	110	104.70	0		105.408	270.9
502C	17	2	120	104.80	0		66.281	278.2
502C	17	2	130	104.90	0		8.375	240.5
502C	17	2	135	104.95	0		37.107	156.2
502C	17	2	140	105.00	0		15.907	144.1
502C	17	2	145	105.05	0		64.556	131.9
502C	17	3	20	105.30	0		222.315	120.7
502C	17	3	30	105.40	0		203.879	118.5
502C	17	3	40	105.50	0		344.456	106.0
502C	17	3	50	105.60	0		280.380	123.0
502C	17	3	60	105.70	0		153.276	116.8
502C	17	3	70	105.80	0		81.719	134.2
502C	17	3	80	105.90	0		60.173	135.9
502C	17	3	90	106.00	0		134.261	127.4
502C	17	3	100	106.10	0		240.427	135.4
502C	17	3	110	106.20	0		193.434	136.3
502C	17	3	120	106.30	0		317.879	150.4
502C	17	3	130	106.40	0		156.796	127.5
502C	17	3	135	106.45	0		115.872	67.4
502C	18	1	20	107.07	0	PHI=050 DEGREES	115.869	140.2
502C	18	1	30	107.17	0		51.657	315.9
502C	18	1	40	107.27	0		217.526	229.3
502C	18	1	50	107.37	0		164.197	246.0
502C	18	1	60	107.47	0		56.441	228.6
502C	18	1	70	107.57	0		104.798	254.3
502C	18	1	80	107.67	0		79.791	14.1
502C	18	1	90	107.77	0		146.873	239.0
502C	18	1	100	107.87	0		188.030	256.4
502C	18	1	110	107.97	0		220.243	240.6
502C	18	1	120	108.07	0		204.840	253.0
502C	18	1	130	108.17	0		264.596	235.4
502C	18	1	140	108.27	0		359.288	253.7
502C	18	2	20	108.43	0		187.719	246.4
502C	18	2	30	108.53	0		172.147	240.9
502C	18	2	40	108.63	0		203.692	237.3
502C	18	2	50	108.73	0		342.783	230.7
502C	18	2	60	108.83	0		413.026	224.7
502C	18	2	70	108.93	0		425.600	229.2
502C	18	2	80	109.03	0		286.695	232.9
502C	18	2	90	109.13	0		296.907	232.8
502C	18	2	100	109.23	0		180.844	242.7
502C	18	2	110	109.33	0		107.877	230.3
502C	18	2	120	109.43	0		61.328	230.8
502C	18	2	120	109.43	1	REPEAT, DOWN IN 5CM STEPS	67.872	229.3
502C	18	2	125	109.48	1		62.738	225.6
502C	18	2	130	109.53	0		66.994	47.7
502C	18	2	130	109.53	1		85.736	46.4
502C	18	2	135	109.58	1		180.291	50.2

*** GRID D 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	18	2	140	109.63	0		276.730	57.0
502C	18	2	140	109.63	1		277.584	56.7
502C	18	2	145	109.68	1		326.221	58.8
502C	18	3	15	109.88	0		352.407	47.6
502C	18	3	20	109.93	0		444.288	45.9
502C	18	3	30	110.03	0		200.592	44.7
502C	18	3	40	110.13	0		413.018	44.8
502C	18	3	50	110.23	0		459.573	45.0
502C	18	3	60	110.33	0		508.485	46.8
502C	18	3	70	110.43	0		468.265	45.6
502C	18	3	80	110.53	0		427.013	46.0
502C	19	1	20	111.40	0	PHI=221 DEGREES	257.676	292.9
502C	19	1	30	111.50	0		85.812	351.8
502C	19	1	40	111.60	0		321.439	345.2
502C	19	1	50	111.70	0		351.796	18.3
502C	19	1	60	111.80	0		561.953	347.2
502C	19	1	70	111.90	0		261.678	8.1
502C	19	1	80	112.00	0		436.593	353.8
502C	19	1	90	112.10	0		328.925	348.6
502C	19	1	100	112.20	0		302.463	345.4
502C	19	1	110	112.30	0		224.547	342.6
502C	19	1	120	112.40	0		225.833	336.1
502C	19	1	130	112.50	0		58.960	10.6
502C	19	1	140	112.60	0		69.523	144.7
502C	19	1	144	112.64	0		72.311	195.3
502C	19	2	10	112.80	0		326.414	185.7
502C	19	2	20	112.90	0		260.952	159.0
502C	19	2	30	113.00	0		299.030	193.5
502C	19	2	38	113.08	0		245.629	156.3
502C	20	1	20	115.80	0	PHI=100 DEGREES	1839.739	85.6
502C	20	1	30	115.90	0		111.429	167.4
502C	20	1	40	116.00	0		151.116	65.3
502C	20	1	50	116.10	0		199.638	117.5
502C	20	1	60	116.20	0		950.609	131.0
502C	20	1	70	116.30	0		556.734	136.2
502C	20	1	80	116.40	0		269.998	123.9
502C	20	1	90	116.50	0		811.892	166.2
502C	20	1	100	116.60	0		357.589	196.2
502C	20	1	110	116.70	0		371.158	114.1
502C	20	1	120	116.80	0		204.062	42.6
502C	20	1	130	116.90	0		384.819	150.3
502C	20	1	140	117.00	0		257.187	124.5
502C	20	2	20	117.30	0		201.755	196.1
502C	20	2	30	117.40	0		254.875	181.8
502C	20	2	40	117.50	0		185.906	150.4
502C	20	2	50	117.60	0		266.488	157.2
502C	20	2	60	117.70	0		113.314	119.3
502C	20	2	70	117.80	0		43.353	96.4
502C	20	2	80	117.90	0		36.600	231.9
502C	20	2	90	118.00	0		140.932	358.2
502C	20	2	100	118.10	0		305.186	345.7
502C	20	2	110	118.20	0		248.782	341.4
502C	20	2	120	118.30	0		619.576	357.8

*** GRID F 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	20	2	130	118.40	0		166.011	287.5
502C	20	2	140	118.50	0		243.628	346.8
502C	20	3	10	118.70	0		232.545	333.9
502C	20	3	20	118.80	0		318.173	339.6
502C	20	3	30	118.90	0		319.893	332.2
502C	20	3	40	119.00	0		339.977	333.4
502C	20	3	50	119.10	0		275.357	324.4
502C	20	3	57	119.17	0		123.587	297.0
502C	21	1	20	120.20	0	PHI=028 DEGREES	473.905	103.1
502C	21	1	30	120.30	0		474.216	130.2
502C	21	1	40	120.40	0		278.519	222.1
502C	21	1	50	120.50	0		203.677	226.2
502C	21	1	60	120.60	0		209.483	245.6
502C	21	1	70	120.70	0		114.904	312.8
502C	21	1	80	120.80	0		1204.795	20.9
502C	21	1	90	120.90	0		49.501	228.9
502C	21	1	100	121.00	0		255.076	160.4
502C	21	1	110	121.10	0		109.273	197.2
502C	21	1	120	121.20	0		7.343	13.2
502C	21	1	130	121.30	0		117.120	121.7
502C	21	1	140	121.40	0		79.724	237.8
502C	21	2	20	121.70	0		206.653	64.2
502C	21	2	30	121.80	0		212.428	42.0
502C	21	2	40	121.90	0		129.064	338.0
502C	21	2	50	122.00	0		207.238	31.1
502C	21	2	60	122.10	0		117.906	37.6
502C	21	2	70	122.20	0		250.103	2.5
502C	21	2	80	122.30	0		302.448	18.8
502C	21	2	90	122.40	0		588.788	348.5
502C	21	2	100	122.50	0		295.100	18.9
502C	21	2	110	122.60	0		210.055	19.6
502C	21	2	120	122.70	0		246.143	32.9
502C	21	2	130	122.80	0	VOID DOWN TO 150 CM	195.757	29.3
502C	21	3	40	122.91	0		160.028	340.9
502C	21	3	50	123.01	0		267.883	299.9
502C	21	3	55	123.06	0		66.690	124.9
502C	22	1	10	124.50	0	PHI=168 DEGREES	71.057	61.4
502C	22	1	20	124.60	0		502.352	47.8
502C	22	1	30	124.70	0		310.329	86.7
502C	22	1	40	124.80	0		416.919	82.5
502C	22	1	50	124.90	0		186.090	95.6
502C	22	1	60	125.00	0		247.467	94.3
502C	22	1	67	125.07	0		165.055	232.5
502C	23	1	20	125.60	0	PHI=168 DEGREES	382.621	336.9
502C	23	1	30	125.58	0		2105.875	178.6
502C	23	1	40	125.68	0		1693.482	62.4
502C	23	1	50	125.75	0		4873.781	149.6
502C	23	1	60	125.85	0		4322.736	256.3
502C	23	1	70	125.95	0		159.668	219.4
502C	23	1	80	126.05	0		114.088	234.2
502C	23	1	90	126.15	0		448.235	309.2
502C	23	1	100	126.25	0		169.645	348.1
502C	23	1	110	126.35	0		96.698	323.5

*** GRID F 11 ***

*** GRID G 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	23	1	120	126.45	0		384.671	43.1
502C	23	1	130	126.55	0		321.810	259.6
502C	23	1	140	126.65	0		204.896	316.5
502C	23	2	20	126.82	0		158.529	126.3
502C	23	2	30	126.92	0		110.168	109.2
502C	23	2	40	127.02	0		171.674	331.7
502C	23	2	50	127.12	0		385.396	352.5
502C	23	2	60	127.22	0		104.566	26.7
502C	23	2	70	127.32	0		205.274	344.7
502C	23	2	80	127.42	0		2.075	29.0
502C	23	2	90	127.52	0		327.531	342.4
502C	23	2	100	127.62	0		1335.722	356.0
502C	23	2	110	127.72	0		2881.830	348.8
502C	23	2	120	127.82	0		413.077	9.4
502C	23	2	130	127.92	0		426.854	4.1
502C	23	2	140	128.02	0		599.085	1.6
502C	23	3	20	128.32	0		383.251	358.9
502C	23	3	30	128.42	0		327.803	2.4
502C	23	3	40	128.52	0		293.337	4.9
502C	23	3	50	128.62	0		467.860	358.3
502C	23	3	60	128.72	0		523.368	359.2
502C	23	3	70	128.82	0		493.950	1.2
502C	23	3	80	128.92	0		404.711	1.3
502C	23	3	90	129.02	0		388.106	1.3
502C	23	3	100	129.12	0		414.204	359.9
502C	23	3	110	129.22	0		431.317	8.3
502C	23	3	120	129.32	0		376.810	9.0
502C	23	3	130	129.42	0		331.864	10.6
502C	23	3	140	129.52	0		215.546	356.0
502C	24	1	20	130.00	0	PHI=085 DEGREES	846.938	161.4
502C	24	1	30	130.10	0	LINER SPLIT	835.638	180.0
502C	24	1	40	130.20	0		520.727	205.0
502C	24	1	50	130.30	0		413.235	214.7
502C	24	1	60	130.40	0		361.066	199.8
502C	24	1	70	130.50	0		134.934	208.6
502C	24	1	80	130.60	0		170.554	188.1
502C	24	1	90	130.70	0		188.301	170.0
502C	24	1	100	130.80	0		317.169	181.4
502C	24	1	110	130.90	0		437.940	208.0
502C	24	1	120	131.00	0		276.875	184.8
502C	24	1	130	131.10	0		481.517	241.6
502C	24	1	140	131.20	0		546.685	210.7
502C	24	2	20	131.45	0	ALIGNMENT SCRATCH	470.570	228.2
502C	24	2	30	131.55	0		283.824	199.7
502C	24	2	40	131.65	0		303.158	194.8
502C	24	2	50	131.75	0		309.604	196.5
502C	24	2	60	131.85	0		163.964	200.3
502C	24	2	70	131.95	0		374.514	193.6
502C	24	2	80	132.05	0		359.972	191.8
502C	24	2	90	132.15	0		188.768	192.7
502C	24	2	100	132.25	0		102.216	176.4
502C	24	2	110	132.35	0		124.145	198.1
502C	24	2	120	132.45	0		108.090	221.8

*** GRID G 11 ***

*** GRID H 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	24	2	130	132.55	0		133.082	186.3
502C	24	2	140	132.65	0		51.529	183.1
502C	24	3	10	132.85	0	NOT ALIGNED EXACTLY	35.848	162.9
502C	24	3	20	132.95	0		52.671	197.1
502C	24	3	30	133.05	0		98.483	206.6
502C	24	3	33	133.08	0		397.123	270.3
502C	25	1	20	134.30	0	PHI=210 DEGREES	3223.026	172.9
502C	25	1	30	134.40	0		2137.385	220.4
502C	25	1	40	134.50	0		3341.197	340.6
502C	25	1	50	134.60	0		7071.871	347.2
502C	25	1	60	134.70	0		1874.137	40.8
502C	25	1	70	134.80	0		853.055	71.7
502C	25	1	80	134.90	0		3566.785	248.2
502C	25	1	90	135.00	0		401.268	66.8
502C	25	1	100	135.10	0		1127.594	19.7
502C	25	1	110	135.20	0		2720.152	142.9
502C	26	1	40	137.45	0	PHI=055 DEGREES	298.963	121.9
502C	26	1	50	137.55	0	TOP 33 CM DAMAGED	166.501	295.6
502C	26	1	60	137.65	0		223.922	119.8
502C	26	1	70	137.75	0		343.317	323.7
502C	26	1	80	137.85	0		330.363	27.9
502C	26	1	90	137.95	0		581.653	330.6
502C	26	1	100	138.05	0		383.127	108.7
502C	26	1	110	138.15	0		20.503	98.5
502C	26	1	120	138.25	0		11.645	165.8
502C	26	1	130	138.35	0		31.743	13.0
502C	26	1	140	138.45	0		13.347	33.8
502C	26	2	20	138.75	0		45.474	84.3
502C	26	2	30	138.85	0		5.027	304.2
502C	26	2	40	138.95	0		41.754	259.7
502C	26	2	50	139.05	0		25.073	299.7
502C	26	2	60	139.15	0		27.005	223.3
502C	26	2	70	139.25	0		20.739	32.4
502C	26	2	80	139.35	0		23.283	26.7
502C	26	2	90	139.45	0		19.917	222.4
502C	26	2	100	139.55	0		13.631	19.6
502C	26	2	110	139.65	0		5.384	182.1
502C	26	2	120	139.75	0		58.291	26.4
502C	26	2	130	139.85	0		30.344	108.7
502C	26	2	140	139.95	0		24.504	182.3
502C	26	3	10	140.15	0		7.928	251.8
502C	26	3	20	140.25	0		25.477	279.3
502C	26	3	25	140.30	0		73.211	124.0
502C	27	1	20	141.22	0	PHI=355 DEGREES	1776.797	27.9
502C	27	1	30	141.32	0		1067.867	268.9
502C	27	1	40	141.42	0		480.855	255.5
502C	27	1	50	141.52	0		373.388	177.0
502C	27	1	60	141.62	0		135.186	235.4
502C	27	1	70	141.72	0		150.297	86.3
502C	27	1	80	141.82	0		213.287	142.3
502C	27	1	90	141.92	0		80.165	273.1
502C	27	1	100	142.02	0		21.583	180.2
502C	27	1	110	142.12	0		136.033	112.3

*** GRID H 11 ***

*** GRID I 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	27	1	120	142.22	0		11.137	286.4
502C	27	1	130	142.32	0		41.329	274.4
502C	27	1	140	142.42	0		37.165	259.3
502C	27	2	10	141.95	0		22.295	65.5
502C	27	2	20	142.05	0		59.226	353.9
502C	27	2	30	142.15	0		41.119	65.1
502C	27	2	40	142.25	0		29.147	223.8
502C	27	2	50	142.35	0		13.032	224.1
502C	27	2	60	142.45	0		13.643	9.2
502C	27	2	70	142.55	0		37.094	159.4
502C	27	2	80	142.65	0		39.842	71.8
502C	27	2	90	142.75	0		17.354	28.7
502C	27	2	100	142.85	0		75.675	47.3
502C	27	2	110	142.95	0		15.610	228.5
502C	27	2	120	143.05	0		23.390	238.5
502C	27	2	130	143.15	0		31.905	72.4
502C	27	2	140	143.25	0		8.450	20.6
502C	28	1	30	210.50	0	PHI=285 DEGREES	210.299	138.7
502C	28	1	40	210.60	0		82.954	307.6
502C	28	1	50	210.70	0		18.594	299.8
502C	28	1	60	210.80	0		26.892	326.8
502C	28	1	70	210.90	0		335.531	93.2
502C	28	1	80	211.00	0		60.534	198.1
502C	28	1	90	211.10	0		155.196	110.1
502C	28	1	100	211.20	0		23.873	63.6
502C	28	1	110	211.30	0		50.262	180.3
502C	28	1	120	211.40	0		43.875	225.5
502C	28	1	130	211.50	0		60.402	166.2
502C	28	2	20	211.91	0		31.119	349.3
502C	28	2	30	212.01	0		2760.351	271.4
502C	28	2	40	212.11	0		1001.177	125.7
502C	28	2	50	212.21	0		507.523	288.6
502C	28	2	60	212.31	0		77.623	30.6
502C	28	2	70	212.41	0		1031.914	279.3
502C	28	2	80	212.51	0		850.456	150.8
502C	28	2	90	212.61	0		17.240	14.4
502C	28	2	100	212.71	0		1260.734	209.4
502C	28	2	110	212.81	0		191.078	225.1
502C	29	1	20	213.40	0	PHI=070 DEGREES	433.316	261.6
502C	29	1	30	213.50	0		84.383	242.8
502C	29	1	40	213.60	0		40.677	198.7
502C	29	1	50	213.70	0		7.236	302.2
502C	29	1	60	213.80	0		43.328	349.8
502C	29	1	70	213.90	0		16.033	247.4
502C	29	1	80	214.00	0		26.770	226.0
502C	29	1	90	214.10	0		17.009	239.9
502C	29	1	100	214.20	0		11.217	275.7
502C	29	1	110	214.30	0		20.985	296.7
502C	29	1	120	214.40	0		180.517	329.4
502C	29	1	130	214.50	0		8.925	259.5
502C	29	1	140	214.60	0		9.836	106.3
502C	29	2	10	214.80	0		11.195	242.7
502C	29	2	20	214.90	0		12.542	250.2

*** GRID I 11 ***

*** GRID J 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	29	2	30	215.00	0		8.077	253.6
502C	29	2	40	215.10	0		4.868	201.3
502C	29	2	49	215.19	0		6.988	80.1
502C	30	1	30	215.00	0	PHI=012 DEGREES	297.208	251.8
502C	30	1	40	215.10	0	DISTURBED,UNORIENTED	1236.092	193.9
502C	30	1	50	215.20	0		534.626	24.2
502C	30	1	60	215.30	0		219.935	309.0
502C	30	1	70	215.40	0		43.451	240.5
502C	30	1	80	215.50	0		645.909	297.0
502C	30	1	90	215.60	0		92.154	200.6
502C	30	1	100	215.70	0		60.163	250.9
502C	30	1	110	215.80	0		496.735	159.9
502C	30	1	120	215.90	0		2985.756	131.2
502C	30	1	130	216.00	0		143.738	244.9
502C	30	1	140	216.10	0		183.278	61.1
502C	31	1	20	216.60	0	PHI=050 DEGREES	631.807	75.4
502C	31	1	30	216.70	0		3272.420	64.8
502C	31	1	40	216.80	0		4947.338	86.4
502C	31	1	50	216.90	0		172.683	315.5
502C	31	1	60	217.00	0		59.511	82.3
502C	31	1	70	217.10	0		63.547	250.5
502C	31	1	80	217.20	0		36.269	344.6
502C	31	1	90	217.30	0		18.657	26.2
502C	31	1	100	217.40	0		141.307	126.7
502C	31	1	110	217.50	0		49.541	80.8
502C	31	1	120	217.60	0		22.579	200.9
502C	31	1	130	217.70	0		16.628	156.8
502C	31	1	140	217.80	0		14.112	13.0
502C	31	2	20	218.00	0		3.927	264.7
502C	31	2	30	218.10	0		1.856	332.9
502C	31	2	40	218.20	0		2.773	76.0
502C	31	2	50	218.30	0		10.236	175.8
502C	31	2	60	218.40	0		18.602	133.2
502C	31	2	70	218.50	0		14.805	124.2
502C	31	2	80	218.60	0		10.070	55.0
502C	31	2	90	218.70	0		10.143	29.4
502C	32	1	20	219.30	0	PHI=156 DEGREES	4037.470	136.1
502C	32	1	30	219.40	0		737.399	144.3
502C	32	1	40	219.50	0		3.082	12.0
502C	32	1	50	219.60	0		159.097	220.8
502C	32	1	60	219.70	0		165.165	342.8
502C	32	1	70	219.80	0		274.554	345.4
502C	32	1	80	219.90	0		33.402	321.7
502C	32	1	90	220.00	0		190.798	187.3
502C	32	1	100	220.10	0		105.281	257.8
502C	32	1	110	220.20	0		251.456	301.6
502C	32	1	120	220.30	0		217.423	101.2
502C	32	1	130	220.40	0		11.608	343.9
502C	32	1	140	220.50	0		196.374	306.1
502C	32	2	10	220.70	0		138.185	20.7
502C	32	2	20	220.80	0		80.150	206.4
502C	32	2	30	220.90	0		7.463	74.0
502C	32	2	40	221.00	0		673.981	31.7

*** GRID J 11 ***

*** GRID K 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
502C	32	2	50	221.10	0		962.786	326.9
502C	33	1	20	221.90	0	PHI=320 DEGREES	311.432	328.3
502C	33	1	30	222.00	0		55.268	287.2
502C	33	1	40	222.10	0		74.014	26.3
502C	33	1	50	222.20	0		91.084	192.0
502C	33	1	60	222.30	0		51.051	42.5
502C	33	1	70	222.40	0		422.293	166.1
502C	33	1	80	222.50	0		21.512	94.2
502C	33	1	90	222.60	0		171.548	43.8
502C	33	1	100	222.70	0		216.219	210.4
502C	33	1	110	222.80	0		63.421	194.4
502C	33	1	120	222.90	0		32.069	346.1
502C	33	1	130	223.00	0		33.791	58.8
502C	33	1	140	223.10	0		34.493	229.4
502C	33	2	10	223.27	0		11.651	27.3
502C	33	2	20	223.37	0		13.261	139.2
502C	33	2	30	223.47	0		9.179	300.5
502C	33	2	40	223.57	0		117.099	188.2
502C	33	2	50	223.67	0		118.196	275.7
502C	33	2	60	223.77	0		30.199	162.4
502C	34	1	75	223.95	0	PHI=327 DEGREES	175.301	221.5
502C	34	1	90	224.10	0	CORE DAMAGED	84.591	175.2
502C	34	1	100	224.20	0		63.448	209.7
502C	34	1	110	224.30	0		82.405	177.4
502C	34	1	120	224.40	0		102.971	169.0
502C	34	1	130	224.50	0		10.396	109.2
502C	34	1	140	224.60	0		25.542	225.8
502C	34	2	10	224.80	0		15.247	89.7
502C	34	2	20	224.90	0		65.209	39.3
502C	34	2	30	225.00	0		43.151	10.3
502C	34	2	40	225.10	0		37.126	78.5
502C	34	2	52	225.22	0		84.649	1.4
502C	35	1	20	225.72	0	PHI=326 DEGREES	1271.575	250.3
502C	35	1	30	225.82	0		1434.292	166.8
502C	35	1	40	225.92	0		256.376	221.4
502C	35	1	50	226.02	0		118.081	317.3
502C	35	1	60	226.12	0		101.369	211.9
502C	35	1	70	226.22	0		220.248	5.2
502C	35	1	80	226.32	0		190.526	173.9
503A	1	1	20	0.20	0	PHI=320 DEGREES	1722.182	152.2
503A	1	1	30	0.30	0		192.764	320.1
503A	1	1	40	0.40	0		188.482	219.4
503A	1	1	50	0.50	0		181.999	207.6
503A	1	1	60	0.60	0		128.745	223.4
503A	1	1	70	0.70	0		100.204	234.9
503A	1	1	80	0.80	0		171.876	230.7
503A	1	1	90	0.90	0		291.889	222.6
503A	1	1	100	1.00	0		205.937	233.7
503A	1	1	110	1.10	0		258.765	228.9
503A	1	1	120	1.20	0		213.271	230.6
503A	1	1	130	1.30	0		219.494	233.8
503A	1	1	140	1.40	0		288.342	229.3
503A	2	1	20	2.00	0	PHI=320 DEGREES	486.631	133.6

*** GRID K 11 ***

*** GRID L 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	2	1	30	2.10	0		43.517	62.1
503A	2	1	40	2.20	0		443.436	115.0
503A	2	1	50	2.30	0		486.540	4.3
503A	2	1	60	2.40	0		644.809	181.5
503A	2	1	70	2.50	0		69.924	132.7
503A	2	1	80	2.60	0		148.566	16.8
503A	2	1	90	2.70	0		103.774	327.5
503A	2	1	100	2.80	0		52.425	359.0
503A	2	1	110	2.90	0		391.950	198.2
503A	2	1	120	3.00	0		145.830	320.3
503A	2	1	130	3.10	0		172.303	289.1
503A	2	1	140	3.20	0		207.887	336.9
503A	2	2	20	3.43	0		278.168	319.6
503A	2	2	30	3.53	0		313.119	319.8
503A	2	2	40	3.63	0		179.995	325.9
503A	2	2	50	3.73	0		172.436	326.1
503A	2	2	60	3.83	0		301.585	315.0
503A	2	2	70	3.93	0		251.892	323.1
503A	2	2	80	4.03	0		188.039	324.8
503A	2	2	90	4.13	0		190.701	339.4
503A	2	2	100	4.23	0		189.037	341.1
503A	2	2	110	4.33	0		208.491	334.3
503A	2	2	120	4.43	0		132.760	335.3
503A	2	2	130	4.53	0		109.703	324.9
503A	2	2	140	4.63	0		61.288	318.5
503A	2	3	20	4.81	0	VOID 60-90CM	46.806	278.6
503A	2	3	30	4.91	0		41.642	300.6
503A	2	3	40	5.01	0		144.394	30.4
503A	2	3	50	5.11	0		189.285	307.3
503A	2	3	60	5.21	0		165.104	281.8
503A	2	3	70	5.27	0		218.259	149.4
503A	2	3	80	5.30	0		35.491	332.6
503A	2	3	90	5.30	0		757.405	220.8
503A	2	3	98	5.33	0		725.738	307.8
503A	4	1	20	10.70	0	PHI=215 DEGREES	212.743	172.2
503A	4	1	30	10.80	0		79.270	88.9
503A	4	1	40	10.90	0		189.438	58.2
503A	4	1	50	11.00	0		60.719	62.7
503A	4	1	60	11.10	0		72.648	12.3
503A	4	1	70	11.20	0		300.902	92.3
503A	4	1	80	11.30	0		18.360	348.6
503A	4	1	90	11.30	0		11.898	102.2
503A	4	1	100	11.30	0		5.397	332.1
503A	4	1	110	11.30	0		7.766	26.1
503A	4	1	120	11.30	0		171.994	106.7
503A	4	1	130	11.30	0		41.380	53.7
503A	4	1	140	11.30	0		34.746	37.2
503A	4	2	10	11.30	0		21.149	293.9
503A	4	2	20	11.30	0		108.670	52.2
503A	4	2	30	11.34	0		99.844	80.8
503A	4	2	40	11.44	0		100.224	87.2
503A	4	2	50	11.54	0		25.744	40.1
503A	4	2	60	11.64	0		40.349	285.4

*** GRID L 11 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	4	2	70	11.74	0		152.077	261.7
503A	4	2	80	11.84	0		51.247	283.4
503A	4	2	90	11.94	0		24.847	88.8
503A	4	2	100	12.04	0		19.189	61.1
503A	4	2	110	12.14	0		14.631	120.3
503A	4	2	120	12.24	0		19.990	284.7
503A	4	2	130	12.34	0		28.922	258.2
503A	4	2	140	12.44	0		41.797	262.6
503A	4	3	5	12.29	0	VOID 70-80CM;DAMAGED	62.040	289.9
503A	4	3	10	12.34	0		101.742	286.1
503A	4	3	20	12.44	0		218.658	273.2
503A	4	3	30	12.54	0		97.305	271.8
503A	4	3	40	12.64	0		147.632	236.7
503A	4	3	50	12.74	0		166.367	301.8
503A	4	3	60	12.84	0		48.065	35.4
503A	4	3	70	12.94	0		81.759	231.3
503A	4	3	80	13.04	0		20.396	312.9
503A	4	3	90	13.14	0		14.709	99.1
503A	4	3	100	13.45	0		182.743	241.4
503A	4	3	110	13.45	0		419.976	354.5
503A	4	3	120	13.55	0		1000.635	87.8
503A	4	3	130	13.65	0		565.108	330.2
503A	4	3	140	13.75	0		67.110	155.1
503A	5	1	20	15.20	0	PHI=350 DEGREES	9854.042	24.4
503A	5	1	30	15.30	0	LINER CRACK LGTH OF CORE	641.539	154.6
503A	5	1	40	15.40	0		721.789	162.9
503A	5	1	50	15.50	0		558.293	138.5
503A	5	1	60	15.60	0		99.863	195.8
503A	5	1	70	15.70	0		656.645	223.1
503A	5	1	80	15.80	0		2786.259	65.8
503A	5	1	90	15.90	0		2160.988	172.6
503A	5	1	100	16.00	0		825.347	98.7
503A	5	1	110	16.10	0		139.866	172.2
503A	5	1	120	16.20	0		45.352	286.3
503A	5	1	130	16.30	0		155.145	179.0
503A	5	1	140	16.40	0		96.859	306.8
503A	5	2	10	16.61	0		172.184	212.9
503A	5	2	20	16.71	0		193.676	213.6
503A	5	2	30	16.81	0		43.176	163.2
503A	5	2	40	16.91	0		235.371	137.5
503A	5	2	50	17.01	0		91.625	201.7
503A	5	2	60	17.11	0		92.850	169.7
503A	5	2	70	17.21	0		204.842	146.1
503A	5	2	80	17.31	0		44.689	180.5
503A	5	2	90	17.41	0		125.970	192.2
503A	5	2	100	17.51	0		93.808	208.9
503A	5	2	110	17.61	0		133.574	189.9
503A	5	2	120	17.71	0		84.202	191.9
503A	5	2	130	17.81	0		44.088	210.4
503A	5	2	140	17.91	0		106.563	198.6
503A	5	3	5	18.06	0		112.291	210.7
503A	5	3	10	18.11	0		126.274	186.4
503A	5	3	20	18.21	0		123.888	184.8

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	5	3	30	18.31	0		134.764	182.9
503A	5	3	40	18.41	0		161.521	168.8
503A	5	3	50	18.51	0		129.401	173.7
503A	5	3	60	18.61	0		157.349	174.8
503A	5	3	70	18.71	0		405.527	134.1
503A	5	3	80	18.81	0	VOID BELOW	19.716	161.9
503A	7	1	20	24.00	0	PHI=279 DEGREES	8869.781	192.1
503A	7	1	30	24.10	0		4280.765	277.3
503A	7	1	40	24.20	0		1300.401	222.1
503A	7	1	50	24.30	0		449.643	274.4
503A	7	1	60	24.40	0		566.223	238.6
503A	7	1	70	24.45	0		244.459	347.6
503A	7	1	80	24.45	0		111.875	347.3
503A	7	1	90	24.45	0		405.739	126.8
503A	7	1	100	24.45	0		778.520	242.3
503A	7	1	110	24.45	0		17095.12	139.3
503A	7	1	120	24.55	0		8086.073	169.1
503A	7	1	130	24.65	0		523.673	101.6
503A	7	1	140	24.75	0		488.998	225.1
503A	7	2	5	25.02	0	VOID 25-33CM	190.520	143.5
503A	7	2	10	25.07	0		215.776	196.0
503A	7	2	20	25.17	0		407.521	168.7
503A	7	2	30	25.10	0		266.896	255.0
503A	7	2	40	25.15	0		354.198	37.7
503A	7	2	50	25.25	0		140.571	139.5
503A	7	2	60	25.35	0		130.295	160.0
503A	7	2	70	25.45	0		125.109	198.9
503A	7	2	80	25.55	0		86.281	69.4
503A	7	2	90	25.65	0		11.004	136.0
503A	7	2	100	25.75	0		83.163	133.9
503A	7	2	110	25.85	0		125.823	132.3
503A	7	2	120	25.95	0		143.777	79.2
503A	7	2	130	26.05	0		113.756	127.8
503A	7	2	140	26.15	0		127.172	148.9
503A	7	2	144	26.19	0		145.156	140.5
503A	7	3	5	26.42	0		136.842	133.5
503A	7	3	10	26.47	0		133.823	140.4
503A	7	3	20	26.57	0		89.627	121.9
503A	7	3	30	26.67	0		94.259	127.6
503A	7	3	40	26.77	0		74.588	143.2
503A	7	3	50	26.87	0		99.566	134.4
503A	7	3	60	26.97	0		98.715	135.3
503A	7	3	80	27.17	0		101.975	145.2
503A	7	3	90	27.27	0		72.265	146.2
503A	7	3	90	27.27	0		168.194	115.6
503A	7	3	100	27.37	0		138.937	144.2
503A	7	3	110	27.47	0		134.529	150.0
503A	7	3	120	27.57	0		154.999	144.8
503A	7	3	130	27.67	0		102.912	159.1
503A	7	3	134	27.71	0		44.298	154.8
503A	9	1	20	32.80	0	PHI=145 DEGREES	2598.574	232.4
503A	9	1	30	32.90	0		10719.58	273.8
503A	9	1	40	32.94	0		12107.64	83.6

*** GRID B 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	9	1	50	33.02	0		9455.185	223.8
503A	9	1	60	33.12	0		879.594	77.8
503A	9	1	70	33.22	0		220.727	275.7
503A	9	1	80	33.32	0		484.786	315.5
503A	9	1	90	33.42	0		149.346	269.2
503A	9	1	100	33.52	0		628.186	170.3
503A	9	1	110	33.62	0		194.432	252.8
503A	9	1	120	33.72	0		275.926	42.7
503A	9	1	130	33.82	0		125.481	329.5
503A	9	1	140	33.92	0		233.537	14.5
503A	9	2	20	34.25	0	VOID 93-104CM, 0-11CM	59.152	188.1
503A	9	2	30	34.25	0		99.110	307.1
503A	9	2	40	34.35	0		105.235	96.7
503A	9	2	50	34.45	0		86.523	311.9
503A	9	2	60	34.55	0		33.719	331.6
503A	9	2	70	34.65	0		93.104	135.4
503A	9	2	80	34.75	0		132.540	153.5
503A	9	2	90	34.85	0		88.951	119.5
503A	9	2	100	34.95	0		7.364	231.7
503A	9	2	110	34.97	0		43.687	112.9
503A	9	2	120	35.05	0		10.216	32.1
503A	9	2	130	35.15	0		59.284	313.3
503A	9	2	140	35.25	0		26.853	164.2
503A	9	2	145	35.30	0		45.208	267.1
503A	9	3	20	35.35	0	VOID 0-22CM	30.368	331.4
503A	9	3	30	35.45	0		52.066	356.0
503A	9	3	40	35.55	0		35.056	299.5
503A	9	3	50	35.65	0		20.870	288.1
503A	9	3	60	35.75	0		43.586	354.9
503A	9	3	70	35.85	0		87.083	3.6
503A	9	3	80	35.95	0		144.228	146.5
503A	10	1	20	37.20	0	DAMAGED, UNORIENTED	20003.57	228.3
503A	10	1	30	37.30	0		6659.190	208.3
503A	10	1	40	37.40	0		16618.54	11.3
503A	10	1	50	37.50	0		1041.711	287.3
503A	10	1	60	37.60	0		3172.600	145.0
503A	10	1	70	37.70	0		11934.31	38.1
503A	10	1	80	37.80	0		2461.161	108.1
503A	10	1	90	37.90	0		3574.426	348.9
503A	10	1	100	38.00	0		4105.035	129.3
503A	10	1	110	38.10	0		7959.836	256.5
503A	10	1	120	38.20	0		3099.116	354.1
503A	10	1	130	38.30	0		2781.314	149.6
503A	10	1	140	38.40	0		3669.362	273.5
503A	10	2	20	38.60	0		6067.329	262.7
503A	10	2	30	38.70	0		2742.428	135.6
503A	10	2	40	38.80	0		1738.465	37.7
503A	10	2	50	38.90	0		72.397	155.0
503A	10	2	60	39.00	0		247.182	322.8
503A	10	2	70	39.10	0		13.393	21.3
503A	10	2	80	39.20	0		4.938	20.1
503A	10	2	90	39.30	0		45.665	149.7
503A	10	2	100	39.40	0		61.767	153.0

*** GRID B 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	10	2	110	39.50	0		184.081	107.5
503A	10	2	120	39.60	0		70.329	238.1
503A	10	2	130	39.70	0		95.138	110.3
503A	10	2	140	39.80	0		106.572	215.8
503A	10	3	10	40.03	0		70.052	278.2
503A	10	3	20	40.13	0		8.431	291.4
503A	10	3	30	40.23	0		6.272	206.5
503A	10	3	40	40.33	0		108.383	294.4
503A	10	3	50	40.43	0		75.676	237.4
503A	10	3	60	40.53	0		116.250	266.3
503A	11	1	20	41.50	0	PHI=352 DEGREES	14307.51	89.6
503A	11	1	30	41.60	0		2333.256	280.5
503A	11	1	40	41.70	0		19782.99	341.2
503A	11	1	50	41.80	0		8201.835	109.7
503A	11	1	60	41.90	0		12954.88	24.4
503A	11	1	70	42.00	0		23320.44	323.0
503A	11	1	80	42.10	0		4808.819	342.9
503A	11	1	90	42.20	0		7059.550	333.9
503A	11	1	100	42.30	0		4762.285	151.3
503A	11	1	110	42.40	0		8301.025	286.9
503A	11	1	120	42.50	0		2735.138	87.8
503A	11	1	130	42.60	0		1008.313	346.9
503A	11	1	140	42.70	0		779.988	18.8
503A	11	2	20	43.03	0		4679.191	299.9
503A	11	2	30	43.13	0		304.262	97.0
503A	11	2	40	43.23	0		269.613	76.4
503A	11	2	50	43.33	0		159.553	90.5
503A	11	2	60	43.43	0		122.403	108.7
503A	11	2	70	43.53	0		183.423	86.8
503A	11	2	80	43.63	0		183.573	103.8
503A	11	2	90	43.73	0		136.179	49.4
503A	11	2	100	43.83	0		174.169	108.9
503A	11	2	110	43.93	0		106.084	78.2
503A	11	2	120	44.03	0		188.220	106.3
503A	11	2	130	44.13	0		161.644	99.7
503A	11	2	140	44.23	0		156.118	98.3
503A	11	3	5	44.38	0		199.484	108.8
503A	11	3	10	44.43	0		174.693	102.9
503A	11	3	20	44.53	0		35.730	155.1
503A	11	3	30	44.63	0		48.794	99.5
503A	11	3	40	44.73	0		64.032	79.8
503A	11	3	50	44.83	0		83.703	132.2
503A	11	3	60	44.93	0		48.461	135.3
503A	11	3	70	45.03	0		59.560	124.2
503A	11	3	80	45.13	0		84.729	140.4
503A	11	3	90	45.23	0		157.514	54.6
503A	11	3	100	45.33	0		575.255	157.3
503A	11	3	110	45.43	0		135.783	179.7
503A	12	1	20	46.00	0	PHI=286 DEGREES	1213.597	178.2
503A	12	1	30	46.10	0	LINER SPLIT	82.537	191.8
503A	12	1	40	46.14	0		3373.190	359.1
503A	12	1	50	46.19	0		259.895	153.3
503A	12	1	60	46.29	0		128.948	309.8

*** GRID D 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	12	1	70	46.39	0		15.195	127.4
503A	12	1	80	46.49	0		95.450	132.2
503A	12	1	90	46.59	0		331.880	139.9
503A	12	1	100	46.69	0		97.021	126.3
503A	12	1	110	46.79	0		121.031	119.9
503A	12	1	120	46.89	0		129.878	147.5
503A	12	1	130	46.99	0		149.010	93.4
503A	12	1	140	47.09	0		65.726	174.4
503A	12	2	5	47.25	0		10.237	161.5
503A	12	2	10	47.30	0		37.559	158.2
503A	12	2	20	47.40	0		178.104	65.1
503A	12	2	30	47.50	0		182.678	98.7
503A	12	2	40	47.60	0		76.551	126.1
503A	12	2	50	47.70	0		99.918	128.6
503A	12	2	60	47.80	0		44.426	43.9
503A	12	2	70	47.90	0		65.177	202.5
503A	12	2	80	48.00	0		53.826	235.3
503A	12	2	90	48.10	0		64.278	295.8
503A	12	2	100	48.20	0		94.231	297.6
503A	12	2	110	48.30	0		135.165	290.5
503A	12	2	120	48.40	0		118.713	321.3
503A	12	2	130	48.50	0		164.551	286.8
503A	12	2	140	48.60	0		128.237	288.1
503A	12	2	144	48.64	0		124.631	294.6
503A	12	3	5	48.75	0		39.787	284.2
503A	12	3	5	48.75	0		38.301	285.6
503A	12	3	10	48.80	0		59.086	351.6
503A	12	3	20	48.90	0		36.236	292.3
503A	12	3	30	49.00	0		44.095	305.4
503A	12	3	40	49.10	0		79.768	345.6
503A	12	3	50	49.20	0		185.791	302.0
503A	12	3	60	49.30	0		200.254	220.4
503A	12	3	70	49.40	0		14.019	334.8
503A	12	3	80	49.50	0		79.669	276.3
503A	13	1	20	50.40	0	PHI=198 DEGREES	351.475	148.1
503A	13	1	30	50.50	0		97.237	351.5
503A	13	1	40	50.60	0		61.852	114.7
503A	13	1	50	50.70	0		170.227	355.0
503A	13	1	60	50.80	0		3450.664	32.0
503A	13	1	70	50.90	0		71.043	134.9
503A	13	1	80	51.00	0		405.926	32.0
503A	13	1	90	51.10	0		250.336	34.6
503A	13	1	100	51.20	0		1630.547	264.4
503A	13	1	110	51.30	0		102.724	328.2
503A	13	1	120	51.40	0		118.992	318.2
503A	13	1	130	51.50	0		121.158	281.4
503A	13	1	140	51.60	0		101.714	299.5
503A	13	2	10	51.70	0		114.255	319.1
503A	13	2	20	51.80	0		111.253	316.8
503A	13	2	30	51.90	0		63.831	330.1
503A	13	2	40	52.00	0		71.007	294.7
503A	13	2	50	52.10	0		105.212	315.9
503A	13	2	60	52.20	0		89.028	322.7

*** GRID D 12 ***

*** GRID E 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	13	2	70	52.30	0		176.502	315.3
503A	13	2	80	52.40	0		182.447	324.5
503A	13	2	90	52.50	0		166.537	321.7
503A	13	2	100	52.60	0		207.981	321.4
503A	13	2	110	52.70	0		124.051	307.9
503A	13	2	120	52.80	0		34.508	358.1
503A	13	2	130	52.90	0		44.388	327.8
503A	13	2	140	53.00	0		28.130	338.1
503A	13	3	10	53.20	0		81.144	317.8
503A	13	3	20	53.30	0		98.501	330.6
503A	13	3	30	53.40	0		79.315	317.8
503A	13	3	40	53.50	0		14.779	78.6
503A	13	3	50	53.60	0		19.788	282.5
503A	13	3	60	53.70	0		32.436	276.7
503A	13	3	70	53.80	0		150.100	309.3
503A	13	3	80	53.90	0		195.933	301.0
503A	13	3	90	54.00	0		196.753	302.1
503A	13	3	100	54.10	0		188.979	323.4
503A	13	3	110	54.20	0		134.963	319.5
503A	14	1	20	54.80	0	PHI=170 DEGREES	12825.96	269.7
503A	14	1	30	54.90	0	LINER BROKE, SECTION 1	19101.11	278.8
503A	14	1	40	55.00	0	UNORIENTED	6183.250	2.7
503A	14	1	50	55.10	0		2464.769	113.4
503A	14	1	60	55.20	0		24654.17	295.4
503A	14	1	70	55.30	0		19492.86	154.6
503A	14	1	80	55.40	0		16719.84	254.3
503A	14	1	90	55.50	0		8952.487	197.7
503A	14	1	100	55.60	0		6171.557	202.5
503A	14	1	110	55.70	0		12716.37	261.0
503A	14	1	120	55.80	0		3361.575	201.1
503A	14	1	130	55.90	0		1939.864	233.1
503A	14	1	140	56.00	0		7005.644	314.7
503A	14	2	5	55.35	0	ORIENTATION SHOULD BE OK	458.721	317.7
503A	14	2	10	55.40	0		1011.363	53.1
503A	14	2	20	55.50	0		4367.039	56.8
503A	14	2	30	55.60	0		6930.616	310.9
503A	14	2	40	55.70	0		109.203	340.7
503A	14	2	50	55.80	0		1998.093	344.9
503A	14	2	60	55.90	0		1199.947	285.9
503A	14	2	70	56.00	0		421.158	279.4
503A	14	2	80	56.10	0		275.815	41.6
503A	14	2	90	56.20	0		742.634	230.9
503A	14	2	100	56.30	0		1066.373	336.4
503A	14	2	110	56.40	0		687.163	106.6
503A	14	2	120	56.50	0		178.934	297.4
503A	14	2	130	56.60	0		270.287	210.4
503A	14	2	140	56.70	0		2355.055	267.7
503A	14	2	144	56.74	0		1349.013	102.7
503A	14	3	5	56.85	0		126.416	287.6
503A	14	3	10	56.90	0		146.012	269.9
503A	14	3	20	57.00	0		85.421	262.5
503A	14	3	30	57.10	0		8.663	29.8
503A	14	3	40	57.20	0		30.441	70.0

*** GRID E 12 ***

*** GRID F 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	14	3	50	57.30	0		53.248	58.8
503A	14	3	60	57.40	0		57.209	298.4
503A	14	3	70	57.50	0		28.899	249.9
503A	14	3	80	57.60	0		790.478	320.2
503A	15	1	80	59.80	0	PHI=155 DEGREES	31789.01	212.5
503A	15	1	90	59.90	0	TOP DAMAGED	10505.50	189.5
503A	15	1	100	60.00	0		11594.53	212.4
503A	15	1	110	60.10	0		12769.08	326.9
503A	15	1	120	60.20	0		12383.56	323.1
503A	15	1	130	60.30	0		16454.86	21.3
503A	15	1	140	60.40	0		23611.24	280.8
503A	15	2	20	60.70	0		12846.38	60.0
503A	15	2	30	60.80	0		15758.64	65.6
503A	15	2	40	60.90	0		9971.701	89.4
503A	15	2	50	61.00	0		3509.877	1.4
503A	15	2	60	61.10	0		5671.510	162.7
503A	15	2	70	61.20	0		5898.356	8.9
503A	15	2	80	61.30	0		3530.985	320.1
503A	15	2	90	61.40	0		3293.393	99.8
503A	15	2	100	61.50	0		3441.739	253.8
503A	15	2	110	61.60	0		5027.806	171.8
503A	15	2	120	61.70	0		1192.379	65.9
503A	15	2	130	61.80	0		1498.035	28.0
503A	15	2	140	61.90	0		955.351	30.7
503A	15	3	10	62.10	0		253.849	185.0
503A	15	3	20	62.20	0		422.531	337.9
503A	15	3	30	62.30	0		55.844	50.4
503A	15	3	40	62.40	0		92.432	222.8
503A	15	3	50	62.50	0		86.210	303.0
503A	15	3	60	62.60	0		295.878	272.0
503A	15	3	70	62.70	0		347.922	252.0
503A	16	1	20	63.60	0	PHI=010 DEGREES	29785.50	153.7
503A	16	1	30	63.70	0		10105.81	180.9
503A	16	1	40	63.80	0		5336.915	86.7
503A	16	1	50	63.90	0		6495.070	183.3
503A	16	1	60	64.00	0		9709.843	96.9
503A	16	1	70	64.10	0		13244.84	32.9
503A	16	1	80	64.20	0		5864.438	200.6
503A	16	1	90	64.30	0		2273.904	90.2
503A	16	1	100	64.40	0		4708.333	8.9
503A	16	1	110	64.50	0		738.168	12.4
503A	16	1	120	64.60	0		72.174	200.1
503A	16	1	130	64.70	0		107.692	134.8
503A	16	1	140	64.80	0		90.909	297.2
503A	16	2	20	64.89	0		558.681	120.5
503A	16	2	30	64.89	0		493.520	174.4
503A	16	2	40	64.89	0		499.178	317.5
503A	16	2	50	64.94	0		304.261	54.1
503A	16	2	60	65.04	0		158.929	153.7
503A	16	2	70	65.14	0		55.788	193.9
503A	16	2	80	65.24	0		16.364	138.2
503A	16	2	90	65.34	0		28.525	144.1
503A	16	2	100	65.44	0		36.274	42.3

*** GRID F 12 ***

*** GRID G 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	16	2	110	65.54	0		10.138	70.4
503A	16	2	120	65.64	0		25.562	66.3
503A	16	2	130	65.74	0		38.278	51.1
503A	16	2	140	65.84	0		17.059	118.6
503A	16	3	5	65.96	0		102.661	198.0
503A	16	3	10	66.01	0		154.030	177.0
503A	16	3	20	66.11	0		141.107	188.7
503A	16	3	30	66.21	0		78.775	193.0
503A	17	1	20	68.00	0	PHI=000 DEGREES	11051.65	342.7
503A	17	1	30	68.10	0	SLUSHY TOP	2791.281	198.2
503A	17	1	40	68.20	0		9011.487	221.9
503A	17	1	50	68.30	0		8051.678	310.3
503A	17	1	60	68.40	0		11299.87	302.6
503A	17	1	70	68.50	0		7580.504	291.9
503A	17	1	80	68.60	0		7191.560	7.0
503A	17	1	90	68.70	0		13843.73	279.1
503A	17	1	100	68.80	0		6923.226	247.9
503A	17	1	110	68.90	0		13374.55	93.2
503A	17	1	120	69.00	0		10936.95	331.0
503A	17	1	130	69.10	0		4471.505	290.5
503A	17	1	140	69.20	0		8044.781	325.3
503A	17	2	5	69.00	0		2452.026	274.6
503A	17	2	10	69.05	0		1021.629	35.1
503A	17	2	15	69.10	0		955.017	148.9
503A	19	1	20	76.80	0	PHI=250 DEGREES	1175.846	344.3
503A	19	1	30	76.90	0		365.989	140.1
503A	19	1	40	77.00	0		47.233	304.9
503A	19	1	50	77.10	0		129.342	139.9
503A	19	1	60	77.00	0		296.027	156.2
503A	19	1	70	77.10	0		618.011	186.3
503A	19	1	80	77.20	0		125.097	138.2
503A	19	1	90	77.30	0		319.936	114.4
503A	19	1	100	77.40	0		30.841	320.6
503A	19	1	110	77.50	0		227.191	358.2
503A	19	1	120	77.60	0		276.681	14.5
503A	19	1	130	77.70	0		575.715	326.0
503A	19	1	140	77.80	0		161.170	178.2
503A	19	1	144	77.84	0		118.483	302.9
503A	19	2	20	77.97	0		295.771	324.2
503A	19	2	30	78.07	0		493.545	115.6
503A	19	2	40	78.17	0		128.164	163.3
503A	19	2	50	78.27	0		60.330	114.9
503A	19	2	60	78.37	0		240.620	255.7
503A	19	2	70	78.47	0		128.748	304.3
503A	19	2	80	78.57	0		108.904	267.2
503A	19	2	90	78.67	0		102.516	223.9
503A	19	2	100	78.77	0		234.236	265.3
503A	19	2	110	78.87	0		87.654	249.2
503A	19	2	120	78.97	0		88.283	183.6
503A	19	2	130	79.07	0		76.283	263.6
503A	19	2	140	79.17	0		88.892	238.4
503A	19	3	10	79.09	0		128.764	302.8
503A	19	3	20	79.19	0		56.639	193.0

*** GRID G 12 ***

*** GRID H 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	19	3	30	79.29	0		34.271	173.4
503A	19	3	40	79.39	0		77.052	267.7
503A	20	1	100	81.75	0	PHI=310 DEGREES	1564.196	195.8
503A	20	1	110	81.85	0	TOP DAMAGED	42.063	243.3
503A	20	1	120	81.95	0		354.263	266.3
503A	20	1	130	82.05	0		607.380	124.1
503A	20	1	140	82.15	0		154.100	35.8
503A	20	2	20	82.53	0		68.946	188.5
503A	20	2	30	82.63	0		496.740	103.5
503A	20	2	40	82.73	0		1912.790	9.8
503A	20	2	50	82.83	0		1321.544	350.4
503A	20	2	60	82.93	0		603.827	104.4
503A	20	2	70	83.03	0		1082.745	54.3
503A	20	2	80	83.13	0		1038.445	298.6
503A	20	2	90	83.23	0		293.930	338.6
503A	20	2	100	83.33	0		159.822	51.7
503A	20	2	110	83.43	0		108.269	74.0
503A	20	2	120	83.53	0		140.584	61.7
503A	20	2	130	83.63	0		189.490	343.8
503A	20	2	140	83.73	0		46.559	79.8
503A	20	3	20	84.04	0		44.579	346.7
503A	20	3	30	84.14	0		28.796	86.5
503A	20	3	40	84.24	0		19.677	129.3
503A	20	3	50	84.34	0		392.546	133.0
503A	20	3	60	84.44	0		44.723	21.3
503A	20	3	70	84.54	0		69.122	0.9
503A	20	3	80	84.64	0		78.416	116.5
503A	20	3	90	84.74	0		91.743	121.2
503A	20	3	100	84.84	0		148.854	189.0
503A	20	3	110	84.94	0		79.164	315.7
503A	20	3	120	85.04	0		54.222	136.8
503A	20	3	130	85.14	0		10.853	164.5
503A	20	3	140	85.24	0		71.852	14.2
503A	21	1	20	85.60	0	PHI=300 DEGREES	5810.999	256.4
503A	21	1	30	85.70	0		3605.316	323.0
503A	21	1	40	85.80	0		3229.932	155.5
503A	21	1	50	85.90	0		666.018	74.0
503A	21	1	60	86.00	0		1195.632	189.5
503A	21	1	70	86.10	0		4403.902	71.9
503A	21	1	80	86.20	0		887.367	91.8
503A	21	1	90	86.30	0		1490.890	111.2
503A	21	1	100	86.40	0		3489.547	340.8
503A	21	1	110	86.50	0		3029.044	243.0
503A	21	1	120	86.60	0		1428.299	88.2
503A	21	1	130	86.70	0		1759.231	275.3
503A	21	1	140	86.80	0		701.574	89.8
503A	21	2	20	87.10	0		359.362	330.0
503A	21	2	20	87.10	0		277.342	215.2
503A	21	2	30	87.20	0		596.289	90.0
503A	21	2	30	87.20	0		232.692	33.5
503A	21	2	40	87.30	0		746.060	265.4
503A	21	2	40	87.30	0		612.415	85.8
503A	21	2	50	87.40	0		838.566	195.1

*** GRID H 12 ***

*** GRID I 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	21	2	50	87.40	0		276.954	101.6
503A	21	2	60	87.50	0		398.337	260.8
503A	21	2	60	87.50	0		220.860	212.4
503A	21	2	70	87.60	0		819.548	79.0
503A	21	2	70	87.60	0		1277.287	318.1
503A	21	2	80	87.70	0		883.867	172.8
503A	21	2	80	87.70	0		1434.116	122.2
503A	21	2	90	87.80	0		153.208	36.6
503A	21	2	90	87.80	0		379.928	137.4
503A	21	2	100	87.90	0		531.810	352.6
503A	21	2	100	87.90	0		997.593	145.4
503A	21	2	110	88.00	0		1104.171	328.9
503A	21	2	110	88.00	0		1381.502	297.5
503A	21	2	120	88.10	0		166.329	336.6
503A	21	2	130	88.20	0		1717.768	143.2
503A	21	2	140	88.30	0		554.399	138.9
503A	23	1	20	94.40	0	PHI=250 DEGREES	480.790	93.5
503A	23	1	40	94.60	0		1744.913	98.6
503A	23	1	60	94.80	0		1558.220	311.3
503A	23	1	80	95.00	0		2078.136	40.3
503A	23	1	100	95.20	0		4057.419	331.6
503A	23	1	120	95.40	0		3004.499	205.6
503A	23	1	140	95.60	0		2141.289	348.3
503A	23	2	20	95.80	0		3191.987	255.7
503A	23	2	30	95.90	0		2071.140	132.3
503A	23	2	40	96.00	0		1849.571	82.7
503A	23	2	50	96.10	0		1184.254	33.6
503A	23	2	60	96.20	0		9384.885	27.8
503A	23	2	70	96.30	0		793.379	256.3
503A	23	2	80	96.40	0		1642.136	6.8
503A	23	2	90	96.50	0		950.071	98.9
503A	23	2	100	96.60	0		919.667	98.4
503A	23	2	110	96.70	0		150.053	120.9
503A	24	1	20	98.80	0	PHI=246 DEGREES	17542.03	18.2
503A	24	1	40	99.00	0		30194.07	356.5
503A	24	1	60	99.20	0		10163.94	124.7
503A	24	1	80	99.40	0		6961.026	348.2
503A	24	1	100	99.60	0		1433.545	4.2
503A	24	1	120	99.80	0		631.756	284.1
503A	24	1	140	100.00	0		601.806	65.0
503A	24	2	20	100.31	0		1276.762	131.4
503A	24	2	30	100.41	0		862.674	115.9
503A	24	2	40	100.51	0		191.559	100.6
503A	24	2	50	100.61	0		700.158	294.1
503A	24	2	60	100.71	0		756.272	34.6
503A	24	2	70	100.81	0		890.619	213.2
503A	24	2	80	100.91	0		305.701	265.2
503A	24	2	90	101.01	0		101.107	131.1
503A	24	2	100	101.11	0		109.671	99.1
503A	24	2	110	101.21	0		343.425	237.4
503A	24	2	120	101.31	0		74.944	166.4
503A	24	2	130	101.41	0		251.099	270.9
503A	24	2	140	101.51	0		142.899	39.4

*** GRID I 12 ***

*** GRID J 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	24	3	10	101.73	0		126.868	41.7
503A	24	3	20	101.83	0		220.056	205.4
503A	24	3	30	101.93	0		159.088	302.9
503A	24	3	40	102.03	0		251.369	344.5
503A	24	3	50	102.13	0		113.545	42.3
503A	24	3	60	102.23	0		155.640	352.9
503A	24	3	70	102.33	0		660.765	313.1
503A	24	3	80	102.43	0		545.730	11.7
503A	29	1	20	120.80	0	PHI=009 DEGREES	8952.532	299.5
503A	29	1	30	120.90	0		1974.623	314.6
503A	29	1	40	121.00	0		663.198	87.2
503A	29	1	50	121.10	0		1163.225	141.3
503A	29	1	60	121.20	0		494.512	292.5
503A	29	1	70	121.30	0		1251.220	329.9
503A	29	1	80	121.40	0		639.556	201.5
503A	29	1	90	121.50	0		1866.428	202.1
503A	29	1	100	121.60	0		49.397	348.8
503A	29	1	110	121.70	0		89.579	289.6
503A	29	1	120	121.80	0		23.603	281.6
503A	29	1	130	121.90	0		20.502	176.0
503A	29	1	140	122.00	0		6.824	144.9
503A	29	2	20	122.30	0		40.767	275.5
503A	29	2	30	122.40	0		76.847	265.5
503A	29	2	40	122.50	0		98.926	256.9
503A	29	2	50	122.60	0		96.657	266.1
503A	29	2	60	122.70	0		84.150	312.0
503A	29	2	70	122.80	0		141.742	261.0
503A	29	2	80	122.90	0		72.473	287.0
503A	29	2	90	123.00	0		135.459	299.5
503A	29	2	100	123.10	0		93.206	270.0
503A	29	2	110	123.20	0		102.572	283.0
503A	29	2	120	123.30	0		114.794	272.1
503A	29	2	130	123.40	0		97.054	273.3
503A	29	2	140	123.50	0		70.750	278.0
503A	29	3	10	123.71	0		132.639	260.0
503A	29	3	20	123.81	0		112.577	269.5
503A	29	3	30	123.91	0		106.728	267.1
503A	29	3	40	124.01	0		156.305	271.5
503A	29	3	50	124.11	0		218.920	253.8
503A	29	3	60	124.21	0		110.368	275.1
503A	29	3	70	124.31	0		116.426	272.3
503A	29	3	80	124.41	0		87.166	262.0
503A	29	3	90	124.51	0		45.691	292.6
503A	29	3	95	124.56	0		89.387	306.4
503A	30	1	20	125.13	0	PHI=190 DEGREES	3515.883	218.4
503A	30	1	30	125.22	0		3419.325	13.9
503A	30	1	40	125.32	0		3754.504	20.4
503A	30	1	50	125.42	0		5057.564	48.8
503A	30	1	60	125.52	0		2034.276	347.2
503A	30	1	70	125.62	0		618.474	70.3
503A	30	1	80	125.72	0		4305.968	112.4
503A	30	1	90	125.82	0		820.231	188.3
503A	30	1	100	125.92	0		2610.284	46.0

*** GRID J 12 ***

*** GRID K 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	30	1	110	126.02	0		639.456	322.0
503A	30	1	120	126.12	0		1319.422	162.5
503A	30	1	130	126.22	0		1199.655	201.6
503A	30	1	140	126.32	0		2049.706	285.5
503A	30	2	20	126.53	0		259.630	112.0
503A	30	2	30	126.63	0		486.246	266.2
503A	30	2	40	126.73	0		766.063	189.7
503A	30	2	50	126.83	0		248.226	279.8
503A	30	2	60	126.93	0		439.825	169.1
503A	30	2	70	127.03	0		385.411	331.3
503A	30	2	80	127.13	0		614.039	113.4
503A	30	2	90	127.23	0		448.906	232.7
503A	30	2	100	127.33	0		954.742	62.7
503A	30	2	110	127.43	0		528.678	304.2
503A	30	2	120	127.53	0		326.354	243.5
503A	30	2	128	127.61	0		448.113	264.2
503A	31	1	20	129.60	0	PHI=250 DEGREES	4088.749	88.6
503A	31	1	50	129.90	0		8413.422	124.0
503A	31	1	60	130.00	0		4259.164	73.9
503A	31	1	70	130.10	0		6275.415	45.7
503A	31	1	80	130.20	0		328.281	192.5
503A	31	1	90	130.30	0		701.764	300.9
503A	31	1	100	130.40	0		160.139	32.9
503A	31	1	110	130.50	0		265.017	303.2
503A	31	1	120	130.60	0		66.773	333.4
503A	31	1	130	130.70	0		207.562	155.4
503A	31	1	140	130.80	0		51.080	90.3
503A	31	2	20	131.05	0		276.858	345.5
503A	31	2	30	131.15	0		239.439	206.3
503A	31	2	40	131.25	0		163.190	202.3
503A	31	2	50	131.35	0		180.435	274.1
503A	31	2	60	131.45	0		134.788	209.2
503A	31	2	70	131.55	0		169.991	235.8
503A	31	2	80	131.65	0		90.722	75.3
503A	31	2	90	131.75	0		215.883	201.1
503A	31	2	100	131.85	0		174.961	117.3
503A	31	2	110	131.95	0		70.928	67.0
503A	31	2	120	132.05	0		31.337	104.9
503A	31	2	130	132.15	0		108.385	8.9
503A	31	2	140	132.25	0		5.748	118.1
503A	31	3	20	132.55	0		46.029	4.3
503A	31	3	30	132.65	0		66.726	37.3
503A	31	3	40	132.75	0		166.088	177.5
503A	31	3	50	132.85	0		267.776	209.0
503A	31	3	60	132.95	0		85.175	36.5
503A	31	3	70	133.05	0		63.236	276.9
503A	31	3	80	133.15	0		51.017	307.6
503A	31	3	90	133.25	0		125.606	122.3
503A	31	3	100	133.35	0		80.529	269.0
503A	31	3	110	133.45	0		42.175	95.6
503A	31	3	120	133.55	0		99.139	74.5
503A	31	3	130	133.65	0		86.258	187.3
503A	33	1	60	138.75	0	PHI=290 DEGREES	9980.217	154.7

*** GRID K 12 ***

*** GRID L 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 e-6)	NRM Declination (deg.)
503A	33	1	70	138.85	0	TOP VOID	3376.652	226.4
503A	33	1	80	138.95	0		4645.869	295.4
503A	33	1	90	139.05	0		11368.28	66.9
503A	33	1	110	139.25	0		21797.85	322.3
503A	33	1	120	139.35	0		7023.085	339.8
503A	33	1	130	139.45	0		3565.213	234.8
503A	33	1	140	139.55	0		1469.605	105.9
503A	34	1	30	142.90	0	PHI=320 DEGREES	26669.12	278.8
503A	34	1	50	143.10	0		19121.88	219.7
503A	34	1	70	143.21	0		1462.066	52.8
503A	34	1	90	143.41	0		4140.653	177.5
503A	34	1	110	143.61	0		742.643	218.8
503A	34	1	130	143.81	0		433.911	193.0
503A	34	1	140	143.64	0		2749.980	282.3
503A	34	3	10	145.44	0		119.061	96.3
503A	34	3	20	145.54	0		252.006	98.6
503A	34	3	30	145.64	0		90.390	345.7
503A	34	3	40	145.74	0		246.718	68.2
503A	34	3	50	145.84	0		92.784	263.4
503A	34	3	59	145.93	0		338.906	99.1
503A	35	1	20	147.20	0	PHI=320 DEGREES	9886.366	61.8
503A	35	1	30	147.30	0		1809.270	232.0
503A	35	1	40	147.40	0		1704.154	205.9
503A	35	1	50	147.50	0		715.501	223.1
503A	35	1	60	147.60	0		1112.849	229.9
503A	35	1	70	147.70	0		578.667	78.9
503A	35	1	80	147.67	0		4474.508	128.2
503A	35	1	89	147.67	0		512.710	191.1
503A	36	1	20	151.60	0	PHI=110 DEGREES	6562.377	81.9
503A	36	1	30	151.70	0		1780.843	307.7
503A	36	1	40	151.80	0		2256.873	79.2
503A	36	1	50	151.90	0		372.362	169.9
503A	36	1	60	151.92	0		857.974	332.6
503A	36	1	70	152.02	0		2032.553	207.0
503A	36	1	80	152.12	0		1015.161	293.3
503A	36	1	90	152.22	0		980.328	55.5
503A	36	1	100	152.32	0		402.533	81.6
503A	36	1	110	152.42	0		261.822	23.2
503A	36	1	120	152.52	0		492.206	231.9
503A	36	1	130	152.62	0		431.143	114.4
503A	36	1	140	152.72	0		587.760	337.7
503A	36	2	20	153.03	0		1733.821	137.8
503A	36	2	30	153.13	0		336.343	181.4
503A	36	2	40	153.23	0		1581.783	170.0
503A	36	2	50	153.33	0		586.287	58.3
503A	36	2	60	153.43	0		1347.649	72.1
503A	36	2	70	153.53	0		21013.95	274.1
503A	36	2	80	153.63	0		1391.776	106.7
503A	36	2	90	153.73	0		1247.345	201.0
503A	36	2	100	153.83	0		992.195	24.2
503A	36	2	110	153.93	0		779.801	275.2
503A	36	2	120	154.03	0		1764.623	305.8
503A	36	2	129	154.12	0		976.035	88.5

*** GRID L 12 ***

*** GRID M 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	36	3	10	154.29	0		2216.853	305.6
503A	36	3	20	154.39	0		1273.858	196.4
503A	36	3	30	154.49	0		561.112	87.2
503A	37	1	40	156.11	0	PHI=070 DEGREES	8898.709	248.3
503A	37	1	60	156.31	0		5119.388	287.9
503A	37	1	70	156.41	0		8523.760	196.9
503A	37	1	80	156.51	0		1320.508	314.4
503A	37	1	80	156.51	0		1341.235	332.0
503A	37	1	90	156.61	0		2058.305	22.8
503A	37	1	100	156.71	0		3366.132	339.0
503A	37	1	100	156.71	0		3375.701	344.2
503A	37	1	110	156.81	0		3151.599	313.4
503A	37	1	120	156.91	0		2046.254	351.6
503A	37	1	120	156.91	0		1804.665	351.8
503A	37	1	130	157.01	0		736.953	136.6
503A	37	1	140	157.11	0		594.352	178.8
503A	37	2	20	157.44	0		641.364	234.5
503A	37	2	30	157.54	0		794.971	270.4
503A	37	2	40	157.64	0		1221.861	297.2
503A	37	2	50	157.74	0		305.251	85.2
503A	37	2	60	157.84	0		684.668	196.3
503A	37	2	70	157.94	0		470.313	191.9
503A	37	2	80	158.04	0		329.192	280.8
503A	37	2	90	158.14	0		196.096	243.8
503A	37	2	100	158.24	0		101.262	242.1
503A	37	2	110	158.34	0		290.196	218.1
503A	37	2	120	158.44	0		42.723	185.9
503A	37	2	130	158.54	0		2.629	228.1
503A	37	2	138	158.62	0		167.424	136.0
503A	39	1	20	164.80	0	PHI=310 DEGREES	10521.98	306.2
503A	39	1	20	164.80	0		146.400	69.8
503A	39	1	30	164.90	0		4129.009	73.9
503A	39	1	30	164.90	0		676.984	222.1
503A	39	1	40	165.00	0		685.193	134.9
503A	39	1	40	165.00	0		4553.354	205.8
503A	39	1	50	165.10	0		1353.716	73.4
503A	39	1	50	165.10	0		948.389	114.3
503A	39	1	60	165.20	0		327.072	18.3
503A	39	1	60	165.20	0		462.081	316.3
503A	39	1	70	165.30	0		949.833	348.5
503A	39	1	70	165.30	0		251.151	355.7
503A	39	1	80	165.40	0		133.466	293.6
503A	39	1	80	165.40	0		1182.063	232.6
503A	39	1	90	165.50	0		2038.762	268.8
503A	39	1	90	165.50	0		325.699	90.1
503A	39	1	100	165.60	0		254.586	243.1
503A	39	1	100	165.60	0		651.245	210.7
503A	39	1	110	165.70	0		232.310	44.8
503A	39	1	110	165.70	0		225.094	170.6
503A	39	1	120	165.80	0		432.681	312.0
503A	39	1	120	165.80	0		290.214	45.9
503A	39	1	130	165.90	0		16.358	241.6
503A	39	1	130	165.90	0		3497.865	64.4

*** GRID M 12 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	39	1	140	166.00	0		867.837	313.2
503A	39	1	140	166.00	0		146.721	200.7
503A	40	1	20	169.11	0	PHI=248 DEGREES	1305.141	162.7
503A	40	1	40	169.16	0		5763.414	284.3
503A	40	1	60	169.36	0		586.186	322.1
503A	40	1	80	169.56	0		2120.130	221.6
503A	40	1	100	169.76	0		4988.653	346.0
503A	40	1	114	169.90	0		2177.711	55.5
503A	41	1	20	173.60	0	PHI=003 DEGREES	1649.885	37.2
503A	41	1	40	173.80	0		1145.568	336.6
503A	41	1	60	174.00	0		3009.607	160.1
503A	41	1	80	174.20	0		2111.049	135.6
503A	41	1	100	174.40	0		27.340	92.9
503A	41	1	120	174.60	0		368.010	355.5
503A	41	1	140	174.80	0		475.597	41.6
503A	41	2	20	175.10	0		574.110	39.6
503A	41	2	30	175.20	0		3538.456	212.9
503A	41	2	40	175.30	0		1502.043	311.8
503A	41	2	50	175.40	0		64.103	333.5
503A	41	2	60	175.50	0		1679.585	218.9
503A	41	2	70	175.60	0		1078.591	196.0
503A	41	2	80	175.70	0		1373.642	243.8
503A	41	2	90	175.80	0		393.811	47.4
503A	41	2	100	175.90	0		172.546	248.9
503A	41	2	110	176.00	0		382.326	130.0
503A	41	2	120	176.10	0		618.044	201.6
503A	41	2	130	176.20	0		166.098	103.1
503A	41	2	140	176.30	0		412.034	98.6
503A	41	3	20	176.61	0		172.807	195.6
503A	41	3	30	176.71	0		132.187	242.7
503A	41	3	40	176.81	0		276.476	186.3
503A	41	3	50	176.91	0		227.465	211.0
503A	41	3	60	177.01	0		459.961	293.9
503A	41	3	70	177.11	0		311.782	212.7
503A	41	3	80	177.21	0		68.526	165.2
503A	41	3	90	177.31	0		532.618	282.1
503A	41	3	100	177.41	0		399.860	290.0
503A	41	3	110	177.51	0		298.874	11.3
503A	42	1	20	178.00	0	PHI=000 DEGREES	4530.370	292.8
503A	42	1	30	178.10	0		3733.099	132.0
503A	42	1	40	178.20	0		2413.225	20.9
503A	42	1	50	178.30	0		1256.666	141.3
503A	42	1	60	178.40	0		3445.010	26.1
503A	42	1	70	178.50	0		1719.357	113.5
503A	42	1	80	178.60	0		955.702	258.2
503A	42	1	90	178.70	0		8157.640	125.6
503A	42	1	100	178.80	0		1460.542	332.6
503A	42	1	110	178.90	0		1180.356	94.1
503A	42	1	120	179.00	0		698.968	115.7
503A	42	1	130	179.10	0		1443.796	156.7
503A	42	1	140	179.20	0		737.548	5.4
503A	42	2	20	179.51	0		348.256	19.7
503A	42	2	30	179.61	0		406.328	304.6

*** GRID B 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	42	2	40	179.71	0		305.945	281.6
503A	42	2	50	179.81	0		742.662	119.3
503A	42	2	60	179.91	0		300.452	336.8
503A	42	2	70	180.01	0		1304.441	74.3
503A	42	2	80	180.11	0		418.712	113.2
503A	42	2	90	180.21	0		1309.916	3.7
503A	42	2	100	180.31	0		3628.270	321.8
503A	42	2	110	180.41	0		627.668	74.1
503A	42	2	120	180.51	0		1250.909	87.2
503A	42	2	130	180.61	0		313.105	211.4
503A	42	2	140	180.71	0		601.197	222.0
503A	42	3	10	180.92	0		270.618	91.9
503A	42	3	20	181.02	0		398.209	334.2
503A	42	3	30	181.12	0		172.475	149.0
503A	42	3	40	181.22	0		341.073	118.9
503A	42	3	50	181.28	0		112.004	48.0
503A	42	3	60	181.38	0		781.863	254.6
503A	42	3	70	181.48	0		295.225	320.9
503A	43	1	20	182.40	0	PHI=060 DEGREES	4379.701	340.2
503A	43	1	30	182.50	0		3754.221	351.8
503A	43	1	40	182.60	0		1074.429	27.0
503A	43	1	50	182.70	0		529.951	27.4
503A	43	1	60	182.80	0		1726.680	246.6
503A	43	1	70	182.90	0		1270.883	308.0
503A	43	1	80	183.00	0		407.700	57.7
503A	43	1	90	183.10	0		638.242	359.9
503A	43	1	100	183.20	0		294.678	225.1
503A	43	1	110	183.30	0		1265.458	87.7
503A	43	1	120	183.40	0		4037.737	69.1
503A	43	1	130	183.50	0		210.489	85.6
503A	43	1	140	183.60	0		112.593	196.5
503A	43	2	20	183.85	0		118.825	299.1
503A	43	2	30	183.95	0		54.191	353.6
503A	43	2	40	184.05	0		87.703	1.8
503A	43	2	50	184.15	0		666.346	62.9
503A	43	2	60	184.25	0		204.142	193.9
503A	43	2	70	184.35	0		397.309	26.5
503A	43	2	80	184.45	0		25.063	175.8
503A	43	2	90	184.55	0		1099.375	23.2
503A	43	2	100	184.65	0		69.597	14.0
503A	43	2	110	184.75	0		550.589	290.3
503A	43	2	120	184.85	0		499.907	242.1
503A	43	2	130	184.95	0		181.367	263.2
503A	43	2	140	185.05	0		7.848	236.0
503A	43	3	10	185.26	0		91.642	262.5
503A	43	3	20	185.36	0		27.094	167.4
503A	43	3	30	185.46	0		9.976	338.9
503A	43	3	40	185.56	0		67.715	120.6
503A	44	1	20	186.80	0	PHI=095 DEGREES	8789.016	4.6
503A	44	1	40	187.00	0		521.839	106.7
503A	44	1	60	187.20	0		1224.239	42.2
503A	44	1	80	187.40	0		840.134	254.7
503A	44	1	100	187.60	0		407.969	266.6

*** GRID B 13 ***

*** GRID C 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	44	1	120	187.80	0		595.224	318.0
503A	44	1	140	188.00	0		1007.643	11.3
503A	44	2	20	188.31	0		668.125	244.7
503A	44	2	40	188.51	0		442.884	65.4
503A	44	2	60	188.71	0		618.119	359.3
503A	44	2	80	188.91	0		193.074	222.9
503A	44	2	100	189.11	0		534.122	230.7
503A	44	2	120	189.31	0		820.777	300.3
503A	44	2	140	189.51	0		393.120	64.6
503A	44	3	20	189.81	0		385.254	292.4
503A	44	3	20	189.81	0		527.216	359.9
503A	44	3	30	189.91	0		224.413	209.8
503A	44	3	40	190.01	0		275.279	190.3
503A	44	3	50	190.11	0		142.186	74.5
503A	44	3	60	190.21	0		1027.780	280.3
503A	44	3	78	190.39	0		818.180	293.3
503A	46	1	80	196.20	0	PHI=075	2586.048	309.6
503A	46	1	90	195.57	0	TOP 75CM VOID,FLAKES	16770.72	339.1
503A	46	1	100	195.67	0		5672.761	265.4
503A	46	1	110	195.77	0		8480.100	108.3
503A	46	1	120	195.87	0		4177.667	213.1
503A	46	1	130	195.97	0		4417.570	170.3
503A	46	1	140	196.07	0		3810.286	118.2
503A	47	1	50	200.02	0	PHI=035 DEGREES	14592.66	93.5
503A	47	1	60	200.12	0	VOID ABOVE	5209.686	259.3
503A	47	1	70	200.22	0		23009.37	334.9
503A	47	1	90	200.42	0		8146.326	173.1
503A	47	1	100	200.52	0		5486.441	103.3
503A	47	1	110	200.62	0		1345.585	248.9
503A	47	1	120	200.72	0		2033.845	121.4
503A	48	2	50	205.92	0	PHI=260 DEGREES	434.601	170.7
503A	48	2	60	206.02	0	LOADED WITH IRON	368.982	314.4
503A	48	2	70	206.12	0		396.720	278.3
503A	48	2	80	206.22	0		383.885	95.2
503A	48	2	90	206.32	0		191.089	316.6
503A	48	2	100	206.42	0		119.412	155.5
503A	48	2	110	206.52	0		110.804	204.7
503A	48	2	120	206.62	0		238.531	359.0
503A	48	2	130	206.72	0		206.885	86.0
503A	48	2	140	206.82	0		288.818	101.8
503A	48	3	10	207.00	0		24.675	103.9
503A	48	3	20	207.10	0		35.238	110.3
503A	48	3	30	207.20	0		74.688	201.4
503A	48	3	40	207.30	0		113.649	339.3
503A	48	3	50	207.40	0		99.116	310.9
503A	48	3	60	207.50	0		41.557	194.2
503A	48	3	70	207.60	0		23.200	310.9
503A	49	1	40	209.00	0	PHI=095 DEGREES	3783.307	309.0
503A	49	1	50	209.10	0	SOUP & VOID ABOVE	4234.023	89.0
503A	49	1	60	209.20	0		1365.598	138.6
503A	49	1	70	209.30	0		1244.941	354.7
503A	49	1	80	209.40	0		2065.106	328.1
503A	49	1	90	209.50	0		1204.181	78.7

*** GRID C 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	49	1	100	209.60	0		351.226	278.9
503A	49	1	110	209.70	0		2131.285	254.3
503A	49	1	120	209.80	0		182.956	196.4
503A	49	1	130	209.90	0		4441.503	43.2
503A	49	1	140	210.00	0		899.590	340.6
503A	49	2	10	210.16	0		1311.617	10.5
503A	49	2	20	210.26	0		877.439	138.6
503A	49	2	30	210.36	0		1421.104	100.5
503A	50	1	20	213.20	0	PHI=110 DEGREES	2323.808	68.5
503A	50	1	40	213.40	0	ABUNDANT SCALE	1235.560	50.9
503A	50	1	60	213.60	0		6144.994	321.7
503A	50	1	80	213.80	0		1523.947	121.1
503A	50	1	100	214.00	0		1336.346	218.9
503A	50	1	120	214.20	0		1183.937	154.9
503A	50	1	140	214.40	0		5123.550	82.5
503A	50	2	20	214.60	0	SCALE VISIBLE THRU LINER	1872.490	231.9
503A	50	2	40	214.80	0		1393.738	12.9
503A	50	2	60	215.00	0		3749.685	197.6
503A	50	2	80	215.20	0		1491.814	82.5
503A	50	2	100	215.40	0		6150.084	214.6
503A	50	2	120	215.60	0		81.714	145.4
503A	50	2	140	215.80	0		225.922	289.8
503A	50	3	20	216.10	0		245.611	301.3
503A	50	3	30	216.20	0		477.013	320.4
503A	50	3	40	216.30	0		127.955	354.8
503A	50	3	50	216.40	0		225.792	240.9
503A	50	3	60	216.50	0		99.752	122.1
503A	50	3	70	216.60	0		51.188	105.6
503A	50	3	80	216.70	0		124.383	5.1
503A	50	3	90	216.80	0		206.123	236.9
503A	50	3	100	216.90	0		147.438	322.6
503A	50	3	110	217.00	0		32.880	187.8
503A	50	3	120	217.10	0		257.190	304.9
503A	51	1	20	217.60	0	PHI=021 DEGREES	9775.054	88.5
503A	51	1	40	217.80	0		1673.593	17.0
503A	51	1	60	218.00	0		8895.449	19.2
503A	51	1	80	218.20	0		3602.521	94.1
503A	51	1	100	218.40	0		2831.604	210.9
503A	51	1	120	218.60	0		2189.471	123.5
503A	51	1	140	218.78	0		889.441	28.4
503A	51	2	20	218.98	0		213.745	196.5
503A	51	2	40	219.18	0		279.325	297.6
503A	51	2	60	219.38	0		1235.848	278.9
503A	51	2	80	219.58	0		223.342	4.1
503A	51	2	100	219.78	0		110.898	267.5
503A	51	2	120	219.98	0		206.050	227.5
503A	51	2	140	220.18	0		335.026	354.5
503A	51	3	5	220.33	0		46.340	80.8
503A	51	3	15	220.43	0		427.509	50.6
503A	51	3	20	220.48	0		191.042	159.4
503A	52	1	40	222.20	0	PHI=052 DEGREES	1033.405	65.5
503A	52	1	60	222.40	0		919.146	346.7
503A	52	1	80	222.60	0		772.568	188.0

*** GRID E 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	52	1	100	222.80	0		1352.904	33.4
503A	52	1	120	223.00	0		444.870	228.2
503A	52	1	140	223.20	0		214.747	123.3
503A	52	2	20	223.51	0		282.408	160.5
503A	52	2	40	223.71	0		1546.135	200.7
503A	52	2	60	223.91	0		966.882	56.6
503A	52	2	80	224.11	0		42.033	173.0
503A	52	2	100	224.31	0		106.061	182.9
503A	52	2	110	224.41	0		86.807	52.3
503A	52	2	120	224.51	0		287.818	345.3
503A	52	2	130	224.61	0		97.316	23.3
503A	52	2	140	224.71	0		144.060	288.7
503A	52	3	10	224.91	0		108.945	71.2
503A	52	3	20	225.01	0		200.963	304.7
503A	52	3	30	225.11	0		114.252	214.3
503A	52	3	40	225.21	0		32.015	152.5
503A	52	3	50	225.31	0		47.673	219.7
503A	52	3	60	225.41	0		72.094	261.6
503A	52	3	70	225.51	0		97.024	56.4
503A	53	1	20	226.40	0	PHI=310 DEGREES	2921.007	47.2
503A	53	1	40	226.60	0		4763.468	169.8
503A	53	1	60	226.80	0		1504.161	13.5
503A	53	1	80	227.00	0		1838.472	255.4
503A	53	1	100	227.20	0		1162.937	9.0
503A	53	1	120	227.40	0		618.983	5.6
503A	53	1	140	227.60	0		448.393	155.6
503A	53	2	20	227.91	0		114.325	258.6
503A	53	2	40	228.11	0		406.046	302.8
503A	53	2	60	228.31	0		970.981	137.2
503A	53	2	80	228.51	0		733.893	240.6
503A	53	2	100	228.66	0		619.835	264.9
503A	53	2	120	228.86	0		1901.566	262.9
503A	53	2	140	229.06	0		509.906	107.6
503A	53	3	10	229.30	0		442.910	159.6
503A	53	3	30	229.50	0		179.220	181.8
503A	53	3	50	229.70	0		869.845	239.2
503A	53	3	70	229.90	0		349.694	63.1
503A	54	1	20	230.80	0	PHI=035 DEGREES	1516.688	3.1
503A	54	1	40	231.00	0		1877.625	142.3
503A	54	1	60	231.20	0		282.723	55.4
503A	54	1	80	231.40	0		1712.173	108.8
503A	54	1	100	231.60	0		90.028	41.4
503A	54	1	120	231.80	0		65.380	37.1
503A	54	1	130	231.90	0		148.979	57.3
503A	54	1	140	232.00	0		174.255	270.2
503A	54	2	20	232.31	0		98.388	112.0
503A	54	2	30	232.41	0		237.089	53.8
503A	54	2	40	232.51	0		8.214	16.5
503A	54	2	50	232.61	0		230.926	326.5
503A	54	2	60	232.71	0		81.907	329.0
503A	54	2	70	232.81	0		30.091	139.8
503A	54	2	80	232.91	0		58.853	231.0
503A	54	2	90	233.01	0		65.475	211.4

*** GRID E 13 ***

*** GRID F 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503A	54	2	100	233.11	0		134.371	212.1
503A	54	2	110	233.21	0		37.025	282.1
503A	54	2	120	233.31	0		29.068	280.3
503A	54	2	130	233.41	0		173.308	213.4
503A	54	2	140	233.51	0		67.031	19.9
503A	54	2	145	233.56	0		49.695	278.1
503A	54	3	10	233.72	0		10.228	308.7
503A	54	3	20	233.82	0		212.812	65.9
503A	54	3	30	233.92	0		25.372	345.0
503A	54	3	40	234.02	0		88.147	254.8
503A	54	3	50	234.12	0		17.154	300.6
503A	54	3	60	234.22	0		118.825	24.5
503A	54	3	70	234.32	0		30.917	340.4
503A	54	3	80	234.42	0		211.563	60.1
503A	54	3	140	235.02	0		762.548	320.9
503B	1	1	20	0.20	0	PHI=143 DEGREES	319.180	112.0
503B	1	1	30	0.30	0		210.636	134.5
503B	1	1	40	0.40	0		304.641	121.9
503B	1	1	50	0.50	0		71.589	28.0
503B	1	1	60	0.60	0		199.249	113.0
503B	1	1	70	0.70	0		180.256	115.4
503B	1	1	80	0.80	0		186.382	116.7
503B	1	1	90	0.90	0		220.130	109.1
503B	1	1	100	1.00	0		262.364	115.8
503B	1	1	110	1.10	0		256.877	107.6
503B	1	1	120	1.20	0		239.658	99.6
503B	1	1	130	1.30	0		227.864	116.0
503B	1	1	140	1.40	0		486.892	128.6
503B	1	2	10	1.58	0		259.723	122.1
503B	1	2	20	1.68	0		484.188	115.5
503B	1	2	30	1.78	0		239.328	113.9
503B	1	2	40	1.88	0		227.692	114.0
503B	1	2	50	1.98	0		247.575	112.8
503B	1	2	60	2.08	0		279.260	110.5
503B	1	2	70	2.18	0		244.063	113.4
503B	1	2	80	2.28	0		239.560	114.7
503B	1	2	90	2.38	0		260.295	114.0
503B	1	2	100	2.48	0		240.110	108.8
503B	1	2	110	2.58	0		127.109	105.9
503B	2	1	20	2.98	0	PHI=020 DEGREES	589.899	174.8
503B	2	1	30	3.08	0		126.526	255.9
503B	2	1	40	3.18	0		314.484	222.1
503B	2	1	50	3.28	0		419.654	199.7
503B	2	1	60	3.38	0		165.494	214.8
503B	2	1	70	3.48	0		276.200	219.7
503B	2	1	80	3.58	0		264.513	221.8
503B	2	1	90	3.68	0		419.601	205.5
503B	2	1	100	3.78	0		303.181	214.6
503B	2	1	110	3.88	0		301.672	218.7
503B	2	1	120	3.98	0		314.113	219.9
503B	2	1	130	4.08	0		267.225	223.4
503B	2	1	140	4.18	0		231.120	211.6
503B	2	2	10	4.39	0		265.712	225.7

*** GRID F 13 ***

*** GRID G 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	2	2	20	4.49	0		284.338	224.5
503B	2	2	30	4.59	0		252.198	225.5
503B	2	2	40	4.69	0		225.697	223.7
503B	2	2	50	4.79	0		242.439	223.8
503B	2	2	60	4.89	0		251.237	224.2
503B	2	2	70	4.99	0		298.082	224.1
503B	2	2	80	5.09	0		254.811	221.7
503B	2	2	90	5.19	0		288.958	220.1
503B	2	2	100	5.29	0		309.492	220.3
503B	2	2	110	5.39	0		266.269	220.3
503B	2	2	120	5.49	0		248.736	220.8
503B	3	1	20	7.38	0	PHI=040 DEGREES	309.597	244.6
503B	3	1	30	7.48	0		1743.367	126.2
503B	3	1	40	7.58	0		368.276	197.4
503B	3	1	50	7.68	0		222.876	152.0
503B	3	1	60	7.78	0		248.988	275.3
503B	3	1	70	7.88	0		235.293	173.7
503B	3	1	80	7.98	0		2375.451	259.4
503B	3	1	90	8.08	0		385.298	167.2
503B	3	1	100	8.18	0		278.366	158.3
503B	3	1	110	8.28	0		255.963	167.3
503B	3	1	120	8.38	0		61.353	275.2
503B	3	1	130	8.48	0		78.746	246.5
503B	3	1	140	8.58	0		119.643	223.3
503B	3	2	10	8.78	0		269.225	152.7
503B	3	2	20	8.88	0		161.506	216.4
503B	3	2	30	8.98	0		170.422	253.0
503B	3	2	40	9.08	0		106.798	193.1
503B	3	2	50	9.18	0		124.233	178.4
503B	3	2	60	9.28	0		278.596	202.5
503B	3	2	70	9.38	0		22.264	276.9
503B	3	2	80	9.48	0		24.306	323.1
503B	3	2	90	9.58	0		117.857	272.0
503B	3	2	100	9.68	0		272.847	352.7
503B	3	2	110	9.78	0		12.540	287.4
503B	3	2	120	9.88	0		55.268	359.1
503B	3	2	130	9.98	0		62.647	7.5
503B	3	2	140	10.08	0		195.256	260.9
503B	3	3	5	10.23	0		52.228	298.9
503B	3	3	10	10.28	0		47.070	211.2
503B	3	3	20	10.38	0		83.968	164.5
503B	3	3	30	10.48	0		207.034	194.0
503B	3	3	40	10.58	0		83.350	185.8
503B	3	3	50	10.68	0		29.204	220.4
503B	3	3	60	10.78	0		35.136	0.3
503B	3	3	70	10.88	0		127.539	354.5
503B	3	3	80	10.98	0		165.872	356.3
503B	3	3	90	11.08	0		156.402	344.6
503B	3	3	100	11.18	0		87.096	4.7
503B	3	3	110	11.28	0		94.499	5.3
503B	3	3	117	11.35	0		72.814	3.2
503B	4	1	20	11.80	0	PHI=125 DEGREES	1551.963	319.9
503B	4	1	30	11.90	0		84.902	263.3

*** GRID G 13 ***

*** GRID H 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	4	1	40	12.00	0		132.960	31.6
503B	4	1	50	12.10	0		97.542	141.4
503B	4	1	60	12.20	0		48.561	217.3
503B	4	1	70	12.30	0		433.455	197.2
503B	4	1	80	12.40	0		47.303	168.4
503B	4	1	90	12.50	0		391.857	150.5
503B	4	1	100	12.60	0		339.672	218.2
503B	4	1	110	12.70	0		44.534	126.6
503B	4	1	120	12.80	0		90.938	118.9
503B	4	1	130	12.90	0		107.842	121.2
503B	4	1	140	13.00	0		95.205	107.9
503B	4	1	144	13.04	0		91.939	113.0
503B	4	2	10	13.08	0		135.362	128.1
503B	4	2	20	13.18	0		95.814	122.0
503B	4	2	30	13.28	0		59.364	111.1
503B	4	2	40	13.38	0		24.768	281.2
503B	4	2	50	13.48	0		79.443	290.4
503B	4	2	60	13.58	0		82.584	289.4
503B	4	2	70	13.68	0		86.433	301.6
503B	4	2	80	13.78	0		96.941	293.6
503B	4	2	90	13.88	0		95.936	297.2
503B	4	2	100	13.98	0		79.956	301.4
503B	4	2	110	14.08	0		26.478	306.7
503B	4	2	120	14.18	0		34.173	130.1
503B	4	2	130	14.28	0		8.758	83.1
503B	4	2	140	14.38	0		13.936	208.0
503B	4	2	145	14.43	0		5.214	206.8
503B	4	3	5	14.54	0		76.495	306.5
503B	4	3	10	14.59	0		105.291	309.5
503B	4	3	20	14.69	0		88.696	306.5
503B	4	3	30	14.79	0		76.903	335.9
503B	4	3	40	14.89	0		56.247	295.7
503B	4	3	50	14.99	0		66.909	311.9
503B	4	3	60	15.09	0		103.365	313.5
503B	4	3	70	15.19	0		67.496	307.2
503B	4	3	80	15.29	0		32.756	323.5
503B	4	3	90	15.39	0		24.688	288.6
503B	4	3	100	15.49	0		72.107	320.6
503B	4	3	110	15.59	0		20.355	323.0
503B	5	1	20	16.20	0	PHI=200 DEGREES	3801.912	152.7
503B	5	1	30	16.30	0		985.557	214.8
503B	5	1	40	16.40	0		129.508	58.8
503B	5	1	50	16.50	0		1303.433	318.6
503B	5	1	60	16.60	0		511.699	31.2
503B	5	1	70	16.70	0		430.483	255.2
503B	5	1	80	16.80	0		2290.261	38.9
503B	5	1	90	16.90	0		206.657	46.5
503B	5	1	100	17.00	0		185.805	301.6
503B	5	1	110	17.10	0		94.101	307.8
503B	5	1	120	17.20	0		194.112	327.5
503B	5	1	130	17.30	0		189.745	319.2
503B	5	1	140	17.40	0		68.238	355.1
503B	5	2	10	17.41	0		89.140	301.8

*** GRID H 13 ***

*** GRID I 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	5	2	20	17.51	0		123.035	293.5
503B	5	2	30	17.61	0		108.271	327.7
503B	5	2	40	17.71	0		104.674	326.7
503B	5	2	50	17.81	0		145.664	314.3
503B	5	2	60	17.91	0		102.430	314.7
503B	5	2	70	18.01	0		144.682	307.9
503B	5	2	80	18.11	0		106.011	310.8
503B	5	2	90	18.21	0		118.512	312.2
503B	5	2	100	18.31	0		113.630	311.2
503B	5	2	110	18.41	0		48.689	316.3
503B	5	2	120	18.51	0		95.101	307.3
503B	5	2	130	18.61	0		91.042	318.4
503B	5	2	140	18.71	0		124.259	303.4
503B	5	3	10	18.91	0		119.901	304.6
503B	5	3	20	19.01	0		116.870	303.9
503B	5	3	30	19.11	0		131.108	306.0
503B	5	3	40	19.21	0		136.079	303.8
503B	5	3	50	19.31	0		135.232	304.2
503B	5	3	60	19.41	0		127.667	304.7
503B	5	3	70	19.51	0		173.536	306.5
503B	5	3	80	19.61	0		137.129	303.6
503B	5	3	90	19.71	0		108.456	308.3
503B	5	3	99	19.80	0		138.826	309.4
503B	6	1	20	20.60	0	PHI=140 DEGREES	4231.674	52.1
503B	6	1	30	20.59	0		1553.331	191.7
503B	6	1	40	20.69	0		415.267	250.5
503B	6	1	50	20.79	0		4568.186	191.1
503B	6	1	60	20.89	0		201.578	54.1
503B	6	1	70	20.99	0		248.951	276.6
503B	6	1	80	21.09	0		433.881	202.5
503B	6	1	90	21.19	0		41.030	101.8
503B	6	1	100	21.29	0		796.249	357.3
503B	6	1	110	21.39	0		115.440	161.5
503B	6	1	120	21.49	0		179.080	79.8
503B	6	1	130	21.59	0		398.720	253.4
503B	6	1	140	21.69	0		135.883	359.4
503B	6	2	10	21.86	0		205.278	6.0
503B	6	2	20	21.96	0		123.172	345.7
503B	6	2	30	22.06	0		243.941	233.9
503B	6	2	40	22.16	0		416.294	265.5
503B	6	2	50	22.26	0		93.299	19.3
503B	6	2	60	22.36	0		109.155	344.6
503B	6	2	70	22.46	0		113.867	344.3
503B	6	2	80	22.56	0		117.170	345.9
503B	6	2	90	22.66	0		116.406	344.6
503B	6	2	100	22.76	0		127.629	344.3
503B	6	2	110	22.86	0		127.633	344.1
503B	6	2	120	22.96	0		137.493	345.2
503B	6	2	130	23.06	0		164.852	346.1
503B	6	2	140	23.16	0		190.248	342.4
503B	6	3	10	23.37	0		152.087	338.1
503B	6	3	20	23.47	0		128.857	341.9
503B	6	3	30	23.57	0		90.195	337.6

*** GRID I 13 ***

*** GRID J 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 a-6)	NRM Declination (deg.)
503B	6	3	40	23.67	0		129.411	340.1
503B	6	3	50	23.77	0		132.902	339.2
503B	6	3	60	23.87	0		159.974	340.8
503B	6	3	70	23.97	0		179.261	341.7
503B	6	3	80	24.07	0		205.254	342.0
503B	6	3	90	24.17	0		189.788	336.8
503B	6	3	100	24.27	0		206.461	338.8
503B	6	3	100	24.27	0		142.989	342.6
503B	6	3	110	24.37	0		163.091	339.4
503B	7	1	20	25.00	0	PHI=120 DEGREES	845.293	295.6
503B	7	1	30	25.10	0		1144.602	79.3
503B	7	1	40	25.20	0		2105.074	232.8
503B	7	1	50	25.30	0		1459.446	328.1
503B	7	1	60	25.40	0		1136.114	298.9
503B	7	1	70	25.50	0		294.920	222.5
503B	7	1	80	25.60	0		188.101	340.5
503B	7	1	90	25.70	0		188.817	293.6
503B	7	1	100	25.80	0		166.712	284.8
503B	7	1	110	25.90	0		166.513	247.4
503B	7	1	120	26.00	0		163.158	314.7
503B	7	1	130	26.10	0		134.750	319.7
503B	7	1	140	26.20	0		25.864	42.5
503B	7	2	10	26.34	0		68.673	265.8
503B	7	2	20	26.44	0		79.521	295.6
503B	7	2	30	26.54	0		95.713	295.0
503B	7	2	40	26.64	0		154.598	343.4
503B	7	2	50	26.74	0		324.444	320.7
503B	7	2	60	26.84	0		141.019	280.0
503B	7	2	70	26.94	0		338.992	271.0
503B	7	2	80	27.04	0		135.407	309.2
503B	7	2	90	27.14	0		123.221	306.9
503B	7	2	100	27.24	0		123.272	304.9
503B	7	2	110	27.34	0		136.599	342.9
503B	7	2	120	27.44	0		135.753	322.8
503B	7	2	130	27.54	0		133.406	316.8
503B	7	2	140	27.64	0		146.900	306.0
503B	7	3	10	27.84	0		153.036	330.3
503B	7	3	20	27.94	0		73.779	291.8
503B	7	3	30	28.04	0		55.648	301.1
503B	7	3	40	28.14	0		423.437	280.0
503B	7	3	50	28.24	0		35.413	38.0
503B	7	3	60	28.34	0		202.078	308.3
503B	7	3	70	28.44	0		188.064	325.2
503B	7	3	80	28.54	0		153.430	289.8
503B	7	3	90	28.64	0		75.828	316.0
503B	7	3	100	28.74	0		230.510	319.4
503B	7	3	110	28.84	0		10.322	266.5
503B	8	1	20	29.40	0	PHI=085 DEGREES	5678.947	224.1
503B	8	1	30	29.50	0	ORIENTATION MAY HAVE	383.858	164.8
503B	8	1	40	29.60	0	BEEN LOST	739.390	167.0
503B	8	1	50	29.70	0		497.205	87.6
503B	8	1	60	29.80	0		730.910	86.9
503B	8	1	70	29.90	0		633.738	275.7

*** GRID J 13 ***

*** GRID K 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	8	1	80	30.00	0		1207.509	23.3
503B	8	1	90	30.10	0		551.034	25.1
503B	8	1	100	30.20	0		217.197	292.1
503B	8	1	110	30.30	0		1261.058	65.1
503B	8	1	120	30.40	0		294.506	181.0
503B	8	1	130	30.50	0		245.537	253.4
503B	8	1	140	30.60	0		216.570	62.0
503B	8	2	20	30.80	0		85.779	64.0
503B	8	2	30	30.90	0		156.102	185.1
503B	8	2	40	31.00	0		99.463	52.4
503B	8	2	50	31.10	0		39.918	223.1
503B	8	2	60	31.20	0		284.945	127.2
503B	8	2	70	31.30	0		619.517	206.2
503B	8	2	80	31.40	0		161.871	155.2
503B	8	2	90	31.50	0		98.325	135.2
503B	8	2	100	31.60	0		349.062	69.3
503B	8	2	110	31.70	0		320.233	189.4
503B	8	2	120	31.80	0		173.822	127.1
503B	8	2	130	31.90	0		120.533	100.6
503B	8	2	140	32.00	0		134.211	119.5
503B	8	2	144	32.04	0		88.568	105.9
503B	8	3	5	32.16	0		176.078	109.0
503B	8	3	10	32.21	0		226.458	107.5
503B	8	3	20	32.31	0		259.258	102.9
503B	8	3	30	32.41	0		503.630	80.6
503B	8	3	40	32.51	0		272.093	157.3
503B	8	3	50	32.61	0		202.609	95.5
503B	8	3	60	32.71	0		174.310	100.8
503B	8	3	70	32.81	0		116.278	138.9
503B	8	3	80	32.91	0		399.365	102.5
503B	8	3	90	33.01	0		905.932	257.0
503B	8	3	100	33.11	0		10.173	146.0
503B	8	3	110	33.19	0		41.403	130.7
503B	8	3	120	33.29	0		50.658	13.0
503B	8	3	120	33.29	0		12.860	48.6
503B	10	1	20	38.20	0	PHI=316 DEGREES	2444.540	158.4
503B	10	1	40	38.40	0		521.671	239.8
503B	10	1	60	38.60	0		531.241	165.5
503B	10	1	80	38.80	0		662.625	300.9
503B	10	1	100	39.00	0		444.283	239.0
503B	10	1	120	39.20	0		597.960	39.7
503B	10	1	140	39.40	0		106.018	54.5
503B	10	2	20	39.67	0		30.949	199.6
503B	10	2	30	39.77	0		220.301	30.4
503B	10	2	40	39.87	0		347.362	6.4
503B	10	2	50	39.97	0		157.810	282.8
503B	10	2	60	40.07	0		155.771	53.4
503B	10	2	70	40.17	0		341.415	58.7
503B	10	2	80	40.27	0		206.133	69.3
503B	10	2	90	40.37	0		715.094	87.3
503B	10	2	100	40.47	0		356.892	17.4
503B	10	2	110	40.57	0		276.809	213.2
503B	10	2	120	40.67	0		242.064	74.5

*** GRID K 13 ***

*** GRID L 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	10	2	130	40.77	0		211.489	348.3
503B	10	2	140	40.87	0		222.493	339.4
503B	10	3	10	41.07	0		175.340	65.3
503B	10	3	20	41.17	0		123.423	359.4
503B	10	3	30	41.27	0		186.449	7.1
503B	10	3	40	41.37	0		184.113	55.5
503B	10	3	50	41.47	0		160.231	329.5
503B	10	3	60	41.57	0		124.019	29.5
503B	10	3	70	41.67	0		183.011	14.5
503B	10	3	80	41.77	0		189.465	4.3
503B	10	3	90	41.87	0		148.369	332.3
503B	10	3	95	41.92	0		55.846	313.5
503B	11	1	20	42.60	0	PHI=150 DEGREES	3742.532	225.9
503B	11	1	30	42.70	0		6865.782	326.5
503B	11	1	40	42.80	0		7168.718	115.4
503B	11	1	50	42.90	0		7982.708	151.3
503B	11	1	60	43.00	0		3147.026	250.3
503B	11	1	70	43.10	0		2776.607	263.3
503B	11	1	80	43.20	0		1643.481	87.4
503B	11	1	90	43.30	0		885.446	21.7
503B	11	1	100	43.40	0		161.060	76.4
503B	11	1	110	43.50	0		381.213	267.4
503B	11	1	120	43.60	0		1917.868	58.0
503B	11	1	130	43.70	0		444.948	327.8
503B	11	1	140	43.80	0		656.559	113.0
503B	11	2	20	43.87	0		1169.860	297.0
503B	11	2	30	43.97	0		488.783	246.8
503B	11	2	40	44.07	0		789.746	347.8
503B	11	2	50	44.17	0		423.256	258.3
503B	11	2	60	44.27	0		81.778	276.9
503B	11	2	70	44.37	0		448.580	149.5
503B	11	2	80	44.47	0		569.099	59.8
503B	11	2	90	44.57	0		463.025	164.5
503B	11	2	100	44.67	0		310.939	337.7
503B	11	2	110	44.77	0		453.040	222.7
503B	11	2	120	44.87	0		164.295	7.7
503B	11	2	130	44.97	0		170.995	341.2
503B	11	2	140	45.07	0		210.143	86.4
503B	11	2	144	45.11	0		220.220	3.0
503B	11	3	10	45.27	0		1763.315	172.2
503B	11	3	20	45.37	0		102.223	270.0
503B	11	3	30	45.47	0		165.383	207.7
503B	11	3	40	45.57	0		191.351	325.2
503B	11	3	50	45.67	0		151.599	177.9
503B	11	3	60	45.77	0		283.748	286.8
503B	11	3	70	45.87	0		394.197	291.7
503B	11	3	80	45.97	0		222.509	174.7
503B	11	3	90	46.07	0		755.607	291.7
503B	11	3	100	46.17	0		285.817	284.3
503B	11	3	110	46.27	0		181.697	318.3
503B	11	3	120	46.37	0		242.522	345.2
503B	11	3	130	46.47	0		124.000	308.8
503B	11	3	134	46.51	0		235.585	329.3

*** GRID L 13 ***

*** GRID M 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	12	1	20	47.00	0	PHI=050 DEGREES	1301.173	80.3
503B	12	1	30	47.10	0		1806.044	2.8
503B	12	1	40	47.20	0		1854.101	13.9
503B	12	1	50	47.30	0		3107.735	241.3
503B	12	1	60	47.40	0		1997.725	282.1
503B	12	1	70	47.50	0		2237.525	169.9
503B	12	1	80	47.60	0		5697.889	166.1
503B	12	1	90	47.70	0		2178.038	36.5
503B	12	1	100	47.80	0		2035.406	75.8
503B	12	1	110	47.90	0		677.344	224.6
503B	12	1	120	48.00	0		1721.862	7.9
503B	12	1	130	48.10	0		111.442	51.2
503B	12	1	140	48.20	0		308.269	339.5
503B	12	2	20	48.50	0		448.654	307.2
503B	12	2	30	48.60	0		371.550	327.4
503B	12	2	40	48.70	0		240.401	322.3
503B	12	2	50	48.80	0		63.232	122.9
503B	12	2	60	48.90	0		106.379	353.7
503B	12	2	70	49.00	0		443.717	53.5
503B	12	2	80	49.10	0		222.419	65.4
503B	12	2	90	49.20	0		88.320	114.2
503B	12	2	100	49.30	0		314.855	177.2
503B	12	2	110	49.40	0		66.801	131.4
503B	12	2	120	49.50	0		246.769	168.7
503B	12	2	130	49.60	0		178.292	161.5
503B	12	2	140	49.70	0		98.997	33.2
503B	12	2	144	49.74	0		124.115	227.7
503B	12	3	5	49.85	0		194.046	142.6
503B	12	3	10	49.90	0		59.461	112.8
503B	12	3	20	50.00	0		37.561	41.8
503B	12	3	30	50.10	0		44.273	151.9
503B	12	3	40	50.20	0	NEAR VOID	33.467	177.1
503B	12	3	50	50.30	0	NEAR VOID	48.320	168.2
503B	12	3	60	50.40	0		86.609	178.1
503B	12	3	70	50.44	0		164.955	162.3
503B	12	3	80	50.54	0		149.234	178.7
503B	12	3	84	50.58	0		20.755	137.5
503B	13	1	20	51.40	0	PHI=110 DEGREES	6402.380	106.0
503B	13	1	40	51.60	0		11640.85	246.2
503B	13	1	60	51.80	0		4047.095	229.7
503B	13	1	80	52.00	0		2218.294	196.0
503B	13	1	100	52.20	0		679.604	9.4
503B	13	1	120	52.40	0		134.002	97.4
503B	13	1	130	52.50	0		5389.270	152.6
503B	13	1	140	52.60	0		404.698	166.2
503B	13	2	20	52.85	0		428.967	352.4
503B	13	2	30	52.95	0		121.767	165.9
503B	13	2	40	53.05	0		58.452	142.3
503B	13	2	50	53.15	0		156.001	211.5
503B	13	2	60	53.25	0		114.112	144.9
503B	13	2	70	53.35	0		406.450	71.2
503B	13	2	80	53.45	0		116.147	176.5
503B	13	2	90	53.55	0		334.753	194.0

*** GRID M 13 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
5038	13	2	100	53.65	0		65.738	119.4
5038	13	2	110	53.75	0		97.868	135.1
5038	13	2	120	53.85	0		116.275	172.9
5038	13	2	130	53.95	0		197.858	151.8
5038	13	2	140	54.05	0		393.971	135.9
5038	13	3	10	54.25	0		263.796	153.3
5038	13	3	20	54.35	0		88.410	130.4
5038	13	3	30	54.45	0		115.331	172.6
5038	13	3	40	54.55	0		148.849	164.3
5038	13	3	50	54.65	0		152.812	68.4
5038	14	1	20	55.80	0	PHI=320 DEGREES	552.949	260.1
5038	14	1	30	55.90	0		18355.48	46.2
5038	14	1	40	56.00	0		2876.146	54.0
5038	14	1	50	56.10	0		6545.400	336.1
5038	14	1	60	56.20	0		2912.314	254.6
5038	14	1	70	56.30	0		1204.222	285.1
5038	14	1	80	56.40	0		493.544	144.7
5038	14	1	90	56.50	0		392.769	16.4
5038	14	1	100	56.60	0		2222.216	141.4
5038	14	1	110	56.70	0		419.229	53.9
5038	14	1	120	56.80	0		921.368	76.9
5038	14	1	130	56.90	0		523.461	28.8
5038	14	1	140	57.00	0		580.822	188.1
5038	14	2	20	56.91	0		86.799	182.2
5038	14	2	30	57.01	0		218.223	149.2
5038	14	2	40	57.11	0		227.669	36.1
5038	14	2	50	57.21	0		116.341	146.9
5038	14	2	60	57.31	0		146.531	125.6
5038	14	2	70	57.41	0		175.545	130.4
5038	14	2	80	57.51	0		1010.575	137.4
5038	14	2	90	57.61	0		286.646	100.3
5038	14	2	100	57.71	0		254.835	102.9
5038	14	2	110	57.81	0		320.482	124.7
5038	14	2	120	57.91	0		350.640	114.1
5038	14	2	130	58.01	0		229.170	130.2
5038	14	2	140	58.11	0		430.028	168.8
5038	14	2	144	58.15	0		331.769	110.2
5038	14	3	5	58.27	0		195.234	116.3
5038	14	3	10	58.32	0		258.148	120.8
5038	14	3	20	58.42	0		236.557	122.4
5038	14	3	30	58.52	0		260.966	129.9
5038	14	3	40	58.62	0		291.599	113.5
5038	14	3	50	58.72	0		296.797	132.9
5038	14	3	60	58.82	0		259.170	125.8
5038	14	3	70	58.92	0		289.642	113.9
5038	14	3	80	59.02	0		445.865	149.4
5038	14	3	84	59.06	0		128.606	42.6
5038	15	1	20	60.20	0	PHI=280 DEGREES	31468.16	331.5
5038	15	1	40	60.40	0		4374.212	349.7
5038	15	1	60	60.60	0		3482.074	200.2
5038	15	1	80	60.80	0		194.598	248.8
5038	15	1	90	60.90	0		1143.258	301.6
5038	15	1	100	61.00	0		258.068	32.9

*** GRID B 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	15	1	110	61.10	0		438.639	128.2
503B	15	1	120	61.20	0		457.944	168.1
503B	15	1	130	61.30	0		86.612	233.0
503B	15	1	140	61.40	0		371.591	96.4
503B	15	1	144	61.44	0		93.712	152.2
503B	15	2	5	61.20	0		271.571	164.2
503B	15	2	10	61.25	0		38.130	181.7
503B	15	2	20	61.35	0		160.362	123.7
503B	15	2	30	61.45	0		106.589	151.3
503B	15	2	40	61.55	0		690.135	341.6
503B	15	2	50	61.65	0		325.076	210.9
503B	15	2	60	61.75	0		181.500	136.5
503B	15	2	70	61.85	0		178.742	134.4
503B	15	2	80	61.95	0		187.944	351.8
503B	15	2	90	62.05	0		127.771	185.7
503B	15	2	100	62.15	0		188.491	110.0
503B	15	2	110	62.25	0		59.773	142.1
503B	15	2	120	62.35	0		28.785	323.1
503B	15	2	130	62.45	0		97.075	177.7
503B	15	2	140	62.55	0		114.990	129.3
503B	15	2	144	62.59	0		75.849	122.8
503B	15	3	5	62.70	0		165.161	152.2
503B	15	3	10	62.75	0		114.764	118.8
503B	15	3	20	62.85	0		269.951	150.8
503B	15	3	30	62.95	0		239.759	60.8
503B	15	3	40	63.05	0		166.650	125.7
503B	15	3	50	63.15	0		288.208	91.2
503B	15	3	60	63.25	0		89.674	114.0
503B	15	3	70	63.35	0		174.320	141.5
503B	15	3	80	63.45	0		301.823	256.3
503B	15	3	90	63.55	0		29.670	86.5
503B	15	3	100	63.65	0		140.200	255.1
503B	15	3	105	63.70	0		26.875	300.8
503B	15	3	110	63.75	0		48.515	278.0
503B	16	1	20	64.60	0	PHI=218 DEGREES	6822.795	338.6
503B	16	1	30	64.70	0		1862.206	285.9
503B	16	1	40	64.80	0		543.780	302.6
503B	16	1	50	64.90	0		75.043	102.4
503B	16	1	60	65.00	0		289.878	86.9
503B	16	1	70	65.10	0		1880.246	355.2
503B	16	1	80	65.20	0		30.534	133.2
503B	16	1	90	65.30	0		101.785	325.9
503B	16	1	100	65.40	0		75.040	211.9
503B	16	1	110	65.50	0		384.639	260.6
503B	16	1	120	65.60	0		130.072	75.3
503B	16	1	130	65.70	0		225.149	292.6
503B	16	1	140	65.80	0		228.985	311.1
503B	16	2	20	65.94	0		269.760	314.0
503B	16	2	30	66.04	0		198.230	274.0
503B	16	2	40	66.14	0		156.816	292.5
503B	16	2	50	66.24	0		58.867	103.0
503B	16	2	60	66.34	0		162.254	172.4
503B	16	2	70	66.44	0		62.972	84.3

*** GRID B 14 ***

*** GRID C 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	16	2	80	66.54	0		332.793	336.6
503B	16	2	90	66.64	0		301.815	83.0
503B	16	2	100	66.74	0		230.882	158.3
503B	16	2	110	66.84	0		139.359	237.7
503B	16	2	120	66.94	0		141.563	58.1
503B	16	2	130	67.04	0		29.019	289.4
503B	16	2	140	67.14	0		125.092	116.6
503B	16	3	20	67.44	0		117.272	149.8
503B	16	3	30	67.54	0		115.172	174.7
503B	16	3	40	67.64	0		86.768	171.3
503B	16	3	50	67.74	0		197.566	330.8
503B	16	3	60	67.84	0		101.120	141.9
503B	16	3	70	67.94	0		114.017	36.9
503B	16	3	80	68.04	0		232.964	136.9
503B	16	3	90	68.14	0		120.505	144.8
503B	16	3	100	68.24	0		118.826	151.0
503B	16	3	106	68.30	0		560.666	113.1
503B	17	1	70	69.50	0	PHI=040 DEGREES	1276.156	256.3
503B	17	1	80	69.60	0	TOP DAMAGED	233.422	82.5
503B	17	1	90	69.70	0		2197.747	60.1
503B	17	1	100	69.80	0		989.939	302.1
503B	17	1	110	69.90	0		548.634	323.8
503B	17	1	120	70.00	0		307.236	160.6
503B	17	1	130	70.10	0		571.274	131.7
503B	17	1	140	70.20	0		562.342	131.3
503B	17	1	146	70.26	0		438.725	66.3
503B	17	2	20	70.41	0		298.179	117.3
503B	17	2	30	70.51	0		246.729	161.2
503B	17	2	40	70.61	0		291.741	109.2
503B	17	2	50	70.71	0		1256.627	43.0
503B	17	2	60	70.81	0		786.999	115.7
503B	17	2	70	70.91	0		132.796	151.4
503B	17	2	80	71.01	0		226.934	150.2
503B	17	2	90	71.11	0		236.804	106.1
503B	17	2	100	71.21	0		160.690	97.2
503B	17	2	110	71.31	0		491.914	108.4
503B	17	2	120	71.41	0		408.162	126.8
503B	17	2	130	71.51	0		258.411	100.0
503B	17	2	140	71.61	0		259.174	85.3
503B	17	2	145	71.66	0		433.058	67.9
503B	17	3	10	71.81	0		214.353	86.1
503B	17	3	20	71.91	0		216.051	113.2
503B	17	3	30	72.01	0		77.169	105.3
503B	17	3	40	72.11	0		49.299	170.7
503B	17	3	50	72.17	0		113.125	80.3
503B	17	3	60	72.27	0		64.687	70.6
503B	17	3	70	72.37	0		20.039	53.5
503B	17	3	80	72.41	0		16.080	94.1
503B	17	3	90	72.50	0		6.298	292.9
503B	17	3	96	72.56	0		47.504	22.6
503B	18	1	30	73.50	0	PHI=005 DEGREES	5540.959	343.5
503B	18	1	40	73.60	0		810.994	319.2
503B	18	1	50	73.70	0		1142.890	226.5

*** GRID C 14 ***

*** GRID D 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	18	1	60	73.80	0		460.405	244.6
503B	18	1	70	73.90	0		1143.275	83.1
503B	18	1	80	74.00	0		386.776	185.2
503B	18	1	90	74.10	0		155.298	278.2
503B	18	1	100	74.20	0		377.757	151.0
503B	18	1	110	74.30	0		940.484	68.6
503B	18	1	120	74.40	0		531.937	264.1
503B	18	1	130	74.50	0		36.107	353.6
503B	18	1	140	74.60	0		235.272	62.2
503B	18	2	20	74.90	0		49.457	297.1
503B	18	2	30	75.00	0		932.697	138.7
503B	18	2	40	75.10	0		22.563	154.3
503B	18	2	50	75.20	0		484.733	83.3
503B	18	2	60	75.30	0		189.569	300.9
503B	18	2	70	75.40	0		247.719	282.1
503B	18	2	80	75.50	0		179.908	173.0
503B	18	2	90	75.60	0		404.569	50.6
503B	18	2	100	75.70	0		565.225	335.0
503B	18	2	110	75.80	0		52.049	104.6
503B	18	2	120	75.90	0		134.642	75.5
503B	18	2	130	76.00	0		48.702	200.4
503B	18	2	140	76.10	0		58.475	88.3
503B	18	3	20	76.41	0		136.321	238.6
503B	18	3	30	76.51	0		449.408	289.6
503B	18	3	40	76.61	0		276.249	295.2
503B	18	3	50	76.71	0		124.967	247.9
503B	18	3	60	76.81	0		218.345	226.4
503B	18	3	70	76.91	0		58.615	299.5
503B	18	3	80	77.01	0		17.617	324.8
503B	18	3	90	77.11	0		40.189	340.8
503B	18	3	100	77.21	0		8.972	187.1
503B	18	3	110	77.31	0		28.160	229.8
503B	18	3	120	77.41	0		55.447	136.2
503B	18	3	130	77.51	0		51.040	329.9
503B	18	3	135	77.56	0		48.236	294.5
503B	19	1	40	78.00	0	PHI=235 DEGREES	498.156	133.5
503B	19	1	50	78.10	0		658.436	334.9
503B	19	1	60	78.20	0		1488.934	272.1
503B	19	1	70	78.30	0		971.987	168.0
503B	19	1	80	78.40	0		1418.147	281.8
503B	19	1	90	78.50	0		1141.802	259.5
503B	19	1	100	78.60	0		798.511	201.1
503B	19	1	110	78.70	0		215.443	287.3
503B	19	1	120	78.80	0		180.808	290.8
503B	19	1	130	78.90	0		212.798	272.1
503B	19	1	140	79.00	0		139.585	261.1
503B	19	2	20	79.11	0		91.588	269.4
503B	19	2	30	79.21	0		183.302	121.9
503B	19	2	40	79.31	0		55.095	258.0
503B	19	2	50	79.41	0		114.712	281.6
503B	19	2	60	79.51	0		98.623	253.1
503B	19	2	70	79.61	0		135.029	266.9
503B	19	2	80	79.71	0		144.447	261.8

*** GRID D 14 ***

*** GRID E 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	19	2	90	79.81	0		138.238	256.9
503B	19	2	100	79.91	0		121.275	263.3
503B	19	2	110	80.01	0		49.306	243.9
503B	19	2	120	80.11	0		48.308	267.5
503B	19	2	130	80.21	0		126.753	241.0
503B	19	2	140	80.31	0		34.857	230.6
503B	19	3	10	80.51	0	SLIPPED IN HOLDER	38.758	253.4
503B	19	3	20	80.61	0		109.850	270.1
503B	19	3	30	80.71	0		205.200	271.4
503B	19	3	40	80.81	0		194.485	273.3
503B	19	3	50	80.91	0		102.860	272.3
503B	20	2	20	82.20	0	PHI=341 DEGREES	10995.66	197.4
503B	20	2	30	82.30	0		4773.554	2.4
503B	20	2	40	82.40	0		1581.093	90.6
503B	20	2	50	82.50	0		2430.566	127.9
503B	20	2	60	82.60	0		2732.989	60.8
503B	20	2	70	82.70	0		1638.631	290.9
503B	20	2	80	82.80	0		689.909	16.7
503B	20	2	90	82.90	0		1644.693	333.2
503B	20	2	100	83.00	0		3005.032	99.9
503B	20	2	110	83.10	0		892.759	180.4
503B	20	2	120	83.20	0		1608.304	47.0
503B	20	2	130	83.30	0		1306.101	277.5
503B	20	2	140	83.40	0		978.699	182.3
503B	20	3	20	83.67	0		47.736	236.4
503B	20	3	30	83.77	0		488.034	66.8
503B	20	3	40	83.87	0		1837.783	243.0
503B	20	3	50	83.97	0		265.622	287.4
503B	20	3	60	84.07	0		87.267	201.4
503B	20	3	70	84.17	0		260.525	190.7
503B	20	3	80	84.27	0		1227.107	287.3
503B	20	3	90	84.37	0		1412.465	190.6
503B	20	3	100	84.47	0		51.340	243.9
503B	20	3	110	84.57	0		21.548	291.4
503B	21	1	20	86.60	0	PHI=357 DEGREES	7246.294	341.7
503B	21	1	40	86.80	0	SHIP CHANGED HEADING,	5992.535	255.7
503B	21	1	60	87.00	0	AFTER CORE 20 WAS CUT,	4680.419	1.6
503B	21	1	80	87.20	0	FROM 165 TO 178	10835.670	36.0
503B	21	1	100	87.40	0		16006.94	16.3
503B	21	1	120	87.60	0		3345.273	15.6
503B	21	1	140	87.80	0		5019.160	7.6
503B	21	2	20	88.05	0		1995.262	71.4
503B	21	2	30	88.15	0		2092.346	128.1
503B	21	2	40	88.25	0		1808.034	205.9
503B	21	2	50	88.35	0		2439.720	37.3
503B	21	2	60	88.45	0		1495.968	283.4
503B	21	2	70	88.55	0		4195.010	60.5
503B	21	2	80	88.65	0		2567.355	5.2
503B	21	2	90	88.75	0		1127.846	39.2
503B	21	2	100	88.85	0		779.895	226.4
503B	21	2	110	88.95	0		404.728	10.6
503B	21	2	120	89.05	0		695.449	242.4
503B	21	2	130	89.15	0		4173.063	119.7

*** GRID E 14 ***

*** GRID F 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	21	2	140	89.25	0		1574.806	206.2
503B	21	3	20	89.55	0		569.273	327.5
503B	21	3	30	89.65	0		1530.220	357.1
503B	21	3	40	89.75	0		610.028	335.6
503B	21	3	50	89.85	0		1156.302	141.3
503B	21	3	60	89.95	0		453.654	310.1
503B	21	3	70	90.05	0		83.842	306.8
503B	21	3	80	90.15	0		989.093	332.7
503B	21	3	90	90.25	0		171.609	224.8
503B	21	3	100	90.35	0		567.590	64.6
503B	21	3	110	90.45	0		129.455	268.9
503B	21	3	120	90.55	0		559.835	228.2
503B	21	3	130	90.65	0		311.901	194.1
503B	21	3	140	90.75	0		109.116	207.5
503B	22	1	50	91.30	0	PHI=157 DEGREES	1475.274	152.5
503B	22	1	60	91.40	0	LOTS OF RUST ABOVE	196.924	170.3
503B	22	1	70	91.50	0		132.305	301.2
503B	22	1	80	91.60	0		882.787	344.3
503B	22	1	90	91.70	0		869.471	179.3
503B	22	1	100	91.80	0		1173.655	206.4
503B	22	1	110	91.90	0		111.997	149.8
503B	22	1	120	92.00	0		2065.582	335.5
503B	22	1	130	92.10	0		1694.186	283.4
503B	22	1	140	92.20	0		1441.110	23.1
503B	22	2	20	92.25	0		192.584	24.7
503B	22	2	30	92.35	0		551.301	329.4
503B	22	2	40	92.45	0		627.838	12.8
503B	22	2	50	92.55	0		243.157	168.4
503B	22	2	60	92.65	0		232.651	352.4
503B	22	2	70	92.75	0		104.895	93.3
503B	22	2	80	92.85	0		210.277	290.8
503B	22	2	90	92.95	0		418.630	107.3
503B	22	2	100	93.05	0		311.221	120.5
503B	22	2	110	93.15	0		28.981	256.8
503B	22	2	120	93.25	0		180.887	0.5
503B	22	2	130	93.35	0		246.505	5.2
503B	22	2	140	93.45	0		136.514	100.1
503B	22	3	20	93.75	0		306.476	305.5
503B	22	3	30	93.85	0		242.414	222.8
503B	22	3	40	93.95	0		5.414	81.8
503B	22	3	50	94.05	0		59.738	82.4
503B	22	3	60	94.15	0		527.745	103.3
503B	22	3	70	94.25	0		696.504	25.8
503B	22	3	80	94.35	0		760.162	223.6
503B	22	3	90	94.45	0		806.400	82.7
503B	22	3	100	94.55	0		120.650	167.5
503B	22	3	110	94.65	0		578.227	121.5
503B	22	3	120	94.75	0		194.001	127.3
503B	22	3	130	94.85	0		122.622	135.3
503B	22	3	140	94.95	0		150.686	173.4
503B	24	1	40	100.00	0	PHI=192 DEGREES	17386.01	174.1
503B	24	1	50	100.10	0		1736.841	285.2
503B	24	1	60	100.20	0		2555.076	77.6

*** GRID F 14 ***

*** GRID G 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 e-6)	NRM Declination (deg.)
5038	24	1	70	100.30	0		2040.067	335.5
5038	24	1	80	100.40	0		1822.555	22.4
5038	24	1	90	100.50	0		2915.733	177.2
5038	24	1	100	100.60	0		2480.855	174.4
5038	24	1	110	100.70	0		2876.347	13.0
5038	24	1	120	100.80	0		1012.583	239.6
5038	24	1	130	100.90	0		666.510	160.1
5038	24	1	140	101.00	0		741.212	233.6
5038	24	2	20	100.85	0		411.214	3.3
5038	24	2	30	100.95	0		353.833	242.5
5038	24	2	40	101.05	0		116.629	133.8
5038	24	2	50	101.15	0		661.026	185.0
5038	24	2	60	101.25	0		747.095	161.2
5038	24	2	70	101.35	0		809.721	53.7
5038	24	2	80	101.45	0		855.918	132.6
5038	24	2	90	101.55	0		620.655	67.2
5038	24	2	100	101.65	0		84.387	337.6
5038	25	1	40	104.40	0	PHI=137 DEGREES	1156.035	209.0
5038	25	1	50	104.50	0	TOP 30 CM VOID	1710.838	3.4
5038	25	1	60	104.60	0		567.551	272.5
5038	25	1	70	104.70	0		343.527	68.5
5038	25	1	80	104.41	0		92.669	303.1
5038	25	1	90	104.51	0		490.731	193.7
5038	25	1	100	104.61	0		523.682	243.7
5038	25	1	110	104.64	0		638.553	326.7
5038	25	1	120	104.74	0		71.466	113.6
5038	25	1	130	104.84	0		71.963	317.6
5038	25	1	140	104.94	0		6.891	304.5
5038	25	2	20	105.24	0		19.618	274.3
5038	25	2	30	105.34	0		155.548	275.2
5038	25	2	40	105.44	0		115.587	313.1
5038	25	2	50	105.49	0		53.906	355.9
5038	25	2	60	105.54	0		104.789	310.7
5038	25	2	70	105.64	0		155.373	302.8
5038	25	2	80	105.74	0		110.638	299.4
5038	25	2	90	105.84	0		204.955	283.3
5038	25	2	100	105.93	0		124.834	262.5
5038	25	2	110	106.01	0		141.612	257.2
5038	25	2	120	106.01	0		78.717	306.0
5038	25	2	130	106.01	0		43.093	226.6
5038	25	2	140	106.01	0		124.705	300.6
5038	25	2	145	106.01	0		499.616	347.1
5038	26	1	20	108.60	0	PHI=047 DEGREES	8100.218	201.6
5038	26	1	30	108.70	0		17816.74	356.6
5038	26	1	40	108.80	0		14976.85	160.0
5038	26	1	50	108.90	0		7275.972	194.9
5038	26	1	60	109.00	0		5292.869	233.7
5038	26	1	70	109.10	0		2738.599	319.1
5038	26	1	80	109.20	0		1958.783	229.2
5038	26	1	90	109.30	0		3779.504	309.1
5038	26	1	100	109.40	0		404.597	125.3
5038	26	1	110	109.50	0		1250.296	221.6
5038	26	1	120	109.60	0		525.056	70.9

*** GRID G 14 ***

*** GRID H 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	RC	Sedimentological Notes	NRM Intensity (gauss x 1.0 @-6)	NRM Declination (deg.)
503B	26	1	130	109.70	0		285.547	218.3
503B	26	1	140	109.80	0		272.945	314.2
503B	26	2	20	109.45	0		186.915	237.4
503B	26	2	30	109.55	0		146.574	217.0
503B	26	2	40	109.65	0		253.200	156.0
503B	26	2	50	109.75	0		104.106	170.7
503B	26	2	60	109.85	0		77.555	54.3
503B	26	2	70	109.95	0		120.679	76.5
503B	26	2	80	110.05	0		224.025	181.0
503B	26	2	90	110.15	0		80.609	11.4
503B	26	2	100	110.25	0		52.745	20.1
503B	26	2	110	110.35	0		11.480	313.8
503B	26	2	120	110.45	0		76.999	158.6
503B	26	2	130	110.55	0		468.397	151.8
503B	26	2	137	110.62	0		645.152	149.8

*** GRID H 14 ***

*** GRID I 14 ***

Table 6: Carbon-Carbonate

Raw Carbonate, Organic Carbon, Total Carbon Data

Note: The "Analysis" column of the table is used to indicate where the sample analysis was performed: "DSDP" signifies that the analysis was performed at the DSDP lab in La Jolla, Calif.; "USGS" signifies that the analysis was performed at the USGS Marine Sediments Lab in Menlo Park, Calif.

*** GRID I 14 ***

*** GRID J 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502B	1	1	10	0.10	USGS	60.0		
502B	1	1	20	0.20	USGS	64.5		
502B	1	1	35	0.35	USGS	58.2	0.29	7.27
502B	1	1	50	0.50	USGS	37.0		
502B	1	1	65	0.65	USGS	43.2	0.29	5.47
502B	1	1	95	0.95	USGS	41.4	0.39	5.36
502B	1	1	110	1.10	USGS	48.5		
502B	1	1	125	1.25	USGS	45.2	0.22	5.64
502B	1	2	5	1.53	USGS	44.6	0.70	6.05
502B	1	2	18	1.66	USGS	37.5		
502B	2	1	20	1.89	USGS	39.5		
502B	2	1	35	2.04	USGS	45.7		
502B	2	1	50	2.19	USGS	51.5		
502B	2	1	65	2.34	USGS	46.2	0.26	5.81
502B	2	1	95	2.64	USGS	32.6	0.30	4.22
502B	2	1	110	2.79	USGS	34.0		
502B	2	1	125	2.94	USGS	40.9	0.47	5.38
502B	2	1	135	3.04	USGS	40.0		
502B	2	1	143	3.12	USGS	47.8	0.22	5.96
502B	2	2	20	3.39	USGS	47.0		
502B	2	2	35	3.54	USGS	54.7	0.14	6.71
502B	2	2	50	3.69	USGS	48.5		
502B	2	2	65	3.84	USGS	57.0	0.16	7.00
502B	2	2	95	4.14	USGS	40.9	0.43	5.33
502B	2	2	110	4.29	USGS	47.0		
502B	2	3	20	4.89	USGS	48.0		
502B	2	3	35	5.04	USGS	48.7	0.20	6.04
502B	2	3	50	5.19	USGS	48.0		
502B	2	3	65	5.34	USGS	53.2	0.37	6.76
502B	3	1	20	6.30	USGS	50.5		
502B	3	1	35	6.45	USGS	51.6	0.61	6.80
502B	3	1	50	6.60	USGS	50.0		
502B	3	1	65	6.75	USGS	48.6	0.25	6.09
502B	3	1	95	7.05	USGS	48.1	0.33	6.10
502B	3	1	110	7.20	USGS	47.0		
502B	3	1	125	7.35	USGS	47.0	0.19	5.83
502B	3	1	140	7.50	USGS	52.0		
502B	3	1	146	7.56	USGS	49.4	0.63	6.55
502B	3	2	20	7.80	USGS	65.5		
502B	3	2	35	7.95	USGS	46.9	0.18	5.81
502B	3	2	50	8.10	USGS	44.0		
502B	3	2	65	8.25	USGS	50.6	0.37	6.44
502B	3	2	95	8.55	USGS	45.2	0.52	5.94
502B	3	2	110	8.70	USGS	52.0		
502B	3	2	125	8.85	USGS	52.4	0.32	6.61
502B	3	2	144	9.04	USGS	53.2	0.34	6.73
502B	3	3	20	9.30	USGS	60.0		
502B	3	3	35	9.45	USGS	61.4	0.67	8.04
502B	3	3	50	9.60	USGS	53.0		
502B	3	3	65	9.75	USGS	59.3	0.56	7.67
502B	3	3	95	10.05	USGS	47.9	0.34	6.09
502B	3	3	110	10.20	USGS	48.0		
502B	3	3	125	10.35	USGS	41.1	0.55	5.47

*** GRID J 14 ***

*** GRID K 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502B	4	1	35	10.89	USGS	42.3	0.38	5.45
502B	4	1	50	11.04	USGS	42.0		
502B	4	1	65	11.19	USGS	42.7	0.20	5.32
502B	4	1	95	11.49	USGS	57.4	0.38	7.26
502B	4	1	110	11.64	USGS	54.0		
502B	4	1	125	11.79	USGS	50.3	0.42	6.46
502B	4	1	140	11.94	USGS	49.5		
502B	4	1	145	11.99	USGS	47.0	0.65	6.29
502B	4	2	20	12.24	USGS	39.0		
502B	4	2	35	12.39	USGS	40.4	0.59	5.44
502B	4	2	50	12.54	USGS	48.0		
502B	4	2	65	12.69	USGS	42.0	0.61	5.65
502B	4	2	95	12.99	USGS	55.0	0.70	7.30
502B	4	2	125	13.29	USGS	58.3	0.24	7.24
502B	4	2	140	13.44	USGS	49.0		
502B	4	2	149	13.49	USGS	47.8	0.51	6.24
502B	4	3	20	13.74	USGS	46.0		
502B	4	3	35	13.89	USGS	59.0	0.68	7.76
502B	4	3	50	14.04	USGS	57.0		
502B	4	3	65	14.19	USGS	41.4	0.57	5.54
502B	4	3	95	14.49	USGS	50.0	0.55	6.55
502B	4	3	110	14.64	USGS	47.5		
502B	4	3	125	14.79	USGS	52.3	0.34	6.61
502B	5	1	60	15.40	USGS	49.0		
502B	5	1	65	15.45	USGS	44.2	0.26	5.56
502B	5	1	95	15.75	USGS	44.1	0.70	5.99
502B	5	1	110	15.90	USGS	46.0		
502B	5	1	125	16.05	USGS	44.9	0.15	5.55
502B	5	1	140	16.20	USGS	54.5		
502B	5	1	149	16.29	USGS	44.0	0.49	5.77
502B	5	2	20	16.50	USGS	35.5		
502B	5	2	35	16.65	USGS	34.5	0.13	4.27
502B	5	2	50	16.80	USGS	31.0		
502B	5	2	65	16.95	USGS	37.6	0.28	4.79
502B	5	2	95	17.08	USGS	49.5	0.15	6.09
502B	5	2	108	17.21	USGS	56.5		
502B	5	2	125	17.27	USGS	49.3	0.34	6.25
502B	5	2	140	17.42	USGS	50.5		
502B	5	2	144	17.46	USGS	50.0	0.35	6.35
502B	5	3	20	17.73	USGS	40.0		
502B	5	3	35	17.88	USGS	42.5		
502B	5	3	50	18.03	USGS	43.5		
502B	5	3	65	18.18	USGS	45.6	0.19	5.67
502B	5	3	95	18.48	USGS	38.3	0.31	4.90
502B	5	3	110	18.63	USGS	46.0		
502B	5	3	126	18.79	USGS	42.6	0.16	5.28
502B	6	1	20	19.55	USGS	45.0		
502B	6	1	35	19.70	USGS	43.8	0.49	5.73
502B	6	1	50	19.85	USGS	40.0		
502B	6	1	65	20.00	USGS	33.0	0.37	4.33
502B	6	1	95	20.30	USGS	53.6	0.29	6.71
502B	6	1	110	20.45	USGS	58.5		
502B	6	1	125	20.60	USGS	42.1	0.37	5.42

*** GRID K 14 ***

*** GRID L 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502B	6	1	140	20.75	USGS	44.0		
502B	6	1	149	20.84	USGS	46.8	0.42	6.04
502B	6	2	15	21.01	USGS	50.5		
502B	6	2	35	21.21	USGS	58.7	0.57	7.61
502B	6	2	50	21.36	USGS	55.0		
502B	6	2	65	21.51	USGS	42.3	0.48	5.56
502B	6	2	95	21.81	USGS	49.5	0.28	6.22
502B	6	2	110	21.96	USGS	53.3		
502B	6	3	20	22.54	USGS	44.0		
502B	6	3	35	22.69	USGS	54.8	0.56	7.14
502B	6	3	50	22.84	USGS	60.0		
502B	6	3	65	22.99	USGS	57.0	0.58	7.42
502B	6	3	95	23.29	USGS	46.0	0.71	6.23
502B	6	3	110	23.44	USGS	50.5		
502B	6	3	125	23.58	USGS	41.8	0.47	5.49
502B	7	1	25	23.98	USGS	55.0		
502B	7	1	26	23.99	USGS	52.6	0.46	6.77
502B	7	2	20	24.23	USGS	45.0		
502B	7	2	35	24.38	USGS	38.8	0.55	5.21
502B	7	2	50	24.53	USGS	43.5		
502B	7	2	65	24.68	USGS	40.2	0.50	5.32
502B	7	2	95	24.98	USGS	38.8	0.26	4.92
502B	7	2	110	25.13	USGS	44.0		
502B	7	2	125	25.28	USGS	50.1	0.56	6.65
502B	7	2	140	25.43	USGS	63.0		
502B	7	2	145	25.48	USGS	49.7	0.32	6.28
502B	7	3	20	25.72	USGS	50.5		
502B	7	3	35	25.87	USGS	55.3	0.52	7.15
502B	7	3	50	26.02	USGS	57.5		
502B	7	3	65	26.17	USGS	59.6	0.39	7.54
502B	7	3	95	26.47	USGS	41.5	0.22	5.20
502B	7	3	110	26.62	USGS	49.5		
502B	7	3	125	26.77	USGS	55.8	0.52	7.21
502B	7	3	140	26.92	USGS	62.0		
502B	7	3	149	27.01	USGS	61.0	0.27	7.60
502B	7	4	20	27.23	USGS	45.0		
502B	7	4	35	27.38	USGS	45.5	0.34	5.80
502B	7	4	50	27.53	USGS	54.0		
502B	7	4	65	27.68	USGS	51.2	0.35	6.50
502B	7	4	95	27.98	USGS	54.5	0.40	6.94
502B	7	4	110	28.13	USGS	40.0		
502B	7	4	125	28.28	USGS	41.4	0.38	5.35
502B	8	1	90	28.94	USGS	46.0		
502B	8	1	95	28.99	USGS	41.5	0.44	5.42
502B	8	1	105	29.09	USGS	41.0		
502B	8	1	125	29.29	USGS	43.7	0.37	5.61
502B	8	1	140	29.44	USGS	44.0		
502B	8	1	149	29.53	USGS	46.5	0.63	6.21
502B	8	2	20	29.74	USGS	48.0		
502B	8	2	35	29.89	USGS	44.5	0.52	5.86
502B	8	2	40	29.94	USGS	38.0		
502B	8	2	95	30.09	USGS	44.4	0.30	5.63
502B	8	2	110	30.24	USGS	46.0		

*** GRID L 14 ***

*** GRID M 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502B	8	2	125	30.39	USGS	40.9	0.54	5.45
502B	8	2	140	30.54	USGS	45.0		
502B	8	2	149	30.63	USGS	45.4	0.46	5.91
502B	8	3	20	30.77	USGS	58.5		
502B	8	3	35	30.92	USGS	61.8	0.47	7.89
502B	8	3	40	30.97	USGS	62.0		
502B	8	3	65	31.22	USGS	39.5	0.59	5.33
502B	8	3	95	31.52	USGS	44.4	0.37	5.70
502B	8	3	100	31.57	USGS	49.5		
502B	9	1	65	33.00	USGS	46.1	0.35	5.87
502B	9	1	95	33.30	USGS	54.5	0.24	6.78
502B	9	1	110	33.45	USGS	50.5		
502B	9	1	125	33.60	USGS	45.7	0.36	5.84
502B	9	1	140	33.75	USGS	43.5		
502B	9	1	149	33.84	USGS	47.2	0.62	6.28
502B	9	2	20	34.06	USGS	59.5		
502B	9	2	35	34.21	USGS	57.5	0.48	7.39
502B	9	2	40	34.26	USGS	55.0		
502B	9	2	65	34.51	USGS	50.3	0.24	6.28
502B	9	2	95	34.81	USGS	59.9	0.46	7.64
502B	9	2	100	34.86	USGS	62.0		
502B	9	2	125	35.05	USGS	61.0	0.47	7.78
502B	9	2	140	35.20	USGS	62.0		
502B	9	2	149	35.29	USGS	63.9	0.42	8.10
502B	9	3	15	35.44	USGS	63.0		
502B	9	3	35	35.58	USGS	42.6	0.54	5.66
502B	9	3	65	35.88	USGS	33.6	0.28	4.30
502	10	1	80	36.10	USGS	57.0		
502	10	1	110	36.40	USGS	46.0		
502	10	1	140	36.70	USGS	44.0		
502	10	2	20	37.00	USGS	47.0		
502	10	2	50	37.30	USGS	41.0		
502	10	2	80	37.60	USGS	40.0		
502	10	2	110	37.90	USGS	59.0		
502	10	2	140	38.20	USGS	59.0		
502	10	3	20	38.51	USGS	30.0		
502	10	3	50	38.81	USGS	47.0		
502	10	3	80	39.11	USGS	41.0		
502	10	3	110	39.41	USGS	45.0		
502	11	1	20	39.99	USGS	38.0		
502	11	1	50	40.29	USGS	40.0		
502	11	1	80	40.59	USGS	53.0		
502	11	1	110	40.89	USGS	58.0		
502B	11	1	20	41.54	USGS	49.0		
502B	11	1	35	41.69	USGS	52.7	0.52	6.84
502B	11	1	45	41.79	USGS	46.0		
502B	11	1	65	41.99	USGS	49.7	0.50	6.46
502B	11	1	95	42.29	USGS	56.6	0.39	7.18
502B	11	1	110	42.44	USGS	49.0		
502B	11	1	125	42.59	USGS	43.6	0.37	5.61
502B	11	1	140	42.74	USGS	53.0		
502B	11	1	149	42.83	USGS	46.6	0.47	6.06
502B	11	2	10	42.94	USGS	51.0		

*** GRID M 14 ***

*** GRID N 14 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502B	11	2	20	43.04	USGS	45.0		
502B	11	2	35	43.19	USGS	42.9	0.43	5.58
502B	11	2	40	43.24	USGS	47.0		
502B	11	2	50	43.34	USGS	54.0		
502B	11	2	65	43.49	USGS	41.4	0.64	5.60
502B	11	2	95	43.79	USGS	47.3	0.29	5.97
502B	11	2	100	43.84	USGS	50.5		
502B	11	2	125	44.09	USGS	62.3	0.36	7.83
502B	11	2	130	44.14	USGS	56.0		
502B	11	2	140	44.24	USGS	51.0		
502B	11	2	149	44.33	USGS	59.8	0.29	7.47
502B	11	3	20	44.55	USGS	57.5		
502B	11	3	35	44.70	USGS	54.0	0.17	6.65
502B	11	3	50	44.85	USGS	44.0		
502B	11	3	65	45.00	USGS	38.7	0.29	4.94
502B	11	3	95	45.30	USGS	42.8	0.52	5.65
502B	11	3	110	45.45	USGS	54.5		
502B	11	3	125	45.60	USGS	47.2	0.52	6.19
502C	2	3	126	45.77	USGS	60.8	0.20	7.50
502C	3	1	36	46.36	USGS	45.0	0.20	5.60
502C	3	1	66	46.66	USGS	45.5	0.30	5.70
502C	3	1	96	46.96	USGS	38.4	0.20	4.80
502C	3	1	126	47.26	USGS	32.2	0.20	4.10
502C	3	1	150	47.50	USGS	57.6	0.20	7.10
502C	3	2	36	47.84	USGS	50.3	0.20	6.20
502C	3	2	66	48.14	USGS	36.5	0.10	4.50
502C	3	2	96	48.44	USGS	44.5	0.20	5.50
502C	3	2	126	48.74	USGS	57.3	0.20	7.10
502C	3	2	150	48.98	USGS	58.7	0.20	7.20
502C	3	3	36	49.34	USGS	48.5	0.20	6.10
502C	4	1	66	50.51	USGS	46.4	0.10	5.70
502B	13	1	50	50.65	USGS	49.0		
502B	13	1	65	50.80	DSDP	54.8	0.20	6.80
502B	13	1	95	51.10	DSDP	56.1	0.20	7.00
502B	13	1	110	51.25	USGS	51.0		
502B	13	1	125	51.40	DSDP	51.4	0.20	6.40
502B	13	1	140	51.55	USGS	53.0		
502B	13	1	149	51.64	DSDP	52.3	0.20	6.50
502B	13	2	20	51.85	USGS	46.0		
502B	13	2	35	52.00	DSDP	50.6	0.20	6.30
502B	13	2	50	52.15	USGS	60.0		
502B	13	2	65	52.30	DSDP	53.7	0.20	6.60
502B	13	2	95	52.60	DSDP	50.1	0.20	6.20
502B	13	2	110	52.75	USGS	48.0		
502B	13	2	125	52.90	DSDP	40.7	0.30	5.10
502B	13	2	140	53.05	USGS	56.0		
502B	13	2	149	53.14	DSDP	57.6	0.30	7.20
502B	13	3	20	53.36	USGS	53.0		
502B	13	3	36	53.52	DSDP	47.1	0.30	5.90
502B	13	3	50	53.66	USGS	44.0		
502B	13	3	66	53.82	DSDP	49.8	0.30	6.20
502B	13	3	96	54.12	DSDP	53.3	0.20	6.60
502B	13	3	110	54.26	USGS	61.0		

*** GRID N 14 ***

*** GRID B 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502B	13	3	126	54.42	DSDP	54.9	0.20	6.80
502B	14	1	20	54.65	USGS	49.0		
502B	14	1	36	54.81	DSDP	48.9	0.20	6.00
502B	14	1	50	54.95	USGS	58.5		
502B	14	1	66	55.11	DSDP	38.5	0.20	4.80
502B	14	1	96	55.41	DSDP	52.3	0.30	6.50
502B	14	1	110	55.55	USGS	53.0		
502B	14	1	126	55.71	DSDP	61.4	0.20	7.60
502B	14	1	140	55.85	USGS	62.0		
502B	14	1	150	55.95	DSDP	53.2	0.30	6.70
502B	14	2	20	56.15	USGS	39.0		
502B	14	2	36	56.31	DSDP	39.4	0.30	5.00
502B	14	2	50	56.45	USGS	54.0		
502B	14	2	66	56.61	DSDP	58.5	0.20	7.20
502B	14	2	110	57.03	USGS	44.0		
502B	14	2	126	57.19	DSDP	37.9	0.20	4.70
502B	14	2	150	57.43	DSDP	41.3	0.30	5.30
502B	14	3	20	57.63	USGS	49.0		
502B	14	3	36	57.79	DSDP	47.3	0.30	6.00
502B	14	3	50	57.93	USGS	46.0		
502B	14	3	66	58.09	DSDP	46.5	0.30	5.80
502B	14	3	96	58.39	DSDP	48.5	0.30	6.10
502B	14	3	110	58.50	USGS	49.5		
502B	15	1	20	59.15	USGS	56.0		
502B	15	1	36	59.31	DSDP	55.5	0.20	6.90
502B	15	1	50	59.45	USGS	57.5		
502B	15	1	66	59.61	DSDP	47.8	0.20	5.90
502B	15	1	96	59.91	DSDP	45.8	0.30	5.80
502B	15	1	110	60.05	USGS	41.5		
502B	15	1	126	60.21	DSDP	55.5	0.30	6.90
502B	15	1	140	60.35	USGS	49.0		
502	16	1	20	61.13	USGS	43.0		
502	16	1	50	61.43	USGS	43.0		
502	16	1	80	61.73	USGS	44.0		
502	16	1	110	62.03	USGS	50.0		
502	16	1	139	62.32	USGS	47.0		
502	16	2	20	62.63	USGS	47.0		
502	16	2	50	62.93	USGS	53.0		
502	16	2	80	63.23	USGS	50.0		
502	16	2	108	63.51	USGS	47.0		
502A	17	1	80	64.30	USGS	58.0		
502A	17	1	110	64.60	USGS	59.0		
502A	17	1	140	64.90	USGS	53.0		
502A	17	2	20	65.21	USGS	49.0		
502	17	1	50	65.80	USGS	48.0		
502	17	1	80	66.10	USGS	55.0		
502	17	1	110	66.40	USGS	46.0		
502	17	1	140	66.70	USGS	50.0		
502	17	2	20	67.00	USGS	56.0		
502	17	2	50	67.30	USGS	46.0		
502	17	2	80	67.60	USGS	47.0		
502	17	2	110	67.90	USGS	53.0		
502B	17	1	20	67.95	USGS	49.5		

*** GRID B 15 ***

*** GRID C 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502B	17	1	50	68.25	USGS	52.0		
502B	17	1	110	68.85	USGS	49.0		
502B	17	1	140	69.15	USGS	55.5		
502B	17	2	20	69.45	USGS	51.0		
502B	17	2	50	69.75	USGS	48.0		
502B	17	2	110	70.35	USGS	44.5		
502B	17	2	140	70.65	USGS	54.0		
502B	17	3	20	70.95	USGS	54.0		
502B	17	3	60	71.35	USGS	54.0		
502B	17	3	110	71.85	USGS	51.0		
502B	18	1	20	72.33	USGS	50.5		
502B	18	1	50	72.63	USGS	49.5		
502B	18	1	110	73.23	USGS	53.0		
502B	18	1	140	73.53	USGS	56.0		
502B	18	2	50	74.14	USGS	51.0		
502B	18	2	110	74.74	USGS	49.0		
502B	18	2	140	75.04	USGS	50.5		
502B	18	3	20	75.34	USGS	51.0		
502B	18	3	50	75.64	USGS	55.0		
502B	18	3	120	76.34	USGS	52.0		
502B	19	1	20	76.75	USGS	44.0		
502B	19	1	50	77.05	USGS	48.0		
502B	19	1	110	77.65	USGS	43.5		
502B	19	1	140	77.95	USGS	49.5		
502B	19	2	20	78.25	USGS	56.0		
502B	19	2	50	78.55	USGS	55.5		
502	20	1	50	78.76	USGS	63.0		
502	20	1	80	79.06	USGS	54.0		
502	20	1	110	79.36	USGS	51.0		
502	20	1	140	79.66	USGS	57.0		
502	20	2	20	79.96	USGS	50.0		
502	20	2	50	80.26	USGS	51.0		
502	20	2	80	80.56	USGS	47.0		
502	20	2	110	80.86	USGS	44.0		
502	20	2	140	81.16	USGS	40.0		
502	20	3	20	81.46	USGS	47.0		
502	20	3	50	81.76	USGS	53.0		
502	20	3	80	82.06	USGS	46.0		
502	21	1	20	82.88	USGS	49.0		
502	21	1	50	83.18	USGS	40.0		
502	21	1	80	83.48	USGS	47.0		
502	21	1	110	83.78	USGS	49.0		
502	21	1	140	84.08	USGS	41.0		
502	21	2	20	84.38	USGS	44.0		
502	21	2	50	84.68	USGS	48.0		
502	21	2	80	84.98	USGS	49.0		
502	21	2	110	85.28	USGS	52.0		
502	21	2	140	85.58	USGS	44.0		
502B	21	1	50	85.74	USGS	44.0		
502B	21	1	110	86.34	USGS	58.5		
502B	21	1	140	86.64	USGS	52.0		
502B	21	2	20	86.94	USGS	52.0		
502B	21	2	50	87.24	USGS	43.5		

*** GRID C 15 ***

*** GRID D 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502	22	1	50	87.70	USGS	41.0		
502	22	1	80	88.00	USGS	49.0		
502	22	1	110	88.30	USGS	55.0		
502	22	1	140	88.60	USGS	55.0		
502	22	2	20	88.89	USGS	44.0		
502	22	2	50	89.19	USGS	38.0		
502	22	2	80	89.49	USGS	47.0		
502	22	2	110	89.79	USGS	51.0		
502	22	3	20	90.01	USGS	55.0		
502	22	3	50	90.31	USGS	43.0		
502	22	3	80	90.61	USGS	47.0		
502	22	3	107	90.88	USGS	49.0		
502	23	2	20	91.91	USGS	40.0		
502	23	2	50	92.21	USGS	44.0		
502	23	2	80	92.51	USGS	39.0		
502	23	2	110	92.81	USGS	40.0		
502	23	2	140	93.11	USGS	45.0		
502	23	3	20	93.41	USGS	40.0		
502	23	3	50	93.71	USGS	[illegible].0		
502	23	3	80	94.01	USGS	49.0		
502	23	3	110	94.31	USGS	43.0		
502	23	3	140	94.61	USGS	45.0		
502	23	4	20	94.91	USGS	43.0		
502	23	4	50	95.21	USGS	48.0		
502	23	4	80	95.51	USGS	37.0		
502A	24	1	110	95.80	USGS	48.0		
502A	24	1	140	96.10	USGS	47.0		
502A	24	2	20	96.41	USGS	45.0		
502A	24	2	50	96.71	USGS	52.0		
502A	24	2	80	97.01	USGS	49.0		
502A	24	2	110	97.31	USGS	57.0		
502A	24	2	140	97.61	USGS	55.0		
502A	24	3	20	97.92	USGS	49.0		
502A	24	3	50	98.22	USGS	47.0		
502A	24	3	80	98.52	USGS	47.0		
502A	24	3	110	98.82	USGS	53.0		
502A	24	3	140	99.12	USGS	40.0		
502A	25	1	20	99.20	USGS	37.0		
502A	25	1	50	99.50	USGS	52.0		
502A	25	1	80	99.80	USGS	47.0		
502A	25	1	110	100.10	USGS	57.0		
502A	25	1	140	100.40	USGS	59.0		
502A	25	2	20	100.72	USGS	52.0		
502A	25	2	50	101.02	USGS	55.0		
502A	25	2	80	101.32	USGS	55.0		
502A	25	2	110	101.62	USGS	57.0		
502A	25	2	140	101.92	USGS	43.0		
502A	25	3	20	102.22	USGS	41.0		
502A	25	3	50	102.52	USGS	56.0		
502A	25	3	80	102.82	USGS	62.0		
502A	25	3	110	103.12	USGS	53.0		
502A	26	1	20	103.63	USGS	56.0		
502A	26	1	50	103.93	USGS	41.0		

*** GRID D 15 ***

*** GRID E 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	26	1	80	104.23	USGS	47.0		
502A	26	1	110	104.53	USGS	39.0		
502A	26	1	140	104.83	USGS	37.0		
502A	26	2	20	105.13	USGS	39.0		
502A	26	2	50	105.43	USGS	44.0		
502A	26	2	80	105.73	USGS	37.0		
502A	26	2	110	106.03	USGS	40.0		
502A	26	2	140	106.33	USGS	37.0		
502A	26	3	20	106.55	USGS	43.0		
502A	26	3	50	106.85	USGS	46.0		
502A	26	3	80	107.15	USGS	39.0		
502A	26	3	110	107.45	USGS	33.0		
502A	26	3	140	107.75	USGS	39.0		
502A	27	1	20	108.10	USGS	35.0		
502A	27	1	50	108.40	USGS	46.0		
502A	27	1	80	108.70	USGS	42.0		
502A	27	1	110	109.00	USGS	36.0		
502A	27	1	140	109.30	USGS	49.0		
502A	27	2	20	109.60	USGS	47.0		
502A	27	2	50	109.90	USGS	32.0		
502A	27	2	80	110.20	USGS	35.0		
502A	27	2	110	110.50	USGS	32.0		
502A	27	2	140	110.80	USGS	39.0		
502A	27	3	20	111.10	USGS	22.0		
502A	27	3	50	111.40	USGS	30.0		
502A	27	3	80	111.70	USGS	38.0		
502A	27	3	110	112.00	USGS	30.0		
502A	28	1	20	112.32	USGS	14.0		
502A	28	1	50	112.62	USGS	27.0		
502A	28	1	80	112.92	USGS	23.0		
502A	28	1	110	113.22	USGS	30.0		
502A	28	1	140	113.52	USGS	29.0		
502A	28	2	20	113.84	USGS	30.0		
502A	28	2	50	114.14	USGS	23.0		
502A	28	2	80	114.44	USGS	38.0		
502A	28	2	110	114.77	USGS	31.0		
502A	28	2	140	115.04	USGS	39.0		
502A	29	1	20	115.50	USGS	31.0		
502A	29	1	50	115.80	USGS	38.0		
502A	29	1	80	116.10	USGS	39.0		
502A	29	1	110	116.40	USGS	27.0		
502A	29	1	140	116.70	USGS	39.0		
502A	29	2	20	117.00	USGS	38.0		
502A	29	2	50	117.30	USGS	24.0		
502A	29	2	80	117.60	USGS	43.0		
502A	29	2	110	117.90	USGS	35.0		
502A	29	2	140	118.20	USGS	43.0		
502A	29	3	20	118.50	USGS	44.0		
502A	30	1	20	118.98	USGS	35.0		
502A	30	1	50	119.28	USGS	51.0		
502A	30	1	90	119.58	USGS	38.0		
502A	30	1	110	119.88	USGS	32.0		
502A	30	1	140	120.18	USGS	26.0		

*** GRID E 15 ***

*** GRID F 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	30	2	20	120.48	USGS	30.0		
502A	30	2	50	120.78	USGS	47.0		
502A	30	2	80	121.08	USGS	49.0		
502A	30	2	110	121.38	USGS	33.0		
502	30	1	140	121.45	USGS	46.0		
502	30	2	20	121.74	USGS	34.0		
502	30	2	50	122.04	USGS	37.0		
502	30	2	80	122.34	USGS	50.0		
502	30	2	110	122.64	USGS	52.0		
502	30	2	140	122.94	USGS	57.0		
502	30	3	20	123.24	USGS	38.0		
502	30	3	50	123.54	USGS	38.0		
502	30	3	80	123.84	USGS	34.0		
502	30	3	105	124.09	USGS	46.0		
502A	32	1	20	124.50	USGS	41.0		
502A	32	1	35	124.65	DSDP	47.9	0.30	6.00
502A	32	1	50	124.80	USGS	34.0		
502A	32	1	65	124.95	DSDP	16.0	0.40	2.30
502A	32	1	80	125.10	USGS	55.0		
502A	32	1	95	125.25	DSDP	51.0	0.30	6.40
502A	32	1	110	125.40	USGS	23.0		
502A	32	1	125	125.55	DSDP	15.6	0.30	2.20
502A	32	1	140	125.70	USGS	12.0		
502A	32	1	150	125.80	DSDP	20.4	0.40	2.80
502A	32	2	20	126.02	USGS	7.0		
502A	32	2	35	126.17	DSDP	20.7	0.30	2.80
502A	32	2	50	126.32	USGS	16.0		
502A	32	2	65	126.47	DSDP	19.6	0.30	2.60
502A	32	2	80	126.62	USGS	11.0		
502A	32	2	95	126.77	DSDP	25.8	0.30	3.40
502A	32	2	110	126.92	USGS	17.0		
502A	32	2	125	127.07	DSDP	25.6	0.30	3.40
502A	32	2	140	127.22	USGS	22.0		
502A	32	2	150	127.32	DSDP	15.4	0.30	2.20
502A	32	3	15	127.48	DSDP	16.4	0.40	2.40
502A	32	3	20	127.53	USGS	22.0		
502A	33	1	35	127.62	DSDP	22.8	0.40	3.10
502A	33	1	50	127.77	USGS	33.0		
502A	33	1	65	127.92	DSDP	20.3	0.30	2.70
502A	33	1	80	128.07	USGS	40.0		
502A	33	1	95	128.22	DSDP	36.1	0.30	4.70
502A	33	1	110	128.37	USGS	47.0		
502A	33	1	125	128.52	DSDP	49.6	0.30	6.20
502A	33	1	140	128.67	USGS	30.0		
502A	33	1	150	128.77	DSDP	47.9	0.30	6.10
502A	33	2	20	128.97	USGS	33.0		
502A	33	2	35	129.12	DSDP	33.1	0.40	4.40
502A	33	2	50	129.27	USGS	34.0		
502A	33	2	65	129.42	DSDP	29.9	0.30	3.90
502A	33	2	80	129.57	USGS	34.0		
502A	33	2	95	129.72	DSDP	41.6	0.30	5.30
502A	33	2	110	129.87	USGS	33.0		
502A	33	2	125	130.02	DSDP	36.9	0.30	4.70

*** GRID F 15 ***

*** GRID G 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	33	2	140	130.17	USGS	42.0		
502A	33	2	150	130.27	DSDP	48.7	0.30	6.10
502A	33	3	4	130.31	DSDP	51.3	0.20	6.40
502A	34	1	20	130.50	USGS	41.0		
502A	34	1	35	130.65	DSDP	36.9	0.30	4.80
502A	34	1	50	130.80	USGS	46.0		
502A	34	1	65	130.95	DSDP	50.2	0.30	6.40
502A	34	1	80	131.10	USGS	34.0		
502A	34	1	95	131.25	DSDP	31.0	0.30	4.10
502A	34	1	110	131.40	USGS	31.0		
502A	34	1	125	131.55	DSDP	35.5	0.40	4.60
502A	34	1	140	131.70	USGS	35.0		
502A	34	1	150	131.80	DSDP	33.3	0.40	4.40
502A	34	2	20	132.00	USGS	34.0		
502A	34	2	35	132.15	DSDP	38.7	0.30	5.00
502A	34	2	50	132.30	USGS	48.0		
502A	34	2	65	132.45	DSDP	44.9	0.30	5.70
502A	34	2	80	132.60	USGS	39.0		
502A	34	2	95	132.75	DSDP	37.8	0.40	4.90
502A	34	2	110	132.90	USGS	39.0		
502A	34	2	125	133.05	DSDP	37.0	0.40	4.80
502A	34	2	140	133.20	USGS	35.0		
502A	34	2	150	133.30	DSDP	39.6	0.30	5.10
502A	35	1	50	133.35	USGS	37.0		
502A	35	1	65	133.50	DSDP	41.6	0.30	5.30
502A	35	1	80	133.65	USGS	48.0		
502A	35	1	95	133.80	DSDP	56.4	0.20	7.00
502A	35	1	110	133.95	USGS	57.0		
502A	35	1	125	134.10	DSDP	53.2	0.30	6.70
502A	35	1	140	134.25	USGS	43.0		
502A	35	1	150	134.35	DSDP	38.8	0.30	5.00
502A	35	2	20	134.55	USGS	28.0		
502A	35	2	35	134.70	DSDP	41.3	0.30	5.20
502A	35	2	50	134.85	USGS	35.0		
502A	35	2	65	135.00	DSDP	36.3	0.40	4.70
502A	35	2	80	135.15	USGS	39.0		
502A	35	2	95	135.30	DSDP	38.8	0.30	5.00
502A	35	2	110	135.45	USGS	43.0		
502A	35	2	125	135.60	DSDP	43.7	0.30	5.60
502A	35	2	140	135.75	USGS	37.0		
502A	35	2	150	135.85	DSDP	40.8	0.30	5.20
502A	35	3	20	136.05	USGS	26.0		
502A	35	3	35	136.20	DSDP	26.4	0.40	3.60
502A	35	3	50	136.35	USGS	38.0		
502A	35	3	65	136.50	DSDP	54.7	0.20	6.80
502A	35	3	80	136.65	USGS	53.0		
502A	35	3	95	136.77	DSDP	53.9	0.30	6.70
502A	36	1	20	136.88	USGS	51.0		
502A	36	1	35	137.03	DSDP	52.5	0.30	6.60
502A	36	1	50	137.18	USGS	49.0		
502A	36	1	65	137.33	DSDP	46.9	0.30	5.90
502A	36	1	80	137.48	USGS	48.0		
502A	36	1	95	137.63	DSDP	58.5	0.20	7.30

*** GRID G 15 ***

*** GRID H 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	36	1	110	137.78	USGS	56.0		
502A	36	1	125	137.93	DSDP	54.2	0.30	6.80
502A	36	1	140	138.08	USGS	48.0		
502A	36	1	150	138.18	DSDP	48.1	0.30	6.10
502A	36	3	20	138.38	USGS	38.0		
502A	36	2	35	138.53	DSDP	45.2	0.30	5.70
502A	36	3	50	138.68	USGS	59.0		
502A	36	2	65	138.83	DSDP	56.0	0.30	7.00
502A	36	3	80	138.98	USGS	46.0		
502A	36	2	90	139.08	DSDP	38.2	0.40	5.00
502A	37	2	20	140.14	USGS	50.0		
502A	37	2	35	140.29	DSDP	57.7	0.20	7.10
502A	37	2	50	140.44	USGS	55.0		
502A	37	2	65	140.59	DSDP	55.0	0.30	6.90
502A	37	2	80	140.74	USGS	52.0		
502A	37	2	100	140.94	DSDP	49.2	0.20	6.20
502A	37	2	110	141.04	USGS	50.0		
502A	37	2	118	141.12	DSDP	52.9	0.30	6.70
502A	38	1	20	141.78	USGS	52.0		
502A	38	1	35	141.93	DSDP	41.3	0.40	5.30
502A	38	1	50	142.08	USGS	45.0		
502A	38	1	65	142.23	DSDP	49.8	0.30	6.30
502A	38	1	80	142.38	USGS	35.0		
502A	38	1	95	142.53	DSDP	37.9	0.30	4.90
502A	38	1	110	142.68	USGS	42.0		
502A	38	1	125	142.83	DSDP	42.0	0.40	5.40
502A	38	1	140	142.98	USGS	38.0		
502A	38	1	150	143.08	DSDP	42.9	0.30	5.50
502A	38	2	5	143.13	DSDP	34.9	0.30	4.50
502A	38	2	20	143.28	USGS	33.0		
502A	39	1	20	143.30	USGS	35.0		
502A	38	2	35	143.43	DSDP	35.8	0.30	4.60
502A	39	1	35	143.45	DSDP	39.7	0.40	5.20
502A	39	1	50	143.60	USGS	39.0		
502A	39	1	66	143.76	DSDP	39.6	0.40	5.10
502A	39	1	80	143.90	USGS	35.0		
502A	39	1	95	144.05	DSDP	43.0	0.40	5.50
502A	39	1	110	144.20	USGS	39.0		
502A	39	1	125	144.35	DSDP	41.7	0.40	5.40
502A	39	1	140	144.50	USGS	37.0		
502A	39	1	150	144.60	DSDP	31.8	0.40	4.20
502A	39	2	20	144.80	USGS	35.0		
502A	39	2	35	144.95	DSDP	43.3	0.60	5.80
502A	39	2	50	145.10	USGS	44.0		
502A	39	2	65	145.25	DSDP	37.1	0.30	4.80
502A	39	2	80	145.40	USGS	45.0		
502A	39	2	95	145.55	DSDP	50.1	0.30	6.30
502A	39	2	110	145.70	USGS	40.0		
502A	39	2	125	145.85	DSDP	45.8	0.20	5.70
502A	40	1	20	146.38	USGS	31.0		
502A	40	1	35	146.53	DSDP	41.0	0.40	5.30
502A	40	1	50	146.68	USGS	49.0		
502A	40	1	65	146.83	DSDP	44.9	0.30	5.70

*** GRID H 15 ***

*** GRID I 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	40	1	80	146.98	USGS	40.0		
502A	40	1	95	147.13	DSDP	46.7	0.30	6.00
502A	40	1	110	147.28	USGS	43.0		
502A	40	1	125	147.43	DSDP	48.0	0.30	6.10
502A	40	1	140	147.58	USGS	45.0		
502A	40	1	150	147.68	DSDP	49.4	0.30	6.20
502A	40	2	20	147.88	USGS	49.0		
502A	40	2	35	148.03	DSDP	46.7	0.40	6.00
502A	40	2	50	148.18	USGS	47.0		
502A	40	2	65	148.33	DSDP	39.2	0.40	5.10
502A	40	2	80	148.48	USGS	29.0		
502A	40	2	95	148.63	DSDP	30.0	0.40	4.00
502A	40	2	110	148.78	USGS	30.0		
502A	41	1	65	148.85	DSDP	38.4	0.30	4.90
502A	41	1	80	149.00	USGS	37.0		
502A	41	1	95	149.15	DSDP	43.1	0.30	5.50
502A	41	1	110	149.30	USGS	44.0		
502A	41	1	125	149.45	DSDP	44.3	0.30	5.60
502A	41	1	140	149.60	USGS	46.0		
502A	41	1	150	149.70	DSDP	48.1	0.40	6.10
502A	41	2	20	149.90	USGS	43.0		
502A	41	2	35	150.05	DSDP	34.7	0.30	4.50
502A	41	2	50	150.20	USGS	39.0		
502A	41	2	65	150.35	DSDP	35.4	0.30	4.60
502A	41	2	80	150.50	USGS	27.0		
502A	41	2	95	150.65	DSDP	33.8	0.40	4.40
502A	41	2	110	150.80	USGS	36.0		
502A	41	2	125	150.95	DSDP	35.3	0.20	4.50
502A	41	2	140	151.10	USGS	32.0		
502A	41	2	150	151.20	DSDP	42.6	0.30	5.40
502A	41	3	15	151.35	DSDP	47.6	0.30	6.00
502A	41	3	20	151.40	USGS	45.0		
502A	42	1	20	152.00	USGS	45.0		
502A	42	1	35	152.15	DSDP	42.5	0.40	5.50
502A	42	1	50	152.30	USGS	35.0		
502A	42	1	65	152.45	DSDP	34.9	0.30	4.50
502A	42	1	80	152.60	USGS	30.0		
502A	42	1	95	152.75	DSDP	27.3	0.50	3.70
502A	42	1	110	152.90	USGS	24.0		
502A	42	1	125	153.05	DSDP	29.8	0.40	4.00
502A	42	1	140	153.20	USGS	33.0		
502A	42	1	150	153.30	DSDP	39.7	0.40	5.10
502A	42	2	20	153.50	USGS	28.0		
502A	42	2	35	153.65	DSDP	33.7	0.30	4.40
502A	42	2	50	153.80	USGS	25.0		
502A	42	2	65	153.95	DSDP	24.0	0.40	3.30
502A	42	2	80	154.10	USGS	25.0		
502A	42	2	95	154.25	DSDP	30.6	0.40	4.10
502A	42	2	110	154.40	USGS	35.0		
502A	43	1	20	154.50	USGS	38.0		
502A	43	1	35	154.65	DSDP	36.1	0.30	4.60
502A	43	1	50	154.80	USGS	35.0		
502A	43	1	65	154.95	DSDP	47.5	0.30	6.00

*** GRID I 15 ***

*** GRID J 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	43	1	80	155.10	USGS	35.0		
502A	43	1	95	155.25	DSDP	25.7	0.30	3.40
502A	43	1	110	155.40	USGS	31.0		
502A	43	1	125	155.55	DSDP	26.5	0.40	3.60
502A	43	1	140	155.65	USGS	20.0		
502A	43	1	150	155.75	DSDP	9.0	0.50	1.60
502A	43	2	20	155.95	USGS	23.0		
502A	43	2	35	156.10	DSDP	30.2	0.40	4.00
502A	43	2	50	156.25	USGS	32.0		
502A	43	2	65	156.40	DSDP	31.7	0.40	4.20
502A	43	2	80	156.55	USGS	33.0		
502A	43	2	95	156.70	DSDP	26.3	0.30	3.50
502A	43	2	100	156.75	DSDP	27.6	0.40	3.70
502A	43	2	110	156.85	USGS	24.0		
502A	43	2	125	157.00	DSDP	28.7	0.30	3.70
502A	44	1	20	157.10	USGS	35.0		
502A	44	1	35	157.25	DSDP	31.1	0.30	4.10
502A	44	1	65	157.55	DSDP	33.1	0.40	4.30
502A	44	1	80	157.70	USGS	31.0		
502A	44	1	95	157.85	DSDP	32.6	0.40	4.30
502A	44	1	110	158.00	USGS	23.0		
502A	44	1	125	158.15	DSDP	11.3	0.20	1.60
502A	44	1	140	158.30	USGS	17.0		
502A	44	1	149	158.39	DSDP	32.5	0.30	4.20
502A	44	2	20	158.60	USGS	30.0		
502A	44	2	35	158.75	DSDP	37.6	0.30	4.80
502A	44	2	50	158.90	USGS	30.0		
502A	44	2	65	159.05	DSDP	24.3	0.30	3.20
502A	44	2	80	159.20	USGS	24.0		
502A	44	2	95	159.35	DSDP	24.1	0.40	3.30
502A	45	1	20	159.88	USGS	17.0		
502A	45	1	35	160.03	DSDP	23.2	0.40	3.10
502A	45	1	50	160.18	USGS	21.0		
502A	45	1	65	160.33	DSDP	31.7	0.40	4.20
502A	45	1	80	160.48	USGS	31.0		
502A	45	1	95	160.63	DSDP	35.7	0.30	4.60
502A	45	1	110	160.78	USGS	33.0		
502A	45	1	125	160.93	DSDP	28.2	0.30	3.70
502A	45	1	140	161.08	USGS	19.0		
502A	45	1	149	161.17	DSDP	30.0	0.30	3.90
502A	45	2	20	161.39	USGS	25.0		
502A	45	2	35	161.54	DSDP	27.8	0.40	3.70
502A	45	2	50	161.69	USGS	23.0		
502A	45	2	65	161.84	DSDP	27.7	0.30	3.60
502A	45	2	78	161.97	USGS	26.0		
502A	46	1	20	162.22	USGS	23.0		
502A	46	1	35	162.37	DSDP	25.0	0.30	3.30
502A	46	1	50	162.52	USGS	38.0		
502A	46	1	65	162.67	DSDP	37.3	0.60	5.00
502A	46	1	80	162.82	USGS	41.0		
502A	46	1	95	162.97	DSDP	41.4	0.30	5.20
502A	46	1	110	163.12	USGS	32.0		
502A	46	1	125	163.27	DSDP	44.9	0.30	5.70

*** GRID J 15 ***

*** GRID K 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	46	1	140	163.42	USGS	36.0		
502A	46	1	149	163.51	DSDP	42.6	0.30	5.40
502A	46	2	20	163.60	USGS	36.0		
502A	46	2	35	163.75	DSDP	29.8	0.30	3.90
502A	46	2	50	163.90	USGS	17.0		
502A	46	2	60	164.00	USGS	23.0		
502A	46	2	65	164.05	DSDP	25.2	0.40	3.40
502A	47	1	35	164.33	DSDP	24.9	0.40	3.30
502A	47	1	50	164.48	USGS	23.0		
502A	47	1	65	164.63	DSDP	20.5	0.40	2.90
502A	47	1	80	164.78	USGS	23.0		
502A	47	1	95	164.93	DSDP	23.2	0.40	3.20
502A	47	1	110	165.08	USGS	16.0		
502A	47	1	125	165.23	DSDP	12.3	0.50	2.00
502A	47	1	140	165.38	USGS	11.0		
502A	47	1	149	165.47	DSDP	21.8	0.50	3.10
502A	47	2	20	165.68	USGS	19.0		
502A	47	2	35	165.83	DSDP	19.0	0.40	2.70
502A	47	2	50	165.98	USGS	26.0		
502A	47	2	65	166.13	DSDP	23.7	0.40	3.20
502A	47	2	80	166.28	USGS	25.0		
502A	47	2	95	166.43	DSDP	25.6	0.50	3.50
502A	47	2	110	166.58	USGS	28.0		
502A	47	2	125	166.73	DSDP	29.1	0.50	4.00
502A	47	2	140	166.88	USGS	13.0		
502A	48	1	20	167.33	USGS	7.0		
502A	48	1	35	167.58	DSDP	21.4	0.40	2.90
502A	48	1	50	167.63	USGS	38.0		
502A	48	1	65	167.88	DSDP	38.7	0.40	5.00
502A	48	1	80	167.93	USGS	30.0		
502A	48	1	95	168.18	DSDP	37.9	0.40	4.90
502A	48	1	110	168.23	USGS	29.0		
502A	48	1	125	168.48	DSDP	30.2	0.40	4.00
502A	48	1	140	168.53	USGS	27.0		
502A	48	1	149	168.72	DSDP	30.2	0.40	4.00
502A	48	2	20	168.83	USGS	29.0		
502A	48	2	32	168.95	DSDP	34.0	0.40	4.50
502A	50	1	20	171.40	USGS	18.0		
502A	50	1	35	171.55	DSDP	21.2	0.40	2.90
502A	50	1	50	171.70	USGS	25.0		
502A	50	1	65	171.85	DSDP	24.4	0.40	3.30
502A	50	1	70	172.00	USGS	21.0		
502A	50	1	95	172.15	DSDP	21.9	0.40	3.00
502A	50	1	110	172.30	USGS	15.0		
502A	50	1	125	172.45	DSDP	18.3	0.40	2.60
502A	50	1	140	172.60	USGS	17.0		
502A	50	1	149	172.69	DSDP	12.9	0.30	1.90
502A	50	2	20	172.89	USGS	16.0		
502A	50	2	35	173.04	DSDP	21.8	0.30	2.90
502A	50	2	50	173.19	USGS	23.0		
502A	50	2	60	173.29	USGS	22.0		
502A	50	2	65	173.34	DSDP	18.6	0.40	2.60
502A	50	2	95	173.64	DSDP	24.3	0.40	3.30

*** GRID K 15 ***

*** GRID L 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	51	1	20	174.50	USGS	32.0		
502A	51	1	35	174.65	DSDP	34.2	0.30	4.40
502A	51	1	50	174.80	USGS	37.0		
502A	51	1	65	174.95	DSDP	46.1	0.30	5.80
502A	51	1	80	175.10	USGS	19.0		
502A	51	1	95	175.25	DSDP	14.5	0.40	2.10
502A	51	1	110	175.40	USGS	23.0		
502A	51	1	125	175.55	DSDP	10.3	0.40	1.70
502A	51	1	140	175.70	USGS	4.0		
502A	51	1	149	175.79	DSDP	7.6	0.40	1.30
502A	51	2	20	176.00	USGS	11.0		
502A	51	2	35	176.15	DSDP	21.8	0.30	3.00
502A	51	2	50	176.30	USGS	14.0		
502A	51	2	55	176.35	DSDP	17.6	0.30	2.40
502A	52	1	20	176.82	USGS	24.0		
502A	52	1	35	176.97	DSDP	14.3	0.30	2.00
502A	52	1	50	177.12	USGS	18.0		
502A	52	1	65	177.27	DSDP	24.6	0.30	3.30
502A	52	1	80	177.42	USGS	19.0		
502A	52	1	95	177.57	DSDP	17.5	0.30	2.40
502A	52	1	110	177.72	USGS	31.0		
502A	52	1	125	177.87	DSDP	29.7	0.30	3.90
502A	52	1	140	178.02	USGS	22.0		
502A	52	1	149	178.11	DSDP	26.1	0.30	3.40
502A	53	1	20	178.70	USGS	22.0		
502A	53	1	35	178.85	DSDP	23.5	0.40	3.30
502A	53	1	50	179.00	USGS	25.0		
502A	53	1	65	179.15	DSDP	35.1	0.30	4.50
502A	53	1	80	179.30	USGS	33.0		
502A	53	1	95	179.45	DSDP	34.0	0.40	4.50
502A	53	1	110	179.60	USGS	32.0		
502A	53	1	125	179.75	DSDP	25.1	0.30	3.30
502A	53	1	140	179.90	USGS	31.0		
502A	53	1	149	179.99	DSDP	33.8	0.30	4.40
502A	54	1	20	180.80	USGS	28.0		
502A	54	1	35	180.95	DSDP	37.0	0.40	4.80
502A	54	1	50	181.10	USGS	29.0		
502A	54	1	65	181.25	DSDP	42.4	0.40	5.50
502A	54	1	80	181.40	USGS	24.0		
502A	54	1	95	181.55	DSDP	38.3	0.30	4.90
502A	54	1	110	181.70	USGS	51.0		
502A	54	1	125	181.85	DSDP	37.1	0.20	4.60
502A	54	1	140	182.00	USGS	33.0		
502A	54	1	149	182.09	DSDP	33.1	0.30	4.30
502A	54	2	20	182.30	USGS	15.0		
502A	54	2	35	182.45	DSDP	37.5	0.20	4.70
502A	54	2	50	182.60	USGS	36.0		
502A	54	2	65	182.75	DSDP	51.8	0.20	6.40
502A	54	2	80	182.90	USGS	39.0		
502A	54	2	92	183.02	DSDP	36.7	0.30	4.70
502A	55	1	20	183.34	USGS	32.0		
502A	55	1	35	183.49	DSDP	27.2	0.30	3.60
502A	55	1	50	183.64	USGS	34.0		

*** GRID L 15 ***

*** GRID M 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	55	1	65	183.79	DSDP	37.3	0.30	4.70
502A	55	1	80	183.94	USGS	32.0		
502A	55	1	95	184.09	DSDP	27.9	0.30	3.60
502A	55	1	110	184.24	USGS	29.0		
502A	55	1	125	184.39	DSDP	27.5	0.10	3.40
502A	55	1	140	184.54	USGS	35.0		
502A	55	1	149	184.63	DSDP	41.6	0.20	5.20
502A	55	2	20	184.85	USGS	33.0		
502A	55	2	35	185.00	DSDP	38.5	0.30	4.90
502A	55	2	48	185.13	USGS	29.0		
502A	56	1	20	185.18	USGS	37.0		
502A	56	1	35	185.33	DSDP	32.3	0.30	4.10
502A	56	1	50	185.48	USGS	25.0		
502A	56	1	65	185.63	DSDP	40.1	0.20	5.00
502A	56	1	80	185.78	USGS	40.0		
502A	56	1	95	185.93	DSDP	39.0	0.20	4.90
502A	56	1	110	186.08	USGS	31.0		
502A	56	1	125	186.23	DSDP	18.4	0.20	2.40
502A	56	1	140	186.38	USGS	35.0		
502A	56	1	149	186.47	DSDP	37.2	0.20	4.70
502A	56	2	20	186.68	USGS	42.0		
502A	56	2	35	186.83	DSDP	45.3	0.20	5.60
502A	56	2	45	186.93	USGS	42.0		
502A	57	1	20	187.30	USGS	44.0		
502A	57	1	35	187.45	DSDP	32.2	0.20	4.10
502A	57	1	50	187.60	USGS	28.0		
502A	57	1	65	187.75	DSDP	14.8	0.20	2.00
502A	57	1	80	187.90	USGS	9.0		
502A	57	1	95	188.05	DSDP	13.9	0.30	2.00
502A	57	1	110	188.20	USGS	35.0		
502A	57	1	125	188.35	DSDP	36.4	0.30	4.60
502A	57	1	140	188.50	USGS	31.0		
502A	57	1	149	188.59	DSDP	30.2	0.20	3.90
502A	57	2	20	188.80	USGS	9.0		
502A	57	2	40	189.00	USGS	23.0		
502A	58	1	35	189.47	DSDP	30.1	0.20	3.80
502A	58	1	50	189.62	USGS	22.0		
502A	58	1	65	189.77	DSDP	18.2	0.30	2.50
502A	58	1	80	189.92	USGS	42.0		
502A	58	1	95	190.07	DSDP	42.7	0.20	5.30
502A	58	1	110	190.22	USGS	36.0		
502A	58	1	125	190.37	DSDP	31.1	0.20	3.90
502A	58	1	140	190.52	USGS	21.0		
502A	58	2	5	190.60	USGS	15.0		
502A	58	1	149	190.61	DSDP	13.5	0.30	1.90
502A	58	2	50	191.05	USGS	30.0		
502A	59	1	5	191.35	USGS	43.0		
502A	59	1	34	191.64	DSDP	36.8	0.30	4.70
502A	60	1	20	193.42	USGS	16.0		
502A	60	1	35	193.57	DSDP	13.4	0.30	1.90
502A	60	1	50	193.72	USGS	0.0		
502A	60	1	65	193.87	DSDP	6.6	0.20	1.00
502A	60	1	80	194.02	USGS	0.0		

*** GRID M 15 ***

*** GRID N 15 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	60	1	95	194.17	DSDP	18.0	0.20	2.40
502A	60	1	110	194.32	USGS	33.0		
502A	60	1	125	194.47	DSDP	26.4	0.20	3.30
502A	60	1	140	194.62	USGS	30.0		
502A	60	1	149	194.71	DSDP	27.0	0.20	3.40
502A	60	2	10	194.82	USGS	34.0		
502A	60	2	20	194.92	DSDP	25.9	0.30	3.40
502A	61	1	35	195.23	DSDP	16.5	0.30	2.30
502A	61	1	50	195.38	USGS	36.0		
502A	61	1	65	195.53	DSDP	33.4	0.20	4.20
502A	61	1	82	195.68	USGS	25.0		
502A	61	1	95	195.83	DSDP	30.0	0.20	3.80
502A	61	1	110	195.98	USGS	46.0		
502A	61	1	125	196.13	DSDP	43.0	0.20	5.30
502A	61	1	140	196.28	USGS	49.0		
502A	61	1	149	196.37	DSDP	45.9	0.20	5.70
502A	62	1	35	197.55	DSDP	25.3	0.30	3.30
502A	62	1	36	197.56	USGS	24.0		
502A	63	1	35	199.42	DSDP	41.2	0.20	5.20
502A	63	1	50	199.57	USGS	53.0		
502A	63	1	65	199.72	DSDP	45.0	0.30	5.70
502A	63	1	80	199.87	USGS	37.0		
502A	63	1	95	200.02	DSDP	21.1	0.30	2.80
502A	63	1	110	200.17	USGS	21.0		
502A	63	1	125	200.32	DSDP	5.7	0.30	1.00
502A	63	1	140	200.47	USGS	18.0		
502A	63	1	149	200.56	DSDP	15.4	0.30	2.20
502A	65	1	20	203.30	USGS	5.0		
502A	65	1	35	203.45	DSDP	14.6	0.30	2.10
502A	65	1	50	203.60	USGS	26.0		
502A	65	1	65	203.75	DSDP	23.7	0.30	3.20
502A	65	1	80	203.90	USGS	19.0		
502A	65	1	95	204.05	DSDP	20.4	0.30	2.70
502A	65	1	110	204.20	USGS	35.0		
502A	65	1	125	204.35	DSDP	34.5	0.30	4.40
502A	65	1	140	204.50	USGS	28.0		
502A	65	1	149	204.59	DSDP	28.9	0.30	3.70
502A	65	2	20	204.82	USGS	40.0		
502A	65	2	35	204.97	DSDP	42.9	0.20	5.30
502A	65	2	50	205.12	USGS	3.0		
502A	66	1	35	205.50	DSDP	29.8	0.30	3.80
502A	66	1	50	205.65	USGS	31.0		
502A	66	1	65	205.80	DSDP	21.7	0.20	2.80
502A	66	1	80	205.95	USGS	31.0		
502A	66	1	95	206.10	DSDP	28.8	0.20	3.70
502A	66	1	110	206.25	USGS	34.0		
502A	66	1	125	206.40	DSDP	18.3	0.30	2.50
502A	66	1	140	206.55	USGS	24.0		
502A	66	1	149	206.64	DSDP	23.4	0.30	3.10
502A	66	2	20	206.85	USGS	19.0		
502A	66	2	29	206.94	DSDP	10.3	0.40	1.70
502A	66	2	50	207.15	USGS	19.0		
502A	67	1	35	207.65	DSDP	19.8	0.40	2.80

*** GRID N 15 ***

*** GRID B 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
502A	67	1	80	207.80	USGS	18.0		
502A	67	1	65	207.95	DSDP	19.2	0.40	2.70
502A	68	1	35	209.15	DSDP	29.7	0.60	4.10
502A	68	1	50	209.30	USGS	0.0		
502A	68	1	65	209.45	DSDP	8.4	0.70	1.80
502A	68	1	70	209.50	USGS	6.0		
502A	68	1	95	209.75	DSDP	7.0	0.60	1.50
502A	68	1	125	210.05	DSDP	6.3	0.60	1.40
502A	68	1	149	210.29	DSDP	14.2	0.60	2.40
502A	68	1	110	210.90	USGS	2.0		
503B	1	1	10	0.08	USGS	56.6	0.52	7.31
503B	1	1	20	0.18	USGS	62.0	0.40	7.84
503B	1	1	30	0.28	USGS	67.6	0.51	8.63
503B	1	1	40	0.38	USGS	67.9	0.40	8.55
503B	1	1	50	0.48	USGS	72.0	0.16	8.80
503B	1	1	60	0.58	USGS	75.0	0.29	9.29
503B	1	1	70	0.68	USGS	74.5	0.28	9.22
503B	1	1	80	0.78	USGS	71.2	0.19	8.74
503B	1	1	90	0.88	USGS	69.3	0.18	8.50
503B	1	1	100	0.98	USGS	39.8	0.48	5.26
503B	1	1	110	1.08	USGS	34.2	0.75	4.85
503B	1	1	120	1.18	USGS	31.0	0.78	4.50
503B	1	1	130	1.28	USGS	32.9	0.50	4.45
503B	1	1	140	1.38	USGS	32.1	0.46	4.31
503B	1	2	6	1.54	USGS	35.5	0.55	4.81
503B	1	2	16	1.64	USGS	43.5	0.14	5.36
503B	1	2	26	1.74	USGS	52.6	0.28	6.60
503B	1	2	36	1.84	USGS	64.9	0.30	8.09
503B	1	2	46	1.94	USGS	68.2	0.20	8.39
503B	1	2	56	2.04	USGS	66.0	0.18	8.10
503B	1	2	66	2.14	USGS	63.1	0.49	8.07
503B	1	2	76	2.24	USGS	54.1	0.58	7.08
503B	1	2	86	2.34	USGS	56.5	0.56	7.34
503B	1	2	96	2.44	USGS	48.2	0.67	6.45
503B	2	1	10	2.88	USGS	53.6	0.39	6.82
503B	2	1	20	2.98	USGS	46.4	0.56	6.13
503B	2	1	30	3.08	USGS	50.0	0.33	6.33
503B	2	1	40	3.18	USGS	37.9	0.70	5.25
503B	2	1	50	3.28	USGS	47.3	0.53	6.21
503B	2	1	60	3.38	USGS	64.6	0.66	8.42
503B	2	1	70	3.48	USGS	70.1	0.38	8.80
503B	2	1	80	3.58	USGS	67.0	0.57	8.61
503B	2	1	90	3.68	USGS	60.1	0.43	7.65
503B	2	1	100	3.78	USGS	45.6	0.58	6.06
503B	2	1	110	3.88	USGS	41.8	0.65	5.67
503B	2	1	120	3.98	USGS	40.6	0.63	5.50
503B	2	1	130	4.08	USGS	40.4	0.54	5.39
503B	2	1	140	4.18	USGS	45.0	0.63	6.03
503B	2	2	10	4.39	USGS	74.8	0.32	9.30
503B	2	2	20	4.49	USGS	77.2	0.17	9.44
503B	2	2	30	4.59	USGS	78.7	0.23	9.67
503B	2	2	40	4.69	USGS	77.6	0.40	9.72
503B	2	2	50	4.79	USGS	75.0	0.45	9.45

*** GRID B 16 ***

*** GRID C 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	2	2	60	4.89	USGS	73.3	0.21	9.01
503B	2	2	70	4.99	USGS	51.7	0.47	6.68
503B	2	2	80	5.09	USGS	46.8	0.54	6.16
503B	2	2	90	5.19	USGS	29.2	0.44	3.95
503B	2	2	100	5.29	USGS	45.3	0.62	6.06
503B	2	2	110	5.39	USGS	62.6	0.14	7.66
503B	2	2	120	5.49	USGS	67.4	0.10	8.19
503B	3	1	30	7.48	USGS	75.5	0.14	9.20
503B	3	1	40	7.58	USGS	72.3	0.05	8.72
503B	3	1	50	7.68	USGS	81.7	0.56	10.37
503B	3	1	60	7.78	USGS	79.1	0.09	9.58
503B	3	1	70	7.88	USGS	68.4	0.30	8.51
503B	3	1	80	7.98	USGS	61.1	0.36	7.69
503B	3	1	90	8.08	USGS	53.1	0.36	6.73
503B	3	1	100	8.18	USGS	44.0	0.53	5.81
503B	3	1	110	8.28	USGS	49.8	0.34	6.32
503B	3	1	120	8.38	USGS	69.4	0.28	8.61
503B	3	1	130	8.48	USGS	57.1	0.28	7.13
503B	3	1	140	8.58	USGS	59.4	0.22	7.35
503B	3	2	10	8.78	USGS	40.7	0.34	5.22
503B	3	2	20	8.88	USGS	31.7	0.78	4.59
503B	3	2	30	8.98	USGS	40.6	0.94	5.81
503B	3	2	40	9.08	USGS	31.9	0.67	4.50
503B	3	2	50	9.18	USGS	31.3	0.61	4.37
503B	3	2	60	9.28	USGS	59.8	0.15	7.33
503B	3	2	70	9.38	USGS	63.6	0.32	7.96
503B	3	2	80	9.48	USGS	69.4	0.19	8.52
503B	3	2	90	9.58	USGS	67.2	0.34	8.41
503B	3	2	100	9.68	USGS	68.7	0.09	8.34
503B	3	2	110	9.78	USGS	72.3	0.48	9.16
503B	3	2	120	9.88	USGS	70.2	0.37	8.80
503B	3	2	130	9.98	USGS	61.6	0.27	7.66
503B	3	2	140	10.08	USGS	56.6	0.39	7.18
503B	3	3	10	10.28	USGS	29.6	0.76	4.31
503B	3	3	20	10.38	USGS	29.2	0.70	4.21
503B	3	3	30	10.48	USGS	20.9	0.69	3.20
503B	3	3	40	10.58	USGS	32.4	0.47	4.36
503B	3	3	50	10.68	USGS	42.0	0.46	5.50
503B	3	3	60	10.78	USGS	51.3	0.22	6.38
503B	3	3	70	10.88	USGS	45.9	0.55	6.06
503B	3	3	80	10.98	USGS	27.3	0.69	3.97
503B	3	3	90	11.08	USGS	21.2	0.83	3.38
503B	3	3	100	11.18	USGS	21.9	0.81	3.44
503B	3	3	110	11.28	USGS	40.9	0.57	5.48
503B	3	3	120	11.38	USGS	29.8	0.76	4.34
503B	4	1	20	11.68	USGS	37.9	0.42	4.97
503B	4	1	30	11.78	USGS	28.7	0.67	4.11
503B	4	1	40	11.88	USGS	32.9	0.76	4.71
503B	4	1	50	11.98	USGS	52.1	0.31	6.56
503B	4	1	60	12.08	USGS	48.1	0.29	6.06
503B	4	1	70	12.18	USGS	44.4	0.60	5.93
503B	4	1	80	12.28	USGS	34.8	0.60	4.78
503B	4	1	90	12.38	USGS	42.8	0.51	5.65

*** GRID C 16 ***

*** GRID D 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	4	1	100	12.48	USGS	51.7	0.56	6.77
503B	4	1	110	12.58	USGS	67.9	0.39	8.54
503B	4	1	120	12.68	USGS	71.7	0.23	8.83
503B	4	1	130	12.78	USGS	64.5	0.20	7.94
503B	4	1	140	12.88	USGS	46.0	0.55	6.07
503B	4	2	10	13.08	USGS	42.2	0.57	5.64
503B	4	2	20	13.18	USGS	28.4	0.55	3.96
503B	4	2	30	13.28	USGS	42.6	0.51	5.62
503B	4	2	40	13.38	USGS	54.0	0.63	7.11
503B	4	2	50	13.48	USGS	66.1	0.25	8.18
503B	4	2	60	13.58	USGS	58.7	0.40	7.45
503B	4	2	70	13.68	USGS	59.6	0.45	7.60
503B	4	2	80	13.78	USGS	60.6	0.35	7.62
503B	4	2	90	13.88	USGS	62.6	0.48	8.00
503B	4	2	100	13.98	USGS	65.7	0.47	8.36
503B	4	2	120	14.18	USGS	48.0	0.60	6.36
503B	4	2	130	14.28	USGS	49.6	0.72	6.68
503B	4	2	140	14.38	USGS	42.2	0.49	5.56
503B	4	3	10	14.59	USGS	35.7	0.67	4.96
503B	4	3	20	14.69	USGS	25.2	0.52	3.54
503B	4	3	30	14.79	USGS	26.2	0.74	3.88
503B	4	3	40	14.89	USGS	37.4	0.70	5.19
503B	4	3	50	14.99	USGS	53.8	0.69	7.15
503B	4	3	60	15.09	USGS	67.2	0.48	8.55
503B	4	3	70	15.19	USGS	74.4	0.16	9.09
503B	4	3	80	15.29	USGS	72.9	0.20	8.95
503B	4	3	90	15.39	USGS	63.1	0.22	7.79
503B	4	3	100	15.49	USGS	50.6	0.40	6.47
503B	5	1	30	16.12	USGS	42.6	0.60	5.71
503B	5	1	40	16.22	USGS	27.9	0.69	4.04
503B	5	1	50	16.32	USGS	35.2	0.54	4.76
503B	5	1	60	16.42	USGS	45.9	0.16	5.67
503B	5	1	70	16.52	USGS	56.6	0.19	6.98
503B	5	1	80	16.62	USGS	61.8	0.36	7.78
503B	5	1	90	16.72	USGS	60.2	0.64	7.87
503B	5	1	100	16.82	USGS	50.0	0.38	6.38
503B	5	1	110	16.92	USGS	49.6	0.37	6.33
503B	5	1	120	17.02	USGS	47.7	0.27	6.00
503B	5	1	130	17.12	USGS	41.7	0.41	5.41
503B	5	1	140	17.22	USGS	51.1	0.48	6.61
503B	5	2	20	17.51	USGS	55.9	0.46	7.17
503B	5	2	30	17.61	USGS	52.3	0.34	6.62
503B	5	2	40	17.71	USGS	42.2	0.57	5.64
503B	5	2	50	17.81	USGS	46.1	0.63	6.16
503B	5	2	60	17.91	USGS	58.1	0.34	7.32
503B	5	2	70	18.01	USGS	64.1	0.34	8.04
503B	5	2	80	18.11	USGS	61.5	0.68	8.06
503B	5	2	90	18.21	USGS	57.6	0.39	7.30
503B	5	2	100	18.31	USGS	38.2	0.90	5.49
503B	5	2	110	18.41	USGS	39.6	0.91	5.66
503B	5	2	120	18.51	USGS	23.9	0.97	3.84
503B	5	2	130	18.61	USGS	18.4	0.92	3.13
503B	5	3	10	18.91	USGS	48.3	0.48	6.28

*** GRID D 16 ***

*** GRID E 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	5	3	20	19.01	USGS	57.9	0.41	7.36
503B	5	3	30	19.11	USGS	57.9	0.32	7.27
503B	5	3	40	19.21	USGS	42.9	0.69	5.84
503B	5	3	50	19.31	USGS	40.4	0.45	5.30
503B	5	3	60	19.41	USGS	63.6	0.16	7.80
503B	5	3	70	19.51	USGS	69.4	0.15	8.48
503B	5	3	80	19.61	USGS	61.3	0.28	7.63
503B	5	3	90	19.71	USGS	51.1	0.32	6.45
503B	5	3	100	19.81	USGS	42.0	0.19	5.23
503B	6	1	110	21.36	USGS	50.0	0.41	6.41
503B	6	1	125	21.51	USGS	46.4	0.57	6.14
503B	6	1	140	21.66	USGS	36.9	0.38	4.81
503B	6	1	149	21.75	USGS	27.7	0.75	4.08
503B	6	2	20	21.96	USGS	55.1	0.37	6.98
503B	6	2	35	22.11	USGS	49.4	0.52	6.45
503B	6	2	65	22.41	USGS	32.2	0.81	4.68
503B	6	2	80	22.56	USGS	32.7	0.82	4.75
503B	6	2	95	22.71	USGS	40.7	0.71	5.60
503B	6	2	110	22.86	USGS	32.7	0.48	4.40
503B	6	2	125	23.01	USGS	36.1	0.72	5.05
503B	6	2	140	23.16	USGS	57.4	0.09	6.98
503B	6	2	149	23.25	USGS	38.0	0.46	5.02
503B	6	3	20	23.47	USGS	37.7	0.29	4.81
503B	6	3	35	23.62	USGS	33.4	0.57	4.58
503B	6	3	50	23.77	USGS	15.0	0.72	2.52
503B	6	3	65	23.92	USGS	37.7	0.73	5.25
503B	6	3	80	24.07	USGS	34.1	0.54	4.63
503B	6	3	95	24.22	USGS	38.9	0.42	5.09
503B	6	3	110	24.37	USGS	35.2	0.58	4.80
503B	6	3	124	24.51	USGS	28.2	0.45	3.83
503A	7	1	20	25.30	USGS	43.0		
503A	7	1	50	25.60	USGS	38.0		
503A	7	1	140	26.05	USGS	31.0		
503A	7	2	20	26.35	USGS	63.0		
503A	7	2	50	26.56	USGS	49.0		
503A	7	2	80	26.86	USGS	45.0		
503A	7	2	110	27.16	USGS	43.0		
503A	7	2	140	27.46	USGS	35.0		
503B	7	3	20	27.94	USGS	12.6	0.72	2.23
503B	7	3	35	28.09	USGS	07.2	0.75	1.61
503B	7	3	50	28.24	USGS	32.6	0.52	4.43
503B	7	3	65	28.39	USGS	45.4	0.62	6.07
503B	7	3	80	28.54	USGS	46.1	0.52	6.05
503B	7	3	95	28.69	USGS	27.0	0.75	3.99
503B	7	3	110	28.84	USGS	32.9	0.48	4.42
503B	8	1	20	29.30	USGS	28.7	0.73	4.17
503B	8	1	35	29.45	USGS	21.3	0.72	3.28
503B	8	1	50	29.60	USGS	27.7	0.81	4.13
503B	8	1	65	29.75	USGS	26.9	0.60	3.83
503B	8	1	80	29.90	USGS	29.8	0.58	4.16
503B	8	1	95	30.05	USGS	20.7	0.68	3.17
503B	8	1	110	30.20	USGS	24.8	0.46	3.44
503B	8	1	125	30.35	USGS	37.2	1.06	5.53

*** GRID E 16 ***

*** GRID F 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	8	1	140	30.50	USGS	34.2	0.55	4.66
503B	8	1	149	30.59	USGS	31.4	0.75	4.52
503B	8	2	20	30.80	USGS	22.7	0.48	3.20
503B	8	2	35	30.95	USGS	39.2	0.47	5.17
503B	8	2	50	31.10	USGS	33.8	0.48	4.54
503B	8	2	65	31.25	USGS	29.7	0.57	4.13
503B	8	2	80	31.40	USGS	40.0	0.59	5.39
503B	8	2	95	31.55	USGS	25.7	0.57	3.66
503B	8	2	110	31.70	USGS	18.6	0.54	2.77
503B	8	2	125	31.85	USGS	14.7	1.05	2.82
503B	8	2	140	32.00	USGS	16.5	0.80	2.78
503B	8	2	149	32.09	USGS	24.1	0.77	3.66
503B	8	3	20	32.31	USGS	10.7	0.66	1.95
503B	8	3	35	32.46	USGS	11.8	0.58	2.00
503B	8	3	50	32.61	USGS	25.7	0.49	3.58
503B	8	3	65	32.76	USGS	25.3	0.55	3.59
503B	8	3	80	32.91	USGS	30.8	0.44	4.14
503B	8	3	95	33.06	USGS	37.7	0.37	4.90
503B	8	3	110	33.12	USGS	36.0	0.36	4.68
503B	8	3	125	33.27	USGS	41.5	0.37	5.35
503A	9	1	50	34.02	USGS	36.0		
503A	9	1	80	34.32	USGS	24.0		
503A	9	1	110	34.62	USGS	28.0		
503A	9	1	140	34.92	USGS	25.0		
503A	9	2	20	35.25	USGS	24.0		
503A	9	2	50	35.45	USGS	22.0		
503A	9	2	80	35.75	USGS	5.0		
503A	9	2	140	36.20	USGS	22.0		
503A	9	3	20	36.35	USGS	26.0		
503A	9	3	50	36.65	USGS	33.0		
503A	9	3	80	36.95	USGS	25.0		
503A	10	1	20	38.20	USGS	55.0		
503A	10	1	50	38.50	USGS	46.0		
503A	10	1	80	38.80	USGS	43.0		
503A	10	1	110	39.10	USGS	26.0		
503A	10	1	140	39.40	USGS	23.0		
503A	10	2	20	39.62	USGS	47.0		
503B	10	2	50	39.97	USGS	47.4	0.25	5.94
503B	10	2	65	40.12	USGS	59.9	0.46	7.65
503B	10	2	80	40.27	USGS	67.6	0.29	8.40
503B	10	2	95	40.42	USGS	50.1	0.44	6.46
503B	10	2	110	40.57	USGS	40.7	0.37	5.25
503B	10	2	140	40.87	USGS	38.2	0.42	5.00
503A	10	3	20	41.13	USGS	42.0		
503A	10	3	50	41.43	USGS	50.0		
503A	11	1	20	42.52	USGS	46.0		
503A	11	1	50	42.82	USGS	35.0		
503B	11	1	80	43.20	USGS	40.6	0.48	5.35
503B	11	1	110	43.50	USGS	28.7	0.62	4.06
503B	11	2	80	44.47	USGS	53.6	0.67	7.10
503B	11	2	110	44.77	USGS	57.2	0.85	7.72
503B	11	2	140	45.07	USGS	39.6	0.64	5.39
503B	11	3	20	45.37	USGS	43.6	0.76	5.99

*** GRID F 16 ***

*** GRID G 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	11	3	35	45.52	USGS	65.4	0.40	8.25
503B	11	3	50	45.67	USGS	66.8	0.46	8.48
503B	11	3	65	45.82	USGS	49.0	0.29	6.17
503B	11	3	80	45.97	USGS	40.3	0.78	5.62
503B	11	3	95	46.12	USGS	44.6	0.38	5.74
503B	11	3	110	46.27	USGS	55.0	0.73	7.33
503B	11	3	125	46.42	USGS	42.5	0.67	5.77
503B	11	3	140	46.57	USGS	33.7	0.94	4.98
503B	12	1	20	47.00	USGS	14.2	0.79	2.50
503B	12	1	50	47.30	USGS	5.1	0.73	1.34
503B	12	1	80	47.60	USGS	22.9	0.62	3.37
503B	12	1	110	47.90	USGS	14.2	0.85	2.55
503B	12	1	140	48.20	USGS	18.5	0.68	2.90
503B	12	2	20	48.50	USGS	6.1	0.73	1.46
503B	12	2	50	48.80	USGS	26.7	0.60	3.80
503B	12	2	80	49.10	USGS	42.1	0.48	5.54
503B	12	2	95	49.25	USGS	25.7	0.29	3.37
503B	12	2	110	49.40	USGS	16.2	1.24	3.19
503B	12	2	125	49.55	USGS	15.7	0.55	2.44
503B	12	2	140	49.70	USGS	30.7	0.83	4.52
503B	12	2	149	49.79	USGS	30.7	0.48	4.16
503B	12	3	20	50.00	USGS	11.2	0.59	1.93
503B	12	3	35	50.15	USGS	21.6	0.40	2.99
503B	12	3	50	50.30	USGS	49.5	0.39	6.33
503B	12	3	65	50.45	USGS	36.2	0.46	4.81
503B	12	3	80	50.60	USGS	20.1	0.78	3.19
503B	13	1	80	51.95	USGS	51.1	0.45	6.59
503B	13	1	110	52.25	USGS	29.4	0.53	4.06
503B	13	1	140	52.55	USGS	71.6	0.20	8.79
503B	13	2	20	52.85	USGS	49.8	0.57	6.55
503B	13	2	50	53.15	USGS	27.6	0.93	4.24
503B	13	2	80	53.45	USGS	31.2	0.89	4.63
503B	13	2	95	53.60	USGS	33.2	0.30	4.28
503B	13	2	110	53.75	USGS	39.7	0.82	5.58
503B	13	2	140	54.05	USGS	40.7	0.47	5.36
503B	13	3	20	54.35	USGS	35.0	0.52	4.72
503B	13	3	35	54.50	USGS	38.1	0.43	5.00
503B	13	3	50	54.65	USGS	42.2	0.54	5.61
503A	13	3	80	54.90	USGS	50.0		
503A	13	3	110	55.20	USGS	47.0		
503B	14	1	65	55.85	USGS	42.6	0.56	5.67
503B	14	1	80	56.00	USGS	45.1	0.43	5.85
503B	14	1	95	56.15	USGS	39.7	0.53	5.30
503B	14	1	110	56.30	USGS	33.0	0.37	4.33
503B	14	1	125	56.45	USGS	40.7	0.51	5.40
503B	14	1	140	56.60	USGS	48.0	0.73	6.49
503B	14	1	149	56.69	USGS	43.8	0.36	5.62
503B	14	2	20	56.91	USGS	47.8	0.38	6.12
503B	14	2	35	57.06	USGS	53.9	0.22	6.69
503B	14	2	50	57.21	USGS	33.7	0.58	4.62
503B	14	2	65	57.36	USGS	30.8	0.57	4.27
503B	14	2	80	57.51	USGS	58.7	0.62	7.67
503B	14	2	95	57.66	USGS	46.9	0.49	6.12

*** GRID G 16 ***

*** GRID H 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	14	2	110	57.81	USGS	45.2	0.43	5.86
503B	14	2	125	57.96	USGS	56.6	0.24	7.04
503B	14	2	140	58.11	USGS	50.6	0.52	6.59
503B	14	2	149	58.20	USGS	42.4	0.33	5.42
503B	14	3	20	58.42	USGS	55.5	0.21	6.87
503B	14	3	35	58.57	USGS	44.9	0.29	5.68
503B	14	3	50	58.72	USGS	54.7	0.43	7.00
503B	14	3	65	58.87	USGS	53.9	0.38	6.85
503B	14	3	80	59.02	USGS	42.2	0.30	5.37
503B	15	1	50	60.15	USGS	26.7	0.70	3.90
503B	15	1	65	60.29	USGS	42.0	0.38	5.42
503B	15	1	80	60.45	USGS	37.6	0.50	5.01
503B	15	1	95	60.59	USGS	55.1	0.11	6.73
503B	15	1	110	60.75	USGS	50.7	0.30	6.39
503B	15	1	125	60.89	USGS	46.1	0.24	5.78
503B	15	1	140	61.05	USGS	45.7	0.49	5.98
503B	15	1	149	61.13	USGS	52.3	0.30	6.58
503B	15	2	20	61.35	USGS	48.6	0.30	6.14
503B	15	2	35	61.50	USGS	33.5	0.43	4.45
503B	15	2	50	61.65	USGS	18.2	0.74	2.92
503B	15	2	65	61.80	USGS	33.0	0.67	4.63
503B	15	2	80	61.95	USGS	52.0	0.49	6.73
503B	15	2	95	62.10	USGS	45.2	0.43	5.86
503B	15	2	110	62.25	USGS	36.1	0.22	4.55
503B	15	2	125	62.40	USGS	33.9	0.18	4.25
503B	15	2	140	62.55	USGS	30.7	0.43	4.12
503B	15	3	20	62.85	USGS	22.8	0.49	3.23
503B	15	3	35	63.00	USGS	39.5	0.29	5.03
503B	15	3	50	63.15	USGS	31.7	0.34	4.14
503B	15	3	65	63.30	USGS	30.5	0.41	4.07
503B	15	3	80	63.45	USGS	34.5	0.41	4.55
503B	15	3	95	63.60	USGS	37.6	0.45	4.96
503B	15	3	110	63.75	USGS	35.7	0.49	4.78
503B	16	1	35	64.60	USGS	40.4	0.21	5.06
503B	16	1	50	64.75	USGS	47.4	0.24	5.93
503B	16	1	65	64.90	USGS	46.6	0.11	5.70
503B	16	1	80	65.05	USGS	49.2	0.35	6.26
503B	16	1	95	65.20	USGS	59.9	0.55	7.74
503B	16	1	110	65.35	USGS	51.6	0.51	6.70
503B	16	1	125	65.50	USGS	44.2	0.45	5.76
503B	16	1	140	65.65	USGS	50.4	0.69	6.74
503B	16	1	149	65.74	USGS	65.6	0.31	8.19
503B	16	2	20	65.94	USGS	40.4	0.63	5.48
503B	16	2	35	66.09	USGS	38.5	0.65	5.27
503B	16	2	50	66.24	USGS	14.2	0.76	2.46
503B	16	2	65	66.39	USGS	27.6	0.49	3.80
503B	16	2	80	66.54	USGS	40.5	0.56	5.42
503B	16	2	95	66.69	USGS	47.4	0.28	5.96
503B	16	2	110	66.84	USGS	53.5	0.17	6.59
503B	16	2	125	66.99	USGS	49.6	0.27	6.23
503B	16	2	140	67.14	USGS	59.7	0.04	7.21
503B	16	2	149	67.23	USGS	53.2	0.26	6.65
503B	16	3	20	67.44	USGS	24.5	0.36	3.30

*** GRID H 16 ***

*** GRID I 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	16	3	35	67.59	USGS	30.1	0.31	3.92
503B	16	3	50	67.74	USGS	54.8	0.58	7.16
503B	16	3	65	67.89	USGS	55.1	0.44	7.05
503B	16	3	80	68.04	USGS	53.2	0.32	6.71
503B	16	3	95	68.19	USGS	50.1	0.57	6.59
503B	16	3	110	68.34	USGS	57.0	0.25	7.09
503B	17	1	20	68.90	USGS	55.8	0.35	7.05
503B	17	1	35	69.05	USGS	55.6	0.32	6.99
503B	17	1	50	69.20	USGS	38.0	0.17	4.73
503B	17	1	65	69.35	USGS	29.5	0.56	4.10
503B	17	1	80	69.50	USGS	52.9	0.13	6.48
503B	17	1	95	69.65	USGS	49.5	0.12	6.06
503B	17	1	110	69.80	USGS	37.8	0.28	4.82
503B	17	1	125	69.95	USGS	42.7	0.07	5.21
503B	17	1	140	70.10	USGS	52.6	0.32	6.63
503B	17	1	149	70.19	USGS	47.4	0.30	5.99
503B	17	2	20	70.41	USGS	44.1	0.34	5.64
503B	17	2	35	70.56	USGS	47.3	0.38	6.05
503B	17	2	50	70.71	USGS	42.0	0.36	5.40
503B	17	2	65	70.86	USGS	32.8	0.25	4.19
503B	17	2	80	71.01	USGS	20.7	0.55	3.04
503B	17	2	95	71.16	USGS	37.2	0.49	4.96
503B	17	2	110	71.31	USGS	41.3	0.41	5.37
503B	17	2	125	71.46	USGS	25.9	0.29	3.40
503B	17	2	137	71.58	USGS	36.9	0.29	4.72
503B	17	2	149	71.70	USGS	34.1	0.32	4.41
503B	17	3	20	71.91	USGS	24.7	0.48	3.44
503B	17	3	35	72.06	USGS	27.9	0.33	3.68
503B	17	3	50	72.19	USGS	37.0	0.53	4.97
503B	17	3	65	72.34	USGS	36.2	0.29	4.61
503B	18	1	20	73.40	USGS	49.5	0.44	6.38
503B	18	1	35	73.55	USGS	37.2	0.26	4.72
503B	18	1	50	73.70	USGS	27.2	0.38	3.64
503B	18	1	65	73.85	USGS	24.2	0.18	3.09
503B	18	1	80	74.00	USGS	16.7	0.59	2.59
503B	18	1	95	74.15	USGS	14.9	0.50	2.29
503B	18	1	110	74.30	USGS	14.3	0.57	2.29
503B	18	1	125	74.45	USGS	14.4	0.34	2.07
503B	18	1	140	74.60	USGS	52.6	0.27	6.58
503B	18	1	149	74.69	USGS	43.3	0.49	5.69
503B	18	2	20	74.90	USGS	61.0	0.21	7.53
503B	18	2	35	75.05	USGS	46.4	0.24	5.81
503B	18	2	50	75.20	USGS	27.4	0.25	3.54
503B	18	2	65	75.35	USGS	13.8	0.44	2.10
503B	18	2	80	75.50	USGS	37.2	0.44	4.90
503B	18	2	95	75.65	USGS	45.1	0.18	5.60
503B	18	2	110	75.80	USGS	40.2	0.35	5.17
503B	18	2	125	75.95	USGS	52.7	0.22	6.55
503B	18	2	140	76.10	USGS	56.0	0.44	7.16
503B	18	2	149	76.19	USGS	51.2	0.12	6.27
503B	18	3	20	76.41	USGS	30.8	0.38	4.08
503B	18	3	35	76.56	USGS	21.5	0.29	2.87
503B	18	3	50	76.71	USGS	23.0	0.32	3.08

*** GRID I 16 ***

*** GRID J 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	18	3	65	76.86	USGS	30.2	0.22	3.85
503B	18	3	95	77.16	USGS	49.1	0.39	6.28
503B	18	3	110	77.31	USGS	38.5	0.47	5.09
503B	18	3	125	77.46	USGS	58.3	0.46	7.46
503B	18	3	140	77.61	USGS	53.7	0.41	6.86
503B	19	1	95	78.35	USGS	29.2	0.30	3.81
503B	19	1	110	78.51	USGS	31.9	0.67	4.50
503B	19	1	125	78.65	USGS	23.0	0.14	2.90
503B	19	1	140	78.81	USGS	39.0	0.48	5.16
503B	19	1	149	78.89	USGS	44.6	0.27	5.63
503B	19	2	20	79.11	USGS	23.7	0.39	3.24
503B	19	2	35	79.26	USGS	7.6	0.38	1.29
503B	19	2	50	79.41	USGS	8.3	0.61	1.61
503B	19	2	65	79.56	USGS	28.6	0.28	3.71
503B	19	2	80	79.71	USGS	27.9	0.56	3.91
503B	19	2	95	79.86	USGS	34.2	0.26	4.37
503B	19	2	125	80.16	USGS	31.1	0.23	3.96
503B	19	2	140	80.31	USGS	39.6	0.27	5.02
503B	19	3	20	80.61	USGS	25.3	0.40	3.44
503B	19	3	35	80.76	USGS	5.6	0.30	0.97
503B	19	3	50	80.91	USGS	11.0	0.42	1.74
503B	20	2	20	82.17	USGS	33.7	0.36	4.40
503B	20	2	37	82.34	USGS	13.5	0.38	2.01
503B	20	2	50	82.47	USGS	11.3	0.54	1.90
503B	20	2	65	82.62	USGS	8.6	0.36	1.40
503B	20	2	80	82.77	USGS	8.0	0.55	1.51
503B	20	2	95	82.92	USGS	7.6	0.53	1.44
503B	20	2	110	83.07	USGS	12.2	0.49	1.95
503B	20	2	125	83.22	USGS	16.2	0.51	2.45
503B	20	2	140	83.37	USGS	13.7	0.39	2.03
503B	20	2	149	83.46	USGS	17.1	0.46	2.51
503B	20	3	20	83.67	USGS	25.2	0.42	3.44
503B	20	3	35	83.82	USGS	23.9	0.57	3.44
503B	20	3	50	83.97	USGS	14.2	0.48	2.18
503B	20	3	66	84.13	USGS	12.0	0.47	1.91
503B	20	3	80	84.27	USGS	65.5	0.28	8.14
503B	20	3	95	84.42	USGS	67.0	0.48	8.52
503B	20	3	110	84.57	USGS	73.0	0.41	9.17
503A	20	3	20	84.74	USGS	69.0		
503A	20	3	50	85.04	USGS	65.0		
503A	20	3	80	85.34	USGS	65.0		
503A	20	3	110	85.64	USGS	66.0		
503A	20	3	140	85.94	USGS	26.0		
503A	21	1	20	86.40	USGS	52.0		
503B	21	1	20	86.55	USGS	53.7	0.25	6.70
503B	21	1	35	86.70	USGS	46.6	0.59	6.19
503B	21	1	50	86.85	USGS	46.0	0.24	5.76
503B	21	1	65	87.00	USGS	54.8	0.68	7.25
503B	21	1	80	87.15	USGS	40.6	0.31	5.18
503B	21	1	95	87.30	USGS	35.5	0.34	4.60
503B	21	1	110	87.45	USGS	43.0	0.29	5.45
503B	21	1	125	87.60	USGS	46.2	0.46	6.01
503B	21	1	140	87.75	USGS	48.9	0.19	6.06

*** GRID J 16 ***

*** GRID K 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	21	1	149	87.84	USGS	53.8	0.43	6.89
503B	21	2	20	88.05	USGS	43.1	0.27	5.45
503B	21	2	35	88.20	USGS	42.7	0.39	5.52
503B	21	2	50	88.35	USGS	57.2	0.47	7.34
503B	21	2	65	88.50	USGS	60.0	0.37	7.57
503B	21	2	80	88.65	USGS	57.8	0.26	7.20
503B	21	2	95	88.80	USGS	54.6	0.23	6.78
503B	21	2	110	88.95	USGS	64.3	0.22	7.94
503B	21	2	125	89.10	USGS	63.1	0.43	8.00
503B	21	2	140	89.25	USGS	50.8	0.45	6.55
503B	21	3	20	89.55	USGS	56.1	0.16	6.90
503B	21	3	35	89.70	USGS	64.5	0.40	8.15
503B	21	3	50	89.85	USGS	59.2	0.33	7.44
503B	21	3	65	90.00	USGS	51.6	0.27	6.47
503B	21	3	80	90.15	USGS	54.6	0.27	6.83
503B	21	3	95	90.30	USGS	47.4	0.12	5.81
503B	21	3	110	90.45	USGS	22.3	0.53	3.21
503B	21	3	125	90.60	USGS	29.4	0.23	3.76
503B	21	3	140	90.75	USGS	51.2	0.39	6.54
503B	22	1	35	90.90	USGS	49.8	0.11	6.09
503B	22	1	50	91.05	USGS	54.9	0.36	6.95
503B	22	1	65	91.20	USGS	53.5	0.20	6.62
503B	22	1	80	91.35	USGS	63.9	0.39	8.06
503B	22	1	95	91.50	USGS	56.6	0.50	7.30
503B	22	1	110	91.65	USGS	51.8	0.38	6.60
503B	22	1	125	91.80	USGS	40.6	0.47	5.34
503B	22	1	140	91.95	USGS	40.7	0.41	5.30
503B	22	1	149	92.04	USGS	30.4	0.36	4.01
503B	22	2	20	92.25	USGS	23.7	0.69	3.53
503B	22	2	35	92.40	USGS	25.3	0.39	3.43
503B	22	2	50	92.55	USGS	33.5	0.55	4.57
503B	22	2	65	92.70	USGS	22.4	0.26	2.95
503B	22	2	80	92.85	USGS	39.5	0.61	5.35
503B	22	2	95	93.00	USGS	41.2	0.25	5.19
503B	22	2	110	93.15	USGS	48.0	0.32	6.08
503B	22	2	125	93.30	USGS	29.5	0.33	3.87
503B	22	2	140	93.45	USGS	18.1	0.49	2.66
503B	22	2	149	93.54	USGS	17.4	0.34	2.43
503B	22	3	20	93.75	USGS	46.5	0.63	6.21
503B	22	3	35	93.90	USGS	42.9	0.35	5.50
503B	22	3	50	94.05	USGS	45.2	0.47	5.90
503B	22	3	65	94.20	USGS	61.1	0.15	7.48
503B	22	3	80	94.35	USGS	58.5	0.27	7.29
503B	22	3	95	94.50	USGS	60.3	0.20	7.44
503B	22	3	110	94.65	USGS	62.8	.06	7.48
503B	22	3	125	94.80	USGS	62.0	0.08	7.52
503B	22	3	140	94.95	USGS	51.2	0.57	6.72
503B	24	1	50	99.65	USGS	60.9	0.20	7.51
503B	24	1	65	99.80	USGS	73.0	0.20	8.96
503B	24	1	80	99.95	USGS	65.9	0.26	8.17
503B	24	1	95	100.10	USGS	74.4	0.16	9.09
503B	24	1	110	100.25	USGS	71.6	0.48	9.08
503B	24	1	125	100.40	USGS	34.6	0.22	4.37

*** GRID K 16 ***

*** GRID L 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503B	24	1	140	100.55	USGS	40.6	0.50	5.37
503B	24	1	149	100.64	USGS	42.1	0.34	5.40
503B	24	2	18	100.83	USGS	61.3	0.56	7.92
503B	24	2	35	101.00	USGS	60.4	0.24	7.49
503B	24	2	50	101.15	USGS	62.5	0.20	7.70
503B	24	2	65	101.30	USGS	33.4	0.21	4.22
503B	24	2	80	101.45	USGS	50.1	0.33	6.35
503A	24	2	20	101.51	USGS	47.0		
503A	24	2	50	101.81	USGS	14.0		
503A	24	2	80	102.11	USGS	63.0		
503A	24	2	110	102.41	USGS	70.0		
503A	24	2	140	102.71	USGS	31.0		
503A	24	3	20	103.03	USGS	53.0		
503A	24	3	50	103.33	USGS	52.0		
503A	24	3	80	103.63	USGS	45.0		
503B	25	1	65	104.31	USGS	77.0	0.28	9.24
503B	25	1	95	104.56	USGS	72.7	0.41	9.13
503B	25	1	125	104.79	USGS	70.7	0.71	9.19
503B	25	1	149	105.03	USGS	56.5	0.57	7.35
503B	25	2	20	105.24	USGS	43.5	0.94	6.16
503B	25	2	35	105.39	USGS	45.5	0.33	5.79
503B	25	2	50	105.49	USGS	63.4	0.68	8.29
503B	25	2	65	105.62	USGS	63.1	0.15	7.73
503B	25	2	80	105.77	USGS	62.4	0.25	7.74
503B	25	2	95	105.88	USGS	67.2	0.21	8.28
503B	25	2	110	106.01	USGS	77.5	0.16	9.46
503B	26	2	35	108.10	USGS	75.3	0.43	9.47
503B	26	2	65	108.40	USGS	55.9	0.46	7.17
503B	26	2	80	108.55	USGS	62.3	0.26	7.74
503B	26	2	95	108.70	USGS	76.7	0.04	9.24
503B	26	2	110	108.85	USGS	74.7	0.07	9.04
503B	26	2	125	109.00	USGS	79.3	0.39	9.91
503A	29	1	20	120.80	USGS	64.0		
503A	29	1	50	121.10	USGS	17.0		
503A	29	1	80	121.40	USGS	52.0		
503A	29	1	110	121.70	USGS	35.0		
503A	29	1	140	122.00	USGS	44.0		
503A	29	2	20	122.30	USGS	35.0		
503A	29	2	50	122.60	USGS	39.0		
503A	29	2	80	122.90	USGS	63.0		
503A	29	2	110	123.20	USGS	35.0		
503A	29	2	140	123.50	USGS	60.0		
503A	29	3	20	123.81	USGS	37.0		
503A	29	3	50	124.11	USGS	44.0		
503A	29	3	80	124.41	USGS	63.0		
503A	30	1	50	125.38	USGS	48.0		
503A	30	1	80	125.68	USGS	52.0		
503A	30	1	110	125.98	USGS	62.0		
503A	30	1	140	126.28	USGS	38.0		
503A	30	2	20	126.58	USGS	65.0		
503A	30	2	50	126.88	USGS	65.0		
503A	30	2	80	127.18	USGS	67.0		
503A	30	2	110	127.48	USGS	69.0		

*** GRID L 16 ***

*** GRID M 16 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503A	31	1	80	130.20	USGS	40.0		
503A	31	1	110	130.50	USGS	30.0		
503A	31	1	140	130.80	USGS	66.0		
503A	31	2	20	131.05	USGS	53.0		
503A	31	2	50	131.35	USGS	63.0		
503A	31	2	80	131.65	USGS	37.0		
503A	31	2	110	131.95	USGS	57.0		
503A	31	2	140	132.25	USGS	52.0		
503A	31	3	20	132.55	USGS	42.0		
503A	31	3	50	132.85	USGS	44.0		
503A	31	3	80	133.15	USGS	54.0		
503A	31	3	110	133.45	USGS	52.0		
503A	31	3	140	133.78	USGS	60.0		
503A	34	2	20	144.03	USGS	48.0		
503A	34	2	50	144.33	USGS	66.0		
503A	34	2	80	144.63	USGS	58.0		
503A	34	2	110	144.93	USGS	2.0		
503A	34	2	140	145.23	USGS	41.0		
503A	34	3	20	145.54	USGS	51.0		
503A	34	3	50	145.84	USGS	41.0		
503A	36	1	20	151.60	USGS	65.0		
503A	36	1	50	151.90	USGS	69.0		
503A	36	1	80	152.11	USGS	63.0		
503A	36	1	110	152.41	USGS	31.0		
503A	36	1	140	152.71	USGS	49.0		
503A	36	2	20	153.01	USGS	65.0		
503A	36	2	50	153.31	USGS	60.0		
503A	36	2	80	153.61	USGS	62.0		
503A	36	2	110	153.91	USGS	63.0		
503A	36	3	20	154.37	USGS	56.0		
503A	37	1	50	156.23	USGS	66.0		
503A	37	1	80	156.53	USGS	68.0		
503A	37	1	110	156.83	USGS	77.0		
503A	37	1	140	157.13	USGS	74.0		
503A	37	2	20	157.44	USGS	41.0		
503A	37	2	50	157.74	USGS	62.0		
503A	37	2	80	158.04	USGS	65.0		
503A	37	2	110	158.34	USGS	71.0		
503A	39	1	110	165.50	USGS	73.0		
503A	39	1	140	165.80	USGS	60.0		
503A	39	2	20	166.10	USGS	63.0		
503A	39	2	50	166.40	USGS	62.0		
503A	39	2	80	166.70	USGS	58.0		
503A	39	2	110	167.00	USGS	43.0		
503A	39	2	140	167.30	USGS	48.0		
503A	40	1	50	169.26	USGS	64.0		
503A	40	1	80	169.56	USGS	48.0		
503A	40	1	110	169.86	USGS	54.0		
503A	41	1	20	173.60	USGS	31.0		
503A	41	1	50	173.90	USGS	32.0		
503A	41	1	80	174.20	USGS	41.0		
503A	41	1	110	174.50	USGS	30.0		
503A	41	1	140	174.80	USGS	44.0		

*** GRID M 16 ***

GRID TABLE

B 01
C 01 1: Shear Vane
D 01
E 01
F 01
G 01
H 01 2: Penetrometer
I 01
J 01
K 01
L 01
M 01
N 01
B 02
C 02
D 02
E 02
F 02
G 02
H 02
I 02
J 02
K 02
L 02
M 02
N 02
B 03
C 03
D 03 3: Sonic Velocity
E 03
F 03
G 03
H 03
I 03
J 03
K 03
L 03
M 03
N 03
B 04
C 04
D 04
E 04
F 04
G 04
H 04
I 04
J 04
K 04 4: Gravimetric Chemistry
L 04
M 04
N 04

GRID TABLE

B 05
C 05
D 05
E 05
F 05
G 05 5: Sediment Paleomagneti
H 05
I 05
J 05
K 05
L 05
M 05
N 05
B 06
C 06
D 06
E 06
F 06
G 06
H 06
I 06
J 06
K 06
L 06
M 06
N 06
B 07
C 07
D 07
E 07
F 07
G 07
H 07
I 07
J 07
K 07
L 07
M 07
N 07
B 08
C 08
D 08
E 08
F 08
G 08
H 08
I 08
J 08
K 08
L 08
M 08
N 08

GRID TABLE

B 09
C 09
D 09
E 09
F 09
G 09
H 09
I 09
J 09
K 09
L 09
M 09
N 09
B 10
C 10
D 10
E 10
F 10
G 10
H 10
I 10
J 10
K 10
L 10
M 10
N 10
B 11
C 11
D 11
E 11
F 11
G 11
H 11
I 11
J 11
K 11
L 11
M 11
N 11
B 12
C 12
D 12
E 12
F 12
G 12
H 12
I 12
J 12
K 12
L 12
M 12
N 12

GRID TABLE

B 13
C 13
D 13
E 13
F 13
G 13
H 13
I 13
J 13
K 13
L 13
M 13
N 13
B 14
C 14
D 14
E 14
F 14
G 14
H 14
I 14 6: Carbon-Carbonate
J 14
K 14
L 14
M 14
N 14
B 15
C 15
D 15
E 15
F 15
G 15
H 15
I 15
J 15
K 15
L 15
M 15
N 15
B 16
C 16
D 16
E 16
F 16
G 16
H 16
I 16
J 16
K 16
L 16
M 16

*** GRID B 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503A	41	2	20	175.10	USGS	59.0		
503A	41	2	50	175.40	USGS	52.0		
503A	41	2	80	175.70	USGS	28.0		
503A	41	2	110	176.00	USGS	59.0		
503A	41	2	140	176.30	USGS	41.0		
503A	41	3	20	176.61	USGS	49.0		
503A	41	3	50	176.91	USGS	56.0		
503A	41	3	80	177.21	USGS	52.0		
503A	41	3	110	177.51	USGS	63.0		
503A	42	1	20	178.00	USGS	63.0		
503A	42	1	50	178.30	USGS	55.0		
503A	42	1	80	178.60	USGS	47.0		
503A	42	1	110	178.90	USGS	48.0		
503A	42	1	140	179.20	USGS	34.0		
503A	42	2	20	179.51	USGS	42.0		
503A	42	2	50	179.81	USGS	44.0		
503A	42	2	80	180.11	USGS	57.0		
503A	42	2	110	180.41	USGS	47.0		
503A	42	2	140	180.71	USGS	68.0		
503A	42	3	20	181.02	USGS	62.0		
503A	42	3	50	181.31	USGS	55.0		
503A	43	1	20	182.35	USGS	53.0		
503A	43	1	50	182.65	USGS	51.0		
503A	43	1	80	182.95	USGS	53.0		
503A	43	1	110	183.25	USGS	51.0		
503A	43	1	140	183.55	USGS	51.0		
503A	43	2	20	183.85	USGS	41.0		
503A	43	2	50	184.15	USGS	40.0		
503A	43	2	80	184.45	USGS	42.0		
503A	43	2	110	184.75	USGS	43.0		
503A	43	2	140	185.05	USGS	48.0		
503A	43	3	20	185.36	USGS	54.0		
503A	44	1	20	186.80	USGS	56.0		
503A	44	1	50	187.10	USGS	38.0		
503A	44	1	80	187.40	USGS	40.0		
503A	44	1	110	187.70	USGS	53.0		
503A	44	1	140	188.00	USGS	52.0		
503A	44	2	20	188.31	USGS	33.0		
503A	44	2	50	188.61	USGS	43.0		
503A	44	2	80	188.91	USGS	41.0		
503A	44	2	110	189.21	USGS	47.0		
503A	44	2	140	189.51	USGS	53.0		
503A	44	3	20	189.81	USGS	52.0		
503A	44	3	50	190.11	USGS	56.0		
503A	44	3	80	190.41	USGS	35.0		
503A	48	1	80	204.70	USGS	75.0		
503A	48	1	110	205.00	USGS	77.0		
503A	48	1	140	205.30	USGS	79.0		
503A	48	2	20	205.60	USGS	78.0		
503A	48	2	50	205.89	USGS	75.0		
503A	48	2	80	206.19	USGS	73.0		
503A	48	2	110	206.49	USGS	73.0		
503A	48	2	140	206.79	USGS	66.0		

*** GRID B 01 ***

*** GRID C 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503A	48	3	20	207.10	USGS	75.0		
503A	48	3	50	207.40	USGS	74.0		
503A	49	1	50	209.06	USGS	72.0		
503A	49	1	80	209.36	USGS	69.0		
503A	49	1	110	209.66	USGS	73.0		
503A	49	1	140	209.96	USGS	78.0		
503A	49	2	20	210.26	USGS	67.0		
503A	50	1	20	213.10	USGS	50.0		
503A	50	1	50	213.40	USGS	53.0		
503A	50	1	80	213.70	USGS	62.0		
503A	50	1	110	214.00	USGS	67.0		
503A	50	1	140	214.30	USGS	48.0		
503A	50	2	20	214.60	USGS	50.0		
503A	50	2	50	214.90	USGS	58.0		
503A	50	2	80	215.20	USGS	56.0		
503A	50	2	110	215.50	USGS	65.0		
503A	50	2	140	215.80	USGS	59.0		
503A	50	3	20	216.10	USGS	55.0		
503A	50	3	50	216.40	USGS	38.0		
503A	50	3	80	216.70	USGS	39.0		
503A	50	3	110	217.00	USGS	44.0		
503A	51	1	50	217.88	USGS	67.0		
503A	51	1	80	218.18	USGS	58.0		
503A	51	1	110	218.48	USGS	63.0		
503A	51	2	20	218.96	USGS	23.0		
503A	51	2	50	219.26	USGS	64.0		
503A	51	2	80	219.56	USGS	54.0		
503A	51	2	110	219.86	USGS	56.0		
503A	51	2	140	220.16	USGS	51.0		
503A	52	1	20	222.00	USGS	58.0		
503A	52	1	50	222.30	USGS	47.0		
503A	52	1	80	222.60	USGS	56.0		
503A	52	1	110	222.90	USGS	50.0		
503A	52	1	140	223.20	USGS	50.0		
503A	52	2	20	223.51	USGS	56.0		
503A	52	2	50	223.81	USGS	64.0		
503A	52	2	80	224.11	USGS	44.0		
503A	52	2	110	224.41	USGS	58.0		
503A	52	2	140	224.71	USGS	75.0		
503A	52	3	20	225.01	USGS	71.0		
503A	52	3	50	225.31	USGS	55.0		
503A	53	1	20	226.40	USGS	42.0		
503A	53	1	50	226.70	USGS	44.0		
503A	53	1	80	227.00	USGS	47.0		
503A	53	1	110	227.30	USGS	19.0		
503A	53	1	140	227.60	USGS	37.0		
503A	53	2	20	227.91	USGS	43.0		
503A	53	2	50	228.21	USGS	44.0		
503A	53	2	80	228.51	USGS	43.0		
503A	53	2	110	228.79	USGS	38.0		
503A	53	2	140	229.09	USGS	38.0		
503A	53	3	20	229.40	USGS	33.0		
503A	53	3	50	229.70	USGS	34.0		

*** GRID C 01 ***

*** GRID D 01 ***

Hole	Core	Section	Interval & Level (cm)	Sub-bottom Depth (m, adj.)	Analysis	Carbon Carbonate	Organic Carbon	Total Carbon
503A	54	1	20	230.80	USGS	34.0		
503A	54	1	50	231.10	USGS	30.0		
503A	54	1	80	231.40	USGS	10.0		
503A	54	1	110	231.70	USGS	50.0		
503A	54	1	140	232.00	USGS	35.0		
503A	54	2	20	232.31	USGS	53.0		
503A	54	2	50	232.61	USGS	41.0		
503A	54	2	80	232.91	USGS	38.0		
503A	54	2	110	233.21	USGS	59.0		
503A	54	2	140	233.51	USGS	50.0		
503A	54	3	20	233.82	USGS	51.0		
503A	54	3	50	234.12	USGS	47.0		
503A	54	3	80	234.42	USGS	51.0		

*** GRID D 01 ***

GRID TABLE

B 01
C 01
D 01

GRID TABLE

GRID TABLE

GRID TABLE